Lenovo PM1633a Enterprise Capacity 12Gb SAS SSDs
Product Guide (withdrawn product)

The Lenovo PM1633a Enterprise Capacity 12Gb SAS solid-state drives (SSDs) in capacities of 3.84 TB, 7.68 TB and 15.36 TB capacities are next-generation high-capacity SSDs suitable for a wide range of applications of running on both System x and ThinkServer platforms.

The PM1633a Enterprise Capacity SSDs are designed for dense storage and with a 12 Gb SAS interface, these drives feature all the capacity and performance that is needed to replace large numbers of 15K rpm and 10K rpm spinning disks, and consolidate storage into tightly packed server configurations.

Figure 1. Lenovo PM1633a Enterprise Capacity 12Gb SAS SSD

Did you know?

Enterprise Capacity SSDs are a category of cost-effective high-capacity SSDs where it makes sense to store all of your data on the SSDs, and not use the SSDs only for caching or indexes.

Unlike SATA drives, the 12 Gb/s SAS interface on these drives supports full duplex data transfer for higher performance, as well as dual port connectivity and enterprise-level error recovery for better availability.

Part number information

Withdrawn from marketing: All drives listed in this product guide are withdrawn from marketing. The suggested replacements are the ThinkSystem PM1643 Capacity SAS 12Gb SSDs.

The following table lists the part numbers and feature codes for ThinkSystem servers.

Table 1. Ordering part numbers and feature codes - ThinkSystem

Part number	Feature code	Description
2.5-inch hot-swap drives		
7N47A00121	AUMK	ThinkSystem 2.5" PM1633a 3.84TB Capacity SAS 12Gb Hot Swap SSD
7N47A00122	AUML	ThinkSystem 2.5" PM1633a 7.68TB Capacity SAS 12Gb Hot Swap SSD
7N47A00123	B116	ThinkSystem 2.5" PM1633a 15.36TB Capacity SAS 12Gb Hot Swap SSD
3.5-inch hot-swap drives		
4XB7A10173	B2XC	ThinkSystem 3.5" PM1633a 3.84TB Capacity SAS 12Gb Hot Swap SSD

The following table lists the part numbers and feature codes for System x servers.

Table 2. Ordering part numbers and feature codes - System x

Part number	Feature code	Description
2.5-inch hot-swap drives with G3HS tray		
01GR786	AVKV	PM1633a 3.84TB Enterprise Capacity 12Gb SAS G3HS 2.5" SSD
01GR771	AUEJ	PM1633a 7.68TB Enterprise Capacity 12Gb SAS G3HS 2.5" SSD
3.5-inch hot-swap drives with hot-swap tray		
01GR791	AVKW	PM1633a 3.84TB Enterprise Capacity 12Gb SAS HS 3.5" SSD
2.5-inch non-hot-swap drives for use in NeXtScale systems		
01GR796	AVKZ	PM1633a 3.84TB Enterprise Capacity 12Gb SAS 2.5" SSD for NeXtScale
01GR776	AUEK	PM1633a 7.68TB Enterprise Capacity 12Gb SAS 2.5" SSD for NeXtScale

Table 3. Ordering part numbers - ThinkServer

Part number	Description
2.5-inch hot-swap drives	
4XB0K12387	Lenovo ThinkServer 2.5" 3.84TB PM1633a Enterprise Capacity SAS 12Gbps HS SSD
4XB0K12402	Lenovo ThinkServer 2.5" 7.68TB PM1633a Enterprise Capacity SAS 12Gb HS SSD
3.5-inch hot-swap drives	
4XB0K12388	Lenovo ThinkServer 3.5" 3.84TB PM1633a Enterprise Capacity SAS 12Gbps HS SSD

The part numbers include the following items:

- One solid-state drive (HS parts include a hot-swap tray)
- Support Flyer for SSDs
- Warranty Flyer
- Important Notices Flyer

Features

The PM1633a Enterprise Capacity SSDs have the following features:

- High capacity server SSD suitable for read-intensive workloads
- Based on Samsung V-NAND technology and TLC flash memory
- Endurance of 1 drive-write per day (DWPD) over 5 years
- 2.5-inch or 3.5-inch industry standard form factor with hot-swap tray
- SAS 12 Gbps interface
- Active-active dual port host interface
- Protect data integrity from unexpected power loss with Samsung's advanced power-loss protection architecture
- Supports Self-Monitoring, Analysis and Reporting Technology (S.M.A.R.T)
- End-to-end data protection
- Support 16 Initiator with Tag Command Queuing (TCQ) Command Set with a queue-depth of up to 128 commands
- Compliant with SCSI Specification (SAS-3 / SPL-3 / SBC-4 / SPC-4 / SAM-5)
- RoHS Compliant

Enterprise Capacity SSDs have similar read and write IOPS performance and similar endurance to Enterprise Entry SSDs, however, the key difference is density - the total amount of storage in each 2.5-inch drive. With large configurations, more storage can be installed internal to the server, changing the need for external JBOD connections thereby saving power and rack space.

SSD write endurance is typically measured by the number of program/erase (P/E) cycles that the drive incurs over its lifetime, listed as the total bytes of written data (TBW) in the device specification. The TBW value assigned to a solid-state device is the total bytes of written data (based on the number of P/E cycles) that a drive can be guaranteed to complete (% of remaining P/E cycles = % of remaining TBW).

Reaching this limit does not cause the drive to immediately fail. It simply denotes the maximum number of writes that can be guaranteed. A solid-state device will not fail upon reaching the specified TBW. At some point based on manufacturing variance margin, after surpassing the TBW value, the drive will reach the end-of-life point, at which the drive will go into a read-only mode.

For example, the PM1633a 7.68 TB drive has an endurance of 14,016 TB of total bytes written (TBW). This means that for full operation over five years, write workload can be up to 7,680 GB of writes per day, which is equivalent to 1.0 full drive writes per day (DWPD). For the device to last three years, the drive write workload can be up to 12,800 GB of writes per day, which is equivalent to 1.7 full drive writes per day.

Users also have the flexibility to use this drive for more write intensive applications because these drives have such a large average daily write capacity. For example, the 3.84 TB has the same average daily write capacity (7,008 TB at 1.0 drive writes per day) as a 400 GB Enterprise Performance drive (7,300 TB at 10 drive writes per day).

Technical specifications

The following tables present technical specifications for the PM1633a Enterprise Capacity SSDs.

Table 4. Technical specifications

Feature	**3.84 TB drive**	**7.68 TB drive**	**15.36 TB drive**
Interface	12 Gbps SAS	12 Gbps SAS	12 Gbps SAS
Capacity	3.84 TB	7.68 TB	15.36 TB
Endurance (drive writes per day for 5 years)	1 DWPD	1 DWPD	1 DWPD
Endurance (total bytes written)	7,008 TB	14,016 TB	28,032 TB
Data reliability (UBER)	< 1 in 10^{17} bits read	< 1 in 10^{17} bits read	< 1 in 10^{17} bits read
MTBF	2,000,000 hours	2,000,000 hours	2,000,000 hours
IOPS reads (4 KB blocks)	180,000	148,000	148,000
IOPS writes (4 KB blocks)	23,000	21,000	21,000
Sequential read rate (128 KB blocks)	940 MBps	640 MBps	640 MBps
Sequential write rate (128 KB blocks)	1000 MBps	450 MBps	450 MBps
Shock, non-operating	1,500 G (Max) at 0.5 ms	1,500 G (Max) at 0.5 ms	1,500 G (Max) at 0.5 ms
Vibration, non-operating	20 G_{RMS} (10-2000 Hz)	20 G_{RMS} (10-2000 Hz)	20 G_{RMS} (10-2000 Hz)
Typical power (R / W)	9 W / 9 W	9 W / 9 W	9 W / 9 W

Server support - ThinkSystem

The following table lists the ThinkSystem servers that are compatible.

Table 5. ThinkSystem server support

Part number	Description	1S Rack & Tower				2S Rack & Tower								4S Rack			Dense/ Blade			
		ST50 (7Y48/7Y50)	ST250 (7Y45/7Y46)	SR150 (7Y54)	SR250 (7Y51/7Y52)	ST550 (7X09/7X10)	SR530 (7X07/7X08)	SR550 (7X03/7X04)	SR570 (7Y02/7Y03)	SR590 (7X98/7X99)	SR630 (7X01/7X02)	SR650 (7X05/7X06)	SR670 (7Y36/7Y37/7Y38)	SR850 (7X18/7X19)	SR860 (7X69/7X70)	SR950 (7X11/12/13)	SD530 (7X21)	SD650 (7X58)	SN550 (7X16)	SN850 (7X15)
7N47A00121	ThinkSystem 2.5" PM1633a 3.84TB Capacity SAS 12Gb Hot Swap SSD	N	N	N	N	Y	Y	Y	Y	Y	Y	Y	N	Y	Y	Y	Y	N	Y	N
7N47A00122	ThinkSystem 2.5" PM1633a 7.68TB Capacity SAS 12Gb Hot Swap SSD	N	N	N	N	Y	Y	Y	Y	Y	Y	Y	N	Y	Y	Y	Y	N	Y	N
7N47A00123	ThinkSystem 2.5" PM1633a 15.36TB Capacity SAS 12Gb Hot Swap SSD	N	N	N	N	Y	N	N	N	N	Y	Y	N	Y	N	N	Y	N	Y	Y
4XB7A10173	ThinkSystem 3.5" PM1633a 3.84TB Capacity SAS 12Gb Hot Swap SSD	N	N	N	N	Y	Y	Y	Y	Y	Y	Y	N	N	N	N	N	N	N	N

Server support - System x

The following tables list the System x servers that are compatible with the PM1633a Enterprise Capacity SSDs.

Support for System x and dense servers with Xeon E5/E7 v4 and E3 v5 processors

Table 6. Support for System x and dense servers with Xeon E5/E7 v4 and E3 v5 processors

Part number	Description	x3250 M6 (3943)	x3250 M6 (3633)	x3550 M5 (8869)	x3650 M5 (8871)	x3850 X6/x3950 X6 (6241, E7 v4)	nx360 M5 (5465, E5 v4)	sd350 (5493)
01GR786	PM1633a 3.84TB Enterprise Capacity 12Gb SAS G3HS 2.5" SSD	N	N	Y	Y	Y	Y	Y
01GR771	PM1633a 7.68TB Enterprise Capacity 12Gb SAS G3HS 2.5" SSD	N	N	Y	Y	Y	N	N
01GR791	PM1633a 3.84TB Enterprise Capacity 12Gb SAS HS 3.5" SSD	N	N	Y	Y	N	N	N
01GR796	PM1633a 3.84TB Enterprise Capacity 12Gb SAS 2.5" SSD NeXtScale	N	N	N	N	N	Y	N
01GR776	PM1633a 7.68TB Enterprise Capacity 12Gb SAS 2.5" SSD NeXtScale	N	N	N	N	N	Y	N

Support for System x and dense servers with Intel E5 v3 and E3 v3 processors

Table 7. Support for servers with Intel Xeon v3 processors

Part number	Description	x3100 M5 (5457)	x3250 M5 (5458)	x3500 M5 (5464)	x3550 M5 (5463)	x3650 M5 (5462)	x3850 X6/x3950 X6 (6241, E7 v3)	nx360 M5 (5465, E5 v3)
01GR786	PM1633a 3.84TB Enterprise Capacity 12Gb SAS G3HS 2.5" SSD	N	N	N	N	N	N	N
01GR771	PM1633a 7.68TB Enterprise Capacity 12Gb SAS G3HS 2.5" SSD	N	N	N	N	N	N	N
01GR791	PM1633a 3.84TB Enterprise Capacity 12Gb SAS HS 3.5" SSD	N	N	N	N	N	N	N
01GR796	PM1633a 3.84TB Enterprise Capacity 12Gb SAS 2.5" SSD for NeXtScale	N	N	N	N	N	N	N
01GR776	PM1633a 7.68TB Enterprise Capacity 12Gb SAS 2.5" SSD for NeXtScale	N	N	N	N	N	N	N

Server support - ThinkServer

The following tables list the ThinkServer systems that are compatible with the PM1633a Enterprise Capacity SSDs.

Support for ThinkServer Generation 5 servers with E5 v4 and E3 v5 processors

Table 8. Support for ThinkServer Generation 5 servers with E5 v4 and E3 v5 processors

Part number	Description	TS150	TS450	TS460	RS160	TD350	RD350 (70Qx)	RD450 (70Qx)	RD550 (70Rx/70Sx)	RD650 (70Rx)
4XB0K12387	Lenovo ThinkServer 2.5" 3.84TB PM1633a Enterprise Capacity SAS 12Gbps HS SSD	N	Y	N	N	Y	Y	Y	Y	Y
4XB0K12402	Lenovo ThinkServer 2.5" 7.68TB PM1633a Enterprise Capacity SAS 12Gb HS SSD	N	N	N	N	Y	Y	Y	Y	Y
4XB0K12388	Lenovo ThinkServer 3.5" 3.84TB PM1633a Enterprise Capacity SAS 12Gbps HS SSD	N	Y	N	N	Y	Y	Y	Y	Y

Support for ThinkServer Generation 5 servers with E5 v3 and E3 v3 processors

Table 9. Support for ThinkServer Generation 5 servers with E5 v3 and E3 v3 processors

Part number	Description	TS140	TS440	RS140	TD350	RD350 (70Dx)	RD450 (70Dx)	RD550 (70Cx)	RD650 (70Dx)
4XB0K12387	Lenovo ThinkServer 2.5" 3.84TB PM1633a Enterprise Capacity SAS 12Gbps HS SSD	N	N	N	N	N	N	N	N
4XB0K12402	Lenovo ThinkServer 2.5" 7.68TB PM1633a Enterprise Capacity SAS 12Gb HS SSD	N	N	N	N	N	N	N	N
4XB0K12388	Lenovo ThinkServer 3.5" 3.84TB PM1633a Enterprise Capacity SAS 12Gbps HS SSD	N	N	N	N	N	N	N	N

Server support - Flex System

The PM1633a Enterprise Capacity SSDs are supported in the following Flex System compute nodes.

Tip: The SN550 and SN850 compute nodes are listed in the ThinkSystem support table.

Table 10. Support for Flex System compute nodes

Part number	Description	x240 (8737, E5-2600 v2)	x240 (7162)	x240 M5 (9532, E5-2600 v3)	x240 M5 (9532, E5-2600 v4)	x440 (7167)	x880/x480/x280 X6 (7903)	x280/x480/x880 X6 (7196)
01GR786	PM1633a 3.84TB Enterprise Capacity 12Gb SAS G3HS 2.5" SSD	N	N	Y	Y	N	N	N
01GR771	PM1633a 7.68TB Enterprise Capacity 12Gb SAS G3HS 2.5" SSD	N	N	Y	Y	N	N	N
01GR791	PM1633a 3.84TB Enterprise Capacity 12Gb SAS HS 3.5" SSD	N	N	N	N	N	N	N
01GR796	PM1633a 3.84TB Enterprise Capacity 12Gb SAS 2.5" SSD for NeXtScale	N	N	N	N	N	N	N
01GR776	PM1633a 7.68TB Enterprise Capacity 12Gb SAS 2.5" SSD for NeXtScale	N	N	N	N	N	N	N

Storage controller support

The PM1633a Enterprise Capacity SSDs require a supported SAS controller.

ThinkSystem controllers and servers are listed in the following table.

Table 11. ThinkSystem server support

Part number	Description	ST550 (7X09/7X10)	SR530 (7X07/7X08)	SR550 (7X03/7X04)	SR570 (7Y02/7Y03)	SR590 (7X98/7X99)	SR630 (7X01/7X02)	SR650 (7X05/7X06)	SR850 (7X18/7X19)	SR860 (7X69/7X70)	SR950 (7X11/12/13)	SD530 (7X21)	SN550 (7X16)	SN850 (7X15)
7Y37A01088	430-8i SAS/SATA 12Gb HBA	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y	N	N	N
7Y37A01089	430-16i SAS/SATA 12Gb HBA	Y	N	Y	Y	Y	Y	Y	Y	Y	Y	N	N	N
7Y37A01082	RAID 530-8i PCIe 12Gb Adapter	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y	N	N	N
7Y37A01083	RAID 730-8i 1GB Cache PCIe 12Gb Adapter	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y	N	N	N
7Y37A01084	RAID 930-8i 2GB Flash PCIe 12Gb Adapter	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y	N	N	N
7Y37A01085	RAID 930-16i 4GB Flash PCIe 12Gb Adapter	Y	N	Y	Y	Y	Y	Y	Y	Y	Y	N	N	N
Feature AUYK	SD530 HW RAID Kit	N	N	N	N	N	N	N	N	N	N	Y	N	N
7M27A03918	RAID 530-4i 2 Drive Adapter Kit for SN550	N	N	N	N	N	N	N	N	N	N	N	Y	N
7M17A03932	RAID 530-4i 4 Drive Adapter Kit for SN850	N	N	N	N	N	N	N	N	N	N	N	N	Y

The following table lists the controllers and the System x servers that support those controllers.

Table 12. Controllers for supported servers

		Xeon v4					FS
Part number	Description	x3550 M5 (8869)	x3650 M5 (8871)	x3850 X6/x3950 X6 (6241, E7 v4)	nx360 M5 (5465, E5-2600 v4)	sd350 (5493)	x240 M5 (9532)
Onboard	ServeRAID M1200e Controller	N	N	N	N	N	Y
46C9114	ServeRAID M1215 Controller	Y	Y	N	Y	N	N
81Y4481	ServeRAID M5110 Controller	N	N	N	N	N	N
46C9110	ServeRAID M5210 Controller	Y	Y	Y	Y	N	N
00JX142	ServeRAID M5215 Controller	N	N	N	N	N	Y
00YD430	H701-L 6Gb HBA Mezz Card	N	N	N	N	Y	N
46C8988	N2115 SAS/SATA HBA	N	N	N	N	N	N

		Xeon v4					FS
Part number	**Description**	**x3550 M5 (8869)**	**x3650 M5 (8871)**	**x3850 X6/x3950 X6 (6241, E7 v4)**	**nx360 M5 (5465, E5-2600 v4)**	**sd350 (5493)**	**x240 M5 (9532)**
47C8675	N2215 SAS/SATA HBA	Y	Y	Y	Y	N	N

The following table list the ThinkServer controllers that support these solid-state drives installed in a supported server.

Table 13. Supported controllers - ThinkServer

		TS450	TD350	RD350	RD450	RD550	RD650
4XB0F28691	AnyRAID 510i	N	Y	N	Y	Y	Y
4XB0F28693	AnyRAID 720i	N	Y	N	Y	Y	Y
4XB0F28694	AnyRAID 720ix	N	Y	N	Y	Y	Y
4XC0G88850	RAID 520i	Y	Y	Y	Y	Y	Y
4XC0G88836	RAID 710	N	N	Y	Y	N	N
4XC0G88849	RAID 720i	Y	Y	Y	Y	Y	Y

Operating system support

SAS and SATA SSDs operate transparently to users, storage systems, applications, databases, and operating systems.

Operating system support is based on the controller used to connect to the drives. Consult the controller product guide for more information:

- RAID controllers: https://lenovopress.com/servers/options/raid
- SAS HBAs: https://lenovopress.com/servers/options/hba

Warranty

The PM1633a Enterprise Capacity SSDs carry a one-year, customer-replaceable unit (CRU) limited warranty. When the SSDs are installed in a supported server, these drives assume the system's base warranty and any warranty upgrades.

Solid State Memory cells have an intrinsic, finite number of program/erase cycles that each cell can incur. As a result, each solid state device has a maximum amount of program/erase cycles to which it can be subjected. The warranty for Lenovo solid state drives (SSDs) is limited to drives that have not reached the maximum guaranteed number of program/erase cycles, as documented in the Official Published Specifications for the SSD product. A drive that reaches this limit may fail to operate according to its Specifications.

Physical specifications

The PM1633a Enterprise Capacity SSDs have the following physical specifications:

Dimensions and weight (approximate, without the hot-swap tray, if applicable):

- Height: 15 mm (0.6 in.)
- Width: 70 mm (2.8 in.)
- Depth: 100 mm (4.0 in.)
- Weight: 160 g (5.6 oz)

Shipping dimensions and weight for the 2.5-inch drives (approximate):

- Height: 63 mm (2.5 in.)
- Width: 133 mm (5.2 in.)
- Depth: 174 mm (6.9 in.)

Shipping dimensions and weight for the 3.5-inch drives (approximate):

- Height: 95 mm (3.7 in.)
- Width: 194 mm (7.6 in.)
- Depth: 257 mm (10.0 in.)

Operating environment

The PM1633a Enterprise Capacity SSDs are supported in the following environment:

- Temperature, operating: 0 - 70 °C (32 - 158 °F)
- Temperature, non-operating: -40 to 85 °C (-40 - 185 °F)
- Relative humidity: 5 - 95% (noncondensing)
- Maximum altitude: -300 - 4,572 m (-1,000 to 15,000 feet)

Agency approvals

The PM1633a Enterprise Capacity SSDs conform to the following regulations:

- UL
- TUV
- FCC
- IC
- CB
- CE Mark
- C-Tick Mark
- BSMI (Taiwan)
- KCC (Korea EMI)
- VCCI

Related publications and links

For more information, see the following documents:

- Lenovo Press product guides and papers on RAID adapters and HBAs
  https://lenovopress.com/servers/options/raid
- Lenovo RAID Management Tools and Resources
  https://lenovopress.com/lp0579-lenovo-raid-management-tools-and-resources
- Lenovo RAID Introduction
  https://lenovopress.com/lp0578-lenovo-raid-introduction

Related product families

Product families related to this document are the following:

- Drives

Notices

Lenovo may not offer the products, services, or features discussed in this document in all countries. Consult your local Lenovo representative for information on the products and services currently available in your area. Any reference to a Lenovo product, program, or service is not intended to state or imply that only that Lenovo product, program, or service may be used. Any functionally equivalent product, program, or service that does not infringe any Lenovo intellectual property right may be used instead. However, it is the user's responsibility to evaluate and verify the operation of any other product, program, or service. Lenovo may have patents or pending patent applications covering subject matter described in this document. The furnishing of this document does not give you any license to these patents. You can send license inquiries, in writing, to:

Lenovo (United States), Inc.
8001 Development Drive
Morrisville, NC 27560
U.S.A.
Attention: Lenovo Director of Licensing

LENOVO PROVIDES THIS PUBLICATION ”AS IS” WITHOUT WARRANTY OF ANY KIND, EITHER EXPRESS OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF NON-INFRINGEMENT, MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE. Some jurisdictions do not allow disclaimer of express or implied warranties in certain transactions, therefore, this statement may not apply to you.

This information could include technical inaccuracies or typographical errors. Changes are periodically made to the information herein; these changes will be incorporated in new editions of the publication. Lenovo may make improvements and/or changes in the product(s) and/or the program(s) described in this publication at any time without notice.

The products described in this document are not intended for use in implantation or other life support applications where malfunction may result in injury or death to persons. The information contained in this document does not affect or change Lenovo product specifications or warranties. Nothing in this document shall operate as an express or implied license or indemnity under the intellectual property rights of Lenovo or third parties. All information contained in this document was obtained in specific environments and is presented as an illustration. The result obtained in other operating environments may vary. Lenovo may use or distribute any of the information you supply in any way it believes appropriate without incurring any obligation to you.

Any references in this publication to non-Lenovo Web sites are provided for convenience only and do not in any manner serve as an endorsement of those Web sites. The materials at those Web sites are not part of the materials for this Lenovo product, and use of those Web sites is at your own risk. Any performance data contained herein was determined in a controlled environment. Therefore, the result obtained in other operating environments may vary significantly. Some measurements may have been made on development-level systems and there is no guarantee that these measurements will be the same on generally available systems. Furthermore, some measurements may have been estimated through extrapolation. Actual results may vary. Users of this document should verify the applicable data for their specific environment.

© Copyright Lenovo 2026. All rights reserved.

This document, LP0612, was created or updated on November 5, 2018.

Send us your comments in one of the following ways:

- Use the online Contact us review form found at:
  https://lenovopress.lenovo.com/LP0612
- Send your comments in an e-mail to:
  comments@lenovopress.com

This document is available online at https://lenovopress.lenovo.com/LP0612.

Trademarks

Lenovo and the Lenovo logo are trademarks or registered trademarks of Lenovo in the United States, other countries, or both. A current list of Lenovo trademarks is available on the Web at https://www.lenovo.com/us/en/legal/copytrade/.

The following terms are trademarks of Lenovo in the United States, other countries, or both:
Lenovo®
System x®
ThinkServer®
ThinkSystem®

The following terms are trademarks of other companies:

Intel®, the Intel logo and Xeon® are trademarks of Intel Corporation or its subsidiaries.

Other company, product, or service names may be trademarks or service marks of others.