

ThinkSystem SR650 Sets World Record with New One-Node SPEC ACCEL OpenCL Result

Performance Benchmark Result

The Lenovo ThinkSystem SR650 server has set a new 1-node 2-socket performance world record with the SPECaccel_ocl_base metric from the SPEC ACCEL Benchmark. The SPEC ACCEL Benchmark suite is the industry standard to evaluate hardware-based accelerator devices and the performance of parallel computing workloads.

This new benchmark result, published in a new SPEC Report on April 2, 2019, demonstrate that the ThinkSystem SR650 continues Lenovo's leadership with outstanding performance for the server industry.



The ThinkSystem SR650 has achieved the following score (1):

- **SPECaccel_ocl_base = 10.9**

This result is the best 1-node 2-socket performance in the industry, 1.87% faster than Lenovo's own result published in March 2019 (2), and 450% faster than the TU Dresden result (3).

Table 1. Comparison of results

Hardware vendor	System	Result (Base)	Cores	CPUs	Memory
Lenovo (1)	ThinkSystem SR650 (Intel Xeon Gold 6240, DDR4-2933MHz, HT off, Turbo on)	10.9	32	2	768
Lenovo (2)	ThinkSystem SR670 (Intel Xeon Gold 6142, DDR4-2666MHz, HT off, Turbo on)	10.7	32	2	768
TU Dresden (3)	Bull R400 (Intel Xeon E5-2680 v3, DDR3-2133MHz)	2.42	80	4	384

The SR650 was configured as follows for the benchmark audit:

- Lenovo ThinkSystem SR650
- 2x Intel Xeon Gold 6240 Processors (16 cores, 2.60GHz)
- 768 GB memory (24x 32GB RDIMMs running at 2933MHz)
- 1 TB 12Gbps SAS 2.5" SSD
- Red Hat Enterprise Linux Server release 7.6, Kernel 3.10.0-957.el7.x86_64
- Accelerator: 1x NVIDIA Tesla V100 16GB

Results referenced are current as of April 2, 2019.

(1) The new Lenovo benchmark result can be found at:
<https://www.spec.org/accel/results/res2019q2/accel-20190312-00123.html>

(2) The previous Lenovo result can be found at:
<https://www.spec.org/accel/results/res2019q1/accel-20190226-00120.html>

(3) The TU Dresden result can be found at:
<https://www.spec.org/accel/results/res2015q3/accel-20150915-00056.html>

About the ThinkSystem SR650

The Lenovo ThinkSystem SR650 server now supports Intel Optane DC Persistent Memory and up to two second-generation Intel Xeon Scalable processors. It features up to 36% total performance improvement compared to the previous generation and supports two 300W high-performance GPUs and ML2 NIC adapters with shared management. Unique Lenovo AnyBay technology provides the flexibility to mix-and-match SAS/SATA HDDs/SSDs and NVMe SSDs in the same drive bays. Support is now available for up to 24 NVMe drives.

For medium to large enterprises, and managed and cloud service providers, Lenovo ThinkSystem SR650 is the optimum 2U, two-socket server—the most widely used server type worldwide. It's engineered to deliver high performance with 205W CPUs, low-latency NVMe drives, and high-power GPUs.

With Lenovo's history of reliability, the highly flexible and configurable SR650 is the ideal platform for hyper-converged infrastructure (HCI) or software-defined storage (SDS). It provides a solid foundation for:

- Transforming physical resources into services, using validated designs for hybrid cloud
- Performing analytics on streaming data, using validated designs for Big Data
- Increasing productivity of virtualized transactional systems, using validated designs for OLTP databases.

Lenovo XClarity Controller is an all-new hardware embedded management engine common in every ThinkSystem server. XClarity Controller features an uncluttered graphical user interface, industry standard Redfish-compliant REST APIs, and enables booting in half the time of prior generation servers, with up to 6x faster firmware updates.

Lenovo XClarity Administrator is a virtualized application that centrally manages ThinkSystem servers, storage, and networking. Via reusable patterns and policies, it ramps up and scales infrastructure provisioning and maintenance. It serves as a central integration point to extend your data center management processes to physical IT. Running XClarity Integrators in external IT applications, or integrating through REST APIs, helps you further speed services provisioning, streamline IT management, and contain costs.

About SPECaccel

The SPEC ACCEL benchmark suite provides a comparative measure the performance of hardware accelerator devices and their supporting software tool chains using computationally-intensive parallel applications. The suite is comprised of scientific applications used in High Performance Computing (HPC) and focuses on parallel computing performance.

The suite has been ported using several accelerator programming models each of which has been released as separate benchmark components:

- SPEC ACCEL OpenCL -- based on the Open Computing Language (OpenCL) 1.1 framework
- SPEC ACCEL OpenACC -- based on the Open Accelerators (OpenACC) 1.0 programming standard for parallel computing
- SPEC ACCEL OpenMP -- based on the Open Multi-Processing (OpenMP) 4.5 application programming interface

The product consists of source code benchmarks that are developed from real user applications.

For more information and SPEC ACCEL results, see <http://www.spec.org/accel/>.

Learn more

To learn more about solutions for parallel computing workloads, please contact your Lenovo Sales Representative.

To find out more about SPEC, visit <https://www.spec.org>

To learn more about the Lenovo ThinkSystem SR650 server, visit the SR650 product web page: <https://www.lenovo.com/us/en/data-center/servers/racks/ThinkSystem-SR650/p/77XX7SR65>

Related product families

Product families related to this document are the following:

- [2-Socket Rack Servers](#)
- [SPECaccel Benchmark Results](#)
- [ThinkSystem SR650 Server](#)

Notices

Lenovo may not offer the products, services, or features discussed in this document in all countries. Consult your local Lenovo representative for information on the products and services currently available in your area. Any reference to a Lenovo product, program, or service is not intended to state or imply that only that Lenovo product, program, or service may be used. Any functionally equivalent product, program, or service that does not infringe any Lenovo intellectual property right may be used instead. However, it is the user's responsibility to evaluate and verify the operation of any other product, program, or service. Lenovo may have patents or pending patent applications covering subject matter described in this document. The furnishing of this document does not give you any license to these patents. You can send license inquiries, in writing, to:

Lenovo (United States), Inc.
8001 Development Drive
Morrisville, NC 27560
U.S.A.
Attention: Lenovo Director of Licensing

LENOVO PROVIDES THIS PUBLICATION "AS IS" WITHOUT WARRANTY OF ANY KIND, EITHER EXPRESS OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF NON-INFRINGEMENT, MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE. Some jurisdictions do not allow disclaimer of express or implied warranties in certain transactions, therefore, this statement may not apply to you.

This information could include technical inaccuracies or typographical errors. Changes are periodically made to the information herein; these changes will be incorporated in new editions of the publication. Lenovo may make improvements and/or changes in the product(s) and/or the program(s) described in this publication at any time without notice.

The products described in this document are not intended for use in implantation or other life support applications where malfunction may result in injury or death to persons. The information contained in this document does not affect or change Lenovo product specifications or warranties. Nothing in this document shall operate as an express or implied license or indemnity under the intellectual property rights of Lenovo or third parties. All information contained in this document was obtained in specific environments and is presented as an illustration. The result obtained in other operating environments may vary. Lenovo may use or distribute any of the information you supply in any way it believes appropriate without incurring any obligation to you.

Any references in this publication to non-Lenovo Web sites are provided for convenience only and do not in any manner serve as an endorsement of those Web sites. The materials at those Web sites are not part of the materials for this Lenovo product, and use of those Web sites is at your own risk. Any performance data contained herein was determined in a controlled environment. Therefore, the result obtained in other operating environments may vary significantly. Some measurements may have been made on development-level systems and there is no guarantee that these measurements will be the same on generally available systems. Furthermore, some measurements may have been estimated through extrapolation. Actual results may vary. Users of this document should verify the applicable data for their specific environment.

© Copyright Lenovo 2024. All rights reserved.

This document, LP1104, was created or updated on April 2, 2019.

Send us your comments in one of the following ways:

- Use the online Contact us review form found at:
<https://lenovopress.lenovo.com/LP1104>
- Send your comments in an e-mail to:
comments@lenovopress.com

This document is available online at <https://lenovopress.lenovo.com/LP1104>.

Trademarks

Lenovo and the Lenovo logo are trademarks or registered trademarks of Lenovo in the United States, other countries, or both. A current list of Lenovo trademarks is available on the Web at <https://www.lenovo.com/us/en/legal/copytrade/>.

The following terms are trademarks of Lenovo in the United States, other countries, or both:

Lenovo®

AnyBay®

ThinkSystem®

XClarity®

The following terms are trademarks of other companies:

Intel®, Intel Optane™, and Xeon® are trademarks of Intel Corporation or its subsidiaries.

Linux® is the trademark of Linus Torvalds in the U.S. and other countries.

SPEC® and SPEC ACCEL® are trademarks of the Standard Performance Evaluation Corporation (SPEC).

Other company, product, or service names may be trademarks or service marks of others.