

ThinkSystem SR950 Sets Six World Records with Three-Socket SPECjbb Results

Performance Benchmark Result

The Lenovo ThinkSystem SR950 server has set six three-socket performance world records for the SPECjbb2015 benchmarks.

SPECjbb2015 is a Java Business Benchmark and is the SPEC benchmark used for evaluating the performance of servers running typical Enterprise Java applications.

The ThinkSystem SR950 with three processors achieved the following six top SPECjbb2015 scores:



- **SPECjbb2015-MultiJVM critical-jOPS: 200,372**
- **SPECjbb2015-MultiJVM max-jOPS: 28,4001**
- **SPECjbb2015-Composite max-jOPS: 220,144**
- **SPECjbb2015-Distributed critical-jOPS: 201,615**
- **SPECjbb2015-Distributed max-jOPS: 266,341**
- **SPECjbb2015-Composite critical-jOPS: 177,141**

SPECjbb2015 measures multi-threaded compute-intensive applications, with mixed industry workloads such as online purchase, inventory management, and supply. Critical-jOPS scores are ideal for measuring latency-critical applications and max-jOPS scores are ideal for measuring throughput-critical applications.

The ThinkSystem SR950 was configured as follows:

For the MultiJVM critical-jOPS, MultiJVM Max-jOPS, Composite Max-jOPS, and Distributed critical-jOPS results:

- 3x Intel Xeon Platinum 8280 processors
 - 2.7 GHz base frequency, 38.5 MB L3 cache
 - 3 processors, each 28 cores and 56 threads
- 3072 GB system memory
- Operating system:
 - SPECjbb2015-MultiJVM critical-jOPS: Red Hat Enterprise Linux 7.6
 - SPECjbb2015-MultiJVM Max-jOPS: SUSE Linux Enterprise Server 15
 - SPECjbb2015-Composite Max-jOPS: Red Hat Enterprise Linux 7.6
 - SPECjbb2015-Distributed critical-jOPS: Red Hat Enterprise Linux 7.6
- Oracle Java HotSpot 64-Bit Server VM, version 11.0.2

For the Distributed Max-jOPS and Composite Critical-jOPS results:

- 3x Intel Xeon Platinum 8180 processors
 - 2.5 GHz base frequency, 38.5 MB L3 cache
 - 3 processors, each 28 cores and 56 threads
- 1152 GB system memory
- Operating system:
 - SPECjbb2015-Distributed Max-jOPS: SUSE Linux Enterprise Server 12 SP2
 - SPECjbb2015-Composite Critical-jOPS: Red Hat Enterprise Linux 7.5
- Red Hat Enterprise Linux Server 7.5
- Oracle Java HotSpot 64-Bit Server VM, version 10.0.2

Results referenced are current as of April 2, 2019. To view details of these results, go to these SPEC web pages:

- SPECjbb2015-MultiJVM critical-jOPS
<https://www.spec.org/jbb2015/results/res2019q2/jbb2015-20190314-00429.html>
- SPECjbb2015-MultiJVM max-jOPS
<https://www.spec.org/jbb2015/results/res2019q2/jbb2015-20190314-00415.html>
- SPECjbb2015-Composite max-jOPS
<https://www.spec.org/jbb2015/results/res2019q2/jbb2015-20190314-00442.html>
- SPECjbb2015-Distributed critical-jOPS
<https://www.spec.org/jbb2015/results/res2019q2/jbb2015-20190314-00401.html>
- SPECjbb2015-Distributed max-jOPS (published September 13, 2018)
<https://www.spec.org/jbb2015/results/res2018q3/jbb2015-20180829-00315.html>
- SPECjbb2015-Composite critical-jOPS (published September 13, 2018)
<https://www.spec.org/jbb2015/results/res2018q3/jbb2015-20180829-00318.html>

To view all SPECjbb2015 results, go to
<https://www.spec.org/jbb2015/results/jbb2015.html>

About the ThinkSystem SR950

Lenovo ThinkSystem SR950 is designed for your most demanding, mission-critical workloads, such as in-memory databases, large transactional databases, batch and real-time analytics, ERP, CRM, and virtualized server workloads. The powerful 4U ThinkSystem SR950 can grow from two to eight second-generation Intel Xeon Scalable Family processors, and with 96 DIMM sockets, supports up to 24 TB of high-speed memory. The modular design of SR950 speeds upgrades and servicing with easy front or rear access to all major subsystems to maximize server availability. The ThinkSystem SR950 also supports Intel Optane DC Persistent Memory delivering a new, flexible tier of memory designed specifically for data center workloads that offer an unprecedented combination of high-capacity, affordability and persistence.

The SR950 packs numerous fault-tolerant and high-availability features into a high-density, 4U rack-optimized design that reduces the space needed to support massive network computing operations and simplify servicing. Lenovo XClarity Controller is an all-new hardware embedded management engine common in every ThinkSystem server. XClarity Controller features an uncluttered graphical user interface, industry standard Redfish-compliant REST APIs, and enables booting in half the time of prior generation servers, with up to 6x faster firmware updates.

Lenovo XClarity Administrator is a virtualized application that centrally manages ThinkSystem servers, storage, and networking. Via reusable patterns and policies, it ramps up and scales infrastructure provisioning and maintenance. It serves as a central integration point to extend your data center management processes to physical IT. Running XClarity Integrators in external IT applications, or integrating through REST APIs, helps you further speed services provisioning, streamline IT management, and contain costs.

ThinkShield is a comprehensive approach to security designed to secure the data center, from the foundation of your infrastructure to the network's edge and guard against a security breach. ThinkShield protects your business with each offering, from development through disposal.

About SPECjbb2015

The SPECjbb 2015 benchmark has been developed from the ground up to measure performance based on the latest Java application features. It is relevant to all audiences who are interested in Java server performance, including JVM vendors, hardware developers, Java application developers, researchers and members of the academic community.

SPECjbb2015 scores are ideal for measuring throughput and latency of multi-threaded compute-intensive applications such as online purchasing, inventory management, and supply.

Learn more

To learn more about solutions for Java applications, please contact your Lenovo Sales Representative.

To find out more about SPEC, visit <https://www.spec.org>

To learn more about the Lenovo ThinkSystem SR950 server, visit the [SR950 product web page](#).

Related product families

Product families related to this document are the following:

- [Mission Critical Servers](#)
- [SPECjbb Benchmark Results](#)
- [ThinkSystem SR950 Server](#)

Notices

Lenovo may not offer the products, services, or features discussed in this document in all countries. Consult your local Lenovo representative for information on the products and services currently available in your area. Any reference to a Lenovo product, program, or service is not intended to state or imply that only that Lenovo product, program, or service may be used. Any functionally equivalent product, program, or service that does not infringe any Lenovo intellectual property right may be used instead. However, it is the user's responsibility to evaluate and verify the operation of any other product, program, or service. Lenovo may have patents or pending patent applications covering subject matter described in this document. The furnishing of this document does not give you any license to these patents. You can send license inquiries, in writing, to:

Lenovo (United States), Inc.
8001 Development Drive
Morrisville, NC 27560
U.S.A.
Attention: Lenovo Director of Licensing

LENOVO PROVIDES THIS PUBLICATION "AS IS" WITHOUT WARRANTY OF ANY KIND, EITHER EXPRESS OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF NON-INFRINGEMENT, MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE. Some jurisdictions do not allow disclaimer of express or implied warranties in certain transactions, therefore, this statement may not apply to you.

This information could include technical inaccuracies or typographical errors. Changes are periodically made to the information herein; these changes will be incorporated in new editions of the publication. Lenovo may make improvements and/or changes in the product(s) and/or the program(s) described in this publication at any time without notice.

The products described in this document are not intended for use in implantation or other life support applications where malfunction may result in injury or death to persons. The information contained in this document does not affect or change Lenovo product specifications or warranties. Nothing in this document shall operate as an express or implied license or indemnity under the intellectual property rights of Lenovo or third parties. All information contained in this document was obtained in specific environments and is presented as an illustration. The result obtained in other operating environments may vary. Lenovo may use or distribute any of the information you supply in any way it believes appropriate without incurring any obligation to you.

Any references in this publication to non-Lenovo Web sites are provided for convenience only and do not in any manner serve as an endorsement of those Web sites. The materials at those Web sites are not part of the materials for this Lenovo product, and use of those Web sites is at your own risk. Any performance data contained herein was determined in a controlled environment. Therefore, the result obtained in other operating environments may vary significantly. Some measurements may have been made on development-level systems and there is no guarantee that these measurements will be the same on generally available systems. Furthermore, some measurements may have been estimated through extrapolation. Actual results may vary. Users of this document should verify the applicable data for their specific environment.

© Copyright Lenovo 2024. All rights reserved.

This document, LP1152, was created or updated on April 18, 2019.

Send us your comments in one of the following ways:

- Use the online Contact us review form found at:
<https://lenovopress.lenovo.com/LP1152>
- Send your comments in an e-mail to:
comments@lenovopress.com

This document is available online at <https://lenovopress.lenovo.com/LP1152>.

Trademarks

Lenovo and the Lenovo logo are trademarks or registered trademarks of Lenovo in the United States, other countries, or both. A current list of Lenovo trademarks is available on the Web at <https://www.lenovo.com/us/en/legal/copytrade/>.

The following terms are trademarks of Lenovo in the United States, other countries, or both:

Lenovo®

ThinkShield®

ThinkSystem®

XClarity®

The following terms are trademarks of other companies:

Intel®, Intel Optane™, and Xeon® are trademarks of Intel Corporation or its subsidiaries.

Linux® is the trademark of Linus Torvalds in the U.S. and other countries.

SPEC® and SPECjbb® are trademarks of the Standard Performance Evaluation Corporation (SPEC).

Other company, product, or service names may be trademarks or service marks of others.