

## ThinkSystem 5300 Mainstream 6Gb SATA SSDs

### Product Guide

The ThinkSystem 5300 Mainstream SATA 6Gb solid-state drives (SSDs) use Micron 96-layer 3D NAND flash memory technology with a 6Gbps SATA interface. They provide an affordable solution for mixed read/write applications such as cache in transactional applications and high-speed storage for enterprise databases.



Figure 1. ThinkSystem 5300 Mainstream SATA 6Gb SSDs

### Did you know?

The 5300 Series of SATA SSDs are the follow-on to the 5200 line of SSDs. The two series share the same controller, firmware, interface and features. The key difference is that the 5300 Series uses a new 96-layer 3D NAND storage medium compared to the 64-layer technology in the 5200. The 5300 drives have higher endurance and lower latency compared to the 5200 SSDs.

Lenovo also offers high-performance self-encrypting drives (SEDs) in the 5300 Mainstream Series. These SSDs adhere to the Trusted Computing Group Enterprise Security Subsystem Class cryptographic standard (TCG Enterprise SSC). Read about them in the [ThinkSystem 5300 Mainstream 6Gb SATA SED SSD product guide](#).

## Part number information

The following table lists the ThinkSystem part numbers.

Table 1. ThinkSystem ordering information

Part number	Feature	Description
2.5-inch hot-swap drives		
4XB7A17088	B8HY	ThinkSystem 2.5" 5300 480GB Mainstream SATA 6Gb Hot Swap SSD
3.5-inch hot-swap drives		
4XB7A17097	B8JF	ThinkSystem 3.5" 5300 480GB Mainstream SATA 6Gb Hot Swap SSD
7mm hot-swap drives		
4XB7A17094	BC6F	ThinkSystem 7mm 5300 480GB Mainstream SATA 6Gb Hot Swap SSD
Trayless drives for water-cooled servers		
4XB7A17187	B95J	ThinkSystem 5300 2.5" 7mm 480GB Mainstream SATA 6Gb Trayless SSD

## Features

The 5300 Mainstream SATA SSDs have the following features:

- Industry standard 2.5-inch or 3.5-inch form factors
- New generation 96-layer 3D TLC NAND flash memory
- Suitable for mixed read/write workloads with an endurance of between 2.5 and 5 drive writes per day (DWPD) for 5 years
- 6 Gbps SATA host interface
- High reliability and enhanced ruggedness
- MTTF of 3 million device hours - 50% more than most drives
- Absence of moving parts to reduce potential failure points in the server
- S.M.A.R.T. support
- Advanced Encrypting Standard (AES) 256-bit encryption

SSDs have a huge but finite number of program/erase (P/E) cycles, which affect how long they can perform write operations and thus their life expectancy. Mainstream SSDs typically have a better cost per read IOPS ratio but lower endurance and performance compared to Performance SSDs. SSD write endurance is typically measured by the number of program/erase cycles that the drive can incur over its lifetime, which is listed as total bytes written (TBW) in the device specification.

The TBW value that is assigned to a solid-state device is the total bytes of written data that a drive can be guaranteed to complete. Reaching this limit does not cause the drive to immediately fail; the TBW simply denotes the maximum number of writes that can be guaranteed. A solid-state device does not fail upon reaching the specified TBW. However, at some point after surpassing the TBW value (and based on manufacturing variance margins), the drive reaches the end-of-life point, at which time the drive goes into read-only mode. Because of such behavior, careful planning must be done to use SSDs in the application environments to ensure that the TBW of the drive is not exceeded before the required life expectancy.

For example, the 5300 Mainstream 1.92 TB drive has an endurance of 17,520 TB of total bytes written (TBW). This means that for full operation over five years, write workload must be limited to no more than 9,600 GB of writes per day, which is equivalent to 5.0 full drive writes per day (DWPD). For the device to last three years, the drive write workload must be limited to no more than 16,000 GB of writes per day, which is equivalent to 8.3 full drive writes per day.

## Technical specifications

The following table presents technical specifications for the 5300 Mainstream SATA SSDs.

**Tip:** Drives listed in this product guide are the Lenovo versions of the Micron 5300 MAX family of SSDs.

Table 2. Technical specifications

Feature	240 GB drive	480 GB drive	960 GB drive	1.92 TB drive	3.84 TB drive
Interface	6 Gbps SATA	6 Gbps SATA	6 Gbps SATA	6 Gbps SATA	6 Gbps SATA
Capacity	240 GB	480 GB	960 GB	1.92 TB	3.84 TB
SED encryption	None	None	None	None	None
Endurance (drive writes per day)	5.0 DWPD	5.0 DWPD	5.0 DWPD	5.0 DWPD	3.5 DWPD
Endurance (total bytes written)	2190 TB	4380 TB	8760 TB	17,520 TB	24,528 TB
Data reliability	< 1 in 10 <sup>17</sup> bits read	< 1 in 10 <sup>17</sup> bits read	< 1 in 10 <sup>17</sup> bits read	< 1 in 10 <sup>17</sup> bits read	< 1 in 10 <sup>17</sup> bits read
MTTF	3,000,000 hours	3,000,000 hours	3,000,000 hours	3,000,000 hours	3,000,000 hours
IOPS reads (4 KB blocks)	82,000	95,000	95,000	95,000	95,000
IOPS writes (4 KB blocks)	60,000	60,000	75,000	70,000	34,000
Sequential read rate (128 KB blocks)	540 MBps	540 MBps	540 MBps	540 MBps	540 MBps
Sequential write rate (128 KB blocks)	380 MBps	460 MBps	520 MBps	520 MBps	520 MBps
Read latency (seq)	175 µs	175 µs	175 µs	175 µs	250 µs
Write latency (seq)	300 µs	100 µs	100 µs	100 µs	200 µs
Shock, non-operating	1,500 G (Max) at 0.5 ms	1,500 G (Max) at 0.5 ms	1,500 G (Max) at 0.5 ms	1,500 G (Max) at 0.5 ms	1,500 G (Max) at 0.5 ms
Vibration, non-operating	3.13 G <sub>RMS</sub> (5-800 Hz)	3.13 G <sub>RMS</sub> (5-800 Hz)	3.13 G <sub>RMS</sub> (5-800 Hz)	3.13 G <sub>RMS</sub> (5-800 Hz)	3.13 G <sub>RMS</sub> (5-800 Hz)
Typical power (R / W)	2.5 / 3.0 W	2.5 / 3.1 W	2.8 / 3.4 W	3.0 / 3.8 W	2.5 / 3.8 W

## Server support

The following tables list the ThinkSystem servers that are compatible.

Table 3. Server support (Part 1 of 4)

Part Number	Description	AMD V3				2S Intel V3/V4				4S 8S Intel V3			Multi Node V3/V4			1S V3					
		SR635 V3 (7D9H / 7D9G)	SR655 V3 (7D9F / 7D9E)	SR645 V3 (7D9D / 7D9C)	SR665 V3 (7D9B / 7D9A)	ST650 V3 (7D7B / 7D7A)	SR630 V3 (7D72 / 7D73)	SR650 V3 (7D75 / 7D76)	SR630 V4 (7DG8 / 7DG9)	SR650 V4 (7DGC / 7DGD)	SR650a V4 (7DGC / 7DGD)	SR850 V3 (7D97 / 7D96)	SR860 V3 (7D94 / 7D93)	SR950 V3 (7DC5 / 7DC4)	SD535 V3 (7DD8 / 7DD1)	SD530 V3 (7DDA / 7DD3)	SD550 V3 (7DD9 / 7DD2)	ST45 V3 (7DH4 / 7DH5)	ST50 V3 (7DF4 / 7DF3)	ST250 V3 (7DCF / 7DCE)	SR250 V3 (7DCM / 7DCL)
<b>2.5-inch hot-swap drives</b>																					
4XB7A17088	ThinkSystem 2.5" 5300 480GB Mainstream SATA 6Gb Hot Swap SSD	N	N	N	N	N	N	N	N	N	N	N	N	N	N	N	N	N	N	N	
<b>3.5-inch hot-swap drives</b>																					
4XB7A17097	ThinkSystem 3.5" 5300 480GB Mainstream SATA 6Gb Hot Swap SSD	N	N	N	N	N	N	N	N	N	N	N	N	N	N	N	N	N	N	N	
<b>7mm hot-swap drives</b>																					
4XB7A17094	ThinkSystem 7mm 5300 480GB Mainstream SATA 6Gb Hot Swap SSD	N	N	N	N	N	N	N	N	N	N	N	N	N	N	N	N	N	N	N	
<b>Trayless drives for water-cooled servers</b>																					
4XB7A17187	ThinkSystem 5300 2.5" 7mm 480GB Mainstream SATA 6Gb Trayless SSD	N	N	N	N	N	N	N	N	N	N	N	N	N	N	N	N	N	N	N	

Table 4. Server support (Part 2 of 4)

Part Number	Description	GPU Rich					Edge					Super Computing							
		SR670 V2 (7Z22 / 7Z23)	SR675 V3 (7D9Q / 7D9R)	SR680a V3 (7DHE)	SR685a V3 (7DHC)	SR780a V3 (7DJ5)	SE100 (7DGR)	SE350 (7Z46 / 7D1X)	SE350 V2 (7DA9)	SE360 V2 (7DAM)	SE450 (7D8T)	SE455 V3 (7DBY)	SC750 V4 (7DDJ)	SC777 V4 (7DKA)	SD665 V3 (7D9P)	SD665-N V3 (7DAZ)	SD650 V3 (7D7M)	SD650-I V3 (7D7L)	SD650-N V3 (7D7N)
<b>2.5-inch hot-swap drives</b>																			
4XB7A17088	ThinkSystem 2.5" 5300 480GB Mainstream SATA 6Gb Hot Swap SSD	Y	N	N	N	N	N	N	N	N	N	N	N	N	N	N	N	N	N
<b>3.5-inch hot-swap drives</b>																			
4XB7A17097	ThinkSystem 3.5" 5300 480GB Mainstream SATA 6Gb Hot Swap SSD	Y	N	N	N	N	N	N	N	N	N	N	N	N	N	N	N	N	N
<b>7mm hot-swap drives</b>																			
4XB7A17094	ThinkSystem 7mm 5300 480GB Mainstream SATA 6Gb Hot Swap SSD	N	N	N	N	N	N	N	N	N	N	N	N	N	N	N	N	N	N
<b>Trayless drives for water-cooled servers</b>																			
4XB7A17187	ThinkSystem 5300 2.5" 7mm 480GB Mainstream SATA 6Gb Trayless SSD	N	N	N	N	N	N	N	N	N	N	N	N	N	N	N	N	N	N

Table 5. Server support (Part 3 of 4)

Part Number	Description	1S Intel V2		2S Intel V2		AMD V1				Dense V2			4S V2	8S					
		ST150 V2 (7D8K / 7D8J)	ST250 V2 (7D8G / 7D8F)	SR250 V2 (7D7R / 7D7Q)	ST650 V2 (7Z75 / 7Z74)	SR630 V2 (7Z70 / 7Z71)	SR650 V2 (7Z72 / 7Z73)	SR635 (7Y98 / 7Y99)	SR655 (7Y00 / 7Z01)	SR655 Client OS	SR645 (7D2Y / 7D2X)	SR665 (7D2W / 7D2V)	SD630 V2 (7D1K)	SD650 V2 (7D1M)	SD650-N V2 (7D1N)	SN550 V2 (7Z69)	SR850 V2 (7D31 / 7D32)	SR860 V2 (7Z59 / 7Z60)	SR950 (7X11 / 7X12)
<b>2.5-inch hot-swap drives</b>																			
4XB7A17088	ThinkSystem 2.5" 5300 480GB Mainstream SATA 6Gb Hot Swap SSD	N	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y	N	N	N	Y	Y	Y	Y
<b>3.5-inch hot-swap drives</b>																			
4XB7A17097	ThinkSystem 3.5" 5300 480GB Mainstream SATA 6Gb Hot Swap SSD	N	N	N	N	Y	Y	Y	Y	Y	Y	Y	N	N	N	N	N	N	N
<b>7mm hot-swap drives</b>																			
4XB7A17094	ThinkSystem 7mm 5300 480GB Mainstream SATA 6Gb Hot Swap SSD	N	N	N	N	N	N	N	N	N	N	N	Y	N	N	N	N	N	N
<b>Trayless drives for water-cooled servers</b>																			
4XB7A17187	ThinkSystem 5300 2.5" 7mm 480GB Mainstream SATA 6Gb Trayless SSD	N	N	N	N	N	N	N	N	N	N	N	N	Y	Y	N	N	N	N

Table 6. Server support (Part 4 of 4)

Part Number	Description	4S V1			1S Intel V1			2S Intel V1							Dense V1					
		SR850 (7X18 / 7X19)	SR850P (7D2F / 2D2G)	SR860 (7X69 / 7X70)	ST50 (7Y48 / 7Y50)	ST250 (7Y45 / 7Y46)	SR150 (7Y54)	SR250 (7Y52 / 7Y51)	ST550 (7X09 / 7X10)	SR530 (7X07 / 7X08)	SR550 (7X03 / 7X04)	SR570 (7Y02 / 7Y03)	SR590 (7X98 / 7X99)	SR630 (7X01 / 7X02)	SR650 (7X05 / 7X06)	SR670 (7Y36 / 7Y37)	SD530 (7X21)	SD650 (7X58)	SN550 (7X16)	SN850 (7X15)
<b>2.5-inch hot-swap drives</b>																				
4XB7A17088	ThinkSystem 2.5" 5300 480GB Mainstream SATA 6Gb Hot Swap SSD	Y	Y	Y	N	Y	N	Y	Y	Y	Y	Y	Y	Y	Y	N	Y	N	Y	Y
<b>3.5-inch hot-swap drives</b>																				
4XB7A17097	ThinkSystem 3.5" 5300 480GB Mainstream SATA 6Gb Hot Swap SSD	N	N	N	N	Y	N	Y	Y	Y	Y	Y	Y	Y	Y	N	N	N	N	N
<b>7mm hot-swap drives</b>																				
4XB7A17094	ThinkSystem 7mm 5300 480GB Mainstream SATA 6Gb Hot Swap SSD	N	N	N	N	N	N	N	N	N	N	N	N	N	N	N	N	N	N	N
<b>Trayless drives for water-cooled servers</b>																				
4XB7A17187	ThinkSystem 5300 2.5" 7mm 480GB Mainstream SATA 6Gb Trayless SSD	N	N	N	N	N	N	N	N	N	N	N	N	N	N	N	N	N	N	N

## Operating system support

SAS and SATA SSDs operate transparently to users, storage systems, applications, databases, and operating systems.

Operating system support is based on the controller used to connect to the drives. Consult the controller product guide for more information:

- RAID controllers: <https://lenovopress.com/servers/options/raid>
- SAS HBAs: <https://lenovopress.com/servers/options/hba>

## Warranty

The 5300 Mainstream SATA SSDs carry a one-year, customer-replaceable unit (CRU) limited warranty. When the SSDs are installed in a supported server, these drives assume the system's base warranty and any warranty upgrades.

Solid State Memory cells have an intrinsic, finite number of program/erase cycles that each cell can incur. As a result, each solid state device has a maximum amount of program/erase cycles to which it can be subjected. The warranty for Lenovo solid state drives (SSDs) is limited to drives that have not reached the maximum guaranteed number of program/erase cycles, as documented in the Official Published Specifications for the SSD product. A drive that reaches this limit may fail to operate according to its Specifications.

## Physical specifications

The drives have the following physical specifications (approximate, without the tray):

- Height: 7 mm (0.3 in.)
- Width: 70 mm (2.8 in.)
- Depth: 100 mm (4.0 in.)
- Weight: 70 g (2.5 oz)

Shipping dimensions and weight - 2.5-inch drives (approximate, including the tray):

- Height: 63 mm (2.5 in.)
- Width: 174 mm (6.9 in.)
- Depth: 133 mm (5.2 in.)
- Weight: 434 g (1.0 lb)

Shipping dimensions and weight - 3.5-inch drives (approximate, including the tray):

- Height: 95 mm (3.7 in.)
- Width: 257 mm (10.1 in.)
- Depth: 193 mm (7.6 in.)
- Weight: 484 g (1.1 lb)

## Operating environment

The SSDs are supported in the following environment:

- Operating temperature: 0 to 70°C (32 to 158°F)
- Non-operating temperature: -40 to 85°C (-40 to 185°F)
- Relative humidity: 5 to 95% (non-condensing)

## Agency approvals

The 5300 Mainstream SATA SSDs conform to the following regulations:

- Micron Green Standard
- Built with sulfur resistant resistors
- CE (Europe): EN 55032 Class B, RoHS
- FCC: CFR Title 47, Part 15 Class B
- UL: UL-60950-1, 2nd Edition
- BSMI (Taiwan): approval to CNS 13438
- RCM (Australia, New Zealand): AS/NZS CISPR32 Class B
- KCC RRL (Korea): approval to KN 32 Class B, KN 35 Class B
- W.E.E.E.: Compliance with EU WEEE directive 2002/96/EC.
- TUV (Germany): approval to IEC60950/EN60950
- VCCI (Japan): 2015-04 Class B
- IC (Canada): CISPR32 Class B: Canadian ICES-003:2016



## Related publications and links

For more information, see the following documents:

- Product Guide on ThinkSystem 5300 Mainstream 6Gb SATA SED SSDs  
<https://lenovopress.com/lp1256>
- Lenovo ThinkSystem storage options product page  
<https://lenovopress.com/lp0761-storage-options-for-thinksystem-servers>
- Micron 5300 series product page  
<https://www.micron.com/5300>
- ServerProven for SSDs  
<http://www.lenovo.com/us/en/serverproven>
- Lenovo RAID Introduction  
<https://lenovopress.com/lp0578-lenovo-raid-introduction>
- Lenovo RAID Management Tools and Resources  
<https://lenovopress.com/lp0579-lenovo-raid-management-tools-and-resources>

## Related product families

Product families related to this document are the following:

- [Drives](#)

## Notices

Lenovo may not offer the products, services, or features discussed in this document in all countries. Consult your local Lenovo representative for information on the products and services currently available in your area. Any reference to a Lenovo product, program, or service is not intended to state or imply that only that Lenovo product, program, or service may be used. Any functionally equivalent product, program, or service that does not infringe any Lenovo intellectual property right may be used instead. However, it is the user's responsibility to evaluate and verify the operation of any other product, program, or service. Lenovo may have patents or pending patent applications covering subject matter described in this document. The furnishing of this document does not give you any license to these patents. You can send license inquiries, in writing, to:

Lenovo (United States), Inc.  
8001 Development Drive  
Morrisville, NC 27560  
U.S.A.  
Attention: Lenovo Director of Licensing

LENOVO PROVIDES THIS PUBLICATION "AS IS" WITHOUT WARRANTY OF ANY KIND, EITHER EXPRESS OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF NON-INFRINGEMENT, MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE. Some jurisdictions do not allow disclaimer of express or implied warranties in certain transactions, therefore, this statement may not apply to you.

This information could include technical inaccuracies or typographical errors. Changes are periodically made to the information herein; these changes will be incorporated in new editions of the publication. Lenovo may make improvements and/or changes in the product(s) and/or the program(s) described in this publication at any time without notice.

The products described in this document are not intended for use in implantation or other life support applications where malfunction may result in injury or death to persons. The information contained in this document does not affect or change Lenovo product specifications or warranties. Nothing in this document shall operate as an express or implied license or indemnity under the intellectual property rights of Lenovo or third parties. All information contained in this document was obtained in specific environments and is presented as an illustration. The result obtained in other operating environments may vary. Lenovo may use or distribute any of the information you supply in any way it believes appropriate without incurring any obligation to you.

Any references in this publication to non-Lenovo Web sites are provided for convenience only and do not in any manner serve as an endorsement of those Web sites. The materials at those Web sites are not part of the materials for this Lenovo product, and use of those Web sites is at your own risk. Any performance data contained herein was determined in a controlled environment. Therefore, the result obtained in other operating environments may vary significantly. Some measurements may have been made on development-level systems and there is no guarantee that these measurements will be the same on generally available systems. Furthermore, some measurements may have been estimated through extrapolation. Actual results may vary. Users of this document should verify the applicable data for their specific environment.

© Copyright Lenovo 2025. All rights reserved.

This document, LP1255, was created or updated on February 22, 2022.

Send us your comments in one of the following ways:

- Use the online Contact us review form found at:  
<https://lenovopress.lenovo.com/LP1255>
- Send your comments in an e-mail to:  
[comments@lenovopress.com](mailto:comments@lenovopress.com)

This document is available online at <https://lenovopress.lenovo.com/LP1255>.

## Trademarks

Lenovo and the Lenovo logo are trademarks or registered trademarks of Lenovo in the United States, other countries, or both. A current list of Lenovo trademarks is available on the Web at <https://www.lenovo.com/us/en/legal/copytrade/>.

The following terms are trademarks of Lenovo in the United States, other countries, or both:

Lenovo®

ServerProven®

ThinkSystem®

The following terms are trademarks of other companies:

AMD is a trademark of Advanced Micro Devices, Inc.

Intel® is a trademark of Intel Corporation or its subsidiaries.

Other company, product, or service names may be trademarks or service marks of others.