

## ThinkSystem PM1643a Entry 12Gb SAS SSDs

### Product Guide (withdrawn product)

The ThinkSystem PM1643a Entry SAS 12Gb solid-state drives (SSDs) are next-generation SSDs suitable for a wide range of applications. The PM1643a SAS SSDs are designed for dense storage and with a 12 Gb SAS interface, these drives feature all the capacity and performance that is needed to replace large numbers of 15K rpm and 10K rpm spinning disks, and consolidate storage into tightly packed server configurations.

The PM1643a SSDs are the follow-on to the PM1643 SSDs and offer improved random write performance.



Figure 1. ThinkSystem PM1643a 12Gb SAS SSDs

### Did you know?

Unlike SATA drives, the 12 Gb/s SAS interface on PM1643a drives supports full duplex data transfer for higher performance, as well as enterprise-level error recovery for better availability.

Rigorous testing of PM1643a Entry SATA SSDs by Lenovo through the ServerProven program assures a high degree of storage subsystem compatibility and reliability. Providing additional peace of mind, these drives are covered under Lenovo warranty.

## Part number information

The following table lists the part numbers and feature codes for ThinkSystem servers.

**Withdrawn:** All drives listed below are now withdrawn from marketing

Table 1. Ordering part numbers and feature codes - ThinkSystem

Part number	Feature code	Description
2.5-inch hot-swap drives		
4XB7A38175	B91A	ThinkSystem 2.5" PM1643a 960GB Entry SAS 12Gb Hot Swap SSD
4XB7A38176	B91B	ThinkSystem 2.5" PM1643a 1.92TB Entry SAS 12Gb Hot Swap SSD
4XB7A17054	B91C	ThinkSystem 2.5" PM1643a 3.84TB Entry SAS 12Gb Hot Swap SSD
4XB7A17055	B91D	ThinkSystem 2.5" PM1643a 7.68TB Entry SAS 12Gb Hot Swap SSD
4XB7A17056	BC4R	ThinkSystem 2.5" PM1643a 15.36TB Entry SAS 12Gb Hot Swap SSD
3.5-inch hot-swap drives		
4XB7A17058	B91E	ThinkSystem 3.5" PM1643a 3.84TB Entry SAS 12Gb Hot Swap SSD
4XB7A17059	BEVK	ThinkSystem 3.5" PM1643a 7.68TB Entry SAS 12Gb Hot Swap SSD

## Features

The ThinkSystem PM1643a Entry SAS SSDs have the following features:

- Enterprise-grade SSD suitable for read-intensive workloads
- Based on Samsung 64-layer V-NAND technology and TLC flash memory
- Endurance of 1 drive-write per day (DWPD) over 5 years
- 2.5-inch or 3.5-inch industry standard form factor with hot-swap tray
- SAS 12 Gbps interface
- Single port host interface
- Protect data integrity from unexpected power loss with Samsung's advanced power-loss protection architecture
- Supports Self-Monitoring, Analysis and Reporting Technology (S.M.A.R.T)
- End-to-end data protection
- Support 16 Initiator with Tag Command Queuing (TCQ) Command Set with a queue-depth of up to 128 commands
- Compliant with SCSI Specification (SAS-3 / SPL-3 / SBC-4 / SPC-4 / SAM-5)
- RoHS Compliant

SSDs have a huge but finite number of program/erase (P/E) cycles, which affect how long they can perform write operations and thus their life expectancy. Entry SSDs typically have a better cost per read IOPS ratio but lower endurance and performance compared to Mainstream or Performance SSDs.

SSD write endurance is typically measured by the number of program/erase (P/E) cycles that the drive incurs over its lifetime, listed as the total bytes of written data (TBW) in the device specification. The TBW value assigned to a solid-state device is the total bytes of written data (based on the number of P/E cycles) that a drive can be guaranteed to complete (% of remaining P/E cycles = % of remaining TBW).

Reaching this limit does not cause the drive to immediately fail. It simply denotes the maximum number of writes that can be guaranteed. A solid-state device will not fail upon reaching the specified TBW. At some point based on manufacturing variance margin, after surpassing the TBW value, the drive will reach the end-of-life point, at which the drive will go into a read-only mode.

## Technical specifications

The following tables present technical specifications for the PM1643a Entry SSDs.

Table 2. Technical specifications

Feature	960 GB drive	1.92 TB drive	3.84 TB drive	7.68 TB drive	15.36 TB drive
Interface	12 Gbps SAS	12 Gbps SAS	12 Gbps SAS	12 Gbps SAS	12 Gbps SAS
Capacity	960 GB	1.92 TB	3.84 TB	7.68 TB	15.36 TB
SED encryption	None	None	None	None	None
Endurance (drive writes per day for 5 years)	1 DWPD	1 DWPD	1 DWPD	1 DWPD	1 DWPD
Endurance (total bytes written)	1,752 TB	3,504 TB	7,008 TB	14,016 TB	28,032 TB
Data reliability (UBER)	< 1 in 10 <sup>17</sup> bits read	< 1 in 10 <sup>17</sup> bits read	< 1 in 10 <sup>17</sup> bits read	< 1 in 10 <sup>17</sup> bits read	< 1 in 10 <sup>17</sup> bits read
MTBF	2,000,000 hours	2,000,000 hours	2,000,000 hours	2,000,000 hours	2,000,000 hours
IOPS reads (4 KB blocks)	230,000	230,000	230,000	230,000	230,000
IOPS writes (4 KB blocks)	40,000	60,000	85,000	90,000	65,000
Sequential read rate (128 KB blocks)	1,000 MBps	1,000 MBps	1,000 MBps	1,000 MBps	1,000 MBps
Sequential write rate (128 KB blocks)	1,000 MBps	1,000 MBps	1,000 MBps	1,000 MBps	1,000 MBps
Read latency (sequential)	240 µs	240 µs	240 µs	240 µs	240 µs
Write latency (sequential)	220 µs	220 µs	220 µs	220 µs	220 µs
Read latency (random)	120 µs	120 µs	120 µs	130 µs	130 µs
Write latency (random)	45 µs	45 µs	45 µs	45 µs	45 µs
Shock, non-operating	1,500 G (Max) at 0.5 ms	1,500 G (Max) at 0.5 ms	1,500 G (Max) at 0.5 ms	1,500 G (Max) at 0.5 ms	1,500 G (Max) at 0.5 ms
Vibration, non-operating	20 G <sub>RMS</sub> (10-2000 Hz)	20 G <sub>RMS</sub> (10-2000 Hz)	20 G <sub>RMS</sub> (10-2000 Hz)	20 G <sub>RMS</sub> (10-2000 Hz)	20 G <sub>RMS</sub> (10-2000 Hz)
Typical power (R / W)	9 W / 12 W	9 W / 12 W	9 W / 12 W	9 W / 12 W	9 W / 12 W

## Server support

The following tables list the ThinkSystem servers that are compatible.

Table 3. Server support (Part 1 of 4)

Part Number	Description	AMD V3				2S Intel V3/V4						4S 8S Intel V3			Multi Node V3/V4		1S V3				
		SR635 V3 (7D9H / 7D9G)	SR655 V3 (7D9F / 7D9E)	SR645 V3 (7D9D / 7D9C)	SR665 V3 (7D9B / 7D9A)	ST650 V3 (7D7B / 7D7A)	SR630 V3 (7D72 / 7D73)	SR650 V3 (7D75 / 7D76)	SR630 V4 (7DG8 / 7DG9)	SR650 V4 (7DGC / 7DGD)	SR650a V4 (7DGC / 7DGD)	SR850 V3 (7D97 / 7D96)	SR860 V3 (7D94 / 7D93)	SR950 V3 (7DC5 / 7DC4)	SD535 V3 (7DD8 / 7DD1)	SD530 V3 (7DDA / 7DD3)	SD550 V3 (7DD9 / 7DD2)	ST45 V3 (7DH4 / 7DH5)	ST50 V3 (7DF4 / 7DF3)	ST250 V3 (7DCF / 7DCE)	SR250 V3 (7DCM / 7DCL)
<b>2.5-inch hot-swap drives</b>																					
4XB7A38175	ThinkSystem 2.5" PM1643a 960GB Entry SAS 12Gb Hot Swap SSD	N	N	N	N	N	N	N	N	N	N	N	N	N	N	N	N	N	N	N	N
4XB7A38176	ThinkSystem 2.5" PM1643a 1.92TB Entry SAS 12Gb Hot Swap SSD	N	N	N	N	N	N	N	N	N	N	N	N	N	N	N	N	N	N	N	N
4XB7A17054	ThinkSystem 2.5" PM1643a 3.84TB Entry SAS 12Gb Hot Swap SSD	N	N	N	N	N	N	N	N	N	N	N	N	N	N	N	N	N	N	N	N
4XB7A17055	ThinkSystem 2.5" PM1643a 7.68TB Entry SAS 12Gb Hot Swap SSD	N	N	N	N	N	N	N	N	N	N	N	N	N	N	N	N	N	N	N	N
4XB7A17056	ThinkSystem 2.5" PM1643a 15.36TB Entry SAS 12Gb Hot Swap SSD	N	N	N	N	N	N	N	N	N	N	N	N	N	N	N	N	N	N	N	N
<b>3.5-inch hot-swap drives</b>																					
4XB7A17058	ThinkSystem 3.5" PM1643a 3.84TB Entry SAS 12Gb Hot Swap SSD	N	N	N	N	N	N	N	N	N	N	N	N	N	N	N	N	N	N	N	N
4XB7A17059	ThinkSystem 3.5" PM1643a 7.68TB Entry SAS 12Gb Hot Swap SSD	N	N	N	N	N	N	N	N	N	N	N	N	N	N	N	N	N	N	N	N

Table 4. Server support (Part 2 of 4)

Part Number	Description	GPU Rich					Edge					Super Computing							
		SR670 V2 (7Z22 / 7Z23)	SR675 V3 (7D9Q / 7D9R)	SR680a V3 (7DHE)	SR685a V3 (7DHC)	SR780a V3 (7DJ5)	SE100 (7DGR)	SE350 (7Z46 / 7D1X)	SE350 V2 (7DA9)	SE360 V2 (7DAM)	SE450 (7D8T)	SE455 V3 (7DBY)	SC750 V4 (7DDJ)	SC777 V4 (7DKA)	SD665 V3 (7D9P)	SD665-N V3 (7DAZ)	SD650 V3 (7D7M)	SD650-I V3 (7D7L)	SD650-N V3 (7D7N)
<b>2.5-inch hot-swap drives</b>																			
4XB7A38175	ThinkSystem 2.5" PM1643a 960GB Entry SAS 12Gb Hot Swap SSD	Y	N	N	N	N	N	N	N	N	N	N	N	N	N	N	N	N	N
4XB7A38176	ThinkSystem 2.5" PM1643a 1.92TB Entry SAS 12Gb Hot Swap SSD	Y	N	N	N	N	N	N	N	N	N	N	N	N	N	N	N	N	N
4XB7A17054	ThinkSystem 2.5" PM1643a 3.84TB Entry SAS 12Gb Hot Swap SSD	Y	N	N	N	N	N	N	N	N	N	N	N	N	N	N	N	N	N
4XB7A17055	ThinkSystem 2.5" PM1643a 7.68TB Entry SAS 12Gb Hot Swap SSD	Y	N	N	N	N	N	N	N	N	N	N	N	N	N	N	N	N	N
4XB7A17056	ThinkSystem 2.5" PM1643a 15.36TB Entry SAS 12Gb Hot Swap SSD	Y	N	N	N	N	N	N	N	N	N	N	N	N	N	N	N	N	N
<b>3.5-inch hot-swap drives</b>																			
4XB7A17058	ThinkSystem 3.5" PM1643a 3.84TB Entry SAS 12Gb Hot Swap SSD	N	N	N	N	N	N	N	N	N	N	N	N	N	N	N	N	N	N
4XB7A17059	ThinkSystem 3.5" PM1643a 7.68TB Entry SAS 12Gb Hot Swap SSD	N	N	N	N	N	N	N	N	N	N	N	N	N	N	N	N	N	N

Table 5. Server support (Part 3 of 4)

Part Number	Description	1S Intel V2			2S Intel V2			AMD V1			Dense V2			4S V2	8S				
		ST50 V2 (7D8K / 7D8J)	ST250 V2 (7D8G / 7D8F)	SR250 V2 (7D7R / 7D7Q)	ST650 V2 (7Z75 / 7Z74)	SR630 V2 (7Z70 / 7Z71)	SR650 V2 (7Z72 / 7Z73)	SR635 (7Y98 / 7Y99)	SR655 (7Y00 / 7Z01)	SR655 Client OS	SR645 (7D2Y / 7D2X)	SR665 (7D2W / 7D2V)	SD630 V2 (7D1K)	SD650 V2 (7D1M)	SD650-N V2 (7D1N)	SN550 V2 (7Z69)	SR850 V2 (7D31 / 7D32)	SR860 V2 (7Z59 / 7Z60)	SR950 (7X11 / 7X12)
<b>2.5-inch hot-swap drives</b>																			
4XB7A38175	ThinkSystem 2.5" PM1643a 960GB Entry SAS 12Gb Hot Swap SSD	N	N	N	Y	Y	Y	Y	Y	N	Y	Y	N	N	N	N	Y	Y	Y
4XB7A38176	ThinkSystem 2.5" PM1643a 1.92TB Entry SAS 12Gb Hot Swap SSD	N	N	N	Y	Y	Y	Y	Y	N	Y	Y	N	N	N	N	Y	Y	Y
4XB7A17054	ThinkSystem 2.5" PM1643a 3.84TB Entry SAS 12Gb Hot Swap SSD	N	N	N	Y	Y	Y	Y	Y	N	Y	Y	N	N	N	N	Y	Y	Y
4XB7A17055	ThinkSystem 2.5" PM1643a 7.68TB Entry SAS 12Gb Hot Swap SSD	N	N	N	Y	Y	Y	Y	Y	N	Y	Y	N	N	N	N	Y	Y	Y
4XB7A17056	ThinkSystem 2.5" PM1643a 15.36TB Entry SAS 12Gb Hot Swap SSD	N	N	N	Y	Y	Y	N	N	N	Y	Y	N	N	N	N	Y	Y	Y
<b>3.5-inch hot-swap drives</b>																			
4XB7A17058	ThinkSystem 3.5" PM1643a 3.84TB Entry SAS 12Gb Hot Swap SSD	N	N	N	Y	Y	Y	Y	Y	N	Y	Y	N	N	N	N	N	N	N
4XB7A17059	ThinkSystem 3.5" PM1643a 7.68TB Entry SAS 12Gb Hot Swap SSD	N	N	N	Y	Y	Y	Y	Y	N	Y	Y	N	N	N	N	N	N	N

Table 6. Server support (Part 4 of 4)

Part Number	Description	4S V1			1S Intel V1			2S Intel V1						Dense V1						
		SR850 (7X18 / 7X19)	SR850P (7D2F / 2D2G)	SR860 (7X69 / 7X70)	ST50 (7Y48 / 7Y50)	ST250 (7Y45 / 7Y46)	SR150 (7Y54)	SR250 (7Y52 / 7Y51)	ST550 (7X09 / 7X10)	SR530 (7X07 / 7X08)	SR550 (7X03 / 7X04)	SR570 (7Y02 / 7Y03)	SR590 (7X98 / 7X99)	SR630 (7X01 / 7X02)	SR650 (7X05 / 7X06)	SR670 (7Y36 / 7Y37)	SD530 (7X21)	SD650 (7X58)	SN550 (7X16)	SN850 (7X15)
<b>2.5-inch hot-swap drives</b>																				
4XB7A38175	ThinkSystem 2.5" PM1643a 960GB Entry SAS 12Gb Hot Swap SSD	Y	Y	Y	N	N	N	N	Y	Y	Y	Y	Y	Y	Y	N	Y	N	Y	Y
4XB7A38176	ThinkSystem 2.5" PM1643a 1.92TB Entry SAS 12Gb Hot Swap SSD	Y	Y	Y	N	N	N	N	Y	Y	Y	Y	Y	Y	Y	N	Y	N	Y	Y
4XB7A17054	ThinkSystem 2.5" PM1643a 3.84TB Entry SAS 12Gb Hot Swap SSD	Y	Y	Y	N	N	N	N	Y	Y	Y	Y	Y	Y	Y	N	Y	N	Y	Y
4XB7A17055	ThinkSystem 2.5" PM1643a 7.68TB Entry SAS 12Gb Hot Swap SSD	Y	Y	Y	N	N	N	N	Y	Y	Y	Y	Y	Y	Y	N	Y	N	Y	Y
4XB7A17056	ThinkSystem 2.5" PM1643a 15.36TB Entry SAS 12Gb Hot Swap SSD	Y	N	Y	N	N	N	N	N	Y	Y	Y	Y	Y	Y	N	Y	N	Y	Y
<b>3.5-inch hot-swap drives</b>																				
4XB7A17058	ThinkSystem 3.5" PM1643a 3.84TB Entry SAS 12Gb Hot Swap SSD	N	N	N	N	N	N	N	Y	Y	Y	Y	Y	Y	Y	N	N	N	N	N
4XB7A17059	ThinkSystem 3.5" PM1643a 7.68TB Entry SAS 12Gb Hot Swap SSD	N	N	N	N	N	N	N	Y	Y	Y	Y	Y	Y	Y	N	N	N	N	N

## Operating system support

SAS and SATA SSDs operate transparently to users, storage systems, applications, databases, and operating systems.

Operating system support is based on the controller used to connect to the drives. Consult the controller product guide for more information:

- RAID controllers: <https://lenovopress.com/servers/options/raid>
- SAS HBAs: <https://lenovopress.com/servers/options/hba>

## Warranty

The PM1643a Entry SAS 12Gb SSDs carry a one-year, customer-replaceable unit (CRU) limited warranty. When the SSDs are installed in a supported server, these drives assume the server's base warranty and any warranty upgrades.

Solid State Memory cells have an intrinsic, finite number of program/erase cycles that each cell can incur. As a result, each solid state device has a maximum amount of program/erase cycles to which it can be subjected. The warranty for Lenovo solid state drives (SSDs) is limited to drives that have not reached the maximum guaranteed number of program/erase cycles, as documented in the Official Published Specifications for the SSD product. A drive that reaches this limit may fail to operate according to its Specifications.



## Physical specifications

The PM1643a Entry SAS 12Gb SSDs have the following physical specifications:

Dimensions and weight (approximate, without the hot-swap tray, if applicable):

- Height: 15 mm (0.6 in.)
- Width: 70 mm (2.8 in.)
- Depth: 100 mm (4.0 in.)
- Weight: 158 g (5.6 oz)

Shipping dimensions and weight for the 2.5-inch drives (approximate):

- Height: 63 mm (2.5 in.)
- Width: 133 mm (5.2 in.)
- Depth: 174 mm (6.9 in.)

Shipping dimensions and weight for the 3.5-inch drives (approximate):

- Height: 95 mm (3.7 in.)
- Width: 194 mm (7.6 in.)
- Depth: 257 mm (10.0 in.)

## Operating environment

The PM1643a Entry SAS 12Gb SSDs are supported in the following environment:

- Temperature, operating: 0 - 70 °C (32 - 158 °F)
- Temperature, non-operating: -40 to 85 °C (-40 - 185 °F)
- Relative humidity: 5 - 95% (noncondensing)
- Maximum altitude: -300 - 4,572 m (-1,000 to 15,000 feet)

## Agency approvals

The PM1643a Entry SAS 12Gb SSDs conform to the following regulations:

- UL
- TUV
- FCC
- IC
- CB
- CE Mark
- C-Tick Mark
- BSMI (Taiwan)
- KCC (Korea EMI)
- VCCI

## Related publications and links

For more information, see the following documents:

- Lenovo Press product guides and papers on RAID adapters and HBAs  
<https://lenovopress.com/servers/options/raid>
- Lenovo RAID Management Tools and Resources  
<https://lenovopress.com/lp0579-lenovo-raid-management-tools-and-resources>
- Lenovo RAID Introduction  
<https://lenovopress.com/lp0578-lenovo-raid-introduction>
- Samsung Enterprise SSDs home page  
<https://www.samsung.com/semiconductor/ssd/enterprise-ssd/>

## Related product families

Product families related to this document are the following:

- [Drives](#)

## Notices

Lenovo may not offer the products, services, or features discussed in this document in all countries. Consult your local Lenovo representative for information on the products and services currently available in your area. Any reference to a Lenovo product, program, or service is not intended to state or imply that only that Lenovo product, program, or service may be used. Any functionally equivalent product, program, or service that does not infringe any Lenovo intellectual property right may be used instead. However, it is the user's responsibility to evaluate and verify the operation of any other product, program, or service. Lenovo may have patents or pending patent applications covering subject matter described in this document. The furnishing of this document does not give you any license to these patents. You can send license inquiries, in writing, to:

Lenovo (United States), Inc.  
8001 Development Drive  
Morrisville, NC 27560  
U.S.A.  
Attention: Lenovo Director of Licensing

LENOVO PROVIDES THIS PUBLICATION "AS IS" WITHOUT WARRANTY OF ANY KIND, EITHER EXPRESS OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF NON-INFRINGEMENT, MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE. Some jurisdictions do not allow disclaimer of express or implied warranties in certain transactions, therefore, this statement may not apply to you.

This information could include technical inaccuracies or typographical errors. Changes are periodically made to the information herein; these changes will be incorporated in new editions of the publication. Lenovo may make improvements and/or changes in the product(s) and/or the program(s) described in this publication at any time without notice.

The products described in this document are not intended for use in implantation or other life support applications where malfunction may result in injury or death to persons. The information contained in this document does not affect or change Lenovo product specifications or warranties. Nothing in this document shall operate as an express or implied license or indemnity under the intellectual property rights of Lenovo or third parties. All information contained in this document was obtained in specific environments and is presented as an illustration. The result obtained in other operating environments may vary. Lenovo may use or distribute any of the information you supply in any way it believes appropriate without incurring any obligation to you.

Any references in this publication to non-Lenovo Web sites are provided for convenience only and do not in any manner serve as an endorsement of those Web sites. The materials at those Web sites are not part of the materials for this Lenovo product, and use of those Web sites is at your own risk. Any performance data contained herein was determined in a controlled environment. Therefore, the result obtained in other operating environments may vary significantly. Some measurements may have been made on development-level systems and there is no guarantee that these measurements will be the same on generally available systems. Furthermore, some measurements may have been estimated through extrapolation. Actual results may vary. Users of this document should verify the applicable data for their specific environment.

© Copyright Lenovo 2025. All rights reserved.

This document, LP1257, was created or updated on April 8, 2024.

Send us your comments in one of the following ways:

- Use the online Contact us review form found at:  
<https://lenovopress.lenovo.com/LP1257>
- Send your comments in an e-mail to:  
[comments@lenovopress.com](mailto:comments@lenovopress.com)

This document is available online at <https://lenovopress.lenovo.com/LP1257>.

## Trademarks

Lenovo and the Lenovo logo are trademarks or registered trademarks of Lenovo in the United States, other countries, or both. A current list of Lenovo trademarks is available on the Web at <https://www.lenovo.com/us/en/legal/copytrade/>.

The following terms are trademarks of Lenovo in the United States, other countries, or both:

Lenovo®

ServerProven®

ThinkSystem®

The following terms are trademarks of other companies:

AMD is a trademark of Advanced Micro Devices, Inc.

Intel® is a trademark of Intel Corporation or its subsidiaries.

Other company, product, or service names may be trademarks or service marks of others.