



World Record Result for SAP BW Edition for SAP HANA Benchmark (31.2B Records) on Lenovo ThinkSystem SR950


Performance Benchmark Result

Lenovo ThinkSystem SR950 8-socket server using Intel Xeon Platinum 8280 processors delivers world record performance (1) for the SAP BW Edition for SAP HANA Benchmark, Version 3, with 31.2 billion (31.2B) initial records in a single-node setup.

The benchmark refers to the SAP Business Warehouse (SAP BW) application running on the SAP HANA platform.

The SR950 configuration was as follows:

- Lenovo ThinkSystem SR950
- Eight Intel Xeon Platinum 8280 Processors, 2.70 GHz
- 64 KB L1 cache, 1024 KB L2 cache and 38.5 MB L3 cache per processor
- 8 processor, 224 total cores, 448 total threads
- 6,144 GB system memory DRAM
- 12,288 GB of Intel Optane DC Persistent Memory
- SUSE Linux Enterprise Server 12 SP4
- SAP HANA 2.0 rev45
- SAP NetWeaver 7.50



- Phase 1: Data load phase = 45,151 (Runtime of last Data Set in seconds)
- Phase 2: Query throughput phase = 2,384 (Query Executions per Hour)
- Phase 3: Query runtime phase = 231 (Total Runtime of complex query phase in seconds)

The result shows that the Lenovo ThinkSystem SR950 offers a performance advantage compared to other vendors.

Results referenced are current as of February 20, 2020. For the latest SAP BW benchmark results, visit: https://www.sap.com/dmc/exp/2018-benchmark-directory/#/bwh.

(1) This benchmark fully complies with the SAP Benchmark Council regulations and has been audited and certified by SAP SE (certification number 2020006). Details can be obtained from Lenovo and SAP. The benchmark was performed at the Lenovo Data Center Performance Lab in Walldorf, Germany, by Lenovo engineers. Configuration: ThinkSystem SR950, 8 processor / 224 cores / 448 threads, Intel Xeon Platinum 8280 processors, 2.70 GHz, 64 KB L1 cache and 1024 KB L2 cache per core, 38.5 MB L3 cache per processor, 6,144 GB (DRAM) plus 12,288 GB (PMEM) main memory.



About the ThinkSystem SR950

Lenovo ThinkSystem SR950 is designed for your most demanding, mission-critical workloads, such as in-memory databases, large transactional databases, batch and real-time analytics, ERP, CRM, and virtualized server workloads. The powerful 4U ThinkSystem SR950 can grow from two to eight second-generation Intel Xeon Scalable Family processors, and with 96 DIMM sockets, supports up to 24 TB of high-speed memory. The modular design of SR950 speeds upgrades and servicing with easy front or rear access to all major subsystems to maximize server availability. The ThinkSystem SR950 also supports Intel Optane DC Persistent Memory delivering a new, flexible tier of memory designed specifically for data center workloads that offer an unprecedented combination of high-capacity, affordability and persistence.

The SR950 packs numerous fault-tolerant and high-availability features into a high-density, 4U rack-optimized design that reduces the space needed to support massive network computing operations and simplify servicing. Lenovo XClarity Controller is an all-new hardware embedded management engine common in every ThinkSystem server. XClarity Controller features an uncluttered graphical user interface, industry standard Redfish-compliant REST APIs, and enables booting in half the time of prior generation servers, with up to 6x faster firmware updates.

Lenovo XClarity Administrator is a virtualized application that centrally manages ThinkSystem servers, storage, and networking. Via reusable patterns and policies, it ramps up and scales infrastructure provisioning and maintenance. It serves as a central integration point to extend your data center management processes to physical IT. Running XClarity Integrators in external IT applications, or integrating through REST APIs, helps you further speed services provisioning, streamline IT management, and contain costs.

ThinkShield is a comprehensive approach to security designed to secure the data center, from the foundation of your infrastructure to the network's edge and guard against a security breach. ThinkShield protects your business with each offering, from development through disposal.

About the SAP BW edition for SAP HANA Benchmark

The SAP BW, edition for SAP HANA Standard Application Benchmark, Version 3, is the latest addition to the list of benchmarks for SAP Business Warehouse. It utilizes the capabilities of SAP HANA to process the benchmark workload. Allowed data volumes are a multiple of 1.3 billion initial records and can be run in single-node and multi-node setups. This benchmark was released in July 2018.

The benchmark scenario represents typical mid-size customer scenario and volumes for SAP BW running on SAP HANA. The benchmark simulates a variety of users with different analytical requirements and measures the key performance indicator (KPI) relevant to each of the three benchmark phases.

The three benchmark phases are as follows:

- 1. Data load phase, testing data latency and load performance
- 2. Query throughput phase, testing query throughput with moderate complex queries
- 3. Query runtime phase, testing the performance of running very complex queries

For more information about the benchmark, go to https://www.sap.com/about/benchmark.html.

Learn more

To learn more about business warehouse and data analytics solutions for SAP applications running on Lenovo Servers visit, https://www.lenovo.com/us/en/data-center/solutions/sap/ or contact your Lenovo Customer Representative.

To learn more about the Lenovo ThinkSystem SR950 server, visit the SR950 product web page.

Related product families

Product families related to this document are the following:

- 8-Socket Rack Servers
- Mission Critical Servers
- SAP Alliance
- SAP BW Benchmark Results
- ThinkSystem SR950 Server

Notices

Lenovo may not offer the products, services, or features discussed in this document in all countries. Consult your local Lenovo representative for information on the products and services currently available in your area. Any reference to a Lenovo product, program, or service is not intended to state or imply that only that Lenovo product, program, or service may be used. Any functionally equivalent product, program, or service that does not infringe any Lenovo intellectual property right may be used instead. However, it is the user's responsibility to evaluate and verify the operation of any other product, program, or service. Lenovo may have patents or pending patent applications covering subject matter described in this document. The furnishing of this document does not give you any license to these patents. You can send license inquiries, in writing, to:

Lenovo (United States), Inc. 8001 Development Drive Morrisville, NC 27560 U.S.A.

Attention: Lenovo Director of Licensing

LENOVO PROVIDES THIS PUBLICATION "AS IS" WITHOUT WARRANTY OF ANY KIND, EITHER EXPRESS OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF NON-INFRINGEMENT, MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE. Some jurisdictions do not allow disclaimer of express or implied warranties in certain transactions, therefore, this statement may not apply to you.

This information could include technical inaccuracies or typographical errors. Changes are periodically made to the information herein; these changes will be incorporated in new editions of the publication. Lenovo may make improvements and/or changes in the product(s) and/or the program(s) described in this publication at any time without notice.

The products described in this document are not intended for use in implantation or other life support applications where malfunction may result in injury or death to persons. The information contained in this document does not affect or change Lenovo product specifications or warranties. Nothing in this document shall operate as an express or implied license or indemnity under the intellectual property rights of Lenovo or third parties. All information contained in this document was obtained in specific environments and is presented as an illustration. The result obtained in other operating environments may vary. Lenovo may use or distribute any of the information you supply in any way it believes appropriate without incurring any obligation to you.

Any references in this publication to non-Lenovo Web sites are provided for convenience only and do not in any manner serve as an endorsement of those Web sites. The materials at those Web sites are not part of the materials for this Lenovo product, and use of those Web sites is at your own risk. Any performance data contained herein was determined in a controlled environment. Therefore, the result obtained in other operating environments may vary significantly. Some measurements may have been made on development-level systems and there is no guarantee that these measurements will be the same on generally available systems. Furthermore, some measurements may have been estimated through extrapolation. Actual results may vary. Users of this document should verify the applicable data for their specific environment.

© Copyright Lenovo 2024. All rights reserved.

This document, LP1297, was created or updated on March 30, 2020.

Send us your comments in one of the following ways:

- Use the online Contact us review form found at: https://lenovopress.lenovo.com/LP1297
- Send your comments in an e-mail to: comments@lenovopress.com

This document is available online at https://lenovopress.lenovo.com/LP1297.

Trademarks

Lenovo and the Lenovo logo are trademarks or registered trademarks of Lenovo in the United States, other countries, or both. A current list of Lenovo trademarks is available on the Web at https://www.lenovo.com/us/en/legal/copytrade/.

The following terms are trademarks of Lenovo in the United States, other countries, or both: Lenovo®
ThinkShield®
ThinkSystem®
XClarity®

The following terms are trademarks of other companies:

Intel®, Intel Optane®, and Xeon® are trademarks of Intel Corporation or its subsidiaries.

Linux® is the trademark of Linus Torvalds in the U.S. and other countries.

Other company, product, or service names may be trademarks or service marks of others.