

ThinkSystem PM1733 Entry NVMe PCIe 4.0 x4 SSDs Product Guide (withdrawn product)

The ThinkSystem PM1733 Entry NVMe PCIe solid-state drives (SSDs), available in capacities up to 15.36TB, are general-purpose yet high-performance NVMe PCIe SSDs. They are engineered for greater performance and endurance in a cost-effective design, and to support a broader set of workloads.



Figure 1. ThinkSystem PM1733 Entry

NVMe PCIe 4.0 x4 SSD

Did you know?

The PM1733 family of SSDs are the first PCIe 4.0 SSDs in the ThinkSystem portfolio. By having a Gen 4 host interface, sequential performance is doubled. The NVMe host interface also maximizes flash storage performance and minimizes latency. The PM1733 drives offer 40% and 60% improvements in latency over SAS and SATA SSDs respectively.

Lenovo Entry SSDs are suitable for read-intensive and general-purpose data center workloads, however their NVMe PCIe interface means the drives also offer high performance. Overall, these SSDs provide outstanding IOPS/watt and cost/IOPS for enterprise solutions.

Part number information

The following table lists the part numbers and feature codes for ThinkSystem servers.

Withdrawn: The drives listed in this product guide are now withdrawn from marketing.

Table 1. Ordering information

Part number	Feature code	Description
4XB7A38196	BC4Y	ThinkSystem U.2 PM1733 1.92TB Entry NVMe PCIe 4.0 x4 Hot Swap SSD
4XB7A38197	BC4Z	ThinkSystem U.2 PM1733 3.84TB Entry NVMe PCIe 4.0 x4 Hot Swap SSD
4XB7A38283	BE2E	ThinkSystem U.2 PM1733 7.68TB Entry NVMe PCIe 4.0 x4 Hot Swap SSD
4XB7A38284	BE2F	ThinkSystem U.2 PM1733 15.36TB Entry NVMe PCIe 4.0 x4 Hot Swap SSD

The part numbers include the following items:

- One solid-state drive
- Documentation flyer

Features

Non-Volatile Memory Express (NVMe) is PCIe high performance SSD technology that provides high I/O throughput and low latency. NVMe interfaces remove SAS/SATA bottlenecks and unleash all of the capabilities of contemporary NAND flash memory. Each NVMe PCI SSD has direct PCIe x4 connection, which provides at significantly greater bandwidth and lower latency than SATA/SAS-based SSD solutions. NVMe drives are also optimized for heavy multi-threaded workloads by using internal parallelism and many other improvements, such as enlarged I/O queues.

The PM1733 Entry NVMe PCIe SSD have the following features:

- Direct PCIe 4.0 x4 connection for each NVMe drive, resulting in up to 7 GBps overall throughput.
- Also supports PCIe 3.0 host connection for servers with first and second-generation Intel Xeon Scalable processors or with PCIe 3.0 NVMe switch adapters
- Low cost, read-intensive SSD from Samsung using TLC flash technology
- Advanced ECC Engine and End-to-End Data Protection
- Samsung's SSD virtualization technology allows a single SSD to be subdivided into smaller SSDs, up to 64, providing independent virtual workspaces. It also enables SSDs to take on certain tasks typically carried out by the server CPUs, such as Single-Root I/O Virtualization (SR-IOV), requiring fewer server CPUs and SSDs.
- V-NAND Machine Learning enables the SSD to accurately predict and verify cell characteristics, as well as detect any variations in circuit patterns.
- Fail-In-Place technology ensures the SSD operates normally even when errors occur at the chip level. It allows the PM1733 to identify failing NAND cells, and actually recover then relocate the data without interrupting normal operations or impacting performance.
- Protect data integrity from unexpected power loss with Samsung's advanced power-loss protection architecture
- Supports Self-Monitoring, Analysis and Reporting Technology (S.M.A.R.T).

Entry SSDs and Performance SSDs have similar read IOPS performance, but the key difference between them is their endurance -- how long they can reliably perform write operations. Entry SSDs have a better

cost/IOPS ratio but lower endurance compared to Performance SSDs. SSD write endurance is typically measured by the number of program/erase (P/E) write cycles that the drive incurs over its lifetime, listed as the total bytes of written data (TBW) in the device specification.

The TBW value assigned to a solid-state device is the total bytes of written data (based on the number of P/E cycles) that a drive can be guaranteed to complete (% of remaining P/E cycles = % of remaining TBW). Reaching this limit does not cause the drive to immediately fail. It simply denotes the maximum number of writes that can be guaranteed. A solid-state device will not fail upon reaching the specified TBW. At some point based on manufacturing variance margin, after surpassing the TBW value, the drive will reach the end-of-life point, at which the drive will go into a read-only mode.

Because of such behavior by Entry solid-state drives, careful planning must be done to use them only in read-intensive or mixed up to 70% read/30% write environments to ensure that the TBW of the drive will not be exceeded before the required life expectancy.

For example, the PM1733 1.92 TB drive has an endurance of 3,504 TB of total bytes written (TBW). This means that for full operation over five years, write workload must be limited to no more than 1,920 GB of writes per day, which is equivalent to 1.0 full drive writes per day (DWPD). For the device to last three years, the drive write workload must be limited to no more than 3,200 GB of writes per day, which is equivalent to 1.7 full drive writes per day.

Technical specifications

The following tables present the technical specifications for the PM1733 Entry NVMe PCIe SSDs. Note that the performance data and power consumption is based on whether the drives are connected to a PCIe 4.0 host interface or a PCIe 3.0 host interface.

Table 2. Technical specifications

Feature	1.92 TB drive	3.84 TB drive	7.68 TB drive	15.36 TB drive
Interface	PCIe 4.0 x4*	PCIe 4.0 x4*	PCIe 4.0 x4*	PCIe 4.0 x4*
Capacity	1.92 TB	3.84 TB	7.68 TB	15.36 TB
SED encryption	None	None	None	None
Endurance (drive writes per day for 5 years)	1 DWPD	1 DWPD	1 DWPD	1 DWPD
Endurance (total bytes written)	3504 TB	7008 TB	14,016 TB	28,032 TB
Data reliability (UBER)	< 1 in 10 ¹⁷ bits read	< 1 in 10 ¹⁷ bits read	< 1 in 10 ¹⁷ bits read	< 1 in 10 ¹⁷ bits read
MTBF	2,000,000 hours	2,000,000 hours	2,000,000 hours	2,000,000 hours
Performance & Power - PCIe 4.0 host interface				
IOPS reads (4 KB blocks)	800,000	1,500,000	1,450,000	1,450,000
IOPS writes (4 KB blocks)	100,000	135,000	135,000	135,000
Sequential read rate (128 KB blocks)	7000 MBps	7000 MBps	7000 MBps	7000 MBps
Sequential write rate (128 KB blocks)	2400 MBps	3500 MBps	3500 MBps	3500 MBps
Latency (random R/W)	100 µs / 25 µs	100 µs / 25 µs	100 µs / 25 µs	100 µs / 25 µs
Latency (sequential R/W)	220 µs / 80 µs	220 µs / 80 µs	220 µs / 80 µs	220 µs / 80 µs
Typical power (R/W)	15 W / 15 W	20 W / 20 W	20 W / 20 W	20 W / 22 W
Performance & Power - PCIe 3.0 host interface				
IOPS reads (4 KB blocks)	800,000	800,000	800,000	800,000
IOPS writes (4 KB blocks)	100,000	135,000	135,000	135,000
Sequential read rate (128 KB blocks)	3400 MBps	3400 MBps	3400 MBps	3400 MBps
Sequential write rate (128 KB blocks)	2400 MBps	3200 MBps	3200 MBps	3200 MBps
Latency (random R/W)	100 µs / 25 µs	100 µs / 25 µs	100 µs / 25 µs	100 µs / 25 µs
Latency (sequential R/W)	250 µs / 100 µs	250 µs / 100 µs	250 µs / 100 µs	250 µs / 100 µs
Typical power (R/W)	15 W / 15 W	15 W / 20 W	15 W / 20 W	15 W / 22 W

* Backwards compatible with a PCIe 3.0 x4 host interface

Server support

The following tables list the ThinkSystem servers that are compatible.

Table 3. Server support (Part 1 of 5)

Part Number	Description	AMD V3				2S Intel V3/V4						Multi Node V3		1S V3			
		SR635 V3 (7D9H / 7D9G)	SR655 V3 (7D9F / 7D9E)	SR645 V3 (7D9D / 7D9C)	SR665 V3 (7D9B / 7D9A)	ST650 V3 (7D7B / 7D7A)	SR630 V3 (7D72 / 7D73)	SR650 V3 (7D75 / 7D76)	SR630 V4 (7D68 / 7D69)	SR650 V4 (7D6C / 7D6D)	SR650a V4 (7D6C / 7D6D)	SD535 V3 (7DD8 / 7DD1)	SD530 V3 (7DDA / 7DD3)	SD550 V3 (7DD9 / 7DD2)	ST45 V3 (7DH4 / 7DH5)	ST50 V3 (7DF4 / 7DF3)	ST250 V3 (7DCF / 7DCE)
2.5-inch drives																	
4XB7A38196	ThinkSystem U.2 PM1733 1.92TB Entry NVMe PCIe 4.0 x4 Hot Swap SSD	N	N	N	N	N	N	N	N	N	N	N	N	N	N	N	N
4XB7A38197	ThinkSystem U.2 PM1733 3.84TB Entry NVMe PCIe 4.0 x4 Hot Swap SSD	N	N	N	N	N	N	N	N	N	N	N	N	N	N	N	N
4XB7A38283	ThinkSystem U.2 PM1733 7.68TB Entry NVMe PCIe 4.0 x4 Hot Swap SSD	N	N	N	N	N	N	N	N	N	N	N	N	N	N	N	N
4XB7A38284	ThinkSystem U.2 PM1733 15.36TB Entry NVMe PCIe 4.0 x4 Hot Swap SSD	N	N	N	N	N	N	N	N	N	N	N	N	N	N	N	N

Table 4. Server support (Part 2 of 5)

Part Number	Description	4S 8S Intel V3/V4				GPU Rich						Edge					
		SR850 V3 (7D97 / 7D96)	SR860 V3 (7D94 / 7D93)	SR950 V3 (7DC5 / 7DC4)	SR850 V4 (7DJT / 7DJS)	SR860 V4 (7DJQ / 7DJN)	SR670 V2 (7Z22 / 7Z23)	SR675 V3 (7D9Q / 7D9R)	SR680a V3 (7DHE)	SR680a V3 B200 (7DM9)	SR685a V3 (7DHC)	SR780a V3 (7DJ5)	SR680a V4 (7DMK)	SE100 (7DGR)	SE350 (7Z46 / 7D1X)	SE350 V2 (7DA9)	SE360 V2 (7DAM)
2.5-inch drives																	
4XB7A38196	ThinkSystem U.2 PM1733 1.92TB Entry NVMe PCIe 4.0 x4 Hot Swap SSD	N	N	N	N	N	N	N	N	N	N	N	N	N	N	N	N
4XB7A38197	ThinkSystem U.2 PM1733 3.84TB Entry NVMe PCIe 4.0 x4 Hot Swap SSD	N	N	N	N	N	N	N	N	N	N	N	N	N	N	N	N
4XB7A38283	ThinkSystem U.2 PM1733 7.68TB Entry NVMe PCIe 4.0 x4 Hot Swap SSD	N	N	N	N	N	N	N	N	N	N	N	N	N	N	N	N

Part Number	Description	4S 8S Intel V3/V4				GPU Rich				Edge									
		SR850 V3 (7D97 / 7D96)	SR860 V3 (7D94 / 7D93)	SR950 V3 (7DC5 / 7DC4)	SR850 V4 (7DJT / 7DJS)	SR860 V4 (7DJQ / 7DJN)	SR670 V2 (7Z22 / 7Z23)	SR675 V3 (7D9Q / 7D9R)	SR680a V3 (7DHE)	SR680a V3 B200 (7DM9)	SR685a V3 (7DHC)	SR780a V3 (7DJ5)	SR680a V4 (7DMK)	SE100 (7DGR)	SE350 (7Z46 / 7D1X)	SE350 V2 (7DA9)	SE360 V2 (7DAM)	SE450 (7D8T)	SE455 V3 (7DBY)
4XB7A38284	ThinkSystem U.2 PM1733 15.36TB Entry NVMe PCIe 4.0 x4 Hot Swap SSD	N	N	N	N	N	N	N	N	N	N	N	N	N	N	N	N	N	N

Table 5. Server support (Part 3 of 5)

Part Number	Description	Super Computing				1S Intel V2	2S Intel V2	AMD V1										
		SC750 V4 (7DDJ)	SC777 V4 (7DKA)	SD665 V3 (7D9P)	SD665-N V3 (7DAZ)	SD650 V3 (7D7M)	SD650-I V3 (7D7L)	SD650-N V3 (7D7N)	ST50 V2 (7D8K / 7D8J)	ST250 V2 (7D8G / 7D8F)	SR250 V2 (7D7R / 7D7Q)	ST650 V2 (7Z75 / 7Z74)	SR630 V2 (7Z70 / 7Z71)	SR650 V2 (7Z72 / 7Z73)	SR635 (7Y98 / 7Y99)	SR655 (7Y00 / 7Z01)	SR645 (7D2Y / 7D2X)	SR665 (7D2W / 7D2V)
2.5-inch drives																		
4XB7A38196	ThinkSystem U.2 PM1733 1.92TB Entry NVMe PCIe 4.0 x4 Hot Swap SSD	N	N	N	N	N	N	N	N	N	N	N	Y	Y	Y	Y	Y	Y
4XB7A38197	ThinkSystem U.2 PM1733 3.84TB Entry NVMe PCIe 4.0 x4 Hot Swap SSD	N	N	N	N	N	N	N	N	N	N	N	Y	Y	Y	Y	Y	Y
4XB7A38283	ThinkSystem U.2 PM1733 7.68TB Entry NVMe PCIe 4.0 x4 Hot Swap SSD	N	N	N	N	N	N	N	N	N	N	N	Y	Y	Y	Y	Y	Y
4XB7A38284	ThinkSystem U.2 PM1733 15.36TB Entry NVMe PCIe 4.0 x4 Hot Swap SSD	N	N	N	N	N	N	N	N	N	N	N	Y	Y	Y	Y	Y	Y

Table 6. Server support (Part 4 of 5)

Part Number	Description	Dense V2				4S V2	8S	4S V1			1S Intel V1			
		SD630 V2 (7D1K)	SD650 V2 (7D1M)	SD650-N V2 (7D1N)	SN550 V2 (7Z69)	SR850 V2 (7D31 / 7D32)	SR860 V2 (7Z59 / 7Z60)	SR950 (7X11 / 7X12)	SR850 (7X18 / 7X19)	SR850P (7D2F / 2D2G)	SR860 (7X69 / 7X70)	ST50 (7Y48 / 7Y50)	ST250 (7Y45 / 7Y46)	SR150 (7Y54)
2.5-inch drives														
4XB7A38196	ThinkSystem U.2 PM1733 1.92TB Entry NVMe PCIe 4.0 x4 Hot Swap SSD	N	N	N	N	N	N	N	N	N	N	N	N	N
4XB7A38197	ThinkSystem U.2 PM1733 3.84TB Entry NVMe PCIe 4.0 x4 Hot Swap SSD	N	N	N	N	N	N	N	N	N	N	N	N	N
4XB7A38283	ThinkSystem U.2 PM1733 7.68TB Entry NVMe PCIe 4.0 x4 Hot Swap SSD	N	N	N	N	N	N	N	N	N	N	N	N	N
4XB7A38284	ThinkSystem U.2 PM1733 15.36TB Entry NVMe PCIe 4.0 x4 Hot Swap SSD	N	N	N	N	N	N	N	N	N	N	N	N	N

Table 7. Server support (Part 5 of 5)

Part Number	Description	2S Intel V1							Dense V1				
		ST550 (7X09 / 7X10)	SR530 (7X07 / 7X08)	SR550 (7X03 / 7X04)	SR570 (7Y02 / 7Y03)	SR590 (7X98 / 7X99)	SR630 (7X01 / 7X02)	SR650 (7X05 / 7X06)	SR670 (7Y36 / 7Y37)	SD530 (7X21)	SD650 (7X58)	SN550 (7X16)	SN850 (7X15)
2.5-inch drives													
4XB7A38196	ThinkSystem U.2 PM1733 1.92TB Entry NVMe PCIe 4.0 x4 Hot Swap SSD	N	N	N	N	N	N	N	N	N	N	N	N
4XB7A38197	ThinkSystem U.2 PM1733 3.84TB Entry NVMe PCIe 4.0 x4 Hot Swap SSD	N	N	N	N	N	Y	Y	N	N	N	N	N
4XB7A38283	ThinkSystem U.2 PM1733 7.68TB Entry NVMe PCIe 4.0 x4 Hot Swap SSD	N	N	N	N	N	Y	Y	N	N	N	N	N
4XB7A38284	ThinkSystem U.2 PM1733 15.36TB Entry NVMe PCIe 4.0 x4 Hot Swap SSD	N	N	N	N	N	Y	Y	N	N	N	N	N

Storage controller support

NVMe PCIe SSDs require a NVMe drive backplane and some form of PCIe connection to processors. PCIe connections can take the form of either an adapter (PCIe Interposer or PCIe extender) or simply a cable that connects to an onboard NVMe connector.

Consult the relevant server product guide for details about required components for NVMe drive support.

Operating system support

The following tables list the supported operating systems.

Tip: These tables are automatically generated based on data from [Lenovo ServerProven](#).

Table 8. Operating system support for ThinkSystem U.2 PM1733 3.84TB Entry NVMe PCIe 4.0 x4 Hot Swap SSD, 4XB7A38197

Operating systems	SR630 (Xeon Gen 2)	SR650 (Xeon Gen 2)	SR635	SR655	SR645	SR665	SR630 (Xeon Gen 1)	SR650 (Xeon Gen 1)	SR650 V2
Microsoft Windows 10	N	N	N	Y ²	N	N	N	N	N
Microsoft Windows 11	N	N	N	Y ²	N	N	N	N	N
Microsoft Windows Server 2012 R2	N	N	N	N	N	N	Y	Y	N
Microsoft Windows Server 2016	Y	Y	Y	Y	Y	Y	Y	Y	Y
Microsoft Windows Server 2019	Y	Y	Y	Y	Y	Y	Y	Y	Y
Microsoft Windows Server 2022	Y	Y	Y	Y	Y	Y	Y	Y	Y
Microsoft Windows Server 2025	N	N	N	N	Y	Y	N	N	Y
Red Hat Enterprise Linux 6.9	N	N	N	N	N	N	Y	Y	N
Red Hat Enterprise Linux 6.10	N	N	N	N	N	N	Y	Y	N
Red Hat Enterprise Linux 7.3	N	N	N	N	N	N	Y	Y	N
Red Hat Enterprise Linux 7.4	N	N	N	N	N	N	Y	Y	N
Red Hat Enterprise Linux 7.5	N	N	N	N	N	N	Y	Y	N
Red Hat Enterprise Linux 7.6	Y	Y	Y ¹	Y ¹	Y ¹	Y ¹	Y	Y	N
Red Hat Enterprise Linux 7.7	Y	Y	Y ¹	Y ¹	Y ¹	Y ¹	Y	Y	N
Red Hat Enterprise Linux 7.8	Y	Y	Y ¹	Y ¹	Y ¹	Y ¹	Y	Y	N
Red Hat Enterprise Linux 7.9	Y	Y	Y ¹	Y ¹	Y ¹	Y ¹	Y	Y	Y
Red Hat Enterprise Linux 8.0	Y	Y	Y ¹	Y ¹	N	N	Y	Y	N
Red Hat Enterprise Linux 8.1	Y	Y	Y ¹	Y ¹	Y ¹	Y ¹	Y	Y	N
Red Hat Enterprise Linux 8.2	Y	Y	Y ¹	Y ¹	Y ¹	Y ¹	Y	Y	Y
Red Hat Enterprise Linux 8.3	Y	Y	Y	Y	Y	Y	Y	Y	Y
Red Hat Enterprise Linux 8.4	Y	Y	Y	Y	Y	Y	Y	Y	N
Red Hat Enterprise Linux 8.5	Y	Y	Y	Y	Y	Y	Y	Y	Y
Red Hat Enterprise Linux 8.6	Y	Y	Y	Y	Y	Y	Y	Y	Y
Red Hat Enterprise Linux 8.7	Y	Y	Y	Y	Y	Y	Y	Y	Y
Red Hat Enterprise Linux 8.8	Y	Y	Y	Y	Y	Y	Y	Y	Y
Red Hat Enterprise Linux 8.9	Y	Y	Y	Y	Y	Y	N	N	Y
Red Hat Enterprise Linux 8.10	N	Y	Y	Y	Y	Y	N	N	Y
Red Hat Enterprise Linux 9.0	Y	Y	Y	Y	Y	Y	Y	Y	Y
Red Hat Enterprise Linux 9.1	Y	Y	Y	Y	Y	Y	Y	Y	Y

	SR630 (Xeon Gen 2)	SR650 (Xeon Gen 2)	SR635	SR655	SR645	SR665	SR630 (Xeon Gen 1)	SR650 (Xeon Gen 1)	SR650 V2
Operating systems									
Red Hat Enterprise Linux 9.2	Y	Y	Y	Y	Y	Y	Y	Y	Y
Red Hat Enterprise Linux 9.3	Y	Y	Y	Y	Y	Y	N	N	Y
Red Hat Enterprise Linux 9.4	N	N	Y	Y	Y	Y	N	N	Y
Red Hat Enterprise Linux 9.5	N	N	Y	Y	Y	Y	N	N	Y
Red Hat Enterprise Linux 9.6	N	N	Y	Y	Y	Y	N	N	Y
Red Hat Enterprise Linux 9.7	N	N	Y	Y	Y	Y	N	N	Y
Red Hat Enterprise Linux 10.0	N	N	N	N	Y	Y	N	N	Y
Red Hat Enterprise Linux 10.1	N	N	N	N	Y	Y	N	N	Y
Red Hat Enterprise Linux 10.2	N	N	N	N	N	N	N	N	Y
SUSE Linux Enterprise Server 11 SP4	N	N	N	N	N	N	Y	Y	N
SUSE Linux Enterprise Server 12 SP2	N	N	N	N	N	N	Y	Y	N
SUSE Linux Enterprise Server 12 SP2 with Xen	N	N	N	N	N	N	Y	Y	N
SUSE Linux Enterprise Server 12 SP3	N	N	N	N	N	N	Y	Y	N
SUSE Linux Enterprise Server 12 SP3 with Xen	N	N	N	N	N	N	Y	Y	N
SUSE Linux Enterprise Server 12 SP4	Y	Y	Y ¹	Y ¹	N	N	Y	Y	N
SUSE Linux Enterprise Server 12 SP4 with Xen	Y	Y	Y ¹	Y ¹	N	N	Y	Y	N
SUSE Linux Enterprise Server 12 SP5	Y	Y	Y	Y	Y	Y	Y	Y	Y
SUSE Linux Enterprise Server 12 SP5 with Xen	Y	Y	Y	Y	Y	Y	Y	Y	Y
SUSE Linux Enterprise Server 15	Y	Y	N	N	N	N	Y	Y	N
SUSE Linux Enterprise Server 15 SP1	Y	Y	Y ¹	Y ¹	Y ¹	Y ¹	Y	Y	N
SUSE Linux Enterprise Server 15 SP1 with Xen	Y	Y	Y ¹	Y ¹	Y ¹	Y ¹	Y	Y	N
SUSE Linux Enterprise Server 15 SP2	Y	Y	Y	Y	Y	Y	Y	Y	Y
SUSE Linux Enterprise Server 15 SP2 with Xen	Y	Y	Y	Y	Y	Y	Y	Y	Y
SUSE Linux Enterprise Server 15 SP3	Y	Y	Y	Y	Y	Y	Y	Y	N
SUSE Linux Enterprise Server 15 SP3 with Xen	Y	Y	Y	Y	Y	Y	Y	Y	N
SUSE Linux Enterprise Server 15 SP4	Y	Y	Y	Y	Y	Y	Y	Y	Y
SUSE Linux Enterprise Server 15 SP4 with Xen	Y	Y	Y	Y	Y	Y	Y	Y	Y
SUSE Linux Enterprise Server 15 SP5	Y	Y	Y	Y	Y	Y	Y	Y	Y
SUSE Linux Enterprise Server 15 SP5 with Xen	Y	Y	Y	Y	Y	Y	Y	Y	Y
SUSE Linux Enterprise Server 15 SP6	N	N	Y	Y	Y	Y	N	N	Y
SUSE Linux Enterprise Server 15 SP7	N	N	Y	Y	Y	Y	N	N	Y
SUSE Linux Enterprise Server 15 with Xen	Y	Y	N	N	N	N	Y	Y	N
SUSE Linux Enterprise Server 16	N	N	N	N	Y	Y	N	N	Y
Ubuntu 18.04.5 LTS or later with HWE kernel	N	N	N	N	N	N	N	N	Y
Ubuntu 20.04 LTS or later with HWE kernel	N	N	N	N	N	N	N	N	Y
Ubuntu 22.04 LTS or later with HWE kernel	Y	Y	Y	Y	Y	Y	Y	Y	Y
Ubuntu 24.04 LTS or later with HWE kernel	N	N	Y	Y	Y	Y	N	N	Y

	SR630 (Xeon Gen 2)	SR650 (Xeon Gen 2)	SR635	SR655	SR645	SR665	SR630 (Xeon Gen 1)	SR650 (Xeon Gen 1)	SR650 V2
Operating systems									
VMware vSphere Hypervisor (ESXi) 6.5	N	N	N	N	N	N	Y	Y	N
VMware vSphere Hypervisor (ESXi) 6.5 U1	N	N	N	N	N	N	Y	Y	N
VMware vSphere Hypervisor (ESXi) 6.5 U2	Y	Y	N	N	N	N	Y	Y	N
VMware vSphere Hypervisor (ESXi) 6.5 U3	Y	Y	N	N	N	N	Y	Y	N
VMware vSphere Hypervisor (ESXi) 6.7	N	N	N	N	N	N	Y	Y	N
VMware vSphere Hypervisor (ESXi) 6.7 U1	Y	Y	N	N	N	N	Y	Y	N
VMware vSphere Hypervisor (ESXi) 6.7 U2	Y	Y	N	N	N	N	Y	Y	N
VMware vSphere Hypervisor (ESXi) 6.7 U3	Y	Y	N	N	Y	Y	Y	Y	Y
VMware vSphere Hypervisor (ESXi) 7.0	Y	Y	Y ¹	Y ¹	Y ¹	Y ¹	Y	Y	N
VMware vSphere Hypervisor (ESXi) 7.0 U1	Y	Y	Y ¹	Y ¹	Y	Y	Y	Y	N
VMware vSphere Hypervisor (ESXi) 7.0 U2	Y	Y	Y	Y	Y	Y	Y	Y	Y
VMware vSphere Hypervisor (ESXi) 7.0 U3	Y	Y	Y	Y	Y	Y	Y	Y	Y
VMware vSphere Hypervisor (ESXi) 8.0	Y	Y	Y	Y	Y	Y	Y	Y	Y
VMware vSphere Hypervisor (ESXi) 8.0 U1	Y	Y	Y	Y	Y	Y	Y	Y	Y
VMware vSphere Hypervisor (ESXi) 8.0 U2	Y	Y	Y	Y	Y	Y	Y	Y	Y
VMware vSphere Hypervisor (ESXi) 8.0 U3	Y	Y	Y	Y	Y	Y	Y	Y	Y
VMware vSphere Hypervisor (ESXi) 9.0	N	N	N	N	Y	Y	N	N	Y
VMware vSphere Hypervisor (ESXi) 9.1	N	N	N	N	Y	Y	N	N	Y

¹ The OS is not supported with EPYC 7003 processors.

² ISG will not sell/preload this OS, but compatibility and cert only.

Table 9. Operating system support for ThinkSystem U.2 PM1733 7.68TB Entry NVMe PCIe 4.0 x4 Hot Swap SSD, 4XB7A38283

	SR630 (Xeon Gen 2)	SR650 (Xeon Gen 2)	SR635	SR655	SR645	SR665	SR630 (Xeon Gen 1)	SR650 (Xeon Gen 1)	SR650 V2
Operating systems									
Microsoft Windows 10	N	N	N	Y ²	N	N	N	N	N
Microsoft Windows 11	N	N	N	Y ²	N	N	N	N	N
Microsoft Windows Server 2016	Y	Y	Y	Y	Y	Y	Y	Y	Y
Microsoft Windows Server 2019	Y	Y	Y	Y	Y	Y	Y	Y	Y
Microsoft Windows Server 2022	Y	Y	Y	Y	Y	Y	Y	Y	Y
Microsoft Windows Server 2025	N	N	N	N	Y	Y	N	N	Y
Red Hat Enterprise Linux 6.9	N	N	N	N	N	N	Y	Y	N
Red Hat Enterprise Linux 6.10	N	N	N	N	N	N	Y	Y	N

	SR630 (Xeon Gen 2)	SR650 (Xeon Gen 2)	SR635	SR655	SR645	SR665	SR630 (Xeon Gen 1)	SR650 (Xeon Gen 1)	SR650 V2
Operating systems									
Red Hat Enterprise Linux 7.3	N	N	N	N	N	N	Y	Y	N
Red Hat Enterprise Linux 7.4	N	N	N	N	N	N	Y	Y	N
Red Hat Enterprise Linux 7.5	N	N	N	N	N	N	Y	Y	N
Red Hat Enterprise Linux 7.6	Y	Y	Y ¹	Y ¹	Y ¹	Y ¹	Y	Y	N
Red Hat Enterprise Linux 7.7	Y	Y	Y ¹	Y ¹	Y ¹	Y ¹	Y	Y	N
Red Hat Enterprise Linux 7.8	Y	Y	Y ¹	Y ¹	Y ¹	Y ¹	Y	Y	N
Red Hat Enterprise Linux 7.9	Y	Y	Y ¹	Y ¹	Y ¹	Y ¹	Y	Y	Y
Red Hat Enterprise Linux 8.0	Y	Y	Y ¹	Y ¹	N	N	Y	Y	N
Red Hat Enterprise Linux 8.1	Y	Y	Y ¹	Y ¹	Y ¹	Y ¹	Y	Y	N
Red Hat Enterprise Linux 8.2	Y	Y	Y ¹	Y ¹	Y ¹	Y ¹	Y	Y	Y
Red Hat Enterprise Linux 8.3	Y	Y	Y	Y	Y	Y	Y	Y	Y
Red Hat Enterprise Linux 8.4	Y	Y	Y	Y	Y	Y	Y	Y	N
Red Hat Enterprise Linux 8.5	Y	Y	Y	Y	Y	Y	Y	Y	Y
Red Hat Enterprise Linux 8.6	Y	Y	Y	Y	Y	Y	Y	Y	Y
Red Hat Enterprise Linux 8.7	Y	Y	Y	Y	Y	Y	Y	Y	Y
Red Hat Enterprise Linux 8.8	Y	Y	Y	Y	Y	Y	Y	Y	Y
Red Hat Enterprise Linux 8.9	Y	Y	Y	Y	Y	Y	N	N	Y
Red Hat Enterprise Linux 8.10	N	Y	Y	Y	Y	Y	N	N	Y
Red Hat Enterprise Linux 9.0	Y	Y	Y	Y	Y	Y	Y	Y	Y
Red Hat Enterprise Linux 9.1	Y	Y	Y	Y	Y	Y	Y	Y	Y
Red Hat Enterprise Linux 9.2	Y	Y	Y	Y	Y	Y	Y	Y	Y
Red Hat Enterprise Linux 9.3	Y	Y	Y	Y	Y	Y	N	N	Y
Red Hat Enterprise Linux 9.4	N	N	Y	Y	Y	Y	N	N	Y
Red Hat Enterprise Linux 9.5	N	N	Y	Y	Y	Y	N	N	Y
Red Hat Enterprise Linux 9.6	N	N	Y	Y	Y	Y	N	N	Y
Red Hat Enterprise Linux 9.7	N	N	Y	Y	Y	Y	N	N	Y
Red Hat Enterprise Linux 10.0	N	N	N	N	Y	Y	N	N	Y
Red Hat Enterprise Linux 10.1	N	N	N	N	Y	Y	N	N	Y
Red Hat Enterprise Linux 10.2	N	N	N	N	N	N	N	N	Y
SUSE Linux Enterprise Server 11 SP4	N	N	N	N	N	N	Y	Y	N
SUSE Linux Enterprise Server 11 SP4 with Xen	N	N	N	N	N	N	Y	Y	N
SUSE Linux Enterprise Server 12 SP2	N	N	N	N	N	N	Y	Y	N
SUSE Linux Enterprise Server 12 SP2 with Xen	N	N	N	N	N	N	Y	Y	N
SUSE Linux Enterprise Server 12 SP3	N	N	N	N	N	N	Y	Y	N
SUSE Linux Enterprise Server 12 SP3 with Xen	N	N	N	N	N	N	Y	Y	N
SUSE Linux Enterprise Server 12 SP4	Y	Y	Y ¹	Y ¹	N	N	Y	Y	N
SUSE Linux Enterprise Server 12 SP4 with Xen	Y	Y	Y ¹	Y ¹	N	N	Y	Y	N

	SR630 (Xeon Gen 2)	SR650 (Xeon Gen 2)	SR635	SR655	SR645	SR665	SR630 (Xeon Gen 1)	SR650 (Xeon Gen 1)	SR650 V2
Operating systems									
SUSE Linux Enterprise Server 12 SP5	Y	Y	Y	Y	Y	Y	Y	Y	Y
SUSE Linux Enterprise Server 12 SP5 with Xen	Y	Y	Y	Y	Y	Y	Y	Y	Y
SUSE Linux Enterprise Server 15	Y	Y	N	N	N	N	Y	Y	N
SUSE Linux Enterprise Server 15 SP1	Y	Y	Y ¹	Y ¹	Y ¹	Y ¹	Y	Y	N
SUSE Linux Enterprise Server 15 SP1 with Xen	Y	Y	Y ¹	Y ¹	Y ¹	Y ¹	Y	Y	N
SUSE Linux Enterprise Server 15 SP2	Y	Y	Y	Y	Y	Y	Y	Y	Y
SUSE Linux Enterprise Server 15 SP2 with Xen	Y	Y	Y	Y	Y	Y	Y	Y	Y
SUSE Linux Enterprise Server 15 SP3	Y	Y	Y	Y	Y	Y	Y	Y	N
SUSE Linux Enterprise Server 15 SP3 with Xen	Y	Y	Y	Y	Y	Y	Y	Y	N
SUSE Linux Enterprise Server 15 SP4	Y	Y	Y	Y	Y	Y	Y	Y	Y
SUSE Linux Enterprise Server 15 SP4 with Xen	Y	Y	Y	Y	Y	Y	Y	Y	Y
SUSE Linux Enterprise Server 15 SP5	Y	Y	Y	Y	Y	Y	Y	Y	Y
SUSE Linux Enterprise Server 15 SP5 with Xen	Y	Y	Y	Y	Y	Y	Y	Y	Y
SUSE Linux Enterprise Server 15 SP6	N	N	Y	Y	Y	Y	N	N	Y
SUSE Linux Enterprise Server 15 SP7	N	N	Y	Y	Y	Y	N	N	Y
SUSE Linux Enterprise Server 15 with Xen	Y	Y	N	N	N	N	Y	Y	N
SUSE Linux Enterprise Server 16	N	N	N	N	Y	Y	N	N	Y
Ubuntu 18.04.5 LTS or later with HWE kernel	N	N	N	N	N	N	N	N	Y
Ubuntu 20.04 LTS or later with HWE kernel	N	N	N	N	N	N	N	N	Y
Ubuntu 22.04 LTS or later with HWE kernel	Y	Y	Y	Y	Y	Y	Y	Y	Y
Ubuntu 24.04 LTS or later with HWE kernel	N	N	Y	Y	Y	Y	N	N	Y
VMware vSphere Hypervisor (ESXi) 6.7 U3	N	N	N	N	N	N	N	N	Y
VMware vSphere Hypervisor (ESXi) 7.0 U1	Y	Y	Y ¹	Y ¹	Y	Y	Y	Y	N
VMware vSphere Hypervisor (ESXi) 7.0 U2	Y	Y	Y	Y	Y	Y	Y	Y	Y
VMware vSphere Hypervisor (ESXi) 7.0 U3	Y	Y	Y	Y	Y	Y	Y	Y	Y
VMware vSphere Hypervisor (ESXi) 8.0	Y	Y	Y	Y	Y	Y	Y	Y	Y
VMware vSphere Hypervisor (ESXi) 8.0 U1	Y	Y	Y	Y	Y	Y	Y	Y	Y
VMware vSphere Hypervisor (ESXi) 8.0 U2	Y	Y	Y	Y	Y	Y	Y	Y	Y
VMware vSphere Hypervisor (ESXi) 8.0 U3	Y	Y	Y	Y	Y	Y	Y	Y	Y
VMware vSphere Hypervisor (ESXi) 9.0	N	N	N	N	Y	Y	N	N	Y
VMware vSphere Hypervisor (ESXi) 9.1	N	N	N	N	Y	Y	N	N	Y

¹ The OS is not supported with EPYC 7003 processors.

² ISG will not sell/preload this OS, but compatibility and cert only.

Warranty

The PM1733 SSDs carry a one-year, customer-replaceable unit (CRU) limited warranty. When the SSDs are installed in a supported server, these drives assume the server's base warranty and any warranty upgrades.

Solid State Memory cells have an intrinsic, finite number of program/erase cycles that each cell can incur. As a result, each solid state device has a maximum amount of program/erase cycles to which it can be subjected. The warranty for Lenovo solid state drives (SSDs) is limited to drives that have not reached the maximum guaranteed number of program/erase cycles, as documented in the Official Published Specifications for the SSD product. A drive that reaches this limit may fail to operate according to its Specifications.

Physical specifications

The PM1733 Entry NVMe PCIe SSDs have the following physical specifications:

Dimensions and weight (approximate, without the drive tray):

- Height: 15 mm (0.6 in.)
- Width: 70 mm (2.8 in.)
- Depth: 100 mm (4.0 in.)
- Weight: 190 g (6.7 oz)

Operating environment

The PM1733 Entry NVMe PCIe SSDs are supported in the following environment:

- Temperature (operating): 0 to 70 °C (32 to 158 °F)
- Temperature (non-operating): -40 to 85 °C (-40 to 185 °F)
- Relative humidity (non-operating): 5 to 95% (noncondensing)
- Maximum altitude: 3,050 m (10,000 ft)
- Shock, operating: 1,500 G (Max) at 0.5 ms
- Vibration: 20 G_{PEAK} (10-2000 Hz) at 15 mins per axis

Agency approvals

The PM1733 Entry NVMe PCIe SSDs conform to the following regulations:

- UL
- TUV
- FCC
- CE Mark
- C-Tick Mark
- BSMI (Taiwan)
- KCC (Korea EMI)

Related publications and links

For more information, see the following documents:

- Lenovo ThinkSystem SSD Portfolio Comparison
<https://lenovopress.com/lp1261-lenovo-thinksystem-ssd-portfolio>
- Lenovo ThinkSystem storage options product web page
<https://lenovopress.com/lp0761-storage-options-for-thinksystem-servers>
- Samsung product page for Enterprise SSDs
<https://www.samsung.com/semiconductor/ssd/enterprise-ssd/>

Related product families

Product families related to this document are the following:

- [Drives](#)

Notices

Lenovo may not offer the products, services, or features discussed in this document in all countries. Consult your local Lenovo representative for information on the products and services currently available in your area. Any reference to a Lenovo product, program, or service is not intended to state or imply that only that Lenovo product, program, or service may be used. Any functionally equivalent product, program, or service that does not infringe any Lenovo intellectual property right may be used instead. However, it is the user's responsibility to evaluate and verify the operation of any other product, program, or service. Lenovo may have patents or pending patent applications covering subject matter described in this document. The furnishing of this document does not give you any license to these patents. You can send license inquiries, in writing, to:

Lenovo (United States), Inc.
8001 Development Drive
Morrisville, NC 27560
U.S.A.
Attention: Lenovo Director of Licensing

LENOVO PROVIDES THIS PUBLICATION "AS IS" WITHOUT WARRANTY OF ANY KIND, EITHER EXPRESS OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF NON-INFRINGEMENT, MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE. Some jurisdictions do not allow disclaimer of express or implied warranties in certain transactions, therefore, this statement may not apply to you.

This information could include technical inaccuracies or typographical errors. Changes are periodically made to the information herein; these changes will be incorporated in new editions of the publication. Lenovo may make improvements and/or changes in the product(s) and/or the program(s) described in this publication at any time without notice.

The products described in this document are not intended for use in implantation or other life support applications where malfunction may result in injury or death to persons. The information contained in this document does not affect or change Lenovo product specifications or warranties. Nothing in this document shall operate as an express or implied license or indemnity under the intellectual property rights of Lenovo or third parties. All information contained in this document was obtained in specific environments and is presented as an illustration. The result obtained in other operating environments may vary. Lenovo may use or distribute any of the information you supply in any way it believes appropriate without incurring any obligation to you.

Any references in this publication to non-Lenovo Web sites are provided for convenience only and do not in any manner serve as an endorsement of those Web sites. The materials at those Web sites are not part of the materials for this Lenovo product, and use of those Web sites is at your own risk. Any performance data contained herein was determined in a controlled environment. Therefore, the result obtained in other operating environments may vary significantly. Some measurements may have been made on development-level systems and there is no guarantee that these measurements will be the same on generally available systems. Furthermore, some measurements may have been estimated through extrapolation. Actual results may vary. Users of this document should verify the applicable data for their specific environment.

© Copyright Lenovo 2026. All rights reserved.

This document, LP1300, was created or updated on November 7, 2023.

Send us your comments in one of the following ways:

- Use the online Contact us review form found at:
<https://lenovopress.lenovo.com/LP1300>
- Send your comments in an e-mail to:
comments@lenovopress.com

This document is available online at <https://lenovopress.lenovo.com/LP1300>.

Trademarks

Lenovo and the Lenovo logo are trademarks or registered trademarks of Lenovo in the United States, other countries, or both. A current list of Lenovo trademarks is available on the Web at <https://www.lenovo.com/us/en/legal/copytrade/>.

The following terms are trademarks of Lenovo in the United States, other countries, or both:

Lenovo®

ServerProven®

ThinkSystem®

The following terms are trademarks of other companies:

AMD is a trademark of Advanced Micro Devices, Inc.

Intel®, the Intel logo and Xeon® are trademarks of Intel Corporation or its subsidiaries.

Linux® is the trademark of Linus Torvalds in the U.S. and other countries.

Microsoft, Windows, and Windows Server are trademarks of Microsoft Corporation in the United States, other countries, or both.

Other company, product, or service names may be trademarks or service marks of others.