

ThinkSystem SR665 Sets World Record with SAP SD Two-Tier Benchmark Result

Performance Benchmark Result

The Lenovo ThinkSystem SR665 server, using two AMD EPYC 7H12 64-core processors running at 2.6 GHz, demonstrates best performance in the industry with the SAP SD 2-tier standard application benchmark on Windows.

Lenovo announces a world record result on Microsoft Windows for the two-tier SAP Sales and Distribution (SD) standard application benchmark.



The result was achieved on the Lenovo ThinkSystem SR665, configured with two AMD EPYC 7H12 processor, using IBM Db2 10.5 and SAP enhancement package 5 for the SAP ERP application release 6.0 (1). The Lenovo result is 11.6% better than the publication by HPE on the 2S AMD processor-based ProLiant DL385 Gen10 plus Server on Windows (2).

Lenovo delivered the following certified result (1):

- **Number of SAP SD benchmark users: 59,160**

Throughput:

- Fully processed order line items per hour: 6,462,000
- Dialog steps per hour: 19,386,000
- SAPS: 323,100
- Average database request time (dialog/update): 14 ms / 26 ms

Configuration of the central server:

- ThinkSystem SR665
- Two AMD EPYC 7H12 processors, 64 cores, 280W, 2.6 GHz
- Each processor 64 KB L1 cache and 512 KB L2 cache per core, 256 MB L3 cache
- 512 GB system memory

Software platform:

- Operating system, central server: Microsoft Windows Server 2019 Datacenter Edition
- RDBMS: IBM Db2 10.5
- SAP Business Suite software: SAP enhancement package 5 for SAP ERP 6.0

Results referenced are current as of May 5, 2020. For the latest SAP benchmark results, visit: <https://www.sap.com/about/benchmark.html>.

(1) This benchmark fully complies with the SAP Benchmark Council regulations and has been audited and certified by SAP SE. Details are available at <https://www.sap.com/dmc/benchmark/2020/Cert20014.pdf>. The benchmark was performed at Data Center Performance Lab, Lenovo in Research Triangle Park, NC, USA, by Lenovo engineers.

(2) The claim of achieving 11.6% better performance is based on HPE publication on 2S AMD ProLiant DL385 Gen10 plus Server using EPYC 7742 64-Core Processor at 2.25GHz. Details at <https://www.sap.com/dmc/benchmark/2019/Cert19057.pdf>

About the ThinkSystem SR665

The Lenovo ThinkSystem SR665 server, now with AMD EPYC 7003 Series processors, delivers outstanding TCO for transactional database, ERP, virtualization, big data & analytics and software-defined deployments. The combination of two AMD EPYC 7003 CPUs with class-leading memory speed, storage, and GPU density, rapidly outpaces the power of prior generation two-socket servers. Lenovo's lauded system reliability, management capabilities, and security infrastructure layer on to the exceptional value that the ThinkSystem SR665 brings to the data center. With the enterprise-class AMD EPYC 7003 Series or 7002 Series processor, the world's first 7nm data center CPU, the ThinkSystem SR665 features two processors with up to an unprecedented 128 total cores with 128 PCIe Gen4 lanes to reduce bottlenecks and increase server utilization.

Compared to the previous processor generations, ThinkSystem SR665 delivers up to 2X performance and 4X floating point capability, providing faster data transfer and analytics without sacrificing memory capacity or I/O with PCIe Gen4 support and faster memory speeds up to 3200 MHz.

Key features:

- 128 cores across two processors to handle heavy-lift ERP, CRM, and virtualization workloads; provides cutting edge application efficiency in health care applications such as medical imaging, EMR, and PACS, or electronic trading platforms for financial services applications.
- Multi-GPU optimized rack server, providing support for up to 8 single-wide GPUs that offer 200% more workload acceleration in AI Inference, and virtualized desktop infrastructure (VDI).
- Support for up to 32 NVMe solid-state drives; when paired with high speed networking, make the system an excellent choice for workloads that need large amounts of low-latency high-bandwidth storage, including virtualized clustered SAN solutions, software-defined storage (SDS), and applications leveraging NVMe over Fabrics.

About SAP SD

SAP SD benchmark is a test for standard sale and distribution business components on SAP ERP, which is indicative of the performance of the application and database on a specific hardware environment. For more information about the benchmark, go to <https://www.sap.com/about/benchmark/appbm/erp.html>.

Learn more

To learn more about SAP solutions on Lenovo servers visit the following page:
<https://www.lenovo.com/us/en/data-center/solutions/sap/>

To learn more about the Lenovo ThinkSystem SR665 server, visit the SR665 product web page:
<https://www.lenovo.com/us/en/data-center/servers/racks/ThinkSystem-SR665-Server/p/77XX7SR552S>

Related product families

Product families related to this document are the following:

- [2-Socket Rack Servers](#)
- [IBM Alliance](#)
- [IBM Db2](#)
- [SAP Alliance](#)
- [SAP SD Benchmark Results](#)
- [ThinkSystem SR665 Server](#)

Notices

Lenovo may not offer the products, services, or features discussed in this document in all countries. Consult your local Lenovo representative for information on the products and services currently available in your area. Any reference to a Lenovo product, program, or service is not intended to state or imply that only that Lenovo product, program, or service may be used. Any functionally equivalent product, program, or service that does not infringe any Lenovo intellectual property right may be used instead. However, it is the user's responsibility to evaluate and verify the operation of any other product, program, or service. Lenovo may have patents or pending patent applications covering subject matter described in this document. The furnishing of this document does not give you any license to these patents. You can send license inquiries, in writing, to:

Lenovo (United States), Inc.
8001 Development Drive
Morrisville, NC 27560
U.S.A.
Attention: Lenovo Director of Licensing

LENOVO PROVIDES THIS PUBLICATION "AS IS" WITHOUT WARRANTY OF ANY KIND, EITHER EXPRESS OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF NON-INFRINGEMENT, MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE. Some jurisdictions do not allow disclaimer of express or implied warranties in certain transactions, therefore, this statement may not apply to you.

This information could include technical inaccuracies or typographical errors. Changes are periodically made to the information herein; these changes will be incorporated in new editions of the publication. Lenovo may make improvements and/or changes in the product(s) and/or the program(s) described in this publication at any time without notice.

The products described in this document are not intended for use in implantation or other life support applications where malfunction may result in injury or death to persons. The information contained in this document does not affect or change Lenovo product specifications or warranties. Nothing in this document shall operate as an express or implied license or indemnity under the intellectual property rights of Lenovo or third parties. All information contained in this document was obtained in specific environments and is presented as an illustration. The result obtained in other operating environments may vary. Lenovo may use or distribute any of the information you supply in any way it believes appropriate without incurring any obligation to you.

Any references in this publication to non-Lenovo Web sites are provided for convenience only and do not in any manner serve as an endorsement of those Web sites. The materials at those Web sites are not part of the materials for this Lenovo product, and use of those Web sites is at your own risk. Any performance data contained herein was determined in a controlled environment. Therefore, the result obtained in other operating environments may vary significantly. Some measurements may have been made on development-level systems and there is no guarantee that these measurements will be the same on generally available systems. Furthermore, some measurements may have been estimated through extrapolation. Actual results may vary. Users of this document should verify the applicable data for their specific environment.

© Copyright Lenovo 2024. All rights reserved.

This document, LP1311, was created or updated on May 5, 2020.

Send us your comments in one of the following ways:

- Use the online Contact us review form found at:
<https://lenovopress.lenovo.com/LP1311>
- Send your comments in an e-mail to:
comments@lenovopress.com

This document is available online at <https://lenovopress.lenovo.com/LP1311>.

Trademarks

Lenovo and the Lenovo logo are trademarks or registered trademarks of Lenovo in the United States, other countries, or both. A current list of Lenovo trademarks is available on the Web at <https://www.lenovo.com/us/en/legal/copytrade/>.

The following terms are trademarks of Lenovo in the United States, other countries, or both:

Lenovo®

ThinkSystem®

The following terms are trademarks of other companies:

Microsoft®, Windows Server®, and Windows® are trademarks of Microsoft Corporation in the United States, other countries, or both.

Other company, product, or service names may be trademarks or service marks of others.