



# ThinkSystem SR665 Sets 2 World Records with New 2-node SPECmpiM Benchmark Result

**Performance Benchmark Result** 

The Lenovo ThinkSystem SR665 has set two new 2-node 2-socket performance world records with the SPECmpiM\_base2007 and SPECmpiM\_peak2007 metrics from the MPI M2007 suite of the SPEC MPI 2007 Benchmark. The SPECmpiM Benchmark suite is an industry standard method to evaluate MPI-parallel, floating point, compute intensive performance across a wide range of cluster and SMP hardware.

This new benchmark result, published in a new SPEC Report on March 15, 2021, demonstrates that the ThinkSystem SR665 continues Lenovo's leadership with outstanding performance for the server industry.



The ThinkSystem SR665 has achieved the following scores:

- SPECmpiM base2007 = 52.6
- SPECmpiM\_peak2007 = 52.6

Each SR665 node was configured as follows for the benchmark audit:

- 2x AMD EPYC 7763 processors (64 cores, 2.45GHz)
- 1TB memory (16x 64GB RDIMMs, 3200MHz)
- 480GB 2.5-inch SSD
- Red Hat Enterprise Linux 8.3

Results referenced are current as of March 15, 2021.

The new Lenovo benchmark result can be found at:

https://www.spec.org/mpi2007/results/res2021q1/mpi2007-20210223-00677.html

# **About the ThinkSystem SR665**

The Lenovo ThinkSystem SR665 server, now with AMD EPYC 7003 Series processors, delivers outstanding TCO for transactional database, ERP, virtualization, big data & analytics and software-defined deployments. The combination of two AMD EPYC 7003 CPUs with class-leading memory speed, storage, and GPU density, rapidly outpaces the power of prior generation two-socket servers. Lenovo's lauded system reliability, management capabilities, and security infrastructure layer on to the exceptional value that the ThinkSystem SR665 brings to the data center. With the enterprise-class AMD EPYC 7003 Series or 7002 Series processor, the world's first 7nm data center CPU, the ThinkSystem SR665 features two processors with up to an unprecedented 128 total cores with 128 PCIe Gen4 lanes to reduce bottlenecks and increase server utilization.

Compared to the previous processor generations, ThinkSystem SR665 delivers up to 2X performance and 4X floating point capability, providing faster data transfer and analytics without sacrificing memory capacity or I/O with PCIe Gen4 support and faster memory speeds up to 3200 MHz.

### Key features:

- 128 cores across two processors to handle heavy-lift ERP, CRM, and virtualization workloads; provides cutting edge application efficiency in health care applications such as medical imaging, EMR, and PACS, or electronic trading platforms for financial services applications.
- Multi-GPU optimized rack server, providing support for up to 8 single-wide GPUs that offer 200% more workload acceleration in AI Inference, and virtualized desktop infrastructure (VDI).
- Support for up to 32 NVMe solid-state drives; when paired with high speed networking, make the
  system an excellent choice for workloads that need large amounts of low-latency high-bandwidth
  storage, including virtualized clustered SAN solutions, software-defined storage (SDS), and
  applications leveraging NVMe over Fabrics.

#### **About SPEC MPI**

The SPEC MPI 2007 benchmark suite evaluates Message-Passing Interface (MPI)-parallel, floating point, compute-intensive performance across a wide range of cluster and symmetric multiprocessing (SMP) server hardware. The suite includes the initial MPIM2007 suite, which contains medium-sized working sets and run times, and the newer MPIL2007 suite, which contains larger working sets and longer run times. This MPI 2007 continues the SPEC tradition of giving users the most objective and representative benchmark suite for measuring and comparing high-performance computer systems.

SPEC MPI 2007 focuses on performance of compute intensive applications using the MPI, which means this benchmark emphasizes the performance of all of the following:

- Type of processor
- Number of computer processors
- MPI Library
- Communication interconnect
- Memory architecture
- · Compiler used
- Type of shared file system

The benchmark is not intended to stress other computer components such as the operating system, graphics, or the I/O system.

For more information about SPEC MPI 2007, see https://www.spec.org/mpi2007/.

#### Learn more

To learn more about solutions for compute-intensive applications, please contact your Lenovo Sales Representative.

To find out more about SPEC, visit <a href="https://www.spec.org">https://www.spec.org</a>

To learn more about the Lenovo ThinkSystem SR665 server, visit the SR665 product web page: https://www.lenovo.com/us/en/data-center/servers/racks/ThinkSystem-SR665/p/77XX7SR552S

# **Related product families**

Product families related to this document are the following:

- 2-Socket Rack Servers
- SPECmpi Benchmark Results
- ThinkSystem SR665 Server

#### **Notices**

Lenovo may not offer the products, services, or features discussed in this document in all countries. Consult your local Lenovo representative for information on the products and services currently available in your area. Any reference to a Lenovo product, program, or service is not intended to state or imply that only that Lenovo product, program, or service may be used. Any functionally equivalent product, program, or service that does not infringe any Lenovo intellectual property right may be used instead. However, it is the user's responsibility to evaluate and verify the operation of any other product, program, or service. Lenovo may have patents or pending patent applications covering subject matter described in this document. The furnishing of this document does not give you any license to these patents. You can send license inquiries, in writing, to:

Lenovo (United States), Inc. 8001 Development Drive Morrisville, NC 27560 U.S.A.

Attention: Lenovo Director of Licensing

LENOVO PROVIDES THIS PUBLICATION "AS IS" WITHOUT WARRANTY OF ANY KIND, EITHER EXPRESS OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF NON-INFRINGEMENT, MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE. Some jurisdictions do not allow disclaimer of express or implied warranties in certain transactions, therefore, this statement may not apply to you.

This information could include technical inaccuracies or typographical errors. Changes are periodically made to the information herein; these changes will be incorporated in new editions of the publication. Lenovo may make improvements and/or changes in the product(s) and/or the program(s) described in this publication at any time without notice.

The products described in this document are not intended for use in implantation or other life support applications where malfunction may result in injury or death to persons. The information contained in this document does not affect or change Lenovo product specifications or warranties. Nothing in this document shall operate as an express or implied license or indemnity under the intellectual property rights of Lenovo or third parties. All information contained in this document was obtained in specific environments and is presented as an illustration. The result obtained in other operating environments may vary. Lenovo may use or distribute any of the information you supply in any way it believes appropriate without incurring any obligation to you.

Any references in this publication to non-Lenovo Web sites are provided for convenience only and do not in any manner serve as an endorsement of those Web sites. The materials at those Web sites are not part of the materials for this Lenovo product, and use of those Web sites is at your own risk. Any performance data contained herein was determined in a controlled environment. Therefore, the result obtained in other operating environments may vary significantly. Some measurements may have been made on development-level systems and there is no guarantee that these measurements will be the same on generally available systems. Furthermore, some measurements may have been estimated through extrapolation. Actual results may vary. Users of this document should verify the applicable data for their specific environment.

© Copyright Lenovo 2024. All rights reserved.

This document, LP1443, was created or updated on March 15, 2021.

Send us your comments in one of the following ways:

- Use the online Contact us review form found at: https://lenovopress.lenovo.com/LP1443
- Send your comments in an e-mail to: comments@lenovopress.com

This document is available online at https://lenovopress.lenovo.com/LP1443.

## **Trademarks**

Lenovo and the Lenovo logo are trademarks or registered trademarks of Lenovo in the United States, other countries, or both. A current list of Lenovo trademarks is available on the Web at <a href="https://www.lenovo.com/us/en/legal/copytrade/">https://www.lenovo.com/us/en/legal/copytrade/</a>.

The following terms are trademarks of Lenovo in the United States, other countries, or both: Lenovo® ThinkSystem®

The following terms are trademarks of other companies:

Linux® is the trademark of Linus Torvalds in the U.S. and other countries.

SPEC® and SPEC MPI® are trademarks of the Standard Performance Evaluation Corporation (SPEC).

Other company, product, or service names may be trademarks or service marks of others.