

Lenovo ThinkAgile VX3520-G, VX5520, VX7520 2U Appliances and VX 2U, VX 2U HANA Certified Nodes (Intel Xeon SP Gen 2)

Product Guide (withdrawn product)

The Lenovo ThinkAgile VX3520-G, VX5520, VX7520 2U Appliances and VX 2U Certified Nodes are 2-socket 2U systems that feature the 2nd Generation Intel Xeon Scalable processors (formerly "Cascade Lake"). These systems are based on the ThinkSystem SR650 with up to 28 cores per processor, up to 3 TB of TruDDR4 memory with up to 2933 MHz memory speeds, and an extensive selection of internal storage and networking options. VMware offers a unique, software-defined approach to hyperconvergence, leveraging the hypervisor to deliver compute, storage and management in a tightly integrated software stack.

The 2U systems are available either as an appliance or certified node:

- VX3520-G Appliance for compute-heavy workloads including those benefiting from the use of GPUs
- VX5520 Appliance for storage-heavy workloads
- VX7520 Appliance for high performance workloads
- VX 2U Certified Node
- VX 2U Certified Node for SAP HANA - certified by SAP for deploying SAP HANA solutions on hyperconverged infrastructure (HCI) in production environments.

Suggested uses: Inference, virtualization, VDI, HPC, Hyperconverged infrastructure



Figure 1. Lenovo ThinkAgile VX with 16x 2.5-inch drive bays

Did you know?

The ThinkAgile VX3520-G, VX5520, VX7520 2U Appliances and VX 2U Certified Nodes are built on the Lenovo ThinkSystem SR650 server that features enterprise-class reliability, management, and security.

The VX3520-G, VX5520 and VX7520 Appliances offer ThinkAgile Advantage Single Point of Support for quick 24/7 problem reporting and resolution.

Key features

The ThinkAgile VX3520-G, VX5520, VX7520 2U Appliances and VX 2U Certified Nodes offer the following key features:

- Factory-integrated, pre-configured ready-to-go appliances built on proven and reliable Lenovo ThinkSystem servers that provide compute power for a variety of workloads and applications and powered by industry-leading hyperconverged infrastructure software from VMware.
- Provide quick and convenient path to implement a hyperconverged solution powered by VMware vSAN with "one stop shop" and a single point of contact provided by Lenovo for purchasing, deploying, and supporting the solution.
- Meet various workload demands with cost-efficient hybrid or performance-optimized all-flash storage configurations.
- Deliver fully validated and integrated hardware and firmware that is certified with VMware software.
- Appliances include Lenovo ThinkAgile Advantage Single Point of Support for quick 24/7 problem reporting and resolution.
- The VX 2U Certified Node for SAP HANA is Certified by SAP to run SAP HANA in production on hyperconverged infrastructure.
- Offer Lenovo deployment services to get customers up and running quickly.

The VMware software running on ThinkAgile VX3520-G, VX5520, VX7520 2U Appliances and VX 2U Certified Nodes delivers the following key features:

- Distributed architecture that allows "pay-as-you-grow", non-disruptive scaling by adding new nodes to the cluster (scale-out) to increase capacity and performance.
- Advanced capacity management, including deduplication, compression, and erasure coding (RAID 5/6), which helps deliver greater storage utilization with dramatically lower storage capacity and costs.
- Automation of VM storage provisioning and control of storage service levels (capacity, performance, availability) with VM-centric policies to load balance storage resources.
- Native HCI security solution with two-factor authentication (SecurID and CAC) and data-at-rest encryption that does not require self-encrypting drives (SEDs).
- Stretched cluster with local and site failure protection between two geographically dispersed sites for higher level of availability with near zero downtime.
- Centralized management with provisioning, administering, and monitoring virtual resources across multiple hosts and clusters from a centralized interface.
- Rapid workload provisioning, simplified data center operations, increased business efficiency, and decreased CAPEX and OPEX costs.
- VM and data protection with agent-less, image-level virtual machine backups and application-aware protection for business-critical Microsoft applications (Exchange, SQL Server, SharePoint) along with WAN-efficient, encrypted backup data replication.
- Reduced unplanned downtime and virtually eliminated planned downtime for server and storage maintenance with live workload migration, high availability, and fault tolerance.
- Enhanced application performance and availability with resource management, load balancing, and access prioritization.
- Intelligent operations management and automation to proactively monitor and manage compute, storage, and networking resources, identify performance bottlenecks, and re-balance workloads by leveraging predictive analytics.
- Capacity planning and optimization guidance to address future needs with performance trends, projections and extended forecasts.

- Managing remote offices and branch offices with rapid provisioning of servers through virtualization, minimization of host configuration drift, and enhanced visibility into regulatory compliance, across multiple sites.

Components and connectors

The ThinkAgile VX3520-G, VX5520, VX7520 2U Appliances and VX 2U Certified Nodes are based on the ThinkSystem SR650 server.

The following figure shows the front view of the VX3520-G appliance.




Figure 2. VX3520-G front view

The following figure shows the front view of the VX5520 appliance.




Figure 3. VX5520 front view

The following figure shows the front view of the VX7520 appliance.




Figure 4. VX7520 front view

The following figure shows the front view of the VX 2U Certified Nodes with 16 SFF drive bays.




Figure 5. VX 2U Certified Nodes front view: 16x SFF drive bays

The following figure shows the front view of the VX 2U Certified Nodes with 24 SFF drive bays.




Figure 6. VX 2U Certified Nodes front view: 24x SFF drive bays

The following figure shows the rear view of the VX3520-G, VX5520, VX7520 and VX 2U Certified Nodes with up to 6 slots.




Figure 7. VX systems rear view without rear drive bays

The following figure shows the rear view of the VX5520 Appliance and VX 2U Certified Node, with rear drive bays and up to 3 slots.




Figure 8. VX5520 rear view with rear drive bays

Standard specifications

The ThinkAgile VX3520-G, VX5520, VX7520 2U Appliances and VX 2U Certified Nodes are based on the ThinkSystem SR650 server.

The following table provides an overview comparison between the VX systems.

Table 1. Comparison of features

	VX3520-G	VX5520	VX7520	VX 2U	VX 2U for HANA
VX offering type	Appliance	Appliance	Appliance	Certified Node	Certified Node
Target workloads	Compute heavy	Storage heavy	High performance	High performance	SAP HANA
Base MTM	7Y94CTO3WW	7Y94CTO1WW	7Y94CTO2WW	7Y94CTO5WW	7Y94CTO6WW
Form Factor	2U	2U	2U	2U	2U
Base platform	SR650	SR650	SR650	SR650	SR650
CPU	2x Intel Xeon SP Gen 2	1x or 2x Intel Xeon SP Gen 2	2x Intel Xeon SP Gen 2	1x or 2x Intel Xeon SP Gen 2	2x Intel Xeon SP Gen 2
Memory	24x DDR4 2933 MHz (3TB max)	24x DDR4 2933 MHz (3TB max)	24x DDR4 2933 MHz (3TB max)	24x DDR4 2933 MHz (3TB max)	24x DDR4 2933 MHz (3TB max)
Hot-swap drive bays	<ul style="list-style-type: none"> 16x 2.5" SAS/SATA (all front accessible) 	<ul style="list-style-type: none"> 12x 3.5" SAS/SATA (front) 14x 3.5" SAS/SATA (12 front, 2 rear) 	<ul style="list-style-type: none"> 20x 2.5" SAS/SATA + 4x 2.5" AnyBay (all front) 16x 2.5" SAS/SATA + 8x 2.5" AnyBay (all front) 	<ul style="list-style-type: none"> Up to 24x 2.5" SAS/SATA/ NVMe (front) + 2x 3.5" (rear) Up to 14x 3.5" SATA/SATA (12 front, 2 rear) 	<ul style="list-style-type: none"> Up to 24x 2.5" SAS/SATA/ NVMe (all front)
Drive Configuration	All Flash Hybrid	Hybrid	All Flash Hybrid	All Flash Hybrid	All Flash
Disk Groups	1 - 4	1 - 2	1 - 4	1 - 4	2 - 4
HBA	430-16i HBA	430-16i HBA	430-8i HBA 430-16i HBA NVMe switch adapters	430-8i HBA 430-16i HBA NVMe switch adapters	430-8i HBA 430-16i HBA NVMe switch adapters
Boot drives	2x M.2 SATA	2x M.2 SATA	2x M.2 SATA	2x M.2 SATA	2x M.2 SATA
LOM networking	1x LOM adapter, 10Gb	1x LOM adapter, 10Gb	1x LOM adapter, 10Gb	1x LOM adapter, 1Gb or 10Gb	1x LOM adapter, 1Gb or 10Gb
PCIe networking	Up to 6x adapters 10Gb, 25Gb, 40Gb, 100Gb	Up to 6x adapters 1Gb, 10Gb, 25Gb, 40Gb, 100Gb	Up to 6x adapters 10Gb, 25Gb, 40Gb, 100Gb	Up to 6x adapters 1Gb, 10Gb, 25Gb, 40Gb, 100Gb	Up to 6x adapters 1Gb, 10Gb, 25Gb, 40Gb, 100Gb
GPUs	2x DW GPU 5x SW GPU	No support	No support	2x DW GPU 5x SW GPU	No support
Hypervisor	VMware ESXi	VMware ESXi	VMware ESXi	VMware ESXi	VMware ESXi

The following table lists the system specifications of the ThinkAgile VX3520-G, VX5520, VX7520 2U Appliances and VX 2U Certified Nodes.

Table 2. System specifications - ThinkAgile VX3520-G, VX5520, VX7520 2U Appliances and VX 2U Certified Nodes

Attribute	Specification
Machine types	7Y94 - 3 year warranty
Form factor	2U rack-mount
Processor	One or two 2nd Gen Intel Xeon Scalable processors (formerly codenamed "Cascade Lake")
Chipset	Intel C624 chipset, part of the platform codenamed "Purley"
Memory	24 DIMM slots (up to 12 DIMMs per processor; six memory channels per processor with two DIMMs per channel) with support for RDIMMs and 3DS RDIMM at up to 2933 MHz.
Persistent memory	VX 2U Certified Nodes support up to 12x TruDDR4 2666 MHz DCPMMs in the DIMM slots.
Memory capacity	Up to 3 TB with 128 GB 3DS RDIMMs and two processors. Memory DIMMs and persistent memory modules (Memory Mode): Up to 6 TB with 12x 512 GB DCPMMs (Up to 3 TB per processor). Note: Systems with more than 1 TB of memory capacity per socket require processors with an L suffix.
Memory protection	Error correction code (ECC), Single Device Data Correction (SDDC; for x4-based memory DIMMs), Adaptive Double Device Data Correction (ADDDC; for x4-based memory DIMMs, requires Intel Xeon Gold or Platinum processors), patrol scrubbing, and demand scrubbing.

Attribute	Specification
Hot-swap drive bays	<ul style="list-style-type: none"> • VX3520-G: 16x 2.5" SAS/SATA (front) • VX5520: <ul style="list-style-type: none"> ◦ 12x 3.5" SAS/SATA (front) ◦ 14x 3.5" SAS/SATA (12 front, 2 rear) • VX7520: <ul style="list-style-type: none"> ◦ 20x 2.5" SAS/SATA + 4x 2.5" AnyBay (front) ◦ 16x 2.5" SAS/SATA + 8x 2.5" AnyBay (front) ◦ 24x 2.5" NVMe (front) • VX 2U Certified Node: <ul style="list-style-type: none"> ◦ Up to 16x 2.5" and 2x 3.5" drive bays: <ul style="list-style-type: none"> ■ 16x 2.5" SAS/SATA (front) + 2x 3.5" SAS/SATA (rear) ■ 12x 2.5" SAS/SATA & 4x 2.5" AnyBay (front) + 2x 3.5" SAS/SATA (rear) ■ 8x 2.5" SAS/SATA & 8x 2.5" AnyBay (front) + 2x 3.5" SAS/SATA (rear) ◦ Up to 24x 2.5" and 2x 3.5" drive bays: <ul style="list-style-type: none"> ■ 24x 2.5" SAS/SATA (front) + 2x 3.5" SAS/SATA (rear) ■ 20x 2.5" SAS/SATA & 4x 2.5" AnyBay (front) + 2x 3.5" SAS/SATA (rear) ■ 16x 2.5" SAS/SATA & 8x 2.5" AnyBay (front) + 2x 3.5" SAS/SATA (rear) ■ 16x 2.5" NVMe & 8x 2.5" SAS/SATA (front) ■ 24x 2.5" NVMe (front) ◦ Up to 14x 3.5" drive bays: <ul style="list-style-type: none"> ■ 12x 3.5" SAS/SATA (front) + 2x 3.5" SAS/SATA (rear) ■ 8x 3.5" SAS/SATA & 4x 3.5" AnyBay (front) + 2x 3.5" SAS/SATA (rear) • VX 2U Certified Node for SAP HANA: <ul style="list-style-type: none"> ◦ Up to 16x 2.5" drive bays: <ul style="list-style-type: none"> ■ 16x 2.5" SAS/SATA (front) ■ 12x 2.5" SAS/SATA & 4x 2.5" AnyBay (front) ■ 8x 2.5" SAS/SATA & 8x 2.5" AnyBay (front) ◦ Up to 24x 2.5" drive bays: <ul style="list-style-type: none"> ■ 24x 2.5" SAS/SATA (front) ■ 20x 2.5" SAS/SATA & 4x 2.5" AnyBay (front) ■ 16x 2.5" SAS/SATA & 8x 2.5" AnyBay (front) ■ 16x 2.5" NVMe + 8x 2.5" SAS/SATA ■ 24x 2.5" NVMe
Internal storage	<ul style="list-style-type: none"> • 1 drive group: 1 cache drive + 2-7 capacity drives. • 2 drive groups: 1 cache drive + 2-6 capacity drives in each group. • 3 drive groups: 1 cache drive + 2-3 capacity drives in each group. • 4 drive groups: 1 cache drive + 2 capacity drives in each group. <p>Note: The quantity of the capacity drives in each drive group must be the same.</p>
Storage controller	<ul style="list-style-type: none"> • 12 Gbps SAS/6 Gbps SATA non-RAID: <ul style="list-style-type: none"> ◦ 430-8i HBA ◦ 430-16i HBA • NVMe PCIe non-RAID (VX7520 and VX 2U Certified Nodes) <ul style="list-style-type: none"> ◦ Onboard NVMe ◦ 810-4P NVMe Switch Adapter ◦ 1610-4P NVMe Switch Adapter ◦ 1610-8P NVMe Switch Adapter
Network interfaces	Onboard LOM slot for an adapter with up to 4x 1Gb or 10 Gb Ethernet ports Additional network adapters in PCIe slots
GPU adapters	VX3520-G supports up to 3x double-wide GPUs or up to 5x single-wide GPUs
Boot drive	2x M.2 non-hot-swap SSDs (RAID-1).

Attribute	Specification
I/O expansion slots	<p>Up to seven slots. Slots 4 and 7 are the fixed slots on the system planar, and the remaining slots depend on the riser cards installed. The slots are as follows:</p> <ul style="list-style-type: none"> Slot 1: PCIe 3.0 x16 or PCIe 3.0 x8; full-height, half-length (PCIe x16 slot is double-wide) Slot 2: PCIe 3.0 x8; full-height, half-length (not present if the slot 1 is PCIe x16) Slot 3: PCIe 3.0 x8 or ML2; full-height, half-length Slot 4: PCIe 3.0 x8; low profile (vertical slot on system planar) Slot 5: PCIe 3.0 x16; full-height, half-length Slot 6: PCIe 3.0 x16; full-height, half-length Slot 7: PCIe 3.0 x8 (dedicated to an internal RAID controller) <p>Slots 5 and 6 require the second processor to be installed.</p>
Ports	<ul style="list-style-type: none"> Front: 1x USB 2.0 port with XClarity Controller access, 1x USB 3.0 port, 1x VGA port (optional) Rear: 2x USB 3.0 ports, 1x VGA port, 1x RJ-45 10/100/1000 Mb Ethernet port for systems management.
Cooling	Five (one processor) or six (two processors) hot-swap system fans with N+1 redundancy.
Power supply	One or two redundant hot-swap 1100 W (100 - 240 V) or 1600 W (200 - 240 V) High Efficiency Platinum power supplies.
Video	Matrox G200 with 16 MB memory integrated into the XClarity Controller. Maximum resolution is 1920x1200 at 60 Hz with 32 bits per pixel.
Hot-swap parts	SSDs, HDDs, power supplies, and fans.
Systems management	Lenovo XClarity Controller (XCC) Enterprise (Pilot 4 chip), proactive platform alerts, light path diagnostics, Lenovo XClarity Administrator with Integrator for VMware vCenter, Lenovo XClarity Energy Manager (optional).
Security features	Power-on password, administrator's password, secure firmware updates, Trusted Platform Module (TPM) 1.2 or 2.0 (configurable UEFI setting). Optional lockable front bezel.
Software	<p>Software licenses that can be purchased from Lenovo or provided by the customer:</p> <ul style="list-style-type: none"> VMware vSAN: Standard, Advanced, Enterprise, Enterprise Plus, ROBO or Desktop VMware vSphere: Standard, Enterprise Plus or ROBO HCI Kit: Essentials, Standard, Advanced, Enterprise or ROBO VMware Horizon: Standard, Advanced or Enterprise VMware Cloud Foundation (VCF): Basic, Standard, Advanced, Enterprise or for VDI VMware vCenter Server: Foundation or Standard
Hypervisors	VMware ESXi. See Operating system support section for details.
Warranty and support	Three- or five-year customer-replaceable unit and onsite limited hardware warranty with ThinkAgile Advantage Support and selectable service levels: 9x5 next business day (NBD) parts delivered, 9x5 NBD onsite response, 24x7 coverage with 2-hour or 4-hour onsite response, or 6-hour or 24-hour committed repair (select areas). Also available are YourDrive YourData, Premier Support, and Enterprise Software Support.
Software maintenance	One- (PRC only), three-, or five-year software support and subscription (matches the duration of the selected warranty period).
Dimensions	Width: 445 mm (17.5 in.), height: 87 mm (3.4 in.), depth: 764 mm (30.1 in.)
Weight	Maximum configuration: 32 kg (70.5 lb).

Models

Factory-integrated models of the ThinkAgile VX Series Appliances are configured by using the Lenovo Data Center Solution Configurator (DCSC), <http://dcsc.lenovo.com>.

During the configuration process, you are selecting one of the Configure-to-Order (CTO) base models first, and then you are adding components (processors, memory, drives, and network adapters) to the selected model.

Note: You are required to engage a Lenovo representative in the project that includes the ThinkAgile VX Series Appliances. ThinkAgile VX certified nodes do not have this requirement.

The following table lists the CTO base models.

Table 3. CTO base models

Machine Type/Model	Description
7Y94CTO3WW	ThinkAgile VX3520-G Appliance
7Y94CTO1WW	ThinkAgile VX5520 Appliance
7Y94CTO2WW	ThinkAgile VX7520 Appliance
7Y94CTO5WW	ThinkAgile VX 2U Certified Node
7Y94CTO6WW	ThinkAgile VX 2U Certified Node for SAP HANA

Models of the VX systems are defined based on whether the systems have 16x 2.5-inch, 24x 2.5-inch or 12x 3.5-inch drive bays at the front. For models, the feature codes for these chassis bases are as listed in the following table.

Table 4. Chassis base feature codes

Feature	Description	Maximum supported				
		VX3520-G	VX5520	VX7520	VX 2U	VX 2U HANA
BVL7	ThinkAgile VX 2U 2.5" 8/16 Bay Chassis v2	1	No	No	1	1
BMWD	ThinkAgile VX 2U 2.5" 8/16 Bay Chassis v2	1	No	No	1	1
BMWE	ThinkAgile VX 2U 2.5" 8/16/24 Bay Chassis v2	No	No	1	1	1
BVL6	ThinkAgile VX 2U 2.5" 8/16/24 Bay Chassis v2	No	No	1	1	1
B1DG	ThinkAgile VX 2U 3.5" 8/12 Bay Chassis	No	1	No	1	No

Comparison with the ThinkSystem SR650

The ThinkAgile VX3520-G, VX5520, VX7520 2U Appliances and VX 2U Certified Nodes are based on the ThinkSystem SR650 server, however there are key differences:

- No onboard SATA controller support
- No RAID adapter support
- No VROC RAID support
- No SATA HDDs
- No SED drive support
- No Fibre Channel support
- No InfiniBand support
- Drives are categorized as Cache or Capacity drives and are formed as disk groups (up to 4 disk groups)

For details about the ThinkSystem SR650, see the SR650 product guide:

<https://lenovopress.com/lp1050-thinksystem-sr650-server>

To verify what specific hardware components are supported with the VX3520-G, VX5520, VX7520 and VX 2U Certified Nodes, see the DCSC configurator:

<https://dcsc.lenovo.com>

Processors

The VX3520-G, VX5520, VX7520 and VX 2U Certified Nodes systems support the following processors.

For details about these options, including configuration rules, see the SR650 product guide:

<https://lenovopress.com/lp1050-thinksystem-sr650-server#processors>

Table 5. Processor choices

Part number	Feature	Description	Maximum supported				
			VX3520-G	VX5520	VX7520	VX 2U	VX 2U HANA
Intel Xeon Bronze processors							
4XG7A37938	B4HU	Intel Xeon Bronze 3204 6C 85W 1.9GHz Processor	2	2	2	2	2
4XG7A37983	B7N3	Intel Xeon Bronze 3206R 8C 85W 1.9GHz Processor	2	2	2	2	2
Intel Xeon Silver processors							
4XG7A37935	B4HT	Intel Xeon Silver 4208 8C 85W 2.1GHz Processor	2	2	2	2	2
4XG7A37932	B4HS	Intel Xeon Silver 4210 10C 85W 2.2GHz Processor	2	2	2	2	2
4XG7A37981	B7N5	Intel Xeon Silver 4210R 10C 100W 2.4GHz Processor	2	2	2	2	2
4XG7A63276	BAZT	Intel Xeon Silver 4210T 10C 95W 2.3GHz Processor	2	2	2	2	2
4XG7A37929	B4HR	Intel Xeon Silver 4214 12C 85W 2.2GHz Processor	2	2	2	2	2
4XG7A37980	B7N6	Intel Xeon Silver 4214R 12C 100W 2.4GHz Processor	2	2	2	2	2
4XG7A37941	B4NW	Intel Xeon Silver 4214Y 12/10/8C 85W 2.2GHz Processor	2	2	2	2	2
4XG7A37926	B4HQ	Intel Xeon Silver 4215 8C 85W 2.5GHz Processor	2	2	2	2	2

Part number	Feature	Description	Maximum supported				
			VX3520-G	VX5520	VX7520	VX 2U	VX 2U HANA
4XG7A63274	BAZU	Intel Xeon Silver 4215R 8C 130W 3.2GHz Processor	2	2	2	2	2
4XG7A37923	B4HP	Intel Xeon Silver 4216 16C 100W 2.1GHz Processor	2	2	2	2	2
Intel Xeon Gold processors							
4XG7A37916	B4HN	Intel Xeon Gold 5215 10C 85W 2.5GHz Processor	2	2	2	2	2
4XG7A37910	B4P9	Intel Xeon Gold 5215L 10C 85W 2.5GHz Processor	2	2	2	2	2
4XG7A37919	B4HM	Intel Xeon Gold 5217 8C 115W 3.0GHz Processor	2	2	2	2	2
4XG7A37895	B4HL	Intel Xeon Gold 5218 16C 125W 2.3GHz Processor	2	2	2	2	2
4XG7A37958	B6BS	Intel Xeon Gold 5218B 16C 125W 2.3GHz Processor	2	2	2	2	2
4XG7A63272	BAZS	Intel Xeon Gold 5218R 20C 125W 2.1GHz Processor	2	2	2	2	2
4XG7A38016	B4P3	Intel Xeon Gold 5218T 16C 105W 2.1GHz Processor	2	2	2	2	2
4XG7A37892	B4HK	Intel Xeon Gold 5220 18C 125W 2.2GHz Processor	2	2	2	2	2
4XG7A37974	B7N9	Intel Xeon Gold 5220R 24C 150W 2.2GHz Processor	2	2	2	2	2
4XG7A38019	B6CW	Intel Xeon Gold 5220S 18C 125W 2.7GHz Processor	2	2	2	2	2
4XG7A38005	B6CQ	Intel Xeon Gold 5220T 18C 105W 1.9GHz Processor	2	2	2	2	2
4XG7A37951	B5S1	Intel Xeon Gold 5222 4C 105W 3.8GHz Processor	2	2	2	2	2
CTO only	BAZV	Intel Xeon Gold 6208U 16C 150W 2.9GHz Processor	1	1	1	1	1
4XG7A38023	B6CV	Intel Xeon Gold 6222V 20C 115W 1.8GHz Processor	2	2	2	2	2
4XG7A38021	B6CL	Intel Xeon Gold 6226 12C 125W 2.7GHz Processor	2	2	2	2	2
4XG7A38082	BAZW	Intel Xeon Gold 6226R 16C 150W 2.9GHz Processor	2	2	2	2	2
4XG7A37889	B4HJ	Intel Xeon Gold 6230 20C 125W 2.1GHz Processor	2	2	2	2	2
4XG7A38028	B5RY	Intel Xeon Gold 6230N 20C 125W 2.3GHz Processor	2	2	No	2	2
4XG7A38081	BAZX	Intel Xeon Gold 6230R 26C 150W 2.1GHz Processor	2	2	2	2	2
4XG7A38006	B6CP	Intel Xeon Gold 6230T 20C 125W 2.1GHz Processor	2	2	2	2	2
4XG7A38001	B6CK	Intel Xeon Gold 6234 8C 130W 3.3GHz Processor	2	2	2	2	2
4XG7A38008	B6CJ	Intel Xeon Gold 6238 22C 140W 2.1GHz Processor	2	2	2	2	2
4XG7A38003	B6CR	Intel Xeon Gold 6238L 22C 140W 2.1GHz Processor	2	2	2	2	2
4XG7A38080	BAZL	Intel Xeon Gold 6238R 28C 165W 2.2GHz Processor	No	2	2	2	2
4XG7A15895	B4HH	Intel Xeon Gold 6240 18C 150W 2.6GHz Processor	2	2	2	2	2
4XG7A38015	B6CS	Intel Xeon Gold 6240L 18C 150W 2.6GHz Processor	2	2	2	2	2
4XG7A38079	BAZM	Intel Xeon Gold 6240R 24C 165W 2.4GHz Processor	No	2	2	2	2
4XG7A37903	B4NV	Intel Xeon Gold 6240Y 18/14/8C 150W 2.6GHz Processor	No	2	2	2	2
4XG7A37886	B4HG	Intel Xeon Gold 6242 16C 150W 2.8GHz Processor	2	2	2	2	2
4XG7A38078	BAZN	Intel Xeon Gold 6242R 20C 205W 3.1GHz Processor	No	No	2	2	2
4XG7A15874	B4HF	Intel Xeon Gold 6244 8C 150W 3.6GHz Processor	No	No	2	2	2
4XG7A37963	B6PD	Intel Xeon Gold 6246 12C 165W 3.3GHz Processor	2	2	2	2	2
4XG7A38077	BAZP	Intel Xeon Gold 6246R 16C 205W 3.4GHz Processor	No	No	2	2	2

Part number	Feature	Description	Maximum supported				
			VX3520-G	VX5520	VX7520	VX 2U	VX 2U HANA
4XG7A15892	B4HE	Intel Xeon Gold 6248 20C 150W 2.5GHz Processor	2	2	2	2	2
4XG7A38076	BAZQ	Intel Xeon Gold 6248R 24C 205W 3.0GHz Processor	No	No	2	2	2
4XG7A38075	B96C	Intel Xeon Gold 6250 8C 185W 3.9GHz Processor	No	No	2	2	2
4XG7A15889	B4HC	Intel Xeon Gold 6252 24C 150W 2.1GHz Processor	2	2	2	2	2
4XG7A38011	B6CT	Intel Xeon Gold 6252N 24C 150W 2.3GHz Processor	2	2	2	2	2
4XG7A15872	B4HD	Intel Xeon Gold 6254 18C 200W 3.1GHz Processor	No	No	2	2	2
4XG7A38074	B96D	Intel Xeon Gold 6256 12C 205W 3.6GHz Processor	No	No	2	2	2
4XG7A38073	BAZR	Intel Xeon Gold 6258R 28C 205W 2.7GHz Processor	No	No	2	2	2
4XG7A38010	B6CU	Intel Xeon Gold 6262V 24C 135W 1.9GHz Processor	2	2	2	2	2
Intel Xeon Platinum processors							
4XG7A37898	B5RZ	Intel Xeon Platinum 8253 16C 125W 2.2GHz Processor	2	2	2	2	2
4XG7A37947	B5S2	Intel Xeon Platinum 8256 4C 105W 3.8GHz Processor	2	2	2	2	2
4XG7A15887	B4HB	Intel Xeon Platinum 8260 24C 165W 2.4GHz Processor	No	2	2	2	2
4XG7A15885	B4P7	Intel Xeon Platinum 8260L 24C 165W 2.4GHz Processor	No	2	2	2	2
4XG7A37901	B4NU	Intel Xeon Platinum 8260Y 24/20/16C 165W 2.4GHz Processor	No	2	2	2	2
4XG7A15870	B4HA	Intel Xeon Platinum 8268 24C 205W 2.9GHz Processor	No	No	2	2	2
4XG7A15868	B4H9	Intel Xeon Platinum 8270 26C 205W 2.7GHz Processor	No	No	2	2	2
4XG7A15881	B4H8	Intel Xeon Platinum 8276 28C 165W 2.2GHz Processor	No	2	2	2	2
4XG7A15877	B4P6	Intel Xeon Platinum 8276L 28C 165W 2.2GHz Processor	No	2	2	2	2
4XG7A15866	B4H7	Intel Xeon Platinum 8280 28C 205W 2.7GHz Processor	No	No	2	2	2
4XG7A15862	B4P5	Intel Xeon Platinum 8280L 28C 205W 2.7GHz Processor	No	No	2	2	2

Memory

The VX3520-G, VX5520, VX7520 and VX 2U Certified Nodes systems support the following memory options.

For details about these options, including configuration rules, see the SR650 product guide:

<https://lenovopress.com/lp1050-thinksystem-sr650-server#memory>

Table 6. Memory options

Part number	Feature	Description	Maximum supported				
			VX3520-G	VX5520	VX7520	VX 2U	VX 2U HANA
RDIMMs - 2933 MHz Performance+							
4X77A12184	B5N6	ThinkSystem 16GB TruDDR4 Performance+ 2933MHz (2Rx8 1.2V) RDIMM	24	24	24	24	24
4X77A12185	B5N7	ThinkSystem 32GB TruDDR4 Performance+ 2933MHz (2Rx4 1.2V) RDIMM	24	24	24	24	24
4X77A12186	B5N8	ThinkSystem 64GB TruDDR4 Performance+ 2933MHz (2Rx4 1.2V) RDIMM	24	24	24	24	24
RDIMMs - 2933 MHz							
4ZC7A08706	B4H1	ThinkSystem 8GB TruDDR4 2933MHz (1Rx8 1.2V) RDIMM	24	24	24	24	24
4ZC7A08707	B4LY	ThinkSystem 16GB TruDDR4 2933 MHz (1Rx4 1.2V) RDIMM	24	24	24	24	24
4ZC7A08708	B4H2	ThinkSystem 16GB TruDDR4 2933MHz (2Rx8 1.2V) RDIMM	24	24	24	24	24
4ZC7A08709	B4H3	ThinkSystem 32GB TruDDR4 2933MHz (2Rx4 1.2V) RDIMM	24	24	24	24	24
4ZC7A08710	B4H4	ThinkSystem 64GB TruDDR4 2933MHz (2Rx4 1.2V) RDIMM	24	24	24	24	24
RDIMMs - 2666 MHz							
7X77A01302	AUNB	ThinkSystem 16GB TruDDR4 2666 MHz (1Rx4 1.2V) RDIMM	24	24	24	24	24
7X77A01303	AUNC	ThinkSystem 16GB TruDDR4 2666 MHz (2Rx8 1.2V) RDIMM	24	24	24	24	24
7X77A01304	AUND	ThinkSystem 32GB TruDDR4 2666 MHz (2Rx4 1.2V) RDIMM	24	24	24	24	24
3DS RDIMMs - 2933 MHz Performance+							
4X77A12187	B5N9	ThinkSystem 128GB TruDDR4 Performance+ 2933MHz (4Rx4 1.2V) 3DS RDIMM	24	24	24	24	24
3DS RDIMMs - 2933 MHz							
4ZC7A15113	B587	ThinkSystem 128GB TruDDR4 2933MHz (4Rx4 1.2V) 3DS RDIMM	24	24	24	24	24
3DS RDIMMs - 2666 MHz							
4ZC7A08716	AUW5	ThinkSystem 64GB TruDDR4 2666MHz (4Rx4, 1.2V) 3DS RDIMM	24	24	24	24	24

Persistent Memory

The VX3520-G, VX5520, VX7520 and VX 2U Certified Nodes systems support the following persistent memory options.

For details about these options, including configuration rules, see the SR650 product guide:

<https://lenovopress.com/lp1050-thinksystem-sr650-server#persistent-memory>

Table 7. Persistent memory options

Part number	Feature	Description	Maximum supported				
			VX3520-G	VX5520	VX7520	VX 2U	VX 2U HANA
4ZC7A15110	B4LV	ThinkSystem 128GB TruDDR4 2666MHz (1.2V) Intel Optane DC Persistent Memory	No	No	No	12	12
4ZC7A15111	B4LW	ThinkSystem 256GB TruDDR4 2666MHz (1.2V) Intel Optane DC Persistent Memory	No	No	No	12	12
4ZC7A15112	B4LX	ThinkSystem 512GB TruDDR4 2666MHz (1.2V) Intel Optane DC Persistent Memory	No	No	No	12	12

Internal storage

Internal storage configurations of the VX3520-G, VX5520, VX7520 and VX 2U Certified Nodes are as follows. All drives are hot-swap and are accessible from the front or rear of the system:

- ThinkAgile VX3520-G Appliance
 - Front drive bays: 16x 2.5-inch SAS/SATA
 - Rear drive bays: None
- ThinkAgile VX5520 Appliance
 - Front drive bays: 12x 3.5-inch SAS/SATA
 - Rear drive bays: 2x 3.5-inch SAS/SATA
- ThinkAgile VX7520 Appliance
 - Front drive bays - 3 configurations:
 - 20x SAS/SATA + 4x AnyBay (Configurations with SAS/SATA capacity drives): 2x SAS/SATA backplanes and 1x AnyBay backplane
 - 16x SAS/SATA + 8x AnyBay (Configurations with NVMe capacity drives): 1x SAS/SATA backplane and 2x AnyBay backplanes
 - 24x NVMe: 3x NVMe backplanes
 - Rear drive bays: None
- ThinkAgile VX 2U Certified Node
 - Up to 16x 2.5" and 2x 3.5" drive bays:
 - 16x 2.5" SAS/SATA (front) + 2x 3.5" SAS/SATA (rear)
 - 12x 2.5" SAS/SATA & 4x 2.5" AnyBay (front) + 2x 3.5" SAS/SATA (rear)
 - 8x 2.5" SAS/SATA & 8x 2.5" AnyBay (front) + 2x 3.5" SAS/SATA (rear)
 - Up to 24x 2.5" and 2x 3.5" drive bays:
 - 24x 2.5" SAS/SATA (front) + 2x 3.5" SAS/SATA (rear)
 - 20x 2.5" SAS/SATA & 4x 2.5" AnyBay (front) + 2x 3.5" SAS/SATA (rear)
 - 16x 2.5" SAS/SATA & 8x 2.5" AnyBay (front) + 2x 3.5" SAS/SATA (rear)
 - 16x 2.5" NVMe & 8x 2.5" SAS/SATA (front)
 - 24x 2.5" NVMe (front)

- Up to 14x 3.5" drive bays:
 - 12x 3.5" SAS/SATA (front) + 2x 3.5" SAS/SATA (rear)
 - 8x 3.5" SAS/SATA & 4x 3.5" AnyBay (front) + 2x 3.5" SAS/SATA (rear)
- ThinkAgile VX 2U Certified Node for SAP HANA
 - Up to 16x 2.5" drive bays:
 - 16x 2.5" SAS/SATA (front)
 - 12x 2.5" SAS/SATA & 4x 2.5" AnyBay (front)
 - 8x 2.5" SAS/SATA & 8x 2.5" AnyBay (front)
 - Up to 24x 2.5" drive bays:
 - 24x 2.5" SAS/SATA (front)
 - 20x 2.5" SAS/SATA & 4x 2.5" AnyBay (front)
 - 16x 2.5" SAS/SATA & 8x 2.5" AnyBay (front)
 - 16x 2.5" NVMe + 8x 2.5" SAS/SATA
 - 24x 2.5" NVMe
 - No rear drives

The server also supports one or two M.2 drives for OS boot purposes, installed in an M.2 adapter internal to the server.

Ordering information is listed in the following table.

Table 8. Drive backplanes

Feature	Description	Maximum supported				
		VX3520-G	VX5520	VX7520	VX 2U	VX 2U HANA
Front 2.5-inch drive backplanes						
AURA	ThinkSystem 2U/Twr 2.5" SATA/SAS 8-Bay Backplane (8x SATA/SATA)	3	No	2	3	3
AUR5	ThinkSystem 2U/Twr 2.5" AnyBay 8-Bay Backplane (4x SAS/SATA + 4x AnyBay)	No	No	2	3	3
B4PC	ThinkSystem 2U 2.5" NVMe 8-Bay Backplane (8x NVMe)	No	No	3	3	3
Front 3.5-inch drive backplanes						
AUR9	ThinkSystem 2U 3.5" SATA/SAS 12-Bay Backplane (12x SAS/SATA)	No	1	No	1	No
AUR8	ThinkSystem 2U 3.5" AnyBay 12-Bay Backplane (8x SAS/SATA + 4x AnyBay)	No	No	No	1	No
Rear 3.5-inch drive backplanes						
AURZ	ThinkSystem SR590/SR650 Rear HDD/SSD Kit (2x SAS/SATA)	No	1	No	1	No

For details about these components, including configuration rules, see the SR650 product guide:
<https://lenovopress.com/lp1050-thinksystem-sr650-server#internal-storage>

The following figures show the internal drive bay configurations.




Figure 9. Drive bay configurations: 2.5-inch 8/16-bay chassis





Figure 10. Drive bay configurations: 2.5-inch 8/16/24-bay chassis

3. Up to 14 LFF hot-swap drive bays



a) 12x 3.5" SAS/SATA (front)

b) 8x 3.5" SAS/SATA +
4x 3.5" AnyBay (front)

+ 2x 3.5-inch SAS/SATA (rear)

Figure 11. Drive bay configurations: 3.5-inch 8/12-bay chassis

Disk Groups

The following table lists the supported Disk Groups for each VX system.

Table 9. Disk Groups

Drive Selection Rules	VX3520-G Appliance	VX5520 Appliance	VX7520 Appliance	VX 2U Certified Node	VX 2U Certified Node for HANA
Model Type	Hybrid (HY) All Flash (AF)	Hybrid (HY) All Flash (AF)	Hybrid (HY) All Flash (AF)	Hybrid (HY) All Flash (AF)	All Flash (AF)
Maximum number of drives	16	14	24	24	24
Number of Disk Groups	1 - 4	1 - 2	1 - 4	1 - 4	2 - 4
Number of Cache Drives per Disk Group	1	1	1	1	1
Number of Capacity Drives per Disk Group	2 - 7	2 - 7	2 - 7	2 - 7	2 - 7
Allowed Capacity Drive Quantities:					
1 Disk Group (1 Cache Drive)	2, 3, 4, 5, 6 or 7	2, 3, 4, 5, 6 or 7	2, 3, 4, 5, 6 or 7	2, 3, 4, 5, 6 or 7	Not supported
2 Disk Groups (2 Cache Drives)	4, 6, 8, 10, 12 or 14	4, 6, 8, 10 or 12	4, 6, 8, 10, 12 or 14	4, 6, 8, 10, 12 or 14	4, 6, 8, 10, 12 or 14
3 Disk Groups (3 Cache Drives)	6, 9 or 12	6 or 9	6, 9, 12, 15, 18 or 21	6, 9, 12, 15, 18 or 21	6, 9, 12, 15, 18 or 21
4 Disk Groups (4 Cache Drives)	8 or 12	8	8, 12, 16 or 20	8, 12, 16 or 20	8, 12, 16 or 20
5 Disk Groups (5 Cache Drives)	10	Not supported	10 or 15	10 or 15	Not supported

Controllers for internal storage

The VX3520-G, VX5520, VX7520 and VX 2U Certified Nodes systems support the following storage controller options.

For details about these components, including configuration rules, see the SR650 product guide:
<https://lenovopress.com/lp1050-thinksystem-sr650-server#controllers-for-internal-storage>

Table 10. Controllers for internal storage

Part number	Feature	Description	Maximum supported				
			VX3520-G	VX5520	VX7520	VX 2U	VX 2U HANA
12 Gb SAS/SATA non-RAID HBAs							
7Y37A01088	AUNL	ThinkSystem 430-8i SAS/SATA 12Gb HBA	No	No	4	4	3
4Y37A72480	BJHH	ThinkSystem 4350-8i SAS/SATA 12Gb HBA	2	2	4	4	3
4Y37A78601	BM51	ThinkSystem 440-8i SAS/SATA PCIe Gen4 12Gb HBA	2	2	4	4	3
7Y37A01089	AUNM	ThinkSystem 430-16i SAS/SATA 12Gb HBA	1	1	2	2	2
4Y37A72481	BJHJ	ThinkSystem 4350-16i SAS/SATA 12Gb HBA	1	1	2	2	2
4Y37A78602	BM50	ThinkSystem 440-16i SAS/SATA PCIe Gen4 12Gb HBA	1	1	2	2	2
NVMe PCIe interfaces							
None	B22D	ThinkSystem 810-4P NVMe Switch Adapter	No	No	4	4	4
7Y37A01081	AUV2	ThinkSystem 1610-4P NVMe Switch Adapter	No	No	3	3	3
None	B4PA	ThinkSystem 1610-8P NVMe Switch Adapter	No	No	1	1	1

Internal drive options

This section lists the supported drives:

- [Boot drives](#)
- [Internal drives for VX3520-G](#)
- [Internal drives for VX5520](#)
- [Internal drives for VX7520](#)
- [Internal drives for VX 2U Certified Node](#)
- [Internal drives for VX 2U for SAP HANA Certified Node](#)

Configuration Note: VMware will no longer support higher capacity drives greater than 8TB

Boot drives

The VX3520-G, VX5520, VX7520 and VX 2U Certified Nodes systems support the following drive for boot functions.

Table 11. Boot drives

Part number	Feature	Description	Maximum supported				
			VX3520-G	VX5520	VX7520	VX 2U	VX 2U HANA
M.2 SSDs - 6 Gb SATA							
4XB7A82286	BQ1Z	ThinkSystem M.2 5400 PRO 240GB Read Intensive SATA 6Gb NHS SSD	2	2	2	2	2
4XB7A82287	BQ1Y	ThinkSystem M.2 5400 PRO 480GB Read Intensive SATA 6Gb NHS SSD	2	2	2	2	2
4XB7A82288	BQ20	ThinkSystem M.2 5400 PRO 960GB Read Intensive SATA 6Gb NHS SSD	2	2	2	2	2

Internal drives for VX3520-G Appliance

The following table lists the drives supported in the VX3520-G Appliance. For both All Flash Storage and Hybrid Storage configurations, drives are classified as either Cache drives, Capacity drives, or both.

Table 12. Drives supported in the VX3520-G Appliance

Part number	Feature	Description	All Flash Storage		Hybrid Storage	
			Cache	Capacity	Cache	Capacity
2.5-inch hot-swap 12 Gb SAS HDDs						
7XB7A00034	AUM6	ThinkSystem 2.5" 1TB 7.2K SAS 12Gb Hot Swap 512n HDD	No	No	No	16
7XB7A00035	AUM7	ThinkSystem 2.5" 2TB 7.2K SAS 12Gb Hot Swap 512n HDD	No	No	No	16
7XB7A00026	AUM0	ThinkSystem 2.5" 900GB 10K SAS 12Gb Hot Swap 512n HDD	No	No	No	16
7XB7A00027	AUM1	ThinkSystem 2.5" 1.2TB 10K SAS 12Gb Hot Swap 512n HDD	No	No	No	16
7XB7A00028	AUM2	ThinkSystem 2.5" 1.8TB 10K SAS 12Gb Hot Swap 512e HDD	No	No	No	16
7XB7A00069	B0YS	ThinkSystem 2.5" 2.4TB 10K SAS 12Gb Hot Swap 512e HDD	No	No	No	16
7XB7A00023	AULX	ThinkSystem 2.5" 900GB 15K SAS 12Gb Hot Swap 512e HDD	No	No	No	16
2.5-inch hot-swap 24 Gb SAS SSDs						
4XB7A80318	BNWC	ThinkSystem 2.5" PM1653 960GB Read Intensive SAS 24Gb HS SSD	No	12	No	No
4XB7A80319	BNWE	ThinkSystem 2.5" PM1653 1.92TB Read Intensive SAS 24Gb HS SSD	No	12	No	No
4XB7A80320	BNWF	ThinkSystem 2.5" PM1653 3.84TB Read Intensive SAS 24Gb HS SSD	No	12	No	No

Part number	Feature	Description	All Flash Storage		Hybrid Storage	
			Cache	Capacity	Cache	Capacity
4XB7A80321	BP3E	ThinkSystem 2.5" PM1653 7.68TB Read Intensive SAS 24Gb HS SSD	No	12	No	No
4XB7A80322	BP3J	ThinkSystem 2.5" PM1653 15.36TB Read Intensive SAS 24Gb HS SSD	No	12	No	No
4XB7A80340	BNW8	ThinkSystem 2.5" PM1655 800GB Mixed Use SAS 24Gb HS SSD	12	12	12	No
4XB7A80341	BNW9	ThinkSystem 2.5" PM1655 1.6TB Mixed Use SAS 24Gb HS SSD	12	12	12	No
4XB7A80342	BNW6	ThinkSystem 2.5" PM1655 3.2TB Mixed Use SAS 24Gb HS SSD	12	12	12	No
4XB7A80343	BP3K	ThinkSystem 2.5" PM1655 6.4TB Mixed Use SAS 24Gb HS SSD	12	12	12	No
2.5-inch hot-swap 12 Gb SAS SSDs						
4XB7A83214	BR10	ThinkSystem 2.5" Nytro 3750 400GB Write Intensive SAS 12Gb HS SSD	12	12	12	No
4XB7A83215	BR0Z	ThinkSystem 2.5" Nytro 3750 800GB Write Intensive SAS 12Gb HS SSD	12	12	12	No
4XB7A83216	BR0Y	ThinkSystem 2.5" Nytro 3750 1.6TB Write Intensive SAS 12Gb HS SSD	12	12	12	No
4XB7A83217	BR0X	ThinkSystem 2.5" Nytro 3750 3.2TB Write Intensive SAS 12Gb HS SSD	12	12	12	No
4XB7A17062	B8HU	ThinkSystem 2.5" PM1645a 800GB Mainstream SAS 12Gb Hot Swap SSD	16	16	16	No
4XB7A38175	B91A	ThinkSystem 2.5" PM1643a 960GB Entry SAS 12Gb Hot Swap SSD	No	16	No	No
4XB7A17056	BC4R	ThinkSystem 2.5" PM1643a 15.36TB Entry SAS 12Gb Hot Swap SSD	16	16	16	No
2.5-inch hot-swap 6 Gb SATA SSDs						
4XB7A17080	B8J2	ThinkSystem 2.5" 5300 7.68TB Entry SATA 6Gb Hot Swap SSD	No	16	No	No
4XB7A17089	B8J6	ThinkSystem 2.5" 5300 960GB Mainstream SATA 6Gb Hot Swap SSD	16	16	16	No
4XB7A17090	B8JE	ThinkSystem 2.5" 5300 1.92TB Mainstream SATA 6Gb Hot Swap SSD	16	16	16	No
4XB7A17091	B8J7	ThinkSystem 2.5" 5300 3.84TB Mainstream SATA 6Gb Hot Swap SSD	16	16	16	No
4XB7A13637	B49Q	ThinkSystem 2.5" S4610 3.84TB Mixed Use SATA 6Gb HS SSD	16	16	16	No
4XB7A17125	BA7Q	ThinkSystem 2.5" S4620 480GB Mixed Use SATA 6Gb HS SSD	16	16	16	No
4XB7A17126	BA4T	ThinkSystem 2.5" S4620 960GB Mixed Use SATA 6Gb HS SSD	16	16	16	No
4XB7A17127	BA4U	ThinkSystem 2.5" S4620 1.92TB Mixed Use SATA 6Gb HS SSD	16	16	16	No

Part number	Feature	Description	All Flash Storage		Hybrid Storage	
			Cache	Capacity	Cache	Capacity
4XB7A17128	BK7L	ThinkSystem 2.5" S4620 3.84TB Mixed Use SATA 6Gb HS SSD	16	16	16	No
4XB7A82289	BQ21	ThinkSystem 2.5" 5400 MAX 480GB Mixed Use SATA 6Gb HS SSD	12	12	12	No
4XB7A82290	BQ24	ThinkSystem 2.5" 5400 MAX 960GB Mixed Use SATA 6Gb HS SSD	12	12	12	No
4XB7A82291	BQ22	ThinkSystem 2.5" 5400 MAX 1.92TB Mixed Use SATA 6Gb HS SSD	12	12	12	No
4XB7A82292	BQ23	ThinkSystem 2.5" 5400 MAX 3.84TB Mixed Use SATA 6Gb HS SSD	12	12	12	No
4XB7A72438	BM8B	ThinkSystem 2.5" PM893 480GB Read Intensive SATA 6Gb HS SSD	No	16	No	No
4XB7A72439	BM8A	ThinkSystem 2.5" PM893 960GB Read Intensive SATA 6Gb HS SSD	No	16	No	No
4XB7A72440	BM89	ThinkSystem 2.5" PM893 1.92TB Read Intensive SATA 6Gb HS SSD	No	16	16	No
4XB7A72441	BM88	ThinkSystem 2.5" PM893 3.84TB Read Intensive SATA 6Gb HS SSD	16	16	16	No
4XB7A72442	BM87	ThinkSystem 2.5" PM893 7.68TB Read Intensive SATA 6Gb HS SSD	16	16	16	No
4XB7A17101	BA7G	ThinkSystem 2.5" S4520 480GB Read Intensive SATA 6Gb HS SSD	No	16	No	No
4XB7A17102	BA7H	ThinkSystem 2.5" S4520 960GB Read Intensive SATA 6Gb HS SSD	No	16	No	No
4XB7A17103	BA7J	ThinkSystem 2.5" S4520 1.92TB Read Intensive SATA 6Gb HS SSD	No	16	No	No
4XB7A17104	BK77	ThinkSystem 2.5" S4520 3.84TB Read Intensive SATA 6Gb HS SSD	No	16	No	No
4XB7A17105	BK78	ThinkSystem 2.5" S4520 7.68TB Read Intensive SATA 6Gb HS SSD	No	16	No	No
4XB7A82258	BQ1Q	ThinkSystem 2.5" 5400 PRO 240GB Read Intensive SATA 6Gb HS SSD	No	12	No	No
4XB7A82259	BQ1P	ThinkSystem 2.5" 5400 PRO 480GB Read Intensive SATA 6Gb HS SSD	No	12	No	No
4XB7A82260	BQ1R	ThinkSystem 2.5" 5400 PRO 960GB Read Intensive SATA 6Gb HS SSD	No	12	No	No
4XB7A82261	BQ1X	ThinkSystem 2.5" 5400 PRO 1.92TB Read Intensive SATA 6Gb HS SSD	No	12	No	No
4XB7A82262	BQ1S	ThinkSystem 2.5" 5400 PRO 3.84TB Read Intensive SATA 6Gb HS SSD	No	12	No	No
4XB7A82263	BQ1T	ThinkSystem 2.5" 5400 PRO 7.68TB Read Intensive SATA 6Gb HS SSD	No	12	No	No
2.5-inch hot-swap PCIe 4.0 NVMe SSDs						
4XB7A17129	BNEG	ThinkSystem 2.5" U.2 P5620 1.6TB Mixed Use NVMe PCIe 4.0 x4 HS SSD	24	24	No	No

Part number	Feature	Description	All Flash Storage		Hybrid Storage	
			Cache	Capacity	Cache	Capacity
4XB7A17130	BNEH	ThinkSystem 2.5" U.2 P5620 3.2TB Mixed Use NVMe PCIe 4.0 x4 HS SSD	24	24	No	No
4XB7A17133	BNEZ	ThinkSystem 2.5" U.2 P5620 6.4TB Mixed Use NVMe PCIe 4.0 x4 HS SSD	24	24	No	No
4XB7A79639	BNF1	ThinkSystem 2.5" U.3 7450 MAX 800GB Mixed Use NVMe PCIe 4.0 x4 HS SSD	24	24	No	No
4XB7A13967	BNEJ	ThinkSystem 2.5" U.3 7450 MAX 1.6TB Mixed Use NVMe PCIe 4.0 x4 HS SSD	24	24	No	No
4XB7A13970	BNEY	ThinkSystem 2.5" U.3 7450 MAX 3.2TB Mixed Use NVMe PCIe 4.0 x4 HS SSD	24	24	No	No
4XB7A13971	BNEL	ThinkSystem 2.5" U.3 7450 MAX 6.4TB Mixed Use NVMe PCIe 4.0 x4 HS SSD	24	24	No	No

Internal drives for VX5520 Appliance

The following table lists the drives supported in the VX5520 Appliance. For both All Flash Storage and Hybrid Storage configurations, drives are classified as either Cache drives, Capacity drives, or both..

Table 13. Drives supported in the VX5520 Appliance

Part number	Feature	Description	All Flash Storage		Hybrid Storage	
			Cache	Capacity	Cache	Capacity
3.5-inch hot-swap 12 Gb SAS HDDs						
7XB7A00042	AUU5	ThinkSystem 3.5" 2TB 7.2K SAS 12Gb Hot Swap 512n HDD	No	No	No	14
7XB7A00043	AUU6	ThinkSystem 3.5" 4TB 7.2K SAS 12Gb Hot Swap 512n HDD	No	No	No	14
7XB7A00044	AUU7	ThinkSystem 3.5" 6TB 7.2K SAS 12Gb Hot Swap 512e HDD	No	No	No	14
7XB7A00045	B0YR	ThinkSystem 3.5" 8TB 7.2K SAS 12Gb Hot Swap 512e HDD	No	No	No	14
3.5-inch hot-swap 24 Gb SAS SSDs						
4XB7A80324	BNWD	ThinkSystem 3.5" PM1653 960GB Read Intensive SAS 24Gb HS SSD	14	14	14	No
4XB7A80325	BNWG	ThinkSystem 3.5" PM1653 1.92TB Read Intensive SAS 24Gb HS SSD	14	14	14	No
4XB7A80326	BNWH	ThinkSystem 3.5" PM1653 3.84TB Read Intensive SAS 24Gb HS SSD	14	14	14	No
4XB7A80327	BP3F	ThinkSystem 3.5" PM1653 7.68TB Read Intensive SAS 24Gb HS SSD	14	14	14	No
4XB7A80328	BP3H	ThinkSystem 3.5" PM1653 15.36TB Read Intensive SAS 24Gb HS SSD	14	14	14	No
4XB7A80344	BNW7	ThinkSystem 3.5" PM1655 800GB Mixed Use SAS 24Gb HS SSD	14	14	14	No

Part number	Feature	Description	All Flash Storage		Hybrid Storage	
			Cache	Capacity	Cache	Capacity
4XB7A80345	BNWA	ThinkSystem 3.5" PM1655 1.6TB Mixed Use SAS 24Gb HS SSD	14	14	14	No
4XB7A80346	BNWB	ThinkSystem 3.5" PM1655 3.2TB Mixed Use SAS 24Gb HS SSD	14	14	14	No
4XB7A80347	BP3G	ThinkSystem 3.5" PM1655 6.4TB Mixed Use SAS 24Gb HS SSD	14	14	14	No
3.5-inch hot-swap 12 Gb SAS SSDs						
4XB7A83218	BR0W	ThinkSystem 3.5" Nytro 3750 400GB Write Intensive SAS 12Gb HS SSD	14	14	14	No
4XB7A83219	BR0V	ThinkSystem 3.5" Nytro 3750 800GB Write Intensive SAS 12Gb HS SSD	14	14	14	No
4XB7A83220	BR0U	ThinkSystem 3.5" Nytro 3750 1.6TB Write Intensive SAS 12Gb HS SSD	14	14	14	No
4XB7A83221	BR0T	ThinkSystem 3.5" Nytro 3750 3.2TB Write Intensive SAS 12Gb HS SSD	14	14	14	No
4XB7A17066	B8HT	ThinkSystem 3.5" PM1645a 800GB Mainstream SAS 12Gb Hot Swap SSD	14	14	14	No
3.5-inch hot-swap 6 Gb SATA SSDs						
4XB7A17098	B8J0	ThinkSystem 3.5" 5300 960GB Mainstream SATA 6Gb Hot Swap SSD	14	14	14	No
4XB7A17099	B8HR	ThinkSystem 3.5" 5300 1.92TB Mainstream SATA 6Gb Hot Swap SSD	14	14	14	No
4XB7A17100	B8HX	ThinkSystem 3.5" 5300 3.84TB Mainstream SATA 6Gb Hot Swap SSD	14	14	14	No
4XB7A17119	BA7L	ThinkSystem 3.5" S4520 480GB Read Intensive SATA 6Gb HS SSD	No	14	No	No
4XB7A17120	BA7M	ThinkSystem 3.5" S4520 960GB Read Intensive SATA 6Gb HS SSD	No	14	No	No
4XB7A17121	BA7N	ThinkSystem 3.5" S4520 1.92TB Read Intensive SATA 6Gb HS SSD	No	14	No	No
4XB7A17122	BK7F	ThinkSystem 3.5" S4520 3.84TB Read Intensive SATA 6Gb HS SSD	No	14	No	No
4XB7A17123	BK7G	ThinkSystem 3.5" S4520 7.68TB Read Intensive SATA 6Gb HS SSD	No	14	No	No
4XB7A13643	B49V	ThinkSystem 3.5" S4610 3.84TB Mixed Use SATA 6Gb HS SSD	14	14	14	No
4XB7A17137	BA4W	ThinkSystem 3.5" S4620 480GB Mixed Use SATA 6Gb HS SSD	No	14	14	No
4XB7A17138	BA4X	ThinkSystem 3.5" S4620 960GB Mixed Use SATA 6Gb HS SSD	14	14	14	No
4XB7A17139	BA4Y	ThinkSystem 3.5" S4620 1.92TB Mixed Use SATA 6Gb HS SSD	14	14	14	No
4XB7A17140	BK7P	ThinkSystem 3.5" S4620 3.84TB Mixed Use SATA 6Gb HS SSD	14	14	14	No

Internal drives for VX7520 Appliance

The following table lists the drives supported in the VX7520 Appliance. For both All Flash Storage and Hybrid Storage configurations, drives are classified as either Cache drives, Capacity drives, or both.

Table 14. Drives supported in the VX7520 Appliance

Part number	Feature	Description	All Flash Storage		Hybrid Storage	
			Cache	Capacity	Cache	Capacity
2.5-inch hot-swap 12 Gb SAS HDDs						
7XB7A00034	AUM6	ThinkSystem 2.5" 1TB 7.2K SAS 12Gb Hot Swap 512n HDD	No	No	No	24
7XB7A00035	AUM7	ThinkSystem 2.5" 2TB 7.2K SAS 12Gb Hot Swap 512n HDD	No	No	No	24
7XB7A00026	AUM0	ThinkSystem 2.5" 900GB 10K SAS 12Gb Hot Swap 512n HDD	No	No	No	24
7XB7A00027	AUM1	ThinkSystem 2.5" 1.2TB 10K SAS 12Gb Hot Swap 512n HDD	No	No	No	24
7XB7A00028	AUM2	ThinkSystem 2.5" 1.8TB 10K SAS 12Gb Hot Swap 512e HDD	No	No	No	24
7XB7A00069	B0YS	ThinkSystem 2.5" 2.4TB 10K SAS 12Gb Hot Swap 512e HDD	No	No	No	24
7XB7A00023	AULX	ThinkSystem 2.5" 900GB 15K SAS 12Gb Hot Swap 512e HDD	No	No	No	24
2.5-inch hot-swap 24 Gb SAS SSDs						
4XB7A80318	BNWC	ThinkSystem 2.5" PM1653 960GB Read Intensive SAS 24Gb HS SSD	No	24	No	No
4XB7A80319	BNWE	ThinkSystem 2.5" PM1653 1.92TB Read Intensive SAS 24Gb HS SSD	No	24	No	No
4XB7A80320	BNWF	ThinkSystem 2.5" PM1653 3.84TB Read Intensive SAS 24Gb HS SSD	No	24	No	No
4XB7A80321	BP3E	ThinkSystem 2.5" PM1653 7.68TB Read Intensive SAS 24Gb HS SSD	No	24	No	No
4XB7A80322	BP3J	ThinkSystem 2.5" PM1653 15.36TB Read Intensive SAS 24Gb HS SSD	No	24	No	No
4XB7A80340	BNW8	ThinkSystem 2.5" PM1655 800GB Mixed Use SAS 24Gb HS SSD	24	24	24	No
4XB7A80341	BNW9	ThinkSystem 2.5" PM1655 1.6TB Mixed Use SAS 24Gb HS SSD	24	24	24	No
4XB7A80342	BNW6	ThinkSystem 2.5" PM1655 3.2TB Mixed Use SAS 24Gb HS SSD	24	24	24	No
4XB7A80343	BP3K	ThinkSystem 2.5" PM1655 6.4TB Mixed Use SAS 24Gb HS SSD	24	24	24	No
2.5-inch hot-swap 12 Gb SAS SSDs						
4XB7A83214	BR10	ThinkSystem 2.5" Nytro 3750 400GB Write Intensive SAS 12Gb HS SSD	24	24	24	No
4XB7A83215	BR0Z	ThinkSystem 2.5" Nytro 3750 800GB Write Intensive SAS 12Gb HS SSD	24	24	24	No

Part number	Feature	Description	All Flash Storage		Hybrid Storage	
			Cache	Capacity	Cache	Capacity
4XB7A83216	BR0Y	ThinkSystem 2.5" Nytro 3750 1.6TB Write Intensive SAS 12Gb HS SSD	24	24	24	No
4XB7A83217	BR0X	ThinkSystem 2.5" Nytro 3750 3.2TB Write Intensive SAS 12Gb HS SSD	24	24	24	No
4XB7A17062	B8HU	ThinkSystem 2.5" PM1645a 800GB Mainstream SAS 12Gb Hot Swap SSD	24	24	24	No
4XB7A38175	B91A	ThinkSystem 2.5" PM1643a 960GB Entry SAS 12Gb Hot Swap SSD	No	24	No	No
4XB7A17056	BC4R	ThinkSystem 2.5" PM1643a 15.36TB Entry SAS 12Gb Hot Swap SSD	24	24	24	No
2.5-inch hot-swap 6 Gb SATA SSDs						
4XB7A17080	B8J2	ThinkSystem 2.5" 5300 7.68TB Entry SATA 6Gb Hot Swap SSD	No	24	No	No
4XB7A17089	B8J6	ThinkSystem 2.5" 5300 960GB Mainstream SATA 6Gb Hot Swap SSD	24	24	24	No
4XB7A17090	B8JE	ThinkSystem 2.5" 5300 1.92TB Mainstream SATA 6Gb Hot Swap SSD	24	24	24	No
4XB7A17091	B8J7	ThinkSystem 2.5" 5300 3.84TB Mainstream SATA 6Gb Hot Swap SSD	24	24	24	No
4XB7A13637	B49Q	ThinkSystem 2.5" S4610 3.84TB Mixed Use SATA 6Gb HS SSD	24	24	24	No
4XB7A17125	BA7Q	ThinkSystem 2.5" S4620 480GB Mixed Use SATA 6Gb HS SSD	24	24	24	No
4XB7A17126	BA4T	ThinkSystem 2.5" S4620 960GB Mixed Use SATA 6Gb HS SSD	24	24	24	No
4XB7A17127	BA4U	ThinkSystem 2.5" S4620 1.92TB Mixed Use SATA 6Gb HS SSD	24	24	24	No
4XB7A17128	BK7L	ThinkSystem 2.5" S4620 3.84TB Mixed Use SATA 6Gb HS SSD	24	24	24	No
4XB7A82289	BQ21	ThinkSystem 2.5" 5400 MAX 480GB Mixed Use SATA 6Gb HS SSD	24	24	24	No
4XB7A82290	BQ24	ThinkSystem 2.5" 5400 MAX 960GB Mixed Use SATA 6Gb HS SSD	24	24	24	No
4XB7A82291	BQ22	ThinkSystem 2.5" 5400 MAX 1.92TB Mixed Use SATA 6Gb HS SSD	24	24	24	No
4XB7A82292	BQ23	ThinkSystem 2.5" 5400 MAX 3.84TB Mixed Use SATA 6Gb HS SSD	24	24	24	No
4XB7A72438	BM8B	ThinkSystem 2.5" PM893 480GB Read Intensive SATA 6Gb HS SSD	No	24	No	No
4XB7A72439	BM8A	ThinkSystem 2.5" PM893 960GB Read Intensive SATA 6Gb HS SSD	No	24	No	No
4XB7A72440	BM89	ThinkSystem 2.5" PM893 1.92TB Read Intensive SATA 6Gb HS SSD	No	24	24	No
4XB7A72441	BM88	ThinkSystem 2.5" PM893 3.84TB Read Intensive SATA 6Gb HS SSD	24	24	24	No

Part number	Feature	Description	All Flash Storage		Hybrid Storage	
			Cache	Capacity	Cache	Capacity
4XB7A72442	BM87	ThinkSystem 2.5" PM893 7.68TB Read Intensive SATA 6Gb HS SSD	24	24	24	No
4XB7A17101	BA7G	ThinkSystem 2.5" S4520 480GB Read Intensive SATA 6Gb HS SSD	No	24	No	No
4XB7A17102	BA7H	ThinkSystem 2.5" S4520 960GB Read Intensive SATA 6Gb HS SSD	No	24	No	No
4XB7A17103	BA7J	ThinkSystem 2.5" S4520 1.92TB Read Intensive SATA 6Gb HS SSD	No	24	No	No
4XB7A17104	BK77	ThinkSystem 2.5" S4520 3.84TB Read Intensive SATA 6Gb HS SSD	No	24	No	No
4XB7A17105	BK78	ThinkSystem 2.5" S4520 7.68TB Read Intensive SATA 6Gb HS SSD	No	24	No	No
4XB7A82258	BQ1Q	ThinkSystem 2.5" 5400 PRO 240GB Read Intensive SATA 6Gb HS SSD	No	24	No	No
4XB7A82259	BQ1P	ThinkSystem 2.5" 5400 PRO 480GB Read Intensive SATA 6Gb HS SSD	No	24	No	No
4XB7A82260	BQ1R	ThinkSystem 2.5" 5400 PRO 960GB Read Intensive SATA 6Gb HS SSD	No	24	No	No
4XB7A82261	BQ1X	ThinkSystem 2.5" 5400 PRO 1.92TB Read Intensive SATA 6Gb HS SSD	No	24	No	No
4XB7A82262	BQ1S	ThinkSystem 2.5" 5400 PRO 3.84TB Read Intensive SATA 6Gb HS SSD	No	24	No	No
4XB7A82263	BQ1T	ThinkSystem 2.5" 5400 PRO 7.68TB Read Intensive SATA 6Gb HS SSD	No	24	No	No
2.5-inch hot-swap PCIe 4.0 NVMe SSDs						
4XB7A17129	BNEG	ThinkSystem 2.5" U.2 P5620 1.6TB Mixed Use NVMe PCIe 4.0 x4 HS SSD	24	24	No	No
4XB7A17130	BNEH	ThinkSystem 2.5" U.2 P5620 3.2TB Mixed Use NVMe PCIe 4.0 x4 HS SSD	24	24	No	No
4XB7A17133	BNEZ	ThinkSystem 2.5" U.2 P5620 6.4TB Mixed Use NVMe PCIe 4.0 x4 HS SSD	24	24	No	No
4XB7A17136	BA4V	ThinkSystem 2.5" U.2 P5620 12.8TB Mixed Use NVMe PCIe 4.0 x4 HS SSD	24	24	No	No
4XB7A79639	BNF1	ThinkSystem 2.5" U.3 7450 MAX 800GB Mixed Use NVMe PCIe 4.0 x4 HS SSD	24	24	No	No
4XB7A13967	BNEJ	ThinkSystem 2.5" U.3 7450 MAX 1.6TB Mixed Use NVMe PCIe 4.0 x4 HS SSD	24	24	No	No
4XB7A13970	BNEY	ThinkSystem 2.5" U.3 7450 MAX 3.2TB Mixed Use NVMe PCIe 4.0 x4 HS SSD	24	24	No	No
4XB7A13971	BNEL	ThinkSystem 2.5" U.3 7450 MAX 6.4TB Mixed Use NVMe PCIe 4.0 x4 HS SSD	24	24	No	No
4XB7A17145	BCFT	ThinkSystem 2.5" U.2 P5500 1.92TB Read Intensive NVMe PCIe 4.0 x4 HS SSD	No	24	No	No
4XB7A13941	BMGD	ThinkSystem 2.5" U.2 P5520 1.92TB Read Intensive NVMe PCIe 4.0 x4 HS SSD	No	24	No	No

Part number	Feature	Description	All Flash Storage		Hybrid Storage	
			Cache	Capacity	Cache	Capacity
4XB7A13942	BMGE	ThinkSystem 2.5" U.2 P5520 3.84TB Read Intensive NVMe PCIe 4.0 x4 HS SSD	No	24	No	No
4XB7A13943	BNEF	ThinkSystem 2.5" U.2 P5520 7.68TB Read Intensive NVMe PCIe 4.0 x4 HS SSD	No	24	No	No
4XB7A13631	BNEQ	ThinkSystem 2.5" U.2 P5520 15.36TB Read Intensive NVMe PCIe 4.0 x4 HS SSD	No	24	No	No
4XB7A79646	BNF3	ThinkSystem 2.5" U.3 7450 PRO 960GB Read Intensive NVMe PCIe 4.0 x4 HS SSD	No	24	No	No
4XB7A79647	BNF2	ThinkSystem 2.5" U.3 7450 PRO 1.92TB Read Intensive NVMe PCIe 4.0 x4 HS SSD	No	24	No	No
4XB7A79648	BNF5	ThinkSystem 2.5" U.3 7450 PRO 3.84TB Read Intensive NVMe PCIe 4.0 x4 HS SSD	No	24	No	No
4XB7A79649	BNF4	ThinkSystem 2.5" U.3 7450 PRO 7.68TB Read Intensive NVMe PCIe 4.0 x4 HS SSD	No	24	No	No
4XB7A83097	BQAV	ThinkSystem 2.5" U.3 7450 PRO 15.36TB Read Intensive NVMe PCIe 4.0 x4 HS SSD	No	24	No	No
4XB7A81951	BPKX	ThinkSystem 2.5" U.3 PM1733a 1.92TB Read Intensive NVMe PCIe 4.0 x4 HS SSD	No	24	No	No
4XB7A81952	BPKY	ThinkSystem 2.5" U.3 PM1733a 3.84TB Read Intensive NVMe PCIe 4.0 x4 HS SSD	No	24	No	No
4XB7A81953	BPKZ	ThinkSystem 2.5" U.3 PM1733a 7.68TB Read Intensive NVMe PCIe 4.0 x4 HS SSD	No	24	No	No
4XB7A81954	BPL0	ThinkSystem 2.5" U.3 PM1733a 15.36TB Read Intensive NVMe PCIe 4.0 x4 HS SSD	No	24	No	No
4XB7A38197	BC4Z	ThinkSystem U.2 PM1733 3.84TB Entry NVMe PCIe 4.0 x4 Hot Swap SSD	24	24	No	No
4XB7A38283	BE2E	ThinkSystem U.2 PM1733 7.68TB Entry NVMe PCIe 4.0 x4 Hot Swap SSD	24	24	No	No
4XB7A38284	BE2F	ThinkSystem U.2 PM1733 15.36TB Entry NVMe PCIe 4.0 x4 Hot Swap SSD	24	24	No	No

Internal drives for VX 2U Certified Node

The following table lists the drives supported in the VX 2U Certified Node. For both All Flash Storage and Hybrid Storage configurations, drives are classified as either Cache drives, Capacity drives, or both.

Table 15. Drives supported in the VX 2U Certified Node

Part number	Feature	Description	All Flash Storage		Hybrid Storage	
			Cache	Capacity	Cache	Capacity
2.5-inch hot-swap 12 Gb SAS HDDs						
7XB7A00034	AUM6	ThinkSystem 2.5" 1TB 7.2K SAS 12Gb Hot Swap 512n HDD	No	No	No	24
7XB7A00035	AUM7	ThinkSystem 2.5" 2TB 7.2K SAS 12Gb Hot Swap 512n HDD	No	No	No	24

Part number	Feature	Description	All Flash Storage		Hybrid Storage	
			Cache	Capacity	Cache	Capacity
7XB7A00026	AUM0	ThinkSystem 2.5" 900GB 10K SAS 12Gb Hot Swap 512n HDD	No	No	No	24
7XB7A00027	AUM1	ThinkSystem 2.5" 1.2TB 10K SAS 12Gb Hot Swap 512n HDD	No	No	No	24
7XB7A00028	AUM2	ThinkSystem 2.5" 1.8TB 10K SAS 12Gb Hot Swap 512e HDD	No	No	No	24
7XB7A00069	B0YS	ThinkSystem 2.5" 2.4TB 10K SAS 12Gb Hot Swap 512e HDD	No	No	No	24
7XB7A00023	AULX	ThinkSystem 2.5" 900GB 15K SAS 12Gb Hot Swap 512e HDD	No	No	No	24
2.5-inch hot-swap 24 Gb SAS SSDs						
4XB7A80318	BNWC	ThinkSystem 2.5" PM1653 960GB Read Intensive SAS 24Gb HS SSD	No	24	No	No
4XB7A80319	BNWE	ThinkSystem 2.5" PM1653 1.92TB Read Intensive SAS 24Gb HS SSD	No	24	No	No
4XB7A80320	BNWF	ThinkSystem 2.5" PM1653 3.84TB Read Intensive SAS 24Gb HS SSD	No	24	No	No
4XB7A80321	BP3E	ThinkSystem 2.5" PM1653 7.68TB Read Intensive SAS 24Gb HS SSD	No	24	No	No
4XB7A80322	BP3J	ThinkSystem 2.5" PM1653 15.36TB Read Intensive SAS 24Gb HS SSD	No	24	No	No
4XB7A80340	BNW8	ThinkSystem 2.5" PM1655 800GB Mixed Use SAS 24Gb HS SSD	24	24	24	No
4XB7A80341	BNW9	ThinkSystem 2.5" PM1655 1.6TB Mixed Use SAS 24Gb HS SSD	24	24	24	No
4XB7A80342	BNW6	ThinkSystem 2.5" PM1655 3.2TB Mixed Use SAS 24Gb HS SSD	24	24	24	No
4XB7A80343	BP3K	ThinkSystem 2.5" PM1655 6.4TB Mixed Use SAS 24Gb HS SSD	24	24	24	No
2.5-inch hot-swap 12 Gb SAS SSDs						
4XB7A83214	BR10	ThinkSystem 2.5" Nytro 3750 400GB Write Intensive SAS 12Gb HS SSD	24	24	24	No
4XB7A83215	BR0Z	ThinkSystem 2.5" Nytro 3750 800GB Write Intensive SAS 12Gb HS SSD	24	24	24	No
4XB7A83216	BR0Y	ThinkSystem 2.5" Nytro 3750 1.6TB Write Intensive SAS 12Gb HS SSD	24	24	24	No
4XB7A83217	BR0X	ThinkSystem 2.5" Nytro 3750 3.2TB Write Intensive SAS 12Gb HS SSD	24	24	24	No
4XB7A17062	B8HU	ThinkSystem 2.5" PM1645a 800GB Mainstream SAS 12Gb Hot Swap SSD	24	24	24	No
4XB7A38175	B91A	ThinkSystem 2.5" PM1643a 960GB Entry SAS 12Gb Hot Swap SSD	No	24	No	No
4XB7A17056	BC4R	ThinkSystem 2.5" PM1643a 15.36TB Entry SAS 12Gb Hot Swap SSD	24	24	24	No
2.5-inch hot-swap 6 Gb SATA SSDs						

Part number	Feature	Description	All Flash Storage		Hybrid Storage	
			Cache	Capacity	Cache	Capacity
4XB7A17080	B8J2	ThinkSystem 2.5" 5300 7.68TB Entry SATA 6Gb Hot Swap SSD	No	24	No	No
4XB7A17089	B8J6	ThinkSystem 2.5" 5300 960GB Mainstream SATA 6Gb Hot Swap SSD	24	24	24	No
4XB7A17090	B8JE	ThinkSystem 2.5" 5300 1.92TB Mainstream SATA 6Gb Hot Swap SSD	24	24	24	No
4XB7A17091	B8J7	ThinkSystem 2.5" 5300 3.84TB Mainstream SATA 6Gb Hot Swap SSD	24	24	24	No
4XB7A13637	B49Q	ThinkSystem 2.5" S4610 3.84TB Mixed Use SATA 6Gb HS SSD	24	24	24	No
4XB7A17125	BA7Q	ThinkSystem 2.5" S4620 480GB Mixed Use SATA 6Gb HS SSD	24	24	24	No
4XB7A17126	BA4T	ThinkSystem 2.5" S4620 960GB Mixed Use SATA 6Gb HS SSD	24	24	24	No
4XB7A17127	BA4U	ThinkSystem 2.5" S4620 1.92TB Mixed Use SATA 6Gb HS SSD	24	24	24	No
4XB7A17128	BK7L	ThinkSystem 2.5" S4620 3.84TB Mixed Use SATA 6Gb HS SSD	24	24	24	No
4XB7A82289	BQ21	ThinkSystem 2.5" 5400 MAX 480GB Mixed Use SATA 6Gb HS SSD	24	24	24	No
4XB7A82290	BQ24	ThinkSystem 2.5" 5400 MAX 960GB Mixed Use SATA 6Gb HS SSD	24	24	24	No
4XB7A82291	BQ22	ThinkSystem 2.5" 5400 MAX 1.92TB Mixed Use SATA 6Gb HS SSD	24	24	24	No
4XB7A82292	BQ23	ThinkSystem 2.5" 5400 MAX 3.84TB Mixed Use SATA 6Gb HS SSD	24	24	24	No
4XB7A72438	BM8B	ThinkSystem 2.5" PM893 480GB Read Intensive SATA 6Gb HS SSD	No	24	No	No
4XB7A72439	BM8A	ThinkSystem 2.5" PM893 960GB Read Intensive SATA 6Gb HS SSD	No	24	No	No
4XB7A72440	BM89	ThinkSystem 2.5" PM893 1.92TB Read Intensive SATA 6Gb HS SSD	No	24	24	No
4XB7A72441	BM88	ThinkSystem 2.5" PM893 3.84TB Read Intensive SATA 6Gb HS SSD	24	24	24	No
4XB7A72442	BM87	ThinkSystem 2.5" PM893 7.68TB Read Intensive SATA 6Gb HS SSD	24	24	24	No
4XB7A17101	BA7G	ThinkSystem 2.5" S4520 480GB Read Intensive SATA 6Gb HS SSD	No	24	No	No
4XB7A17102	BA7H	ThinkSystem 2.5" S4520 960GB Read Intensive SATA 6Gb HS SSD	No	24	No	No
4XB7A17103	BA7J	ThinkSystem 2.5" S4520 1.92TB Read Intensive SATA 6Gb HS SSD	No	24	No	No
4XB7A17104	BK77	ThinkSystem 2.5" S4520 3.84TB Read Intensive SATA 6Gb HS SSD	No	24	No	No

Part number	Feature	Description	All Flash Storage		Hybrid Storage	
			Cache	Capacity	Cache	Capacity
4XB7A17105	BK78	ThinkSystem 2.5" S4520 7.68TB Read Intensive SATA 6Gb HS SSD	No	24	No	No
4XB7A82258	BQ1Q	ThinkSystem 2.5" 5400 PRO 240GB Read Intensive SATA 6Gb HS SSD	No	24	No	No
4XB7A82259	BQ1P	ThinkSystem 2.5" 5400 PRO 480GB Read Intensive SATA 6Gb HS SSD	No	24	No	No
4XB7A82260	BQ1R	ThinkSystem 2.5" 5400 PRO 960GB Read Intensive SATA 6Gb HS SSD	No	24	No	No
4XB7A82261	BQ1X	ThinkSystem 2.5" 5400 PRO 1.92TB Read Intensive SATA 6Gb HS SSD	No	24	No	No
4XB7A82262	BQ1S	ThinkSystem 2.5" 5400 PRO 3.84TB Read Intensive SATA 6Gb HS SSD	No	24	No	No
4XB7A82263	BQ1T	ThinkSystem 2.5" 5400 PRO 7.68TB Read Intensive SATA 6Gb HS SSD	No	24	No	No
2.5-inch hot-swap PCIe 4.0 NVMe SSDs						
4XB7A17129	BNEG	ThinkSystem 2.5" U.2 P5620 1.6TB Mixed Use NVMe PCIe 4.0 x4 HS SSD	24	24	No	No
4XB7A17130	BNEH	ThinkSystem 2.5" U.2 P5620 3.2TB Mixed Use NVMe PCIe 4.0 x4 HS SSD	24	24	No	No
4XB7A17133	BNEZ	ThinkSystem 2.5" U.2 P5620 6.4TB Mixed Use NVMe PCIe 4.0 x4 HS SSD	24	24	No	No
4XB7A17136	BA4V	ThinkSystem 2.5" U.2 P5620 12.8TB Mixed Use NVMe PCIe 4.0 x4 HS SSD	24	24	No	No
4XB7A79639	BNF1	ThinkSystem 2.5" U.3 7450 MAX 800GB Mixed Use NVMe PCIe 4.0 x4 HS SSD	10	10	No	No
4XB7A13967	BNEJ	ThinkSystem 2.5" U.3 7450 MAX 1.6TB Mixed Use NVMe PCIe 4.0 x4 HS SSD	10	10	No	No
4XB7A13970	BNEY	ThinkSystem 2.5" U.3 7450 MAX 3.2TB Mixed Use NVMe PCIe 4.0 x4 HS SSD	10	10	No	No
4XB7A13971	BNEL	ThinkSystem 2.5" U.3 7450 MAX 6.4TB Mixed Use NVMe PCIe 4.0 x4 HS SSD	10	10	No	No
4XB7A17145	BCFT	ThinkSystem 2.5" U.2 P5500 1.92TB Read Intensive NVMe PCIe 4.0 x4 HS SSD	No	24	No	No
4XB7A13941	BMGD	ThinkSystem 2.5" U.2 P5520 1.92TB Read Intensive NVMe PCIe 4.0 x4 HS SSD	No	24	No	No
4XB7A13942	BMGE	ThinkSystem 2.5" U.2 P5520 3.84TB Read Intensive NVMe PCIe 4.0 x4 HS SSD	No	24	No	No
4XB7A13943	BNEF	ThinkSystem 2.5" U.2 P5520 7.68TB Read Intensive NVMe PCIe 4.0 x4 HS SSD	No	24	No	No
4XB7A13631	BNEQ	ThinkSystem 2.5" U.2 P5520 15.36TB Read Intensive NVMe PCIe 4.0 x4 HS SSD	No	24	No	No
4XB7A79646	BNF3	ThinkSystem 2.5" U.3 7450 PRO 960GB Read Intensive NVMe PCIe 4.0 x4 HS SSD	No	24	No	No
4XB7A79647	BNF2	ThinkSystem 2.5" U.3 7450 PRO 1.92TB Read Intensive NVMe PCIe 4.0 x4 HS SSD	No	24	No	No

Part number	Feature	Description	All Flash Storage		Hybrid Storage	
			Cache	Capacity	Cache	Capacity
4XB7A79648	BNF5	ThinkSystem 2.5" U.3 7450 PRO 3.84TB Read Intensive NVMe PCIe 4.0 x4 HS SSD	No	24	No	No
4XB7A79649	BNF4	ThinkSystem 2.5" U.3 7450 PRO 7.68TB Read Intensive NVMe PCIe 4.0 x4 HS SSD	No	24	No	No
4XB7A83097	BQAV	ThinkSystem 2.5" U.3 7450 PRO 15.36TB Read Intensive NVMe PCIe 4.0 x4 HS SSD	No	24	No	No
4XB7A81951	BPKX	ThinkSystem 2.5" U.3 PM1733a 1.92TB Read Intensive NVMe PCIe 4.0 x4 HS SSD	No	24	No	No
4XB7A81952	BPKY	ThinkSystem 2.5" U.3 PM1733a 3.84TB Read Intensive NVMe PCIe 4.0 x4 HS SSD	No	24	No	No
4XB7A81953	BPKZ	ThinkSystem 2.5" U.3 PM1733a 7.68TB Read Intensive NVMe PCIe 4.0 x4 HS SSD	No	24	No	No
4XB7A81954	BPL0	ThinkSystem 2.5" U.3 PM1733a 15.36TB Read Intensive NVMe PCIe 4.0 x4 HS SSD	No	24	No	No
4XB7A38197	BC4Z	ThinkSystem U.2 PM1733 3.84TB Entry NVMe PCIe 4.0 x4 Hot Swap SSD	24	24	No	No
4XB7A38283	BE2E	ThinkSystem U.2 PM1733 7.68TB Entry NVMe PCIe 4.0 x4 Hot Swap SSD	24	24	No	No
4XB7A38284	BE2F	ThinkSystem U.2 PM1733 15.36TB Entry NVMe PCIe 4.0 x4 Hot Swap SSD	24	24	No	No
3.5-inch hot-swap 12 Gb SAS HDDs						
7XB7A00042	AUU5	ThinkSystem 3.5" 2TB 7.2K SAS 12Gb Hot Swap 512n HDD	No	No	No	14
7XB7A00043	AUU6	ThinkSystem 3.5" 4TB 7.2K SAS 12Gb Hot Swap 512n HDD	No	No	No	14
7XB7A00044	AUU7	ThinkSystem 3.5" 6TB 7.2K SAS 12Gb Hot Swap 512e HDD	No	No	No	14
7XB7A00045	B0YR	ThinkSystem 3.5" 8TB 7.2K SAS 12Gb Hot Swap 512e HDD	No	No	No	14
3.5-inch hot-swap 24 Gb SAS SSDs						
4XB7A80324	BNWD	ThinkSystem 3.5" PM1653 960GB Read Intensive SAS 24Gb HS SSD	14	14	14	No
4XB7A80325	BNWG	ThinkSystem 3.5" PM1653 1.92TB Read Intensive SAS 24Gb HS SSD	14	14	14	No
4XB7A80326	BNWH	ThinkSystem 3.5" PM1653 3.84TB Read Intensive SAS 24Gb HS SSD	14	14	14	No
4XB7A80327	BP3F	ThinkSystem 3.5" PM1653 7.68TB Read Intensive SAS 24Gb HS SSD	14	14	14	No
4XB7A80328	BP3H	ThinkSystem 3.5" PM1653 15.36TB Read Intensive SAS 24Gb HS SSD	14	14	14	No
4XB7A80344	BNW7	ThinkSystem 3.5" PM1655 800GB Mixed Use SAS 24Gb HS SSD	14	14	14	No
4XB7A80345	BNWA	ThinkSystem 3.5" PM1655 1.6TB Mixed Use SAS 24Gb HS SSD	14	14	14	No

Part number	Feature	Description	All Flash Storage		Hybrid Storage	
			Cache	Capacity	Cache	Capacity
4XB7A80346	BNWB	ThinkSystem 3.5" PM1655 3.2TB Mixed Use SAS 24Gb HS SSD	14	14	14	No
4XB7A80347	BP3G	ThinkSystem 3.5" PM1655 6.4TB Mixed Use SAS 24Gb HS SSD	14	14	14	No
3.5-inch hot-swap 12 Gb SAS SSDs						
4XB7A83218	BR0W	ThinkSystem 3.5" Nytro 3750 400GB Write Intensive SAS 12Gb HS SSD	14	14	14	No
4XB7A83219	BR0V	ThinkSystem 3.5" Nytro 3750 800GB Write Intensive SAS 12Gb HS SSD	14	14	14	No
4XB7A83220	BR0U	ThinkSystem 3.5" Nytro 3750 1.6TB Write Intensive SAS 12Gb HS SSD	14	14	14	No
4XB7A83221	BR0T	ThinkSystem 3.5" Nytro 3750 3.2TB Write Intensive SAS 12Gb HS SSD	14	14	14	No
4XB7A17066	B8HT	ThinkSystem 3.5" PM1645a 800GB Mainstream SAS 12Gb Hot Swap SSD	14	14	14	No
3.5-inch hot-swap 6 Gb SATA SSDs						
4XB7A17098	B8J0	ThinkSystem 3.5" 5300 960GB Mainstream SATA 6Gb Hot Swap SSD	14	14	14	No
4XB7A17099	B8HR	ThinkSystem 3.5" 5300 1.92TB Mainstream SATA 6Gb Hot Swap SSD	14	14	14	No
4XB7A17100	B8HX	ThinkSystem 3.5" 5300 3.84TB Mainstream SATA 6Gb Hot Swap SSD	14	14	14	No
4XB7A17081	B8JB	ThinkSystem 3.5" 5300 240GB Entry SATA 6Gb Hot Swap SSD	No	14	No	No
4XB7A17086	B8J3	ThinkSystem 3.5" 5300 7.68TB Entry SATA 6Gb Hot Swap SSD	No	14	No	No
4XB7A17119	BA7L	ThinkSystem 3.5" S4520 480GB Read Intensive SATA 6Gb HS SSD	No	14	No	No
4XB7A17120	BA7M	ThinkSystem 3.5" S4520 960GB Read Intensive SATA 6Gb HS SSD	No	14	No	No
4XB7A17121	BA7N	ThinkSystem 3.5" S4520 1.92TB Read Intensive SATA 6Gb HS SSD	No	14	No	No
4XB7A17122	BK7F	ThinkSystem 3.5" S4520 3.84TB Read Intensive SATA 6Gb HS SSD	No	14	No	No
4XB7A17123	BK7G	ThinkSystem 3.5" S4520 7.68TB Read Intensive SATA 6Gb HS SSD	No	14	No	No
4XB7A13643	B49V	ThinkSystem 3.5" S4610 3.84TB Mixed Use SATA 6Gb HS SSD	14	14	14	No
4XB7A17137	BA4W	ThinkSystem 3.5" S4620 480GB Mixed Use SATA 6Gb HS SSD	No	14	14	No
4XB7A17138	BA4X	ThinkSystem 3.5" S4620 960GB Mixed Use SATA 6Gb HS SSD	14	14	14	No
4XB7A17139	BA4Y	ThinkSystem 3.5" S4620 1.92TB Mixed Use SATA 6Gb HS SSD	14	14	14	No

Part number	Feature	Description	All Flash Storage		Hybrid Storage	
			Cache	Capacity	Cache	Capacity
4XB7A17140	BK7P	ThinkSystem 3.5" S4620 3.84TB Mixed Use SATA 6Gb HS SSD	14	14	14	No

Internal drives for VX 2U Certified Node for SAP HANA

The following table lists the drives supported in the VX 2U Certified Node for SAP HANA. For both All Flash Storage and Hybrid Storage configurations, drives are classified as either Cache drives, Capacity drives, or both.

Table 16. Drives supported in the VX 2U Certified Node for SAP HANA

Part number	Feature	Description	All Flash Storage	
			Cache	Capacity
2.5-inch hot-swap 24 Gb SAS SSDs				
4XB7A80318	BNWC	ThinkSystem 2.5" PM1653 960GB Read Intensive SAS 24Gb HS SSD	No	24
4XB7A80319	BNWE	ThinkSystem 2.5" PM1653 1.92TB Read Intensive SAS 24Gb HS SSD	No	24
4XB7A80320	BNWF	ThinkSystem 2.5" PM1653 3.84TB Read Intensive SAS 24Gb HS SSD	No	24
4XB7A80321	BP3E	ThinkSystem 2.5" PM1653 7.68TB Read Intensive SAS 24Gb HS SSD	No	24
4XB7A80322	BP3J	ThinkSystem 2.5" PM1653 15.36TB Read Intensive SAS 24Gb HS SSD	No	24
4XB7A80340	BNW8	ThinkSystem 2.5" PM1655 800GB Mixed Use SAS 24Gb HS SSD	24	24
4XB7A80341	BNW9	ThinkSystem 2.5" PM1655 1.6TB Mixed Use SAS 24Gb HS SSD	24	24
4XB7A80342	BNW6	ThinkSystem 2.5" PM1655 3.2TB Mixed Use SAS 24Gb HS SSD	24	24
4XB7A80343	BP3K	ThinkSystem 2.5" PM1655 6.4TB Mixed Use SAS 24Gb HS SSD	24	24
2.5-inch hot-swap 12 Gb SAS SSDs				
4XB7A83214	BR10	ThinkSystem 2.5" Nytro 3750 400GB Write Intensive SAS 12Gb HS SSD	24	24
4XB7A83215	BR0Z	ThinkSystem 2.5" Nytro 3750 800GB Write Intensive SAS 12Gb HS SSD	24	24
4XB7A83216	BR0Y	ThinkSystem 2.5" Nytro 3750 1.6TB Write Intensive SAS 12Gb HS SSD	24	24
4XB7A83217	BR0X	ThinkSystem 2.5" Nytro 3750 3.2TB Write Intensive SAS 12Gb HS SSD	24	24
4XB7A17062	B8HU	ThinkSystem 2.5" PM1645a 800GB Mainstream SAS 12Gb Hot Swap SSD	24	24
4XB7A38175	B91A	ThinkSystem 2.5" PM1643a 960GB Entry SAS 12Gb Hot Swap SSD	No	24
4XB7A17056	BC4R	ThinkSystem 2.5" PM1643a 15.36TB Entry SAS 12Gb Hot Swap SSD	24	24
2.5-inch hot-swap 6 Gb SATA SSDs				
4XB7A17080	B8J2	ThinkSystem 2.5" 5300 7.68TB Entry SATA 6Gb Hot Swap SSD	No	24

Part number	Feature	Description	All Flash Storage	
			Cache	Capacity
4XB7A17089	B8J6	ThinkSystem 2.5" 5300 960GB Mainstream SATA 6Gb Hot Swap SSD	24	24
4XB7A17090	B8JE	ThinkSystem 2.5" 5300 1.92TB Mainstream SATA 6Gb Hot Swap SSD	24	24
4XB7A17091	B8J7	ThinkSystem 2.5" 5300 3.84TB Mainstream SATA 6Gb Hot Swap SSD	24	24
4XB7A13637	B49Q	ThinkSystem 2.5" S4610 3.84TB Mixed Use SATA 6Gb HS SSD	24	24
4XB7A82289	BQ21	ThinkSystem 2.5" 5400 MAX 480GB Mixed Use SATA 6Gb HS SSD	24	24
4XB7A82290	BQ24	ThinkSystem 2.5" 5400 MAX 960GB Mixed Use SATA 6Gb HS SSD	24	24
4XB7A82291	BQ22	ThinkSystem 2.5" 5400 MAX 1.92TB Mixed Use SATA 6Gb HS SSD	24	24
4XB7A82292	BQ23	ThinkSystem 2.5" 5400 MAX 3.84TB Mixed Use SATA 6Gb HS SSD	24	24
4XB7A72438	BM8B	ThinkSystem 2.5" PM893 480GB Read Intensive SATA 6Gb HS SSD	No	24
4XB7A72439	BM8A	ThinkSystem 2.5" PM893 960GB Read Intensive SATA 6Gb HS SSD	No	24
4XB7A72440	BM89	ThinkSystem 2.5" PM893 1.92TB Read Intensive SATA 6Gb HS SSD	No	24
4XB7A72441	BM88	ThinkSystem 2.5" PM893 3.84TB Read Intensive SATA 6Gb HS SSD	24	24
4XB7A72442	BM87	ThinkSystem 2.5" PM893 7.68TB Read Intensive SATA 6Gb HS SSD	24	24
4XB7A17104	BK77	ThinkSystem 2.5" S4520 3.84TB Read Intensive SATA 6Gb HS SSD	No	24
4XB7A17105	BK78	ThinkSystem 2.5" S4520 7.68TB Read Intensive SATA 6Gb HS SSD	No	24
4XB7A82258	BQ1Q	ThinkSystem 2.5" 5400 PRO 240GB Read Intensive SATA 6Gb HS SSD	No	24
4XB7A82259	BQ1P	ThinkSystem 2.5" 5400 PRO 480GB Read Intensive SATA 6Gb HS SSD	No	24
4XB7A82260	BQ1R	ThinkSystem 2.5" 5400 PRO 960GB Read Intensive SATA 6Gb HS SSD	No	24
4XB7A82261	BQ1X	ThinkSystem 2.5" 5400 PRO 1.92TB Read Intensive SATA 6Gb HS SSD	No	24
4XB7A82262	BQ1S	ThinkSystem 2.5" 5400 PRO 3.84TB Read Intensive SATA 6Gb HS SSD	No	24
4XB7A82263	BQ1T	ThinkSystem 2.5" 5400 PRO 7.68TB Read Intensive SATA 6Gb HS SSD	No	24
2.5-inch hot-swap PCIe 4.0 NVMe SSDs				
4XB7A17129	BNEG	ThinkSystem 2.5" U.2 P5620 1.6TB Mixed Use NVMe PCIe 4.0 x4 HS SSD	24	24
4XB7A17130	BNEH	ThinkSystem 2.5" U.2 P5620 3.2TB Mixed Use NVMe PCIe 4.0 x4 HS SSD	24	24
4XB7A17133	BNEZ	ThinkSystem 2.5" U.2 P5620 6.4TB Mixed Use NVMe PCIe 4.0 x4 HS SSD	24	24

Part number	Feature	Description	All Flash Storage	
			Cache	Capacity
4XB7A17136	BA4V	ThinkSystem 2.5" U.2 P5620 12.8TB Mixed Use NVMe PCIe 4.0 x4 HS SSD	24	24
4XB7A79639	BNF1	ThinkSystem 2.5" U.3 7450 MAX 800GB Mixed Use NVMe PCIe 4.0 x4 HS SSD	24	24
4XB7A13967	BNEJ	ThinkSystem 2.5" U.3 7450 MAX 1.6TB Mixed Use NVMe PCIe 4.0 x4 HS SSD	24	24
4XB7A13970	BNEY	ThinkSystem 2.5" U.3 7450 MAX 3.2TB Mixed Use NVMe PCIe 4.0 x4 HS SSD	24	24
4XB7A13971	BNEL	ThinkSystem 2.5" U.3 7450 MAX 6.4TB Mixed Use NVMe PCIe 4.0 x4 HS SSD	24	24
4XB7A17145	BCFT	ThinkSystem 2.5" U.2 P5500 1.92TB Read Intensive NVMe PCIe 4.0 x4 HS SSD	No	24
4XB7A13941	BMGD	ThinkSystem 2.5" U.2 P5520 1.92TB Read Intensive NVMe PCIe 4.0 x4 HS SSD	No	24
4XB7A13942	BMGE	ThinkSystem 2.5" U.2 P5520 3.84TB Read Intensive NVMe PCIe 4.0 x4 HS SSD	No	24
4XB7A13943	BNEF	ThinkSystem 2.5" U.2 P5520 7.68TB Read Intensive NVMe PCIe 4.0 x4 HS SSD	No	24
4XB7A13631	BNEQ	ThinkSystem 2.5" U.2 P5520 15.36TB Read Intensive NVMe PCIe 4.0 x4 HS SSD	No	24
4XB7A79646	BNF3	ThinkSystem 2.5" U.3 7450 PRO 960GB Read Intensive NVMe PCIe 4.0 x4 HS SSD	No	24
4XB7A79647	BNF2	ThinkSystem 2.5" U.3 7450 PRO 1.92TB Read Intensive NVMe PCIe 4.0 x4 HS SSD	No	24
4XB7A79648	BNF5	ThinkSystem 2.5" U.3 7450 PRO 3.84TB Read Intensive NVMe PCIe 4.0 x4 HS SSD	No	24
4XB7A79649	BNF4	ThinkSystem 2.5" U.3 7450 PRO 7.68TB Read Intensive NVMe PCIe 4.0 x4 HS SSD	No	24
4XB7A83097	BQAV	ThinkSystem 2.5" U.3 7450 PRO 15.36TB Read Intensive NVMe PCIe 4.0 x4 HS SSD	No	24
4XB7A38197	BC4Z	ThinkSystem U.2 PM1733 3.84TB Entry NVMe PCIe 4.0 x4 Hot Swap SSD	24	24
4XB7A38283	BE2E	ThinkSystem U.2 PM1733 7.68TB Entry NVMe PCIe 4.0 x4 Hot Swap SSD	24	24
4XB7A38284	BE2F	ThinkSystem U.2 PM1733 15.36TB Entry NVMe PCIe 4.0 x4 Hot Swap SSD	24	24

Network adapters

The VX3520-G, VX5520, VX7520 and VX 2U Certified Nodes systems support the following networking options.

For details about these options, including configuration rules, see the SR650 product guide:

<https://lenovopress.com/lp1050-thinksystem-sr650-server#i-o-expansion>

<https://lenovopress.com/lp1050-thinksystem-sr650-server#network-adapters>

Table 17. LOM network adapters

Part number	Feature	Description	Maximum supported				
			VX3520-G	VX5520	VX7520	VX 2U	VX 2U HANA
LOM cards - 1 Gb Ethernet							
7ZT7A00544	AUKG	ThinkSystem 1Gb 2-port RJ45 LOM	No	No	No	1	1
7ZT7A00545	AUKH	ThinkSystem 1Gb 4-port RJ45 LOM	No	No	No	1	1
LOM cards - 10 Gb Ethernet							
7ZT7A00548	AUKL	ThinkSystem 10Gb 2-port Base-T LOM	1	1	1	1	1
7ZT7A00546	AUKJ	ThinkSystem 10Gb 2-port SFP+ LOM	1	1	1	1	1
7ZT7A00549	AUKM	ThinkSystem 10Gb 4-port Base-T LOM	1	1	1	1	1
7ZT7A00547	AUKK	ThinkSystem 10Gb 4-port SFP+ LOM	1	1	1	1	1

Table 18. PCIe network adapters

Part number	Feature	Description	Maximum supported				
			VX3520-G	VX5520	VX7520	VX 2U	VX 2U HANA
ML2 adapters - 10 Gb Ethernet							
01CV770	AU7Z	Emulex VFA5.2 ML2 2x10 GbE SFP+ Adapter and FCoE/iSCSI SW	No	No	No	1	1
00JY940	ATRH	Intel X710-DA2 ML2 2x10GbE SFP+ Adapter	No	No	No	1	1
ML2 adapters - 25 Gb Ethernet							
00MN990	ATZR	Mellanox ConnectX-4 Lx 10/25GbE SFP28 1-port ML2 Adapter	No	No	No	1	1
7ZT7A00507	AUKU	ThinkSystem Mellanox ConnectX-4 Lx 10/25GbE SFP28 2-Port ML2 Ethernet Adapter	No	No	No	1	1
PCIe Low Profile adapters - 1 Gb Ethernet							
7ZT7A00482	AUZX	ThinkSystem Broadcom 5720 1GbE RJ45 2-Port PCIe Ethernet Adapter	No	No	No	6	6
7ZT7A00484	AUZV	ThinkSystem Broadcom 5719 1GbE RJ45 4-Port PCIe Ethernet Adapter	No	No	No	6	6
7ZT7A00534	AUZY	ThinkSystem I350-T2 PCIe 1Gb 2-Port RJ45 Ethernet Adapter	No	No	No	6	6
7ZT7A00535	AUZW	ThinkSystem I350-T4 PCIe 1Gb 4-Port RJ45 Ethernet Adapter	No	2	No	6	6
PCIe Low Profile adapters - 10 Gb Ethernet							
7ZT7A00496	AUKP	ThinkSystem Broadcom 57416 10GBASE-T 2-Port PCIe Ethernet Adapter	6	6	6	6	6
00AG570	AT7S	Emulex VFA5.2 2x10 GbE SFP+ PCIe Adapter	6	6	6	6	6

Part number	Feature	Description	Maximum supported				
			VX3520-G	VX5520	VX7520	VX 2U	VX 2U HANA
00MM860	ATPX	Intel X550-T2 Dual Port 10GBase-T Adapter	6	6	6	6	6
7ZT7A00537	AUKX	ThinkSystem Intel X710-DA2 PCIe 10Gb 2-Port SFP+ Ethernet Adapter	6	6	6	6	6
4XC7A08225	B31G	ThinkSystem QLogic QL41134 PCIe 10Gb 4-Port Base-T Ethernet Adapter	6	6	6	6	6
4XC7A79699	BMXB	ThinkSystem Intel X710-T4L 10GBase-T 4-Port PCIe Ethernet Adapter	6	6	6	6	6
PCIe Full Height adapters - 10 Gb Ethernet							
7ZT7A00493	AUKN	ThinkSystem Emulex OCE14104B-NX PCIe 10Gb 4-Port SFP+ Ethernet Adapter	6	6	6	6	6
PCIe Low Profile adapters - 25 Gb Ethernet							
7ZT7A00505	AUKS	ThinkSystem Broadcom 57412 25GbE SFP28 1-Port PCIe Ethernet Adapter	6	6	6	6	6
4XC7A08238	B5T0	ThinkSystem Broadcom 57414 10/25GbE SFP28 2-port PCIe Ethernet Adapter	6	6	6	6	6
4XC7A08316	BD49	ThinkSystem Broadcom 57454 10/25GbE SFP28 4-port PCIe Ethernet Adapter V2	6	6	6	6	6
7XC7A05523	B0WY	ThinkSystem Intel XXV710-DA2 10/25GbE SFP28 2-Port PCIe Ethernet Adapter	6	6	6	6	6
01GR250	AUAJ	Mellanox ConnectX-4 Lx 10/25GbE SFP28 2-port PCIe Ethernet Adapter	6	6	6	6	6
4XC7A62580	BE4U	ThinkSystem Mellanox ConnectX-6 Lx 10/25GbE SFP28 2-Port PCIe Ethernet Adapter	6	6	6	6	6
4XC7A08228	B21R	ThinkSystem QLogic QL41262 10/25GbE SFP28 2-Port PCIe Ethernet Adapter	6	6	6	6	6
PCIe Low Profile adapters - 40 Gb Ethernet							
00MM950	ATRN	Mellanox ConnectX-4 Lx 1x40GbE QSFP+ Adapter	6	6	6	6	6
4XC7A08229	B31C	ThinkSystem Mellanox ConnectX-5 Ex 25/40GbE 2-port Low-Latency Adapter	3	3	3	3	3
PCIe x16 Low Profile adapters - 100 Gb Ethernet							
00MM960	ATRP	Mellanox ConnectX-4 2x100GbE/EDR IB QSFP28 VPI Adapter	3	3	3	3	3
4XC7A08248	B8PP	ThinkSystem Mellanox ConnectX-6 Dx 100GbE QSFP56 2-port PCIe Ethernet Adapter	3	3	3	3	3
4C57A14177	B4R9	ThinkSystem Mellanox ConnectX-6 HDR100/100GbE QSFP56 1-port PCIe VPI Adapter	2	2	2	2	2
4C57A14178	B4RA	ThinkSystem Mellanox ConnectX-6 HDR100/100GbE QSFP56 2-port PCIe VPI Adapter	2	2	2	2	2

GPU adapters

The VX3520-G, VX5520, VX7520 and VX 2U Certified Nodes systems support the following GPU options.

For details about these options, including configuration rules, see the SR650 product guide:

<https://lenovopress.com/lp1050-thinksystem-sr650-server#gpu-adapters>

Table 19. GPU adapters

Part number	Feature	Description	Maximum supported				
			VX3520-G	VX5520	VX7520	VX 2U	VX 2U HANA
Single-wide PCIe x16 GPU adapters							
CTO Only	BQZT	ThinkSystem NVIDIA A2 16GB PCIe Gen4 Passive GPU w/o CEC	5	No	No	5	No
CTO Only	BQZS	ThinkSystem NVIDIA A10 24GB PCIe Gen4 Passive GPU w/o CEC	4	No	No	4	No
4X67A14926	B4YB	ThinkSystem NVIDIA T4 16GB PCIe Passive GPU	5	No	No	5	No
Double-wide PCIe x16 GPU adapters							
4X67A76715	BQZP	ThinkSystem NVIDIA A100 80GB PCIe Gen4 Passive GPU w/o CEC	2	No	No	2	No
CTO Only	BQZU	ThinkSystem NVIDIA A16 64GB Gen4 PCIe Passive GPU w/o CEC	2	No	No	2	No
4X67A76581	BQZR	ThinkSystem NVIDIA A30 24GB PCIe Gen4 Passive GPU w/o CEC	2	No	No	2	No
4X67A71310	BFT0	ThinkSystem NVIDIA RTX A6000 48GB PCIe Active GPU	2	No	No	2	No
7C57A02891	B15V	NVIDIA Tesla M10 GPU, PCIe passive	2	No	No	2	No

Operating system support

The ThinkAgile VX3520-G Appliance supports the following operating systems:

- VMware ESXi 6.5 U2
- VMware ESXi 6.5 U3
- VMware ESXi 6.7 U1
- VMware ESXi 6.7 U2
- VMware ESXi 6.7 U3
- VMware ESXi 7.0
- VMware ESXi 7.0 U1
- VMware ESXi 7.0 U2
- VMware ESXi 7.0 U3
- VMware ESXi 8.0
- VMware ESXi 8.0 U1
- VMware ESXi 8.0 U2
- VMware ESXi 8.0 U3

The ThinkAgile VX5520 Appliance supports the following operating systems:

- VMware ESXi 6.5 U2

- VMware ESXi 6.5 U3
- VMware ESXi 6.7 U1
- VMware ESXi 6.7 U2
- VMware ESXi 6.7 U3
- VMware ESXi 7.0
- VMware ESXi 7.0 U1
- VMware ESXi 7.0 U2
- VMware ESXi 7.0 U3
- VMware ESXi 8.0
- VMware ESXi 8.0 U1
- VMware ESXi 8.0 U2
- VMware ESXi 8.0 U3

The ThinkAgile VX7520 Appliance supports the following operating systems:

- VMware ESXi 6.5 U2
- VMware ESXi 6.5 U3
- VMware ESXi 6.7 U1
- VMware ESXi 6.7 U2
- VMware ESXi 6.7 U3
- VMware ESXi 7.0
- VMware ESXi 7.0 U1
- VMware ESXi 7.0 U2
- VMware ESXi 7.0 U3
- VMware ESXi 8.0
- VMware ESXi 8.0 U1
- VMware ESXi 8.0 U2
- VMware ESXi 8.0 U3

The ThinkAgile VX 2U Certified Node supports the following operating systems:

- VMware ESXi 6.5 U2
- VMware ESXi 6.5 U3
- VMware ESXi 6.7 U1
- VMware ESXi 6.7 U2
- VMware ESXi 6.7 U3
- VMware ESXi 7.0
- VMware ESXi 7.0 U1
- VMware ESXi 7.0 U2
- VMware ESXi 7.0 U3
- VMware ESXi 8.0
- VMware ESXi 8.0 U1
- VMware ESXi 8.0 U2
- VMware ESXi 8.0 U3

The ThinkAgile VX 2U Certified Node for SAP HANA supports the following operating systems:

- VMware ESXi 6.5 U2
- VMware ESXi 6.5 U3
- VMware ESXi 6.7 U1
- VMware ESXi 6.7 U2
- VMware ESXi 6.7 U3
- VMware ESXi 7.0
- VMware ESXi 7.0 U1
- VMware ESXi 7.0 U2
- VMware ESXi 7.0 U3
- VMware ESXi 8.0 U1
- VMware ESXi 8.0 U2

- VMware ESXi 8.0 U3

For further details, including any restrictions, see the OS Interoperability Guide:

<https://lenovopress.com/osig#term=vx%2520purley%2520u%2520%2522gen%2520%2522&support=all>

Software

ThinkAgile VX Series offerings are available with the VMware Cloud Foundation (VCF) and VMware vSphere Foundation (VVF) primary software stack options. Licenses can be purchased through flexible term subscription-based models with 3-year or 5-year durations. In addition to the primary stack options, advanced service add-on options are available for features like vSAN additional capacity, Live Recovery, Firewall with Advanced Threat Prevention, Avi Load Balancer and Private AI Foundation.

Customers who have purchased VMware Licenses directly from Broadcom or an approved distributor have the flexibility to choose “Customer has VMware by Broadcom Software License” in their DCSC configuration.

Lenovo offers the following VMware software license and support options for ThinkAgile VX Series systems:

- Primary Software
 1. VMware Cloud Foundation (VCF)
 2. VMware vSphere Foundation (VVF)
- Add-On Options (requires purchase of a Primary Software version)
 1. VMware vSAN (for capacity over TiB allocation from primary SKU)
 2. VMware Live Recovery
 3. VMware vDefend Firewall Bundle (requires VCF)
 4. VMware vDefend Firewall with Advanced Threat Prevention Bundle (requires VCF)
 5. VMware Avi Load Balancer
 6. VMware Private AI Foundation (requires VCF)

For details and ordering information, see the VMware Software Solution Product Guide:

<https://lenovopress.com/lp1265-vmware-software-solution-product-guide>

Configuration notes:

- VMware software licenses that are available for selection include 3-year, or 5-year software support (matches the duration of the selected solution-level warranty period).
- The quantity of processor core count-based licenses is derived by the configuration tool based on the number of processors selected.
- The quantity of VM-based licenses is specified based on VM requirements.

For the VX 2U Certified Node for SAP HANA, HANA software licenses are purchased separately from SAP. Also, SUSE Linux Enterprise Server or Red Hat Enterprise Linux Server licenses are needed for deploying virtual machines for the SAP HANA virtualized environment. Optional Lenovo Professional Services are available to deploy SAP HANA software stack at the customer site.

Warranty and Support

The VX3520-G, VX5520, VX7520 and VX 2U Certified Nodes have a 3-year warranty based on the machine type:

- 7Y94 - 3 year warranty

The ThinkAgile VX Series Appliances can be configured with a three- or five-year hardware warranty with 24x7 ThinkAgile Advantage Single Point of Support (Lenovo server hardware and VMware software; requires an active software support contract purchased either from VMware or Lenovo) and various levels of coverage with a well-defined scope of services, including service hours, response time, term of service, and service agreement terms and conditions.

The Lenovo local support centers perform problem determination and resolution for hardware-related issues and escalate to VMware, on behalf of the customer, for software-related problem determination. VMware will contact the customer and will own the software-related problem resolution until closure.

Our global network of regional support centers offers consistent, local-language support enabling you to vary response times and level of service to match the criticality of your support needs:

- **Standard Next Business Day** – Best choice for non-essential systems requiring simple maintenance.
- **Premier Next Business Day** – Best choice for essential systems requiring technical expertise from senior-level Lenovo engineers.
- **Premier 24x7 4-Hour Response** – Best choice for systems where maximum uptime is critical.
- **Premier Enhanced Storage Support 24x7 4-Hour Response** – Best choice for storage systems where maximum uptime is critical.

For more information, consult the brochure [Lenovo Operational Support Services for Data Centers Services](#).

Software maintenance

The ThinkAgile VX Series Integrated Systems (appliances) or Certified Nodes can include three-, or five-year software subscription (matches the duration of the selected warranty period) that entitles customers to submit service requests to troubleshoot VMware software issues and receive code updates, including fixes, patches, and new software releases.

The Lenovo local support centers perform problem determination and resolution for hardware-related issues and escalate to VMware, on behalf of the customer, for software-related problem determination. Lenovo will contact the customer and will own the software-related problem resolution until closure.

For the VMware by Broadcom license purchased from Lenovo together with the ThinkAgile VX Series Certified Nodes, software support that is provided by VMware includes Production-level support with 24x7 phone and web coverage with the following target response times (priorities are defined by VMware based on the impact on productivity):

- Severity 1 (Critical: Substantial loss or disruption of service, significant risk of data loss): 30 minutes
- Severity 2 (Major: Operations are severely constrained, significant impact): 4 business hours
- Severity 3 (Minor: Non-critical loss of functionality, minimal impact): 8 business hours
- Severity 4 (Cosmetic: General questions): 12 business hours

For the VMware software and subscription licenses provided by the customer, software support that is provided by VMware is based on the support level included with these licenses. VMware by Broadcom will contact the customer and will own the software-related problem resolution until closure.

Deployment services

The following optional Lenovo basic installation services are available for the ThinkAgile VX Series Integrated Systems (appliances):

- Unpacking and inspecting the systems
- Mounting the systems in a rack cabinet
- Connecting the systems to electrical power and network
- Checking and updating firmware to the latest levels
- Verifying operations
- Disposal of the packaging materials (within the customer site)

ThinkAgile VX Integrated Systems include deployment services delivered by Lenovo Professional Services for the ultimate customer experience. However, “Channel Partner Provided” option is also available on DCSC. By choosing this option, Lenovo Customer or Lenovo Business Partner assumes the full responsibility to perform the deployment services for the quoted system. It is strongly recommended that Lenovo Professional Services or approved business partners are used to perform the deployment services.

The following additional Lenovo deployment services are available for the ThinkAgile VX Series with VMware vSphere Foundation solution to get customers up and running quickly. You can use the table below to add these services:

- Conducting remote preparation and planning
- Verifying firmware versions and performing firmware updates, if needed
- Configuring XCC management settings
- Configuring hypervisor settings
- Configuring vSAN
- Configuring VMware vCenter Server and discovering hosts and storage
- Configuring Lenovo XClarity network settings and performing discovery and inventory
- Transferring knowledge
- Developing post-installation documentation

The following Lenovo deployment services are provided with the ThinkAgile VX Series with VMware Cloud Foundation co-engineered solution to get customers up and running quickly:

- Planning and Design
 - Collect technical details for hardware and VMware environment
 - Plan the architecture based on Customer's business and tech requirements
 - Fill the VCF Plan, Prepare Workbook
- Implementation
 - Configure hardware (XCC IP, UEFI), upgrade firmware via OneCLI or BoMC
 - Deploy & Configure ESXi, Cloud Builder & import VCF Workbook, Lenovo xClarity software components
 - Check compliance with VX Best Recipes
- Handover
 - BAU updates based on VCF releases and VX Best Recipes
 - VMware Async Patch Tool (if required)
- Readiness Handover
 - Create handover document and knowledge transfer
 - Includes details for each deployed component

The following table lists ThinkAgile Health Check & Deployment offerings are available for ThinkAgile VX customers. These offerings are performed by Lenovo Professional Services.

- **Onsite Deployment:** Install, configure, and validate solution on-site, and conduct knowledge transfer.
- **Remote Deployment:** Install, configure, and validate solution remotely, and conduct knowledge transfer.
- **Remote Health Check:** Report & remediation of hardware and cluster health issues, including firmware and software updates.

Table 20. ThinkAgile Deployment offerings

Part number	Description
Onsite deployment services	
5MS7B00082	ThinkAgile VX Onsite Deployment (up to 4 nodes)
5MS7B00083	ThinkAgile VX Onsite Deployment (additional node)
Remote deployment services	
5MS7A87711	ThinkAgile VX Remote Deployment (up to 4 nodes)
5MS7A87712	ThinkAgile VX Remote Deployment (additional node)
Remote Health Check	
5MS7B00178	ThinkAgile VX 1X Remote Health Check (up to 4 node cluster)
5MS7B00179	ThinkAgile VX 1X Remote Health Check (additional node)
5MS7B00059	ThinkAgile VX 1X Remote Health Check & Update (up to 4 node cluster)
5MS7B00060	ThinkAgile VX 1X Remote Health Check & Update (additional node)

For more information, refer to the Data Center Implementation Services web page:

<https://www.lenovo.com/us/en/data-center/services/implementation-services/>

The SAP HANA onsite deployment that is provided by Lenovo Professional Services is optional for the ThinkAgile VX 2U Certified Node for SAP HANA.

Lenovo TruScale

Lenovo TruScale XaaS is your set of flexible IT services that makes everything easier. Streamline IT procurement, simplify infrastructure and device management, and pay only for what you use – so your business is free to grow and go anywhere.

Lenovo TruScale is the unified solution that gives you simplified access to:

- The industry's broadest portfolio – from pocket to cloud – all delivered as a service
- A single-contract framework for full visibility and accountability
- The global scale to rapidly and securely build teams from anywhere
- Flexible fixed and metered pay-as-you-go models with minimal upfront cost
- The growth-driving combination of hardware, software, infrastructure, and solutions – all from one single provider with one point of accountability.

For information about Lenovo TruScale offerings that are available in your region, contact your local Lenovo sales representative or business partner.

Regulatory compliance

The server conforms to the following standards:

- ANSI/UL 62368-1
- IEC 62368-1(CB Certificate and CB Test Report)
- FCC - Verified to comply with Part 15 of the FCC Rules, Class A
- Canada ICES-003, issue 7, Class A
- CSA C22.2 No. 62368-1
- CISPR 32, Class A, CISPR 35
- Japan VCCI, Class A
- Taiwan BSMI CNS13438, Class A; CNS 14336-1; Section 5 of CNS15663
- CE, UKCA Mark (EN55032 Class A, EN62368-1, EN55024, EN55035, EN61000-3-2, EN61000-3-3, (EU) 2019/424, and EN50581)
- Korea KN32, Class A, KN35
- Russia, Belorussia and Kazakhstan, TP EAC 037/2016 (for RoHS)
- Australia/New Zealand AS/NZS CISPR 32, Class A; AS/NZS 62368.1
- China CELP certificate, HJ 2507-2011
- UL Green Guard, UL2819
- Energy Star 3.0
- EPEAT (NSF/ ANSI 426) Bronze
- China CCC certificate, GB17625.1;GB4943.1;GB/T9254
- China CECP certificate, CQC3135
- Japanese Energy-Saving Act

Lenovo Financial Services

Why wait to obtain the technology you need now? No payments for 90 days and predictable, low monthly payments make it easy to budget for your Lenovo solution.

- **Flexible**

Our in-depth knowledge of the products, services and various market segments allows us to offer greater flexibility in structures, documentation and end of lease options.

- **100% Solution Financing**

Financing your entire solution including hardware, software, and services, ensures more predictability in your project planning with fixed, manageable payments and low monthly payments.

- **Device as a Service (DaaS)**

Leverage latest technology to advance your business. Customized solutions aligned to your needs. Flexibility to add equipment to support growth. Protect your technology with Lenovo's Premier Support service.

- **24/7 Asset management**

Manage your financed solutions with electronic access to your lease documents, payment histories, invoices and asset information.

- **Fair Market Value (FMV) and \$1 Purchase Option Leases**

Maximize your purchasing power with our lowest cost option. An FMV lease offers lower monthly payments than loans or lease-to-own financing. Think of an FMV lease as a rental. You have the flexibility at the end of the lease term to return the equipment, continue leasing it, or purchase it for the fair market value. In a \$1 Out Purchase Option lease, you own the equipment. It is a good option when you are confident you will use the equipment for an extended period beyond the finance term. Both lease types have merits depending on your needs. We can help you determine which option will best meet your technological and budgetary goals.

Ask your Lenovo Financial Services representative about this promotion and how to submit a credit application. For the majority of credit applicants, we have enough information to deliver an instant decision and send a notification within minutes.

Related publications and links

For more information, see these resources:

- Lenovo ThinkAgile VX Series
<https://www.lenovo.com/us/en/data-center/software-defined-infrastructure/ThinkAgile-VX-Series/p/WMD00000340>
- ThinkAgile VX - Best Recipes
<http://datacentersupport.lenovo.com/us/en/solutions/HT505302>
- VMware documentation
<https://docs.vmware.com/>
- ThinkSystem SR650 product guide:
<https://lenovopress.com/lp1050-thinksystem-sr650-server>
- Interactive 3D Tour of the ThinkSystem SR650:
<https://lenovopress.com/lp0673-3d-tour-thinksystem-sr650>
- Lenovo Press video walk-through of the ThinkSystem SR650:
<https://lenovopress.com/lp0700-thinksystem-sr650-server-video-walkthrough>

Related product families

Product families related to this document are the following:

- [2-Socket Rack Servers](#)
- [Hyperconverged Infrastructure](#)
- [ThinkAgile VX Series for VMware](#)

Notices

Lenovo may not offer the products, services, or features discussed in this document in all countries. Consult your local Lenovo representative for information on the products and services currently available in your area. Any reference to a Lenovo product, program, or service is not intended to state or imply that only that Lenovo product, program, or service may be used. Any functionally equivalent product, program, or service that does not infringe any Lenovo intellectual property right may be used instead. However, it is the user's responsibility to evaluate and verify the operation of any other product, program, or service. Lenovo may have patents or pending patent applications covering subject matter described in this document. The furnishing of this document does not give you any license to these patents. You can send license inquiries, in writing, to:

Lenovo (United States), Inc.
8001 Development Drive
Morrisville, NC 27560
U.S.A.
Attention: Lenovo Director of Licensing

LENOVO PROVIDES THIS PUBLICATION "AS IS" WITHOUT WARRANTY OF ANY KIND, EITHER EXPRESS OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF NON-INFRINGEMENT, MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE. Some jurisdictions do not allow disclaimer of express or implied warranties in certain transactions, therefore, this statement may not apply to you.

This information could include technical inaccuracies or typographical errors. Changes are periodically made to the information herein; these changes will be incorporated in new editions of the publication. Lenovo may make improvements and/or changes in the product(s) and/or the program(s) described in this publication at any time without notice.

The products described in this document are not intended for use in implantation or other life support applications where malfunction may result in injury or death to persons. The information contained in this document does not affect or change Lenovo product specifications or warranties. Nothing in this document shall operate as an express or implied license or indemnity under the intellectual property rights of Lenovo or third parties. All information contained in this document was obtained in specific environments and is presented as an illustration. The result obtained in other operating environments may vary. Lenovo may use or distribute any of the information you supply in any way it believes appropriate without incurring any obligation to you.

Any references in this publication to non-Lenovo Web sites are provided for convenience only and do not in any manner serve as an endorsement of those Web sites. The materials at those Web sites are not part of the materials for this Lenovo product, and use of those Web sites is at your own risk. Any performance data contained herein was determined in a controlled environment. Therefore, the result obtained in other operating environments may vary significantly. Some measurements may have been made on development-level systems and there is no guarantee that these measurements will be the same on generally available systems. Furthermore, some measurements may have been estimated through extrapolation. Actual results may vary. Users of this document should verify the applicable data for their specific environment.

© Copyright Lenovo 2025. All rights reserved.

This document, LP1500, was created or updated on June 1, 2023.

Send us your comments in one of the following ways:

- Use the online Contact us review form found at:
<https://lenovopress.lenovo.com/LP1500>
- Send your comments in an e-mail to:
comments@lenovopress.com

This document is available online at <https://lenovopress.lenovo.com/LP1500>.

Trademarks

Lenovo and the Lenovo logo are trademarks or registered trademarks of Lenovo in the United States, other countries, or both. A current list of Lenovo trademarks is available on the Web at <https://www.lenovo.com/us/en/legal/copytrade/>.

The following terms are trademarks of Lenovo in the United States, other countries, or both:

Lenovo®

AnyBay®

ThinkAgile®

ThinkSystem®

XClarity®

The following terms are trademarks of other companies:

Intel®, Intel Optane®, and Xeon® are trademarks of Intel Corporation or its subsidiaries.

Linux® is the trademark of Linus Torvalds in the U.S. and other countries.

Microsoft®, SQL Server®, and SharePoint® are trademarks of Microsoft Corporation in the United States, other countries, or both.

Other company, product, or service names may be trademarks or service marks of others.