



# Intel Smart Edge Solutions with Lenovo ThinkEdge SE450

## Solution Brief

### **Faster, flexible innovation at the edge**

The growing rollout of both public and private 5G services is enabling a new edge computing paradigm. These high-bandwidth, low-latency, and more secure 5G networks provide access to cloud compute resources nearer to the devices that are delivering the data to the users consuming the information.

As edge services continue to gain momentum, the ecosystem and enterprises need a more efficient approach to abstract complexity and simplify development and deployment of infrastructure and apps for the edge. There is a clear demand for cloud-native flexibility to seamlessly move workloads from cloud to edge—where businesses need it.

Intel Smart Edge is a Kubernetes-based portfolio of edge software solutions that enables highly optimized edge platforms to manage applications and network functions with cloud-like agility across any type of network.

The portfolio consists of Intel Smart Edge Open (previously called OpenNESS), a royalty free edge computing software toolkit, and a commercial edge software from Intel, Intel Smart Edge. Intel Smart Edge is based on Intel Smart Edge Open, and is delivered with added differentiated features, business terms and conditions and dedicated support.

## Overview

The Intel Smart Edge Controller provides a centralized provisioning and management platform for Mobile Edge Computing Edge Nodes, functions and services. The platform is comprised of five components detailed within this site.

Collectively these modules provide the following core services to an Intel Smart Edge solution:

- Centralized discovery of hardware and orchestration of all required software components for all edge computing Edge Nodes
- Select aggregation and normalization of 3rd party Application Programming Interfaces (API) for services running on the edge
- Lifecycle and configuration management of Edge Node firmware and software (including the operating environment), core Edge Node software features, and 3rd party software
- Centralized reporting and capacity planning
- Role-based Access Control (RBAC) and user provisioning with integration into existing Evolved Packet Core (EPC) modules and 3rd party infrastructure
- Centralized management of service assurance features with configurable Fault Configuration Accounting Performance Security (FCAPS) policies

Lenovo and Intel leverage the best of our capabilities across our edge offerings to deliver better business outcomes.

The new ThinkEdge SE450 server is designed to process a huge amount of data, directly at edge sites and deliver the insights needed for edge AI use cases to become a reality. It is created to deliver the promise of AI at the edge by using the latest Intel technologies and acceleration cards.

Intel Smart Edge portfolio offers edge computing software validated on the SE450, to onboard and manage applications and network functions across On-Premise and the Network Edge.

Delivering advanced capabilities required at the edge for AI, Media, Security, Networking and many more, the Smart Edge portfolio supports workload convergence at the edge across Networking and IoT workloads, thereby enabling our customers and partners with the most optimized platforms for service acceleration at the edge.

“Our collaboration with Lenovo helps enterprises across many sectors drive business value through network transformation and edge computing,” said Jeni Panhorst, Vice President and General Manager of the Network & Edge Platforms Division at Intel. “Resilient and flexible edge servers built with 3rd Gen Intel Xeon Scalable processors provide enhanced performance enabling the delivery of innovative AI-driven services where customers will expect them.”

## Lenovo ThinkEdge SE450

The ThinkEdge SE450 is purposely designed to operate outside of the datacenter, where the data is created and where the users need it. The small form factor of the server allows it to be installed in remote locations with no typical IT infrastructure. For example, the SE450 can be installed in a small cabinet, mounted on the wall or self-standing with a floor stand. The server is also built to operate in ruggedized conditions, sustaining wider operating temperature as well as shock and vibration.



Figure 1. Lenovo ThinkEdge SE450

The small form factor and ruggedized server does not compromise on performance by supporting Intel's 3rd Gen Xeon Scalable processors and up to four (4) PCI expansion cards.

Security at the edge is crucial, which is why the SE450 includes the latest TPM 2.0 technology and various secure technologies protecting the device and data it contains.

The new SE450 is designed to process a huge amount of data, directly at edge sites and deliver the insights needed for edge AI use cases to become a reality. It is created to deliver the promise of AI at the edge by using the latest Intel technologies and several AI acceleration cards.

While the SE450 is deployed in several remote locations, it is easily configured centrally by xClarity Orchestrator and the Cloud infrastructure is automatically installed and managed with Lenovo Open Cloud Automation (LOC-a). Remote access to the server via a completely out-of-band wireless access avoids any unnecessary trip to the edge locations.

## Specifications

Form Factor	2U rack server 300mm (11.8in) depth with 4x FHHL adapters; or 2U rack server 360mm (14.2in) depth with 4x FHFL adapters
Processor	1x 3rd Gen Intel Xeon Platinum processor, up to 36 cores, up to 225W TDP
Drive Bays	Up to 6x 2.5-inch 7mm drives; Up to 6x NVMe drives supported; 2x M.2 boot drives (RAID 1)
Memory	10x DDR4 memory slots; Maximum 1TB using 8x 128GB 3DS RDIMMs; Supports up to 4x Intel Optane™ Persistent Memory 200 Series modules (PMem)
Expansion Slots	Up to 4x PCIe 4.0 slots, 1x OCP 3.0 slot
GPUs	Up to 4x single-width GPUs or 2x double-width GPUs
Network Interface	LOM adapter installed in the OCP 3.0 slot; PCIe adapters
Ports	Front: 1x Power Button, 1x system locator, health with LED, 1x VGA, 2x USB 3.1, 1x Serial Port (optional), 1x RJ-45 1Gb for dedicated management, 1x system locator LED; Optional Wi-Fi (management)
HBA/RAID Support	SW RAID standard; optional HW RAID with or without cache, or SAS HBAs
Power	Dual redundant power supplies AC (up to 1100W Platinum) or Dual redundant power supplies -48V DC 1100W
Systems Management	Lenovo XClarity Controller
OS Support	Microsoft, Red Hat, Ubuntu, CentOS, VMware.
Limited Warranty	3-year customer replaceable unit and onsite service, next business day 9x5; optional service upgrades

The SE450 exceeds the performance benchmarks required to address challenges emerging at the network Edge and has also been verified for Intel Select Solution for vRAN.

You can learn more about [SE450 downloading the datasheet](#) for this server.

## Conclusion

With the Lenovo ThinkEdge SE450 server and Intel Smart Edge solutions, CoSPs and enterprises can quickly and efficiently deploy edge-centric networks, compute capabilities, and workload convergence across a range of vertical industries. Together, Lenovo and Intel help clients deploy robust network infrastructure to support edge computing from common locations on the network and on-premises edge.

## Related product families

Product families related to this document are the following:

- [Edge Servers](#)
- [ThinkEdge SE450 Edge Server](#)

## Notices

Lenovo may not offer the products, services, or features discussed in this document in all countries. Consult your local Lenovo representative for information on the products and services currently available in your area. Any reference to a Lenovo product, program, or service is not intended to state or imply that only that Lenovo product, program, or service may be used. Any functionally equivalent product, program, or service that does not infringe any Lenovo intellectual property right may be used instead. However, it is the user's responsibility to evaluate and verify the operation of any other product, program, or service. Lenovo may have patents or pending patent applications covering subject matter described in this document. The furnishing of this document does not give you any license to these patents. You can send license inquiries, in writing, to:

Lenovo (United States), Inc.  
8001 Development Drive  
Morrisville, NC 27560  
U.S.A.  
Attention: Lenovo Director of Licensing

LENOVO PROVIDES THIS PUBLICATION "AS IS" WITHOUT WARRANTY OF ANY KIND, EITHER EXPRESS OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF NON-INFRINGEMENT, MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE. Some jurisdictions do not allow disclaimer of express or implied warranties in certain transactions, therefore, this statement may not apply to you.

This information could include technical inaccuracies or typographical errors. Changes are periodically made to the information herein; these changes will be incorporated in new editions of the publication. Lenovo may make improvements and/or changes in the product(s) and/or the program(s) described in this publication at any time without notice.

The products described in this document are not intended for use in implantation or other life support applications where malfunction may result in injury or death to persons. The information contained in this document does not affect or change Lenovo product specifications or warranties. Nothing in this document shall operate as an express or implied license or indemnity under the intellectual property rights of Lenovo or third parties. All information contained in this document was obtained in specific environments and is presented as an illustration. The result obtained in other operating environments may vary. Lenovo may use or distribute any of the information you supply in any way it believes appropriate without incurring any obligation to you.

Any references in this publication to non-Lenovo Web sites are provided for convenience only and do not in any manner serve as an endorsement of those Web sites. The materials at those Web sites are not part of the materials for this Lenovo product, and use of those Web sites is at your own risk. Any performance data contained herein was determined in a controlled environment. Therefore, the result obtained in other operating environments may vary significantly. Some measurements may have been made on development-level systems and there is no guarantee that these measurements will be the same on generally available systems. Furthermore, some measurements may have been estimated through extrapolation. Actual results may vary. Users of this document should verify the applicable data for their specific environment.

© Copyright Lenovo 2025. All rights reserved.

This document, LP1546, was created or updated on December 8, 2021.

Send us your comments in one of the following ways:

- Use the online Contact us review form found at:  
<https://lenovopress.lenovo.com/LP1546>
- Send your comments in an e-mail to:  
[comments@lenovopress.com](mailto:comments@lenovopress.com)

This document is available online at <https://lenovopress.lenovo.com/LP1546>.

## Trademarks

Lenovo and the Lenovo logo are trademarks or registered trademarks of Lenovo in the United States, other countries, or both. A current list of Lenovo trademarks is available on the Web at <https://www.lenovo.com/us/en/legal/copytrade/>.

The following terms are trademarks of Lenovo in the United States, other countries, or both:

Lenovo®

ThinkEdge®

XClarity®

The following terms are trademarks of other companies:

Intel®, Intel Optane®, and Xeon® are trademarks of Intel Corporation or its subsidiaries.

Microsoft® is a trademark of Microsoft Corporation in the United States, other countries, or both.

Other company, product, or service names may be trademarks or service marks of others.