

ThinkSystem NVIDIA ConnectX-7 NDR InfiniBand OSFP400 Adapters

Product Guide

The ThinkSystem NVIDIA ConnectX-7 NDR InfiniBand OSFP400 Adapters offer 400 Gb/s InfiniBand connectivity for high-performance connectivity when running HPC, cloud, storage and machine learning applications.

The following figure shows the ThinkSystem NVIDIA ConnectX-7 NDR OSFP400 1-Port PCIe Gen5 x16 InfiniBand Adapter (the standard heat sink has been removed in this photo).



Figure 1. ThinkSystem NVIDIA ConnectX-7 NDR OSFP400 1-Port PCIe Gen5 x16 InfiniBand Adapter

Did you know?

The ConnectX-7 NDR adapters are optimized to deliver accelerated networking for modern cloud, artificial intelligence, and traditional enterprise workloads. ConnectX-7 provides a broad set of software-defined, hardware-accelerated networking, storage, and security capabilities which enable organizations to modernize and secure their IT infrastructures.

Part number information

The following table shows the part numbers for the adapters.

Table 1. Ordering information

Part number	Feature code	NVIDIA equivalent	Description
Air-cooled adapter			
4XC7A80289	BQ1N	MCX75510AAS-NEAT	ThinkSystem NVIDIA ConnectX-7 NDR OSFP400 1-Port PCIe Gen5 x16 InfiniBand Adapter
Water-cooled adapters			
4XC7A86671	BKSN	MCX75510AAS-NEAT-DWC	ThinkSystem NVIDIA ConnectX-7 NDR OSFP400 1-Port PCIe Gen5 x16 InfiniBand Adapter DWC
4XC7A86670	BKSP	MCX75510AAS-NEAT-DWC	ThinkSystem NVIDIA ConnectX-7 NDR OSFP400 1-Port PCIe Gen5 x16 InfiniBand Adapter (SharedIO) DWC

Non-DWC adapter part numbers includes the following:

- One NVIDIA adapter with full-height (3U) adapter bracket attached
- Low-profile (2U) adapter bracket
- Documentation

Supported transceivers and cables

The ConnectX-7 NDR adapters have an empty OSFP400 cage for connectivity. The following table lists the supported transceivers.

The following table lists the supported transceivers.

Table 2. Transceivers

Part number	Feature code	Description
400Gb Transceivers		
4TC7A81826	BQJT	ThinkSystem NDR OSFP400 IB Multi Mode Solo-Transceiver

The following table lists the supported fiber optic cables and Active Optical Cables.

Table 3. Optical cables

Part number	Feature code	Description
Mellanox NDR Multi Mode Fibre Optical Cables		
4X97A81748	BQJN	Lenovo 3m NVIDIA NDR Multi Mode Optical Cable
4X97A81749	BQJP	Lenovo 5m NVIDIA NDR Multi Mode Optical Cable
4X97A81750	BQJQ	Lenovo 7m NVIDIA NDR Multi Mode MPO12 APC Optical Cable
4X97A81751	BQJR	Lenovo 10m NVIDIA NDR Multi Mode Optical Cable
4X97A81752	BQJS	Lenovo 20m NVIDIA NDR Multi Mode Optical Cable
4X97A85349	BSN6	Lenovo 30m NVIDIA NDR Multi Mode MPO12 APC Optical Cable

The following table lists the supported direct-attach copper (DAC) cables.

Table 4. Copper cables

Part number	Feature code	Description
Mellanox NDRx2 OSFP800 to 2x NDR OSFP400 Splitter Copper Cables		
4X97A81827	BQJV	Lenovo 1m NVIDIA NDRx2 OSFP800 to 2x NDR OSFP400 Passive Copper Splitter Cable
4X97A81828	BQJW	Lenovo 1.5m NVIDIA NDRx2 OSFP800 to 2x NDR OSFP400 Passive Copper Splitter Cable
4X97A81829	BQJX	Lenovo 2m NVIDIA NDRx2 OSFP800 to 2x NDR OSFP400 Passive Copper Splitter Cable
4X97A81830	BQJY	Lenovo 3m NVIDIA NDRx2 OSFP800 to 2x NDR OSFP400 Passive Copper Splitter Cable

Features

The adapters have the following features:

- **Accelerated Networking and Security**

ConnectX-7 provides a broad set of software-defined, hardware-accelerated networking, storage, and security capabilities which enable organizations to modernize and secure their IT infrastructures. Moreover, ConnectX-7 empowers agile and high-performance solutions from edge to core data centers to clouds, all while enhancing network security and reducing the total cost of ownership.

- **Accelerate Data-Driven Scientific Computing**

ConnectX-7 provides ultra-low latency, extreme throughput, and innovative NVIDIA In-Network Computing engines to deliver the acceleration, scalability, and feature-rich technology needed for today's modern scientific computing workloads.

- **Accelerate Software- Defined Networking**

NVIDIA ASAP² technology accelerates software-defined networking, delivering line-rate performance with no CPU penalty.

- **Enhance Storage Performance**

ConnectX-7 enables high- performance and efficient data storage by leveraging RDMA/RoCE, GPUDirect Storage, and hardware-based NVMe-oF offload engines.

- **SharedIO (4XC7A86670 only)**

SharedIO (Shared I/O or Multi-Host) is an implementation of Sockets Direct that is offered in Lenovo direct water-cooled (DWC) servers such as the SD650 V3, where there are two server nodes per DWC tray. In this implementation, the ConnectX-7 adapter is installed in a PCIe slot in one node and the adapter is connected via a cable to a PCIe connector on the second node. The result is that the two nodes share the network connection of the adapter with significant savings both in the cost of the adapters but also the cost of switch ports.

Technical specifications

The adapters have the following technical specifications:

- Networking interfaces
 - One OSFP400 cage for 400 Gb/s connectivity
- InfiniBand connectivity
 - Support for InfiniBand NDR
 - InfiniBand Trade Association Spec 1.5 compliant
 - RDMA, send/receive semantics
 - 16 million input/output (IO) channels
 - 256 to 4Kbyte maximum transmission unit (MTU), 2Gbyte messages
- Enhanced InfiniBand Networking
 - Hardware-based reliable transport
 - Extended Reliable Connected (XRC)
 - Dynamically Connected Transport (DCT)
 - GPUDirect RDMA
 - GPUDirect Storage
 - Adaptive routing support
 - Enhanced atomic operations
 - Advanced memory mapping, allowing user mode registration (UMR)
 - On-demand paging (ODP), including registration-free RDMA memory access
 - Enhanced congestion control
 - Burst buffer offload
 - Single root IO virtualization (SR-IOV)
 - Optimized for HPC software libraries including: NVIDIA HPC-X, UCX, UCC, NCCL, OpenMPI, MVAPICH, MPICH, OpenSHMEM, PGAS
 - Collective operations offloads
 - Support for NVIDIA Scalable Hierarchical Aggregation and Reduction Protocol (SHARP)
 - Rendezvous protocol offload
 - In-network on-board memory
- Storage Accelerations
 - Block-level encryption: XTS-AES 256/512-bit key
 - NVMe over Fabrics (NVMe-oF)
 - NVMe over TCP (NVMe/TCP)
 - T10 Data Integrity Field (T10-DIF) signature handover
 - SRP, iSER, NFS over RDMA, SMB Direct
- Management and Control
 - NC-SI, MCTP over SMBus, and MCTP over PCIe
 - PLDM for Monitor and Control DSP0248
 - PLDM for Firmware Update DSP0267
 - PLDM for Redfish Device Enablement DSP0218
 - PLDM for FRU DSP0257
 - SPDM DSP0274
 - Serial Peripheral Interface (SPI) to flash
 - JTAG IEEE 1149.1 and IEEE 1149.6
- Remote Boot
 - Remote boot over InfiniBand
 - Remote boot over iSCSI
 - UEFI
 - PXE
- Cybersecurity
 - Platform security: secure boot with hardware root-of-trust, secure firmware update, flash encryption, and device attestation

- *)PCI Express Interface
 - PCIe Gen 5.0 x16 host interface
 - Support for PCIe bifurcation
 - SharedIO (NVIDIA Multi-Host) supports connection of up to two hosts (on supported water-cooled nodes only)
 - Transaction layer packet (TLP) processing hints (TPH)
 - PCIe switch Downstream Port Containment (DPC)
 - Support for MSI/MSI-X mechanisms
 - Advanced error reporting (AER)
 - Access Control Service (ACS) for peer-to-peer secure communication
 - Process Address Space ID (PASID)
 - Address translation services (ATS)
 - Support for SR-IOV

NVIDIA Unified Fabric Manager

NVIDIA Unified Fabric Manager (UFM) is InfiniBand networking management software that combines enhanced, real-time network telemetry with fabric visibility and control to support scale-out InfiniBand data centers.

The two offerings available from Lenovo are as follows:

- UFM Telemetry** for Real-Time Monitoring
 The UFM Telemetry platform provides network validation tools to monitor network performance and conditions, capturing and streaming rich real-time network telemetry information, application workload usage, and system configuration to an on-premises or cloud-based database for further analysis.
- UFM Enterprise** for Fabric Visibility and Control
 The UFM Enterprise platform combines the benefits of UFM Telemetry with enhanced network monitoring and management. It performs automated network discovery and provisioning, traffic monitoring, and congestion discovery. It also enables job schedule provisioning and integrates with industry-leading job schedulers and cloud and cluster managers, including Slurm and Platform Load Sharing Facility (LSF).

The following table lists the subscription licenses available from Lenovo.

Table 5. NVIDIA Unified Fabric Manager subscriptions

Part number	Feature code (7S02CTO1WW)	Description
UFM Telemetry		
7S02003HWW	S88D	UFM Telemetry 1-year License and Gold-Support for Lenovo clusters. Per node.
7S02003JWW	S88E	UFM Telemetry 3-year License and Gold-Support for Lenovo clusters. Per node.
7S02003KWW	S88F	UFM Telemetry 5-year License and Gold-Support for Lenovo clusters. Per node.
UFM Enterprise		
7S02003LWW	S88G	UFM Enterprise 1-year License and Gold-Support for Lenovo clusters. Per node.
7S02003MWW	S88H	UFM Enterprise 3-year License and Gold-Support for Lenovo clusters. Per node.
7S02003NWW	S88J	UFM Enterprise 5-year License and Gold-Support for Lenovo clusters. Per node.

For more information, see the following web page:
<https://www.nvidia.com/en-us/networking/infiniband/ufm/>

Server support

The following tables list the ThinkSystem servers that are compatible.

Table 6. Server support (Part 1 of 4)

Part Number	Description	2S AMD V3				2S Intel V3		4S 8S Intel V3		Multi Node	GPU Rich			1S V3							
		SR635 V3 (7D9H / 7D9G)	SR655 V3 (7D9F / 7D9E)	SR645 V3 (7D9D / 7D9C)	SR665 V3 (7D9B / 7D9A)	ST650 V3 (7D7B / 7D7A)	SR630 V3 (7D72 / 7D73)	SR650 V3 (7D75 / 7D76)	SR850 V3 (7D97 / 7D96)	SR860 V3 (7D94 / 7D93)	SR950 V3 (7DC5 / 7DC4)	SD535 V3 (7DD8 / 7DD1)	SD530 V3 (7DDA / 7DD3)	SD550 V3 (7DD9 / 7DD2)	SR670 V2 (7Z22 / 7Z23)	SR675 V3 (7D9Q / 7D9R)	SR680a V3 (7DHE)	SR685a V3 (7DHC)	ST50 V3 (7DF4 / 7DF3)	ST250 V3 (7DCF / 7DCE)	SR250 V3 (7DCM / 7DCL)
4XC7A80289	ThinkSystem NVIDIA ConnectX-7 NDR OSFP400 1-Port PCIe Gen5 x16 InfiniBand Adapter	Y	Y	Y	Y	N	Y	Y	Y	Y	N	N	N	Y	Y	Y	Y	N	N	N	
4XC7A86671	ThinkSystem NVIDIA ConnectX-7 NDR OSFP400 1-Port PCIe Gen5 x16 InfiniBand Adapter DWC	N	N	N	N	N	N	N	N	N	N	N	N	N	N	N	N	N	N	N	N
4XC7A86670	ThinkSystem NVIDIA ConnectX-7 NDR OSFP400 1-Port PCIe Gen5 x16 InfiniBand Adapter (SharedIO) DWC	N	N	N	N	N	N	N	N	N	N	N	N	N	N	N	N	N	N	N	N

Table 7. Server support (Part 2 of 4)

Part Number	Description	Edge				Super Computing				1S Intel V2		2S Intel V2				
		SE350 (7Z46 / 7D1X)	SE350 V2 (7DA9)	SE360 V2 (7DAM)	SE450 (7D8T)	SE455 V3 (7DBY)	SD665 V3 (7D9P)	SD665-N V3 (7DAZ)	SD650 V3 (7D7M)	SD650-I V3 (7D7L)	SD650-N V3 (7D7N)	ST50 V2 (7D8K / 7D8J)	ST250 V2 (7D8G / 7D8F)	SR250 V2 (7D7R / 7D7Q)	ST650 V2 (7Z75 / 7Z74)	SR630 V2 (7Z70 / 7Z71)
4XC7A80289	ThinkSystem NVIDIA ConnectX-7 NDR OSFP400 1-Port PCIe Gen5 x16 InfiniBand Adapter	N	N	N	N	N	N	N	N	N	N	N	N	N	Y	Y
4XC7A86671	ThinkSystem NVIDIA ConnectX-7 NDR OSFP400 1-Port PCIe Gen5 x16 InfiniBand Adapter DWC	N	N	N	N	N	Y	N	Y	Y	N	N	N	N	N	N
4XC7A86670	ThinkSystem NVIDIA ConnectX-7 NDR OSFP400 1-Port PCIe Gen5 x16 InfiniBand Adapter (SharedIO) DWC	N	N	N	N	N	Y	N	Y	N	N	N	N	N	N	N

Table 8. Server support (Part 3 of 4)

Part Number	Description	AMD V1					Dense V2				4S V2	8S	4S V1		1S Intel V1					
		SR635 (7Y98 / 7Y99)	SR655 (7Y00 / 7Z01)	SR655 Client OS	SR645 (7D2Y / 7D2X)	SR665 (7D2W / 7D2V)	SD630 V2 (7D1K)	SD650 V2 (7D1M)	SD650-N V2 (7D1N)	SN550 V2 (7Z69)	SR850 V2 (7D31 / 7D32)	SR860 V2 (7Z59 / 7Z60)	SR950 (7X11 / 7X12)	SR850 (7X18 / 7X19)	SR850P (7D2F / 2D2G)	SR860 (7X69 / 7X70)	ST50 (7Y48 / 7Y50)	ST250 (7Y45 / 7Y46)	SR150 (7Y54)	SR250 (7Y52 / 7Y51)
4XC7A80289	ThinkSystem NVIDIA ConnectX-7 NDR OSFP400 1-Port PCIe Gen5 x16 InfiniBand Adapter	N	N	N	Y	Y	N	N	N	N	Y	N	N	N	N	N	N	N	N	N
4XC7A86671	ThinkSystem NVIDIA ConnectX-7 NDR OSFP400 1-Port PCIe Gen5 x16 InfiniBand Adapter DWC	N	N	N	N	N	N	N	N	N	N	N	N	N	N	N	N	N	N	N
4XC7A86670	ThinkSystem NVIDIA ConnectX-7 NDR OSFP400 1-Port PCIe Gen5 x16 InfiniBand Adapter (SharedIO) DWC	N	N	N	N	N	N	N	N	N	N	N	N	N	N	N	N	N	N	N

Table 9. Server support (Part 4 of 4)

Part Number	Description	2S Intel V1							Dense V1				
		ST550 (7X09 / 7X10)	SR530 (7X07 / 7X08)	SR550 (7X03 / 7X04)	SR570 (7Y02 / 7Y03)	SR590 (7X98 / 7X99)	SR630 (7X01 / 7X02)	SR650 (7X05 / 7X06)	SR670 (7Y36 / 7Y37)	SD530 (7X21)	SD650 (7X58)	SN550 (7X16)	SN850 (7X15)
4XC7A80289	ThinkSystem NVIDIA ConnectX-7 NDR OSFP400 1-Port PCIe Gen5 x16 InfiniBand Adapter	N	N	N	N	N	N	N	N	N	N	N	N
4XC7A86671	ThinkSystem NVIDIA ConnectX-7 NDR OSFP400 1-Port PCIe Gen5 x16 InfiniBand Adapter DWC	N	N	N	N	N	N	N	N	N	N	N	N
4XC7A86670	ThinkSystem NVIDIA ConnectX-7 NDR OSFP400 1-Port PCIe Gen5 x16 InfiniBand Adapter (SharedIO) DWC	N	N	N	N	N	N	N	N	N	N	N	N

Operating system support

The adapters support the operating systems listed in the following tables.

- [ThinkSystem NVIDIA ConnectX-7 NDR OSFP400 1-Port PCIe Gen5 x16 InfiniBand Adapter, 4XC7A80289](#)
- [ThinkSystem NVIDIA ConnectX-7 NDR OSFP400 1-Port PCIe Gen5 x16 InfiniBand Adapter DWC, 4XC7A86671](#)

- [ThinkSystem NVIDIA ConnectX-7 NDR OSFP400 1-Port PCIe Gen5 x16 InfiniBand Adapter \(SharedIO\) DWC, 4XC7A86670](#)

Tip: These tables are automatically generated based on data from [Lenovo ServerProven](#).

Table 10. Operating system support for ThinkSystem NVIDIA ConnectX-7 NDR OSFP400 1-Port PCIe Gen5 x16 InfiniBand Adapter, 4XC7A80289

Operating systems	SD535 V3	SR630 V3 (4th Gen Xeon)	SR630 V3 (5th Gen Xeon)	SR635 V3	SR645 V3	SR650 V3 (4th Gen Xeon)	SR650 V3 (5th Gen Xeon)	SR655 V3	SR665 V3	SR675 V3	SR685a V3	SR850 V3	SR860 V3	SR630 V2	SR650 V2	SR670 V2	SR850 V2	SR645	SR665
Microsoft Windows Server 2019	N	Y	Y	Y	Y	Y	Y	Y	Y	Y	N	Y	Y	Y	Y	Y	Y	Y	Y
Microsoft Windows Server 2022	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y	N	Y	Y	Y	Y	Y	Y	Y	Y
Red Hat Enterprise Linux 8.6	N	Y	N	Y	Y	Y	N	Y	Y	Y	N	Y	Y	Y	Y	Y	Y	Y	Y
Red Hat Enterprise Linux 8.7	N	Y	N	Y	Y	Y	N	Y	Y	Y	N	Y	Y	Y	Y	Y	Y	Y	Y
Red Hat Enterprise Linux 8.8	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y	N	Y	Y	Y	Y	Y	Y	Y	Y
Red Hat Enterprise Linux 8.9	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y	N	Y	Y	Y	Y	Y	Y	Y	Y
Red Hat Enterprise Linux 9.0	N	Y	N	Y	Y	Y	N	Y	Y	Y	N	Y	Y	Y	Y	Y	Y	Y	Y
Red Hat Enterprise Linux 9.1	N	Y	N	Y	Y	Y	N	Y	Y	Y	N	Y	Y	Y	Y	Y	Y	Y	Y
Red Hat Enterprise Linux 9.2	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y	N	Y	Y	Y	Y	Y	Y	Y	Y
Red Hat Enterprise Linux 9.3	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y	N	Y	Y	Y	Y	Y	Y	Y	Y
SUSE Linux Enterprise Server 12 SP5	N	N	N	N	N	N	N	N	N	N	N	N	N	Y	Y	Y	Y	Y	Y
SUSE Linux Enterprise Server 15 SP3	N	N	N	N	N	N	N	N	N	N	N	N	N	Y	Y	Y	Y	Y	Y
SUSE Linux Enterprise Server 15 SP4	N	Y	N	Y	Y	Y	N	Y	Y	Y	N	Y	Y	Y	Y	Y	Y	Y	Y
SUSE Linux Enterprise Server 15 SP5	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y	N	Y	Y	Y	Y	Y	Y	Y	Y
Ubuntu 22.04 LTS	N	Y	N	Y	Y	Y	N	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y
Ubuntu 22.04.3 LTS	Y	N	N	N	N	N	N	N	N	N	N	N	N	N	N	N	N	N	N

Table 11. Operating system support for ThinkSystem NVIDIA ConnectX-7 NDR OSFP400 1-port PCIe Gen5 x16 InfiniBand Adapter DWC, 4XC7A86671

	SD650 V3	SD650 V3 (5th Gen Xeon)	SD650-I V3 (4th Gen Xeon)	SD650-I V3 (5th Gen Xeon)
Operating systems				
Red Hat Enterprise Linux 8.6	Y	N	Y	N
Red Hat Enterprise Linux 8.8	Y	Y	Y	Y
Red Hat Enterprise Linux 9.0	Y	N	N	N
Red Hat Enterprise Linux 9.2	Y	Y	Y	Y
SUSE Linux Enterprise Server 15 SP4	Y	N	Y	N
SUSE Linux Enterprise Server 15 SP5	Y	Y	Y	Y
Ubuntu 22.04 LTS	Y	N	Y	N
Ubuntu 22.04.3 LTS	N	Y	N	Y

Table 12. Operating system support for ThinkSystem NVIDIA ConnectX-7 NDR OSFP400 1-port PCIe Gen5 x16 InfiniBand Adapter (SharedIO) DWC, 4XC7A86670

	SD650 V3	SD650 V3 (5th Gen Xeon)	SD650-I V3 (4th Gen Xeon)	SD650-I V3 (5th Gen Xeon)
Operating systems				
Red Hat Enterprise Linux 8.6	Y	N	Y	N
Red Hat Enterprise Linux 8.8	Y	Y	Y	Y
Red Hat Enterprise Linux 9.0	Y	N	N	N
Red Hat Enterprise Linux 9.2	Y	Y	Y	Y
SUSE Linux Enterprise Server 15 SP4	Y	N	Y	N
SUSE Linux Enterprise Server 15 SP5	Y	Y	Y	Y
Ubuntu 22.04 LTS	Y	N	Y	N
Ubuntu 22.04.3 LTS	N	Y	N	Y

Regulatory approvals

The adapters have the following regulatory approvals:

- Safety: CB / cTUVus / CE
- EMC: CE / FCC / VCCI / ICES / RCM / KC
- RoHS: RoHS Compliant

Operating environment

The adapters have the following operating characteristics:

- Maximum power available through OSFP port: 17W
- Temperature
 - Operational: 0°C to 55°C
 - Non-operational: -40°C to 70°C
- Humidity: 90% relative humidity

Warranty

One year limited warranty. When installed in a Lenovo server, the adapter assumes the server's base warranty and any warranty upgrades.

Related publications

For more information, refer to these documents:

- Networking Options for ThinkSystem Servers:
<https://lenovopress.com/lp0765-networking-options-for-thinksystem-servers>
- ServerProven compatibility:
<http://www.lenovo.com/us/en/serverproven>
- NVIDIA InfiniBand product page:
<https://www.nvidia.com/en-us/networking/infiniband-adapters/>
- ConnectX-7 user manual:
<https://docs.nvidia.com/networking/display/ConnectX7VPI/Specifications>

Related product families

Product families related to this document are the following:

- [InfiniBand & Omni-Path Adapters](#)

Notices

Lenovo may not offer the products, services, or features discussed in this document in all countries. Consult your local Lenovo representative for information on the products and services currently available in your area. Any reference to a Lenovo product, program, or service is not intended to state or imply that only that Lenovo product, program, or service may be used. Any functionally equivalent product, program, or service that does not infringe any Lenovo intellectual property right may be used instead. However, it is the user's responsibility to evaluate and verify the operation of any other product, program, or service. Lenovo may have patents or pending patent applications covering subject matter described in this document. The furnishing of this document does not give you any license to these patents. You can send license inquiries, in writing, to:

Lenovo (United States), Inc.
8001 Development Drive
Morrisville, NC 27560
U.S.A.
Attention: Lenovo Director of Licensing

LENOVO PROVIDES THIS PUBLICATION "AS IS" WITHOUT WARRANTY OF ANY KIND, EITHER EXPRESS OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF NON-INFRINGEMENT, MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE. Some jurisdictions do not allow disclaimer of express or implied warranties in certain transactions, therefore, this statement may not apply to you.

This information could include technical inaccuracies or typographical errors. Changes are periodically made to the information herein; these changes will be incorporated in new editions of the publication. Lenovo may make improvements and/or changes in the product(s) and/or the program(s) described in this publication at any time without notice.

The products described in this document are not intended for use in implantation or other life support applications where malfunction may result in injury or death to persons. The information contained in this document does not affect or change Lenovo product specifications or warranties. Nothing in this document shall operate as an express or implied license or indemnity under the intellectual property rights of Lenovo or third parties. All information contained in this document was obtained in specific environments and is presented as an illustration. The result obtained in other operating environments may vary. Lenovo may use or distribute any of the information you supply in any way it believes appropriate without incurring any obligation to you.

Any references in this publication to non-Lenovo Web sites are provided for convenience only and do not in any manner serve as an endorsement of those Web sites. The materials at those Web sites are not part of the materials for this Lenovo product, and use of those Web sites is at your own risk. Any performance data contained herein was determined in a controlled environment. Therefore, the result obtained in other operating environments may vary significantly. Some measurements may have been made on development-level systems and there is no guarantee that these measurements will be the same on generally available systems. Furthermore, some measurements may have been estimated through extrapolation. Actual results may vary. Users of this document should verify the applicable data for their specific environment.

© Copyright Lenovo 2024. All rights reserved.

This document, LP1692, was created or updated on December 6, 2023.

Send us your comments in one of the following ways:

- Use the online Contact us review form found at:
<https://lenovopress.lenovo.com/LP1692>
- Send your comments in an e-mail to:
comments@lenovopress.com

This document is available online at <https://lenovopress.lenovo.com/LP1692>.

Trademarks

Lenovo and the Lenovo logo are trademarks or registered trademarks of Lenovo in the United States, other countries, or both. A current list of Lenovo trademarks is available on the Web at <https://www.lenovo.com/us/en/legal/copytrade/>.

The following terms are trademarks of Lenovo in the United States, other countries, or both:

Lenovo®

ServerProven®

ThinkSystem®

The following terms are trademarks of other companies:

Intel® and Xeon® are trademarks of Intel Corporation or its subsidiaries.

Linux® is the trademark of Linus Torvalds in the U.S. and other countries.

Microsoft®, Windows Server®, and Windows® are trademarks of Microsoft Corporation in the United States, other countries, or both.

Other company, product, or service names may be trademarks or service marks of others.