

ThinkSystem SR650 V3 Sets 3 World Records with New TPC-E Benchmark Result

Performance Benchmark Result

Lenovo has published a new TPC-E benchmark result that has set three new world records. The result has been achieved on the powerful Lenovo ThinkSystem SR650 V3 server. The benchmark results are:

- The world's #1 overall TPC-E result for performance
- The world's best TPC-E result for performance on 2-processor systems
- The world's best TPC-E price/performance for a system with 120 processor cores

The TPC-E benchmark is designed to enable customers to objectively measure and compare the performance and price of various Online Transaction Processing (OLTP) and database systems.



The ThinkSystem SR650 V3 server achieved the following score (1):

- **12,436.66 tpsE (transactions per second E) @ \$95.46 USD/tpsE**

This result is the best overall TPC-E performance in the industry:

- 2.25% higher than the best 4P result's performance (2), and
- 3.40% higher than the previous best 2P result's performance (3)

Including this new result, Lenovo servers have the #1 1P (4), 2P (1,5), 4P (2), and overall (1,5) TPC-E performance and price/performance results.

The SR650 V3 achieved this record level of OLTP performance using the following configuration:

- 2x Intel Xeon Platinum 8490H 60-core processors at 1.9GHz (2 processors, 120 total cores, 240 total threads)
- 2048 GB of Lenovo TruDDR5 memory
- Microsoft SQL Server 2022 Enterprise Edition
- Microsoft Windows Server 2022 Standard Edition

This result also relied on Lenovo Storage D1224 DAS enclosures. Six D1224 storage enclosures and 126 SAS SSDs were used in the benchmark configuration, attached directly to the server using six ThinkSystem RAID 940-8e controllers configured with RAID-5.

Results referenced are current as of March 13, 2023. To view all TPC results, visit www.tpc.org.

(1) The total solution availability for this TPC-E benchmark result is May 18, 2023. See the details for this result at <http://tpc.org/4091>.

(2) The 4P Lenovo ThinkSystem SR860 V2 is the #1 4P TPC-E performance result and the #1 4P TPC-E price/performance result. Result details are from <http://tpc.org/4087>.

(3) The 2P Lenovo ThinkSystem SR665 was the previous #1 2P TPC-E performance result. Result details are from <http://tpc.org/4088>.

(4) The 1P Lenovo ThinkSystem SR655 is the #1 1P TPC-E performance result and the #1 1P TPC-E price/performance result. Result details are from <http://tpc.org/4089>.

(5) The 2P Lenovo ThinkSystem SR665 is the #1 overall TPC-E price/performance result. Result details are from <http://tpc.org/4090>.

About the ThinkSystem SR650 V3

The Lenovo ThinkSystem SR650 V3 is an ideal 2-socket 2U rack server, based on the new 5th generation Intel Xeon Scalable processor family. The SR650 V3 is for small business up to large enterprises that need industry-leading reliability, management, and security, as well as maximizing performance and flexibility for future growth. The server offers a broad selection of drive and slot configurations and offers numerous high performance features. Outstanding reliability, availability, and serviceability (RAS) and high-efficiency design can improve business operation and help save operational costs.

SR650 V3 offers the low-latency, high capacity performance necessary to keep up with the workloads of today. It's designed to handle a wide range of workloads, such as databases, virtualization and cloud computing, virtual desktop infrastructure (VDI), infrastructure security, systems management, enterprise applications, collaboration/email, streaming media, web, and HPC.

About the Lenovo Storage D1212 and D1224 Enclosures

The Lenovo Storage D1212 and D1224 Disk Expansion Enclosures offer 12 Gbps SAS direct-attached storage expansion capabilities that are designed to provide simplicity, speed, scalability, security, and high availability for small to large businesses.

The D1212 (with 3.5-inch drives) and D1224 (with 2.5-inch drives), deliver enterprise-class storage technology in a cost-effective solution with flexible drive configurations and RAID or JBOD (non-RAID) host connectivity.



About TPC-E

TPC Benchmark E (TPC-E) is an Online Transaction Processing (OLTP) workload designed to enable customers to objectively measure and compare the performance and price of various OLTP and database systems. TPC-E is a mixture of read-only and update intensive transactions that simulate the activities found in complex OLTP application environments.

Learn more

To learn more about solutions for database and OLTP applications, please contact your Lenovo Sales Representative.

To find out more about TPC, visit <http://www.tpc.org>.

To learn more about the Lenovo ThinkSystem SR650 V3 server, visit the SR650 V3 product web page: <https://www.lenovo.com/us/en/p/servers-storage/servers/racks/thinksystem-sr650-v3/len21ts0013>

Related product families

Product families related to this document are the following:

- [2-Socket Rack Servers](#)
- [Direct-Attached Storage](#)
- [Microsoft SQL Server](#)
- [TPC-E Benchmark Results](#)
- [ThinkSystem SR650 V3 Server](#)

Notices

Lenovo may not offer the products, services, or features discussed in this document in all countries. Consult your local Lenovo representative for information on the products and services currently available in your area. Any reference to a Lenovo product, program, or service is not intended to state or imply that only that Lenovo product, program, or service may be used. Any functionally equivalent product, program, or service that does not infringe any Lenovo intellectual property right may be used instead. However, it is the user's responsibility to evaluate and verify the operation of any other product, program, or service. Lenovo may have patents or pending patent applications covering subject matter described in this document. The furnishing of this document does not give you any license to these patents. You can send license inquiries, in writing, to:

Lenovo (United States), Inc.
8001 Development Drive
Morrisville, NC 27560
U.S.A.
Attention: Lenovo Director of Licensing

LENOVO PROVIDES THIS PUBLICATION "AS IS" WITHOUT WARRANTY OF ANY KIND, EITHER EXPRESS OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF NON-INFRINGEMENT, MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE. Some jurisdictions do not allow disclaimer of express or implied warranties in certain transactions, therefore, this statement may not apply to you.

This information could include technical inaccuracies or typographical errors. Changes are periodically made to the information herein; these changes will be incorporated in new editions of the publication. Lenovo may make improvements and/or changes in the product(s) and/or the program(s) described in this publication at any time without notice.

The products described in this document are not intended for use in implantation or other life support applications where malfunction may result in injury or death to persons. The information contained in this document does not affect or change Lenovo product specifications or warranties. Nothing in this document shall operate as an express or implied license or indemnity under the intellectual property rights of Lenovo or third parties. All information contained in this document was obtained in specific environments and is presented as an illustration. The result obtained in other operating environments may vary. Lenovo may use or distribute any of the information you supply in any way it believes appropriate without incurring any obligation to you.

Any references in this publication to non-Lenovo Web sites are provided for convenience only and do not in any manner serve as an endorsement of those Web sites. The materials at those Web sites are not part of the materials for this Lenovo product, and use of those Web sites is at your own risk. Any performance data contained herein was determined in a controlled environment. Therefore, the result obtained in other operating environments may vary significantly. Some measurements may have been made on development-level systems and there is no guarantee that these measurements will be the same on generally available systems. Furthermore, some measurements may have been estimated through extrapolation. Actual results may vary. Users of this document should verify the applicable data for their specific environment.

© Copyright Lenovo 2025. All rights reserved.

This document, LP1708, was created or updated on March 13, 2023.

Send us your comments in one of the following ways:

- Use the online Contact us review form found at:
<https://lenovopress.lenovo.com/LP1708>
- Send your comments in an e-mail to:
comments@lenovopress.com

This document is available online at <https://lenovopress.lenovo.com/LP1708>.

Trademarks

Lenovo and the Lenovo logo are trademarks or registered trademarks of Lenovo in the United States, other countries, or both. A current list of Lenovo trademarks is available on the Web at <https://www.lenovo.com/us/en/legal/copytrade/>.

The following terms are trademarks of Lenovo in the United States, other countries, or both:

Lenovo®

ThinkSystem®

The following terms are trademarks of other companies:

Intel® and Xeon® are trademarks of Intel Corporation or its subsidiaries.

Microsoft®, SQL Server®, Windows Server®, and Windows® are trademarks of Microsoft Corporation in the United States, other countries, or both.

TPC® and TPC Benchmark® are trademarks of Transaction Processing Performance Council.

Other company, product, or service names may be trademarks or service marks of others.