

New 4th Gen AMD EPYC Processors for ThinkSystem V3 Servers

Article

AMD processors

Today, AMD has announced new 4th Gen AMD EPYC™ processors:

- 4th Gen AMD EPYC processors based on Zen 4c architecture (formerly codenamed "Bergamo")
The newest iteration of 4th Gen AMD EPYC processors are optimized Zen 4c architecture. These processors have higher core counts, up to 128 cores, targeted at cloud native applications that are designed to exploit the scale, elasticity, resiliency, and flexibility of private & public clouds. The processors offer leadership x86 core density and energy efficiency while maintaining the proven, trusted Zen software compatibility.
- 4th Gen AMD EPYC processors with AMD 3D V-Cache Technology (formerly codenamed "Genoa-X")

Designed with up to 96 powerful Zen 4 cores and up to 1.15 GB of L3 cache, 4th Gen AMD EPYC processors with AMD 3D V-Cache technology deliver breakthrough performance on targeted technical computing workloads such as Electronic Design Automation (EDA), Computational Fluid Dynamics (CFD) and Finite Element Analysis (FEA) software and solutions. For many challenging workloads, having access to this large L3 cache enables improved performance by continuously feeding the processor with data without having to access main memory outside of the CPU, and empowering customers to realize faster time-to-results.




Figure 1. 4th Gen AMD EPYC processors with AMD 3D V-Cache Technology offer larger L3 cache, best suited for technical computing workloads

Processor features

The following table lists the features of the new AMD EPYC processors.

Key features of these processors:

- The processors with AMD 3D V-Cache have much larger L3 cache, up to 1150 MB
- The processors with Zen 4c architecture have higher core counts, up to 128 cores

Table 1. Processor specifications

EPYC model	Cores / Threads	Base Frequency	Max Boost Frequency†	L3 Cache	Memory channels	Memory bus	TDP
4th Gen AMD EPYC processors with AMD 3D V-Cache							
9184X	16 / 32	3.55 GHz	4.20 GHz	768 MB	12	4800 MHz	320W
9384X	32 / 64	3.1 GHz	3.9 GHz	768 MB	12	4800 MHz	320W
9684X	96 / 192	2.55 GHz	3.7 GHz	1150 MB	12	4800 MHz	400W
4th Gen AMD EPYC processors with Zen 4c architecture							
9734	112 / 224	2.2 GHz	3.0 GHz	256 MB	12	4800 MHz	340W
9754	128 / 256	2.25 GHz	3.2 GHz	256 MB	12	4800 MHz	360W

† The maximum single-core frequency that the processor is capable of operating

ThinkSystem V3 servers

Lenovo plans to support these processors in our full portfolio of ThinkSystem V3 servers based on AMD EPYC processors. You can make configurations in [Lenovo DCSC configurator](#).

- [ThinkSystem SD665 V3 Neptune DWC Server](#) (twin 2S water cooled nodes)
- [ThinkSystem SD665-N V3 Neptune DWC Server](#) (2S water cooled node with NVIDIA GPUs)
- [ThinkSystem SR675 V3](#) (3U GPU-rich)
- [ThinkSystem SR665 V3](#) (2U 2-socket) - support planned for July 2023
- [ThinkSystem SR645 V3](#) (1U 2-socket) - support planned for July 2023
- [ThinkSystem SR655 V3](#) (2U 1-socket) - support planned for July 2023
- [ThinkSystem SR635 V3](#) (1U 1-socket) - support planned for July 2023




Figure 2. The Lenovo ThinkSystem SD665 V3 supports the new AMD processors

World record benchmark results

Lenovo has set **47 world records** with the new AMD EPYC 9754 processor installed in ThinkSystem V3 servers. See our benchmark reports for details:

On the SR665 V3, our 2U2S server

- [ThinkSystem SR665 V3 Sets 10 World Records with New SPECcpu Benchmark Result](#)
- [ThinkSystem SR665 V3 Sets 5 World Records with New SPECjbb Benchmark Result](#)
- [ThinkSystem SR665 V3 Sets 3 World Records with New SPECPower on Windows Benchmark Result](#)
- [ThinkSystem SR665 V3 Sets World Record with New SPECPower on Linux Benchmark Result](#)
- [ThinkSystem SR665 V3 Sets 2 World Records with New SPECCompG Benchmark Result](#)

On the SR645 V3, our 1U2S server

- [ThinkSystem SR645 V3 Sets 2 World Records with New SPECPower on Windows Benchmark Result](#)
- [ThinkSystem SR645 V3 Sets World Record with New SPECPower on Linux Benchmark Result](#)

On the SR655 V3, our 2U1S server:

- [ThinkSystem SR655 V3 Sets 8 World Records with New SPECjbb Benchmark Results](#)
- [ThinkSystem SR655 V3 Sets 8 World Records with New SPECcpu Benchmark Results](#)
- [ThinkSystem SR655 V3 Sets 2 World Records with New SPECCompG Benchmark Result](#)
- [ThinkSystem SR655 V3 Sets World Record with New SPECPower on Linux Benchmark Result](#)
- [ThinkSystem SR655 V3 Sets World Record with New SPECPower on Windows Benchmark Result](#)

On the SR635 V3, our 1U1S server

- [ThinkSystem SR635 V3 Sets World Record with New SPECPower on Linux Benchmark Result](#)
- [ThinkSystem SR635 V3 Sets World Record with New SPECPower on Windows Benchmark Result](#)
- [ThinkSystem SR635 V3 Sets World Record with New SPECPower on Windows Benchmark Result](#)

For more information

For more information, see the following pages:

- Lenovo-AMD alliance landing page:
<https://www.lenovo.com/us/en/servers-storage/alliance/amd/>
- Lenovo DCSC configurator:
<https://dcsc.lenovo.com>

Related product families

Product families related to this document are the following:

- [ThinkSystem SD665 V3 Server](#)
- [ThinkSystem SD665-N V3 Server](#)
- [ThinkSystem SR635 V3 Server](#)
- [ThinkSystem SR645 V3 Server](#)
- [ThinkSystem SR655 V3 Server](#)
- [ThinkSystem SR665 V3 Server](#)
- [ThinkSystem SR675 V3 Server](#)

Notices

Lenovo may not offer the products, services, or features discussed in this document in all countries. Consult your local Lenovo representative for information on the products and services currently available in your area. Any reference to a Lenovo product, program, or service is not intended to state or imply that only that Lenovo product, program, or service may be used. Any functionally equivalent product, program, or service that does not infringe any Lenovo intellectual property right may be used instead. However, it is the user's responsibility to evaluate and verify the operation of any other product, program, or service. Lenovo may have patents or pending patent applications covering subject matter described in this document. The furnishing of this document does not give you any license to these patents. You can send license inquiries, in writing, to:

Lenovo (United States), Inc.
8001 Development Drive
Morrisville, NC 27560
U.S.A.
Attention: Lenovo Director of Licensing

LENOVO PROVIDES THIS PUBLICATION "AS IS" WITHOUT WARRANTY OF ANY KIND, EITHER EXPRESS OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF NON-INFRINGEMENT, MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE. Some jurisdictions do not allow disclaimer of express or implied warranties in certain transactions, therefore, this statement may not apply to you.

This information could include technical inaccuracies or typographical errors. Changes are periodically made to the information herein; these changes will be incorporated in new editions of the publication. Lenovo may make improvements and/or changes in the product(s) and/or the program(s) described in this publication at any time without notice.

The products described in this document are not intended for use in implantation or other life support applications where malfunction may result in injury or death to persons. The information contained in this document does not affect or change Lenovo product specifications or warranties. Nothing in this document shall operate as an express or implied license or indemnity under the intellectual property rights of Lenovo or third parties. All information contained in this document was obtained in specific environments and is presented as an illustration. The result obtained in other operating environments may vary. Lenovo may use or distribute any of the information you supply in any way it believes appropriate without incurring any obligation to you.

Any references in this publication to non-Lenovo Web sites are provided for convenience only and do not in any manner serve as an endorsement of those Web sites. The materials at those Web sites are not part of the materials for this Lenovo product, and use of those Web sites is at your own risk. Any performance data contained herein was determined in a controlled environment. Therefore, the result obtained in other operating environments may vary significantly. Some measurements may have been made on development-level systems and there is no guarantee that these measurements will be the same on generally available systems. Furthermore, some measurements may have been estimated through extrapolation. Actual results may vary. Users of this document should verify the applicable data for their specific environment.

© Copyright Lenovo 2024. All rights reserved.

This document, LP1744, was created or updated on July 10, 2023.

Send us your comments in one of the following ways:

- Use the online Contact us review form found at:
<https://lenovopress.lenovo.com/LP1744>
- Send your comments in an e-mail to:
comments@lenovopress.com

This document is available online at <https://lenovopress.lenovo.com/LP1744>.

Trademarks

Lenovo and the Lenovo logo are trademarks or registered trademarks of Lenovo in the United States, other countries, or both. A current list of Lenovo trademarks is available on the Web at <https://www.lenovo.com/us/en/legal/copytrade/>.

The following terms are trademarks of Lenovo in the United States, other countries, or both:

Lenovo®

ThinkSystem®

The following terms are trademarks of other companies:

Linux® is the trademark of Linus Torvalds in the U.S. and other countries.

Windows® is a trademark of Microsoft Corporation in the United States, other countries, or both.

SPECjbb® is a trademark of the Standard Performance Evaluation Corporation (SPEC).

Other company, product, or service names may be trademarks or service marks of others.