

ThinkAgile VX650 V3 Sets World Record with New SAP BW Edition for SAP HANA (7.8B Records) Benchmark Result

Performance Benchmark Result

The Lenovo ThinkAgile VX650 V3 Certified Node, powered by VMware vSAN and using two Intel Xeon Platinum 8490H processors, delivers world record performance for the Throughput Phase for SAP® BW edition for SAP HANA® Standard Application Benchmark Version 3 with 7.8 billion initial records in a scale-up configuration.

The benchmark refers to the SAP Business Warehouse (SAP BW) application running on the SAP HANA database. The benchmark consists of three phases and the VX650 V3 server achieved the following performance results (1):



- **Phase 1: Data load phase = 15,738** (Runtime of last Data Set in seconds)
- **Phase 2: Query throughput phase = 4933** (Query Executions per Hour) (World Record)
- **Phase 3: Query runtime phase = 109.9** (Total Runtime of complex query phase in seconds)

This world record result for the Throughput Phase shows that the ThinkAgile VX650 V3 Certified Node offers a significant performance advantage compared to other vendors.

The ThinkAgile VX650 V3 Certified Node configuration for the benchmark was as follows:

- 2x Intel Xeon Platinum 8490H processors
 - 1.90 GHz base frequency
 - 80 KB L1 cache and 2048 KB L2 cache per core
 - 112.5 MB L3 cache per processor
 - 60 total cores / 120 total threads
- 4 TB DDR5 system memory
- VMware ESXi 8.0
- SUSE Linux Enterprise Server 15 SP4 for the virtual machine
- SAP HANA 2.0
- SAP NetWeaver® 7.50
- One VM with 240 vCPUs and 3968 GB DRAM

Results referenced are current as of July 24, 2023. For the latest SAP BW benchmark results, visit: <https://www.sap.com/dmc/exp/2018-benchmark-directory/#/bwh>.

(1) This benchmark fully complies with the SAP Benchmark Council regulations and has been audited and certified by SAP SE ([certification number 2023030](#)). Details can be obtained from Lenovo and SAP. The benchmark was performed at the Lenovo Data Center Performance Lab in Walldorf, Germany, by VMware engineers. Configuration: 1x ThinkAgile VX650 V3 Certified Node configured with 2 processor / 60 cores / 120 threads, Intel Xeon Platinum 8490H processors, 1.90 GHz, 80 KB L1 cache and 2048 KB L2 cache per core, 112.5 MB L3 cache per processor, 4 TB DRAM.

About the ThinkAgile VX650 V3 Certified Node

The Lenovo ThinkAgile VX650 V3 Integrated Systems and Certified Nodes are 2-socket 2U systems that feature the 4th Generation Intel Xeon Scalable processors. With up to 60 cores per processor and support for the new PCIe 5.0 standard for I/O, the VX650 V3 systems offer the ultimate in two-socket performance in a 2U form factor. The ThinkAgile VX650 V3, when combined with VMware vSAN and VMware vSphere offers a unique, software-defined approach to hyper convergence, leveraging the hypervisor to deliver compute, storage, and management in a tightly integrated software stack.

The ThinkAgile VX650 V3 Integrated System and Certified Node offer the following key features:

- Factory-integrated, pre-configured ready-to-go integrated systems built on proven and reliable Lenovo ThinkSystem servers that provide compute power for a variety of workloads and applications and powered by industry-leading hyperconverged infrastructure software from VMware.
- Provide quick and convenient path to implement a hyperconverged solution powered by VMware vSAN with "one stop shop" and a single point of contact provided by Lenovo for purchasing, deploying, and supporting the solution.
- Meet various workload demands with cost-efficient hybrid or performance-optimized all-flash storage configurations.
- Deliver fully validated and integrated hardware and firmware that is certified with VMware software.

About the SAP BW edition for SAP HANA Benchmark

The SAP BW, edition for SAP HANA Standard Application Benchmark, Version 3, is the latest addition to the list of benchmarks for SAP Business Warehouse. It utilizes the capabilities of SAP HANA to process the benchmark workload. Allowed data volumes are a multiple of 1.3 billion initial records and can be run in single-node and multi-node setups. This benchmark was released in July 2018.

The benchmark scenario represents typical mid-size customer scenario and volumes for SAP BW running on SAP HANA. The benchmark simulates a variety of users with different analytical requirements and measures the key performance indicator (KPI) relevant to each of the three benchmark phases.

The three benchmark phases are as follows:

1. Data load phase, testing data latency and load performance
2. Query throughput phase, testing query throughput with moderate complex queries
3. Query runtime phase, testing the performance of running very complex queries

For more information about the benchmark, go to <https://www.sap.com/about/benchmark.html>.

Learn more

To learn more about business warehouse and data analytics solutions for SAP applications running on Lenovo Servers visit, <https://www.lenovo.com/us/en/data-center/solutions/sap/> or contact your Lenovo Customer Representative.

To learn more about the ThinkAgile VX650 V3 Certified Node, see the following web page:

- ThinkAgile VX650 V3 Certified Node Product Guide:
<https://lenovopress.lenovo.com/lp1673-thinkagile-vx650-v3-2u-integrated-system-and-certified-node>

Related product families

Product families related to this document are the following:

- [SAP Alliance](#)
- [SAP BW Benchmark Results](#)
- [ThinkAgile VX Series for VMware](#)

Notices

Lenovo may not offer the products, services, or features discussed in this document in all countries. Consult your local Lenovo representative for information on the products and services currently available in your area. Any reference to a Lenovo product, program, or service is not intended to state or imply that only that Lenovo product, program, or service may be used. Any functionally equivalent product, program, or service that does not infringe any Lenovo intellectual property right may be used instead. However, it is the user's responsibility to evaluate and verify the operation of any other product, program, or service. Lenovo may have patents or pending patent applications covering subject matter described in this document. The furnishing of this document does not give you any license to these patents. You can send license inquiries, in writing, to:

Lenovo (United States), Inc.
8001 Development Drive
Morrisville, NC 27560
U.S.A.
Attention: Lenovo Director of Licensing

LENOVO PROVIDES THIS PUBLICATION "AS IS" WITHOUT WARRANTY OF ANY KIND, EITHER EXPRESS OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF NON-INFRINGEMENT, MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE. Some jurisdictions do not allow disclaimer of express or implied warranties in certain transactions, therefore, this statement may not apply to you.

This information could include technical inaccuracies or typographical errors. Changes are periodically made to the information herein; these changes will be incorporated in new editions of the publication. Lenovo may make improvements and/or changes in the product(s) and/or the program(s) described in this publication at any time without notice.

The products described in this document are not intended for use in implantation or other life support applications where malfunction may result in injury or death to persons. The information contained in this document does not affect or change Lenovo product specifications or warranties. Nothing in this document shall operate as an express or implied license or indemnity under the intellectual property rights of Lenovo or third parties. All information contained in this document was obtained in specific environments and is presented as an illustration. The result obtained in other operating environments may vary. Lenovo may use or distribute any of the information you supply in any way it believes appropriate without incurring any obligation to you.

Any references in this publication to non-Lenovo Web sites are provided for convenience only and do not in any manner serve as an endorsement of those Web sites. The materials at those Web sites are not part of the materials for this Lenovo product, and use of those Web sites is at your own risk. Any performance data contained herein was determined in a controlled environment. Therefore, the result obtained in other operating environments may vary significantly. Some measurements may have been made on development-level systems and there is no guarantee that these measurements will be the same on generally available systems. Furthermore, some measurements may have been estimated through extrapolation. Actual results may vary. Users of this document should verify the applicable data for their specific environment.

© Copyright Lenovo 2024. All rights reserved.

This document, LP1790, was created or updated on August 9, 2023.

Send us your comments in one of the following ways:

- Use the online Contact us review form found at:
<https://lenovopress.lenovo.com/LP1790>
- Send your comments in an e-mail to:
comments@lenovopress.com

This document is available online at <https://lenovopress.lenovo.com/LP1790>.

Trademarks

Lenovo and the Lenovo logo are trademarks or registered trademarks of Lenovo in the United States, other countries, or both. A current list of Lenovo trademarks is available on the Web at <https://www.lenovo.com/us/en/legal/copytrade/>.

The following terms are trademarks of Lenovo in the United States, other countries, or both:

Lenovo®

ThinkAgile®

ThinkSystem®

The following terms are trademarks of other companies:

Intel® and Xeon® are trademarks of Intel Corporation or its subsidiaries.

Linux® is the trademark of Linus Torvalds in the U.S. and other countries.

Other company, product, or service names may be trademarks or service marks of others.