

ThinkSystem SR860 V3 Sets World Record with New SAP BW Edition for SAP HANA (7.8B Records) Benchmark Result

Performance Benchmark Result

The Lenovo ThinkSystem SR860 V3 server, using Intel Xeon Platinum 8490H processors, delivers world record performance for complex query KPI (phase 3) for SAP Business Warehouse, edition for SAP HANA® Standard Application Benchmark Version 3 with 7.8 billion (7.8B) initial records in a single-node setup.

The benchmark refers to the SAP Business Warehouse (SAP BW) application running on the SAP HANA platform. The benchmark consists of three phases and the SR860 V3 server achieved the following performance results (1):



- **Phase 1: Data load phase = 8,722** (Runtime of last Data Set in seconds)
- **Phase 2: Query throughput phase = 10,814** (Query Executions per Hour)
- **Phase 3: Query runtime phase = 83** (Total Runtime of complex query phase in seconds) (World Record)

This world record result for Phase 3, Query runtime phase shows that the ThinkSystem SR860 V3 offers a significant performance advantage compared to other vendors.

The SR860 V3 was configured as follows:

- Four Intel Xeon Platinum 8490H processors, 1.90 GHz
 - 240 total cores / 480 total threads
 - 80 KB L1 cache and 2048 KB L2 cache per core
 - 112.5 MB L3 cache per processor
- 4096 GB DRAM system memory
- SUSE Linux Enterprise Server 15 SP4
- SAP HANA 2.0
- SAP NetWeaver® 7.50

Results referenced are current as of August 15, 2023. For the latest SAP BW benchmark results, visit: <https://www.sap.com/dmc/exp/2018-benchmark-directory/#/bwh>.

(1) This benchmark fully complies with the SAP Benchmark Council regulations and has been audited and certified by SAP SE (certification number [2023036](#)). Details can be obtained from Lenovo and SAP. The benchmark was performed in Bucharest, Romania, by Lenovo engineers. Configuration: ThinkSystem SR860 V3 with 4 processor / 240 cores / 480 threads, Intel Xeon Platinum 8490H processors, 1.90 GHz, 80 KB L1 cache and 2048 KB L2 cache per core, 112.5 MB L3 cache per processor, 4096 GB DRAM.

About the ThinkSystem SR860 V3

The Lenovo ThinkSystem SR860 V3 mission-critical server provides the speed and reliability you require today with the scalability and workload versatility you'll need to manage the explosive growth of data for tomorrow. Purpose-built to deliver affordable scalability in an industry-standard x86 platform, the SR860 V3 is ideal for mission critical workloads such as SAP HANA in-memory computing, transactional databases, analytics, big data, and enterprise resource planning tasks.

The Lenovo ThinkSystem SR860 V3 is a 4-socket server that features a 4U rack design, providing technology advances, including 4th Gen Intel® Xeon® Scalable processors, 4800 MHz DDR5 memory, large internal storage, and PCIe Gen 5 slots with support for up to eight high-performance GPUs, offering considerable adaptability to match system configurations to projected workloads. The system has the capability to scale from two to four 4th Gen Intel® Xeon® Scalable processor family CPUs that offers a simple “pay as you grow” upgrade for both processors and memory, resulting in greater system performance to handle growing next-generation workloads.

Server reliability, availability, and serviceability (RAS) are crucial issues for modern enterprise IT shops that deliver mission-critical applications and services, and application delivery failures can be extremely costly per hour of system downtime. Intel Xeon Scalable processors running on ThinkSystem servers continue to be at the top of the industry in regards to RAS features. For further information on the importance of RAS and a comprehensive list of the key RAS features of the Lenovo ThinkSystem servers with Intel Xeon Scalable processors, read [RAS Features of the Lenovo ThinkSystem Intel Servers](#) .

About the SAP BW edition for SAP HANA Benchmark

The SAP BW, edition for SAP HANA Standard Application Benchmark, Version 3, is the latest addition to the list of benchmarks for SAP Business Warehouse. It utilizes the capabilities of SAP HANA to process the benchmark workload. Allowed data volumes are a multiple of 1.3 billion initial records and can be run in single-node and multi-node setups. This benchmark was released in July 2018.

The benchmark scenario represents typical mid-size customer scenario and volumes for SAP BW running on SAP HANA. The benchmark simulates a variety of users with different analytical requirements and measures the key performance indicator (KPI) relevant to each of the three benchmark phases.

The three benchmark phases are as follows:

1. Data load phase, testing data latency and load performance
2. Query throughput phase, testing query throughput with moderate complex queries
3. Query runtime phase, testing the performance of running very complex queries

For more information about the benchmark, go to <https://www.sap.com/about/benchmark.html>.

Learn more

To learn more about business warehouse and data analytics solutions for SAP applications running on Lenovo Servers visit, <http://www.lenovo.com/sap/hana> or contact your Lenovo Customer Representative.

To learn more about the Lenovo ThinkSystem SR860 V3 server, visit the SR860 V3 product web page: <https://www.lenovo.com/us/en/p/servers-storage/servers/mission-critical/thinksystem-sr860-v3/7d931000na>

Related product families

Product families related to this document are the following:

- [4-Socket Rack Servers](#)
- [SAP Alliance](#)
- [SAP BW Benchmark Results](#)
- [ThinkSystem SR860 V3 Server](#)

Notices

Lenovo may not offer the products, services, or features discussed in this document in all countries. Consult your local Lenovo representative for information on the products and services currently available in your area. Any reference to a Lenovo product, program, or service is not intended to state or imply that only that Lenovo product, program, or service may be used. Any functionally equivalent product, program, or service that does not infringe any Lenovo intellectual property right may be used instead. However, it is the user's responsibility to evaluate and verify the operation of any other product, program, or service. Lenovo may have patents or pending patent applications covering subject matter described in this document. The furnishing of this document does not give you any license to these patents. You can send license inquiries, in writing, to:

Lenovo (United States), Inc.
8001 Development Drive
Morrisville, NC 27560
U.S.A.
Attention: Lenovo Director of Licensing

LENOVO PROVIDES THIS PUBLICATION "AS IS" WITHOUT WARRANTY OF ANY KIND, EITHER EXPRESS OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF NON-INFRINGEMENT, MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE. Some jurisdictions do not allow disclaimer of express or implied warranties in certain transactions, therefore, this statement may not apply to you.

This information could include technical inaccuracies or typographical errors. Changes are periodically made to the information herein; these changes will be incorporated in new editions of the publication. Lenovo may make improvements and/or changes in the product(s) and/or the program(s) described in this publication at any time without notice.

The products described in this document are not intended for use in implantation or other life support applications where malfunction may result in injury or death to persons. The information contained in this document does not affect or change Lenovo product specifications or warranties. Nothing in this document shall operate as an express or implied license or indemnity under the intellectual property rights of Lenovo or third parties. All information contained in this document was obtained in specific environments and is presented as an illustration. The result obtained in other operating environments may vary. Lenovo may use or distribute any of the information you supply in any way it believes appropriate without incurring any obligation to you.

Any references in this publication to non-Lenovo Web sites are provided for convenience only and do not in any manner serve as an endorsement of those Web sites. The materials at those Web sites are not part of the materials for this Lenovo product, and use of those Web sites is at your own risk. Any performance data contained herein was determined in a controlled environment. Therefore, the result obtained in other operating environments may vary significantly. Some measurements may have been made on development-level systems and there is no guarantee that these measurements will be the same on generally available systems. Furthermore, some measurements may have been estimated through extrapolation. Actual results may vary. Users of this document should verify the applicable data for their specific environment.

© Copyright Lenovo 2024. All rights reserved.

This document, LP1801, was created or updated on September 6, 2023.

Send us your comments in one of the following ways:

- Use the online Contact us review form found at:
<https://lenovopress.lenovo.com/LP1801>
- Send your comments in an e-mail to:
comments@lenovopress.com

This document is available online at <https://lenovopress.lenovo.com/LP1801>.

Trademarks

Lenovo and the Lenovo logo are trademarks or registered trademarks of Lenovo in the United States, other countries, or both. A current list of Lenovo trademarks is available on the Web at <https://www.lenovo.com/us/en/legal/copytrade/>.

The following terms are trademarks of Lenovo in the United States, other countries, or both:

Lenovo®

ThinkSystem®

The following terms are trademarks of other companies:

Intel® and Xeon® are trademarks of Intel Corporation or its subsidiaries.

Linux® is the trademark of Linus Torvalds in the U.S. and other countries.

Other company, product, or service names may be trademarks or service marks of others.