

ThinkSystem Vendor Agnostic Read Intensive NVMe SSDs

Product Guide

The ThinkSystem Vendor Agnostic Read Intensive NVMe SSDs are general-purpose yet high-performance drives with a PCIe x4 interface. They are designed for greater performance and endurance in a cost-effective design, and to support a broader set of workloads. Vendor Agnostic SSDs are non-vendor-specific drives which can streamline and simplify the ordering and delivery of SATA SSDs. The drives offered in the Vendor Agnostic SSD program consists of SSDs that are readily available, ensuring the shortest supply lead time.

The drives are enabled with SED encryption to help ensure data security, even when the drive is removed from the server.



Figure 1. ThinkSystem Vendor Agnostic Read Intensive NVMe SSDs in 2.5-inch hot-swap form factor

Did you know?

Lenovo Read Intensive SSDs are suitable for read-intensive and general-purpose data center workloads. Overall, these SSDs provide outstanding IOPS/watt and cost/IOPS for enterprise solutions and are an excellent choice for applications such as web serving, hyperscale cloud, content delivery, caching, databases, and analytics.

Self-encrypting drives (SEDs) provide benefits by encrypting data on-the-fly at the drive level with no performance impact, by providing instant secure erasure thereby making the data no longer readable, and by enabling auto-locking to secure active data if a drive is misplaced or stolen from a system while in use. These features are essential for many businesses, especially those storing customer data.

Part number information

VMware vSAN and Microsoft S2D configurations: Vendor Agnostic (VA) drives are based on drives from multiple vendors, and not all vendor variants are VMware vSAN or Microsoft S2D certified. Additionally, ISVs require a single drive vendor per host and cluster to ensure optimal performance; a requirement that VA drives may not consistently meet. To ensure certification compliance, hardware uniformity, and alignment with VMware and Microsoft best practices, use ThinkAgile VX or ThinkAgile FX for all vSAN configurations and ThinkAgile MX for all S2D configurations, instead of general purpose ThinkSystem servers.

The following table lists the part numbers and feature codes.

Table 1. Ordering part numbers and feature codes

Part number	Feature	Description	SED support
2.5-inch hot-swap drives with PCIe 5.0 interface			
4XB7B11683	CCZF	ThinkSystem 2.5" U.2 VA 960GB Read Intensive NVMe PCIe 4.0 x4 HS SSD	Supported
4XB7A93122	C0ZV	ThinkSystem 2.5" U.2 VA 1.92TB Read Intensive NVMe PCIe 5.0 x4 HS SSD	Supported
4XB7A93123	C0ZU	ThinkSystem 2.5" U.2 VA 3.84TB Read Intensive NVMe PCIe 5.0 x4 HS SSD	Supported
4XB7A93124	C0ZT	ThinkSystem 2.5" U.2 VA 7.68TB Read Intensive NVMe PCIe 5.0 x4 HS SSD	Supported
4XB7A93125	C0ZS	ThinkSystem 2.5" U.2 VA 15.36TB Read Intensive NVMe PCIe 5.0 x4 HS SSD	Supported
4XB7A93126	C1W7	ThinkSystem 2.5" U.2 VA 30.72TB Read Intensive NVMe PCIe 5.0 x4 HS SSD	Supported
2.5-inch hot-swap drives with PCIe 4.0 interface			
4XB7A93892	C18N	ThinkSystem 2.5" U.2 VA 1.92TB Read Intensive NVMe PCIe 4.0 x4 HS SSD	Supported
4XB7A93893	C18M	ThinkSystem 2.5" U.2 VA 3.84TB Read Intensive NVMe PCIe 4.0 x4 HS SSD	Supported
4XB7A93894	C18L	ThinkSystem 2.5" U.2 VA 7.68TB Read Intensive NVMe PCIe 4.0 x4 HS SSD	Supported
4XB7A93895	C18K	ThinkSystem 2.5" U.2 VA 15.36TB Read Intensive NVMe PCIe 4.0 x4 HS SSD	Supported
3.5-inch hot-swap drives with PCIe 5.0 interface			
4XB7B13984	CFA6	ThinkSystem 3.5" U.2 VA 1.92TB Read Intensive NVMe PCIe 5.0 x4 HS SSD	Supported
4XB7B13985	CFA5	ThinkSystem 3.5" U.2 VA 3.84TB Read Intensive NVMe PCIe 5.0 x4 HS SSD	Supported
4XB7B13986	CFA4	ThinkSystem 3.5" U.2 VA 7.68TB Read Intensive NVMe PCIe 5.0 x4 HS SSD	Supported
4XB7B13987	CFA3	ThinkSystem 3.5" U.2 VA 15.36TB Read Intensive NVMe PCIe 5.0 x4 HS SSD	Supported
E3.S 1T hot-swap drives with PCIe 5.0 interface			
4XB7A93131	C1W8	ThinkSystem E3.S 1T VA 1.92TB Read Intensive NVMe PCIe 5.0 x4 HS SSD v2	Supported
4XB7A93132	C1W9	ThinkSystem E3.S 1T VA 3.84TB Read Intensive NVMe PCIe 5.0 x4 HS SSD v2	Supported
4XB7A93133	C1WA	ThinkSystem E3.S 1T VA 7.68TB Read Intensive NVMe PCIe 5.0 x4 HS SSD v2	Supported
4XB7A93134	C1WB	ThinkSystem E3.S 1T VA 15.36TB Read Intensive NVMe PCIe 5.0 x4 HS SSD v2	Supported
15mm trayless (non-hot-swap) drives with PCIe 4.0 interface			

Part number	Feature	Description	SED support
4XB7B09657	CBT6	ThinkSystem 2.5" 15mm VA 1.92TB Read Intensive NVMe PCIe 4.0 x4 Trayless SSD	Supported
4XB7B09658	CBT7	ThinkSystem 2.5" 15mm VA 3.84TB Read Intensive NVMe PCIe 4.0 x4 Trayless SSD	Supported
4XB7B09659	CBT8	ThinkSystem 2.5" 15mm VA 7.68TB Read Intensive NVMe PCIe 4.0 x4 Trayless SSD	Supported
7mm trayless (non-hot-swap) drives with PCIe 4.0 interface			
4XB7B09654	CBT3	ThinkSystem 2.5" 7mm VA 960GB Read Intensive NVMe PCIe 4.0 x4 Trayless SSD	Supported
4XB7B09655	CBT4	ThinkSystem 2.5" 7mm VA 1.92TB Read Intensive NVMe PCIe 4.0 x4 Trayless SSD	Supported
4XB7B09656	CBT5	ThinkSystem 2.5" 7mm VA 3.84TB Read Intensive NVMe PCIe 4.0 x4 Trayless SSD	Supported
E3.S 1T trayless (non-hot-swap) drives with PCIe 5.0 interface			
4XB7B12180	CE88	ThinkSystem E3.S 1T VA 1.92TB Read Intensive NVMe PCIe 5.0 x4 Trayless SSD	Supported
4XB7B12181	CE87	ThinkSystem E3.S 1T VA 3.84TB Read Intensive NVMe PCIe 5.0 x4 Trayless SSD	Supported
4XB7B12182	CE86	ThinkSystem E3.S 1T VA 7.68TB Read Intensive NVMe PCIe 5.0 x4 Trayless SSD	Supported
4XB7B12183	CE85	ThinkSystem E3.S 1T VA 15.36TB Read Intensive NVMe PCIe 5.0 x4 Trayless SSD	Supported
M.2 drives with PCIe 4.0 interface - not for B550 or B350 M.2 adapters			
4XB7B09650	CBSZ	ThinkSystem M.2 VA 480GB Read Intensive NVMe PCIe 4.0 x4 NHS SSD	Supported
4XB7B09651	CBT0	ThinkSystem M.2 VA 960GB Read Intensive NVMe PCIe 4.0 x4 NHS SSD	Supported
4XB7B09652	CBT1	ThinkSystem M.2 VA 1.92TB Read Intensive NVMe PCIe 4.0 x4 NHS SSD	Supported
4XB7B09653	CBST	ThinkSystem M.2 VA 3.84TB Read Intensive NVMe PCIe 4.0 x4 NHS SSD	Supported
M.2 drives with PCIe 4.0 interface - only for B550i or B350i internal M.2 adapters			
4XB7A93140	C286	ThinkSystem M.2 VA 480GB Read Intensive NVMe NHS SSD	Supported
4XB7A93141	C287	ThinkSystem M.2 VA 960GB Read Intensive NVMe NHS SSD	Supported
4XB7A93142	C288	ThinkSystem M.2 VA 1.92TB Read Intensive NVMe NHS SSD	Supported
M.2 drives with PCIe 4.0 interface - only for B550p or B550d hot-swap M.2 adapters			
4XB7B14665	C286	ThinkSystem M.2 VA 480GB Read Intensive NVMe HS SSD	Supported
4XB7B14666	C287	ThinkSystem M.2 VA 960GB Read Intensive NVMe HS SSD	Supported
4XB7B14667	C288	ThinkSystem M.2 VA 1.92TB Read Intensive NVMe HS SSD	Supported

The part numbers include the following items:

- One 2.5-inch, EDSFF E3.S 1T, or M.2 solid-state drive
- Hot-swap drives include a ThinkSystem hot-swap tray
- Documentation flyer

Features

The Vendor Agnostic SSDs have the following features:

- Low cost SSD for read-intensive workloads from industry leading SSD vendors
- PCIe 5.0 x4 or PCIe 4.0 x4 connection for each NVMe drive

- SED drive encryption (TCG Opal or TCG Enterprise)
- Advanced ECC Engine and End-to-End Data Protection
- TLC V-NAND stacks the vertical NAND layers in three dimensions, solving the cell-to-cell interference that causes data corruption in planar NAND.
- Power Loss Protection (PLP) architecture
- Supports Self-Monitoring, Analysis and Reporting Technology (S.M.A.R.T).

Read-Intensive (Entry) SSDs and Write-Intensive (Performance) SSDs have similar read and write IOPS performance, but the key difference between them is their endurance (or lifetime) (that is, how long they can perform write operations because SSDs have a finite number of program/erase (P/E) cycles). Read-Intensive SSDs have a better cost/IOPS ratio but lower endurance compared to Write-Intensive SSDs. SSD write endurance is typically measured by the number of program/erase (P/E) cycles that the drive incurs over its lifetime, listed as the total bytes of written data (TBW) in the device specification.

The TBW value assigned to a solid-state device is the total bytes of written data (based on the number of P/E cycles) that a drive can be guaranteed to complete (% of remaining P/E cycles = % of remaining TBW). Reaching this limit does not cause the drive to immediately fail. It simply denotes the maximum number of writes that can be guaranteed. A solid-state device will not fail upon reaching the specified TBW. At some point based on manufacturing variance margin, after surpassing the TBW value, the drive will reach the end-of-life point, at which the drive will go into a read-only mode. Because of such behavior by Read-Intensive solid-state drives, careful planning must be done to use them only in read-intensive or mix-use up to 70% read/30% write environments to ensure that the TBW of the drive will not be exceeded before the required life expectancy.

The benefits of drive encryption

Self-encrypting drives (SEDs) provide benefits in three main ways:

- By encrypting data on-the-fly at the drive level with no performance impact
- By providing instant secure erasure (cryptographic erasure, thereby making the data no longer readable)
- By enabling auto-locking to secure active data if a drive is misplaced or stolen from a system while in use

The following sections describe the benefits in more details.

Automatic encryption

It is vital that a company keep its data secure. With the threat of data loss due to physical theft or improper inventory practices, it is important that the data be encrypted. However, challenges with performance, scalability, and complexity have led IT departments to push back against security policies that require the use of encryption. In addition, encryption has been viewed as risky by those unfamiliar with key management, a process for ensuring a company can always decrypt its own data. Self-encrypting drives comprehensively resolve these issues, making encryption both easy and affordable.

When the self-encrypting drive is in normal use, its owner need not maintain authentication keys (otherwise known as credentials or passwords) in order to access the data on the drive. The self-encrypting drive will encrypt data being written to the drive and decrypt data being read from it, all without requiring an authentication key from the owner.

Drive retirement and disposal

When hard drives are retired and moved outside the physically protected data center into the hands of others, the data on those drives is put at significant risk. IT departments retire drives for a variety of reasons, including:

- Returning drives for warranty, repair, or expired lease agreements
- Removal and disposal of drives
- Repurposing drives for other storage duties

Nearly all drives eventually leave the data center and their owner's control. Corporate data resides on such drives, and when most leave the data center, the data they contain is still readable. Even data that has been striped across many drives in a RAID array is vulnerable to data theft because just a typical single stripe in today's high-capacity arrays is large enough to expose for example, hundreds of names and bank account numbers.

In an effort to avoid data breaches and the ensuing customer notifications required by data privacy laws, companies use different methods to erase the data on retired drives before they leave the premises and potentially fall into the wrong hands. Current retirement practices that are designed to make data unreadable rely on significant human involvement in the process, and are thus subject to both technical and human failure.

The drawbacks of today's drive retirement practices include the following:

- Overwriting drive data is expensive, tying up valuable system resources for days. No notification of completion is generated by the drive, and overwriting won't cover reallocated sectors, leaving that data exposed.
- Methods that include degaussing or physically shredding a drive are expensive. It is difficult to ensure the degauss strength is optimized for the drive type, potentially leaving readable data on the drive. Physically shredding the drive is environmentally hazardous, and neither practice allows the drive to be returned for warranty or expired lease.
- Some companies have concluded the only way to securely retire drives is to keep them in their control, storing them indefinitely in warehouses. But this is not truly secure because a large volume of drives coupled with human involvement inevitably leads to some drives being lost or stolen.
- Professional disposal services is an expensive option and includes the cost of reconciling the services as well as internal reports and auditing. Transporting of the drives also has the potential of putting the data at risk.

Self-encrypting drives eliminate the need to overwrite, destroy, or store retired drives. When the drive is to be retired, it can be cryptographically erased, a process that is nearly instantaneous regardless of the capacity of the drive.

Instant secure erase

The self-encrypting drive provides instant data encryption key destruction via cryptographic erasure. When it is time to retire or repurpose the drive, the owner sends a command to the drive to perform a cryptographic erasure. Cryptographic erasure simply replaces the encryption key inside the encrypted drive, making it impossible to ever decrypt the data encrypted with the deleted key.

Self-encrypting drives reduce IT operating expenses by reducing asset control challenges and disposal costs. Data security with self-encrypting drives helps ensure compliance with privacy regulations without hindering IT efficiency. So called "Safe Harbor" clauses in government regulations allow companies to not have to notify customers of occurrences of data theft if that data was encrypted and therefore unreadable.

Furthermore, self-encrypting drives simplify decommissioning and preserve hardware value for returns and repurposing by:

- Eliminating the need to overwrite or destroy the drive
- Securing warranty returns and expired lease returns
- Enabling drives to be repurposed securely

Auto-locking

Insider theft or misplacement is a growing concern for businesses of all sizes; in addition, managers of branch offices and small businesses without strong physical security face greater vulnerability to external theft. Self-encrypting drives include a feature called auto-lock mode to help secure active data against theft.

Using a self-encrypting drive when auto-lock mode is enabled simply requires securing the drive with an authentication key. When secured in this manner, the drive's data encryption key is locked whenever the drive is powered down. In other words, the moment the self-encrypting drive is switched off or unplugged, it automatically locks down the drive's data.

When the self-encrypting drive is then powered back on, it requires authentication before being able to unlock its encryption key and read any data on the drive, thus protecting against misplacement and theft.

While using self-encrypting drives just for the instant secure erase is an extremely efficient and effective means to help securely retire a drive, using self-encrypting drives in auto-lock mode provides even more advantages. From the moment the drive or system is removed from the data center (with or without

authorization), the drive is locked. No advance thought or action is required from the data center administrator to protect the data. This helps prevent a breach should the drive be mishandled and helps secure the data against the threat of insider or outside theft.

Technical specifications

The following table lists the technical specifications for the drives.

Performance and endurance values: The numbers listed in these tables for performance and endurance are the minimums for Vendor Agnostic SSDs.

- [Technical specifications for 2.5-inch, 3.5-inch, and E3.S 1T drives](#)
- [Technical specifications for M.2 drives](#)

Technical specifications for 2.5-inch, 3.5-inch, and E3.S 1T drives

Table 2. Technical specifications for 2.5-inch and E3.S 1T form factor drives

Feature	960 GB drive	1.92 TB drive	3.84 TB drive	7.68 TB drive	15.36 TB drive	30.72 TB drive
Interface	PCIe x4	PCIe x4	PCIe x4	PCIe x4	PCIe x4	PCIe x4
Capacity	960 GB	1.92 TB	3.84 TB	7.68 TB	15.36 TB	30.72 TB
SED encryption	Yes	Yes	Yes	Yes	Yes	Yes
Endurance (drive writes per day for 5 years)	1 DWPD	1 DWPD	1 DWPD	1 DWPD	1 DWPD	1 DWPD
Endurance (total bytes written)	-	3,504 TB	7,008 TB	14,016 TB	28,032 TB	56,064 TB
Data reliability (UBER)	< 1 in 10 ¹⁷ bits read	< 1 in 10 ¹⁷ bits read	< 1 in 10 ¹⁷ bits read	< 1 in 10 ¹⁷ bits read	< 1 in 10 ¹⁷ bits read	< 1 in 10 ¹⁷ bits read
MTBF	2,000,000 hours	2,000,000 hours	2,000,000 hours	2,000,000 hours	2,000,000 hours	2,000,000 hours
Shock, non-operating	1,500 G (Max) at 0.5 ms	1,500 G (Max) at 0.5 ms	1,500 G (Max) at 0.5 ms	1,500 G (Max) at 0.5 ms	1,500 G (Max) at 0.5 ms	1,500 G (Max) at 0.5 ms
Vibration, non-operating	2.17 G _{RMS} (5-700 Hz)	2.17 G _{RMS} (5-700 Hz)	2.17 G _{RMS} (5-700 Hz)	2.17 G _{RMS} (5-700 Hz)	2.17 G _{RMS} (5-700 Hz)	2.17 G _{RMS} (5-700 Hz)
Performance data for 2.5-inch PCIe 5.0 drives						
IOPS reads (4 KB blocks)	-	1,440,000	1,710,000	1,800,000	1,800,000	1,400,000
IOPS writes (4 KB blocks)	-	135,000	180,000	180,000	180,000	135,000
Sequential read rate (128 KB blocks)	-	10,800 MBps	10,800 MBps	10,800 MBps	10,800 MBps	8100 MBps
Sequential write rate (128 KB blocks)	-	3150 MBps	4950 MBps	4950 MBps	4950 MBps	4500 MBps
Performance data for 2.5-inch PCIe 4.0 drives						
IOPS reads (4 KB blocks)	500,000	630,000	90,000	90,000	90,000	-
IOPS writes (4 KB blocks)	65,000	102,600	16,200	193,500	180,000	-
Sequential read rate (128 KB blocks)	6,000 MBps	4,750 MBps	6,000 MBps	6,100 MBps	6,100 MBps	-

Feature	960 GB drive	1.92 TB drive	3.84 TB drive	7.68 TB drive	15.36 TB drive	30.72 TB drive
Sequential write rate (128 KB blocks)	1300 MBps	1700 MBps	3250 MBps	3800 MBps	3600 MBps	-
Performance data for E3.S 1T PCIe 5.0 drives						
IOPS reads (4 KB blocks)	-	1,440,000	1,530,000	1,800,000	1,800,000	-
IOPS writes (4 KB blocks)	-	135,000	180,000	180,000	180,000	-
Sequential read rate (128 KB blocks)	-	10,800 MBps	10,800 MBps	10,800 MBps	10,800 MBps	-
Sequential write rate (128 KB blocks)	-	3150 MBps	4950 MBps	4950 MBps	4950 MBps	-

Technical specifications for M.2 drives

Table 3. Technical specifications for M.2 drives

Feature	480 GB drive	960 GB drive	1.92 TB drive	3.84 TB drive
Form factor	M.2 2280	M.2 2280 or 22110	M.2 22110	M.2 22110
Interface	PCIe 4.0 x4	PCIe 4.0 x4	PCIe 4.0 x4	PCIe 4.0 x4
Capacity	480 GB	960 GB	1.92 TB	3.84 TB
SED encryption	Yes	Yes	Yes	Yes
Endurance (drive writes per day for 5 years)	0.9 DWPD	1.0 DWPD	1.0 DWPD	1.0 DWPD
Endurance (total bytes written)	800 TB	1700 TB	3500 TB	7000 TB
Data reliability (UBER)	< 1 in 10 ¹⁷ bits read	< 1 in 10 ¹⁷ bits read	< 1 in 10 ¹⁷ bits read	< 1 in 10 ¹⁷ bits read
MTBF	2,000,000 hours	2,000,000 hours	2,000,000 hours	2,000,000 hours
IOPS reads (4 KB blocks)	252,000	468,000	662,000	662,000
IOPS writes (4 KB blocks)	32,000	59,000	90,000	144,000
Sequential read rate (128 KB blocks)	4,500 MBps	4,500 MBps	4,500 MBps	4,500 MBps
Sequential write rate (128 KB blocks)	630 MBps	1300 MBps	1650 MBps	2300 MBps

Server support

The following tables list the ThinkSystem servers that are compatible.

Table 4. Server support (Part 1 of 5)

Part Number	Description	AMD V3				2S Intel V3/V4						Multi Node V3		1S V3			
		SR635 V3 (7D9H / 7D9G)	SR655 V3 (7D9F / 7D9E)	SR645 V3 (7D9D / 7D9C)	SR665 V3 (7D9B / 7D9A)	ST650 V3 (7D7B / 7D7A)	SR630 V3 (7D72 / 7D73)	SR650 V3 (7D75 / 7D76)	SR630 V4 (7DG8 / 7DG9)	SR650 V4 (7DGC / 7DGD)	SR650a V4 (7DGC / 7DGD)	SD535 V3 (7DD8 / 7DD1)	SD530 V3 (7DDA / 7DD3)	SD550 V3 (7DD9 / 7DD2)	ST45 V3 (7DH4 / 7DH5)	ST50 V3 (7DF4 / 7DF3)	ST250 V3 (7DCF / 7DCE)
2.5-inch hot-swap drives with PCIe 5.0 interface																	
4XB7B11683	ThinkSystem 2.5" U.2 VA 960GB Read Intensive NVMe PCIe 4.0 x4 HS SSD	N	N	Y	Y	N	Y	Y	N	N	N	Y	N	Y	N	N	N
4XB7A93122	ThinkSystem 2.5" U.2 VA 1.92TB Read Intensive NVMe PCIe 5.0 x4 HS SSD	Y	Y	Y	Y	N	Y	Y	Y	Y	Y	Y	N	Y	N	N	N
4XB7A93123	ThinkSystem 2.5" U.2 VA 3.84TB Read Intensive NVMe PCIe 5.0 x4 HS SSD	Y	Y	Y	Y	N	Y	Y	Y	Y	Y	Y	N	Y	N	N	N
4XB7A93124	ThinkSystem 2.5" U.2 VA 7.68TB Read Intensive NVMe PCIe 5.0 x4 HS SSD	Y	Y	Y	Y	N	Y	Y	Y	Y	Y	Y	N	Y	N	N	N
4XB7A93125	ThinkSystem 2.5" U.2 VA 15.36TB Read Intensive NVMe PCIe 5.0 x4 HS SSD	Y	Y	Y	Y	N	Y	Y	Y	Y	Y	Y	N	Y	N	N	N
4XB7A93126	ThinkSystem 2.5" U.2 VA 30.72TB Read Intensive NVMe PCIe 5.0 x4 HS SSD	Y	Y	Y	Y	N	Y	Y	Y	Y	Y	Y	N	Y	N	N	N
2.5-inch hot-swap drives with PCIe 4.0 interface																	
4XB7A93892	ThinkSystem 2.5" U.2 VA 1.92TB Read Intensive NVMe PCIe 4.0 x4 HS SSD	Y	Y	Y	Y	N	Y	Y	N	N	N	N	N	Y	N	N	N
4XB7A93893	ThinkSystem 2.5" U.2 VA 3.84TB Read Intensive NVMe PCIe 4.0 x4 HS SSD	Y	Y	Y	Y	N	Y	Y	N	N	N	N	N	Y	N	N	N
4XB7A93894	ThinkSystem 2.5" U.2 VA 7.68TB Read Intensive NVMe PCIe 4.0 x4 HS SSD	Y	Y	Y	Y	N	Y	Y	N	N	N	N	N	Y	N	N	N
4XB7A93895	ThinkSystem 2.5" U.2 VA 15.36TB Read Intensive NVMe PCIe 4.0 x4 HS SSD	Y	Y	Y	Y	N	Y	Y	N	N	N	N	N	Y	N	N	N
3.5-inch hot-swap drives with PCIe 5.0 interface																	
4XB7B13984	ThinkSystem 3.5" U.2 VA 1.92TB Read Intensive NVMe PCIe 5.0 x4 HS SSD	N	Y	N	Y	N	N	Y	N	Y	N	N	N	N	N	N	N
4XB7B13985	ThinkSystem 3.5" U.2 VA 3.84TB Read Intensive NVMe PCIe 5.0 x4 HS SSD	N	Y	N	Y	N	N	Y	N	Y	N	N	N	N	N	N	N
4XB7B13986	ThinkSystem 3.5" U.2 VA 7.68TB Read Intensive NVMe PCIe 5.0 x4 HS SSD	N	Y	N	Y	N	N	Y	N	Y	N	N	N	N	N	N	N
4XB7B13987	ThinkSystem 3.5" U.2 VA 15.36TB Read Intensive NVMe PCIe 5.0 x4 HS SSD	N	Y	N	Y	N	N	Y	N	Y	N	N	N	N	N	N	N

Part Number	Description	AMD V3				2S Intel V3/V4						Multi Node V3		1S V3			
		SR635 V3 (7D9H / 7D9G)	SR655 V3 (7D9F / 7D9E)	SR645 V3 (7D9D / 7D9C)	SR665 V3 (7D9B / 7D9A)	ST650 V3 (7D7B / 7D7A)	SR630 V3 (7D72 / 7D73)	SR650 V3 (7D75 / 7D76)	SR630 V4 (7DG8 / 7DG9)	SR650 V4 (7DGC / 7DGD)	SR650a V4 (7DGC / 7DGD)	SD535 V3 (7DD8 / 7DD1)	SD530 V3 (7DDA / 7DD3)	SD550 V3 (7DD9 / 7DD2)	ST45 V3 (7DH4 / 7DH5)	ST50 V3 (7DF4 / 7DF3)	ST250 V3 (7DCF / 7DCE)
E3.S 1T hot-swap drives with PCIe 5.0 interface																	
4XB7A93131	ThinkSystem E3.S 1T VA 1.92TB Read Intensive NVMe PCIe 5.0 x4 HS SSD v2	N	N	N	N	N	N	N	Y	Y	Y	N	Y	N	N	N	N
4XB7A93132	ThinkSystem E3.S 1T VA 3.84TB Read Intensive NVMe PCIe 5.0 x4 HS SSD v2	N	N	N	N	N	N	N	Y	Y	Y	N	Y	N	N	N	N
4XB7A93133	ThinkSystem E3.S 1T VA 7.68TB Read Intensive NVMe PCIe 5.0 x4 HS SSD v2	N	N	N	N	N	N	N	Y	Y	Y	N	Y	N	N	N	N
4XB7A93134	ThinkSystem E3.S 1T VA 15.36TB Read Intensive NVMe PCIe 5.0 x4 HS SSD v2	N	N	N	N	N	N	N	Y	Y	Y	N	Y	N	N	N	N
15mm trayless (non-hot-swap) drives with PCIe 4.0 interface																	
4XB7B09657	ThinkSystem 2.5" 15mm VA 1.92TB Read Intensive NVMe PCIe 4.0 x4 Trayless SSD	N	N	N	N	N	N	N	N	N	N	N	N	N	N	N	N
4XB7B09658	ThinkSystem 2.5" 15mm VA 3.84TB Read Intensive NVMe PCIe 4.0 x4 Trayless SSD	N	N	N	N	N	N	N	N	N	N	N	N	N	N	N	N
4XB7B09659	ThinkSystem 2.5" 15mm VA 7.68TB Read Intensive NVMe PCIe 4.0 x4 Trayless SSD	N	N	N	N	N	N	N	N	N	N	N	N	N	N	N	N
7mm trayless (non-hot-swap) drives with PCIe 4.0 interface																	
4XB7B09654	ThinkSystem 2.5" 7mm VA 960GB Read Intensive NVMe PCIe 4.0 x4 Trayless SSD	N	N	N	N	N	N	N	N	N	N	N	N	N	N	N	N
4XB7B09655	ThinkSystem 2.5" 7mm VA 1.92TB Read Intensive NVMe PCIe 4.0 x4 Trayless SSD	N	N	N	N	N	N	N	N	N	N	N	N	N	N	N	N
4XB7B09656	ThinkSystem 2.5" 7mm VA 3.84TB Read Intensive NVMe PCIe 4.0 x4 Trayless SSD	N	N	N	N	N	N	N	N	N	N	N	N	N	N	N	N
E3.S 1T trayless (non-hot-swap) drives with PCIe 5.0 interface																	
4XB7B12180	ThinkSystem E3.S 1T VA 1.92TB Read Intensive NVMe PCIe 5.0 x4 Trayless SSD	N	N	N	N	N	N	N	N	N	N	N	N	N	N	N	N
4XB7B12181	ThinkSystem E3.S 1T VA 3.84TB Read Intensive NVMe PCIe 5.0 x4 Trayless SSD	N	N	N	N	N	N	N	N	N	N	N	N	N	N	N	N
4XB7B12182	ThinkSystem E3.S 1T VA 7.68TB Read Intensive NVMe PCIe 5.0 x4 Trayless SSD	N	N	N	N	N	N	N	N	N	N	N	N	N	N	N	N
4XB7B12183	ThinkSystem E3.S 1T VA 15.36TB Read Intensive NVMe PCIe 5.0 x4 Trayless SSD	N	N	N	N	N	N	N	N	N	N	N	N	N	N	N	N
M.2 drives with PCIe 4.0 interface - not for B550 or B350 M.2 adapters																	
4XB7B09650	ThinkSystem M.2 VA 480GB Read Intensive NVMe PCIe 4.0 x4 NHS SSD	Y	Y	Y	Y	Y	Y	Y	N	Y	N	Y	N	N	N	N	N
4XB7B09651	ThinkSystem M.2 VA 960GB Read Intensive NVMe PCIe 4.0 x4 NHS SSD	N	N	N	N	N	N	N	N	N	N	N	N	N	N	N	N

Part Number	Description	AMD V3				2S Intel V3/V4					Multi Node V3		1S V3				
		SR635 V3 (7D9H / 7D9G)	SR655 V3 (7D9F / 7D9E)	SR645 V3 (7D9D / 7D9C)	SR665 V3 (7D9B / 7D9A)	ST650 V3 (7D7B / 7D7A)	SR630 V3 (7D72 / 7D73)	SR650 V3 (7D75 / 7D76)	SR630 V4 (7DG8 / 7DG9)	SR650 V4 (7DGC / 7DGD)	SR650a V4 (7DGC / 7DGD)	SD535 V3 (7DD8 / 7DD1)	SD530 V3 (7DDA / 7DD3)	SD550 V3 (7DD9 / 7DD2)	ST45 V3 (7DH4 / 7DH5)	ST50 V3 (7DF4 / 7DF3)	ST250 V3 (7DCF / 7DCE)
4XB7B09652	ThinkSystem M.2 VA 1.92TB Read Intensive NVMe PCIe 4.0 x4 NHS SSD	N	N	N	N	N	N	N	N	N	Y	N	N	N	N	N	N
4XB7B09653	ThinkSystem M.2 VA 3.84TB Read Intensive NVMe PCIe 4.0 x4 NHS SSD	N	N	N	N	N	N	N	N	N	N	N	N	N	N	N	N
M.2 drives with PCIe 4.0 interface - only for B550i or B350i internal M.2 adapters																	
4XB7A93140	ThinkSystem M.2 VA 480GB Read Intensive NVMe NHS SSD	N	N	N	N	N	N	N	Y	Y	Y	N	N	N	N	N	N
4XB7A93141	ThinkSystem M.2 VA 960GB Read Intensive NVMe NHS SSD	N	N	N	N	N	N	N	Y	Y	Y	N	N	N	N	N	N
4XB7A93142	ThinkSystem M.2 VA 1.92TB Read Intensive NVMe NHS SSD	N	N	N	N	N	N	N	Y	Y	Y	N	N	N	N	N	N
M.2 drives with PCIe 4.0 interface - only for B550p or B550d hot-swap M.2 adapters																	
4XB7B14665	ThinkSystem M.2 VA 480GB Read Intensive NVMe HS SSD	N	N	N	N	N	N	N	Y	Y	Y	N	N	N	N	N	N
4XB7B14666	ThinkSystem M.2 VA 960GB Read Intensive NVMe HS SSD	N	N	N	N	N	N	N	Y	Y	Y	N	N	N	N	N	N
4XB7B14667	ThinkSystem M.2 VA 1.92TB Read Intensive NVMe HS SSD	N	N	N	N	N	N	N	Y	Y	Y	N	N	N	N	N	N

Table 5. Server support (Part 2 of 5)

Part Number	Description	4S 8S Intel V3/V4					GPU Rich					Edge						
		SR650 V3 (7D97 / 7D96)	SR660 V3 (7D94 / 7D93)	SR950 V3 (7DC5 / 7DC4)	SR850 V4 (7DJT / 7DJS)	SR860 V4 (7DJQ / 7DJN)	SR670 V2 (7Z22 / 7Z23)	SR675 V3 (7D9Q / 7D9R)	SR680a V3 (7DHE)	SR680a V3 B200 (7DM9)	SR685a V3 (7DHC)	SR780a V3 (7DJ5)	SR680a V4 (7DMK)	SE100 (7DGR)	SE350 (7Z46 / 7D1X)	SE350 V2 (7DA9)	SE360 V2 (7DAM)	SE450 (7D8T)
2.5-inch hot-swap drives with PCIe 5.0 interface																		
4XB7B11683	ThinkSystem 2.5" U.2 VA 960GB Read Intensive NVMe PCIe 4.0 x4 HS SSD	Y	Y	N	N	N	N	Y	N	N	N	N	N	N	N	N	Y	Y
4XB7A93122	ThinkSystem 2.5" U.2 VA 1.92TB Read Intensive NVMe PCIe 5.0 x4 HS SSD	Y	Y	N	Y	Y	N	Y	N	N	N	N	N	N	N	N	N	N

Part Number	Description	4S 8S Intel V3/V4					GPU Rich					Edge							
		SR850 V3 (7D97 / 7D96)	SR860 V3 (7D94 / 7D93)	SR950 V3 (7DC5 / 7DC4)	SR850 V4 (7DJT / 7DJS)	SR860 V4 (7DJQ / 7DJN)	SR670 V2 (7Z22 / 7Z23)	SR675 V3 (7D9Q / 7D9R)	SR680a V3 (7DHE)	SR680a V3 B200 (7DM9)	SR685a V3 (7DHC)	SR780a V3 (7DJ5)	SR680a V4 (7DMK)	SE100 (7DGR)	SE350 (7Z46 / 7D1X)	SE350 V2 (7DA9)	SE360 V2 (7DAM)	SE450 (7D8T)	SE455 V3 (7DBY)
4XB7A93123	ThinkSystem 2.5" U.2 VA 3.84TB Read Intensive NVMe PCIe 5.0 x4 HS SSD	Y	Y	N	Y	Y	N	Y	N	N	N	N	N	N	N	N	N	N	N
4XB7A93124	ThinkSystem 2.5" U.2 VA 7.68TB Read Intensive NVMe PCIe 5.0 x4 HS SSD	Y	Y	N	Y	Y	N	Y	N	N	N	N	N	N	N	N	N	N	N
4XB7A93125	ThinkSystem 2.5" U.2 VA 15.36TB Read Intensive NVMe PCIe 5.0 x4 HS SSD	Y	Y	N	Y	Y	N	Y	N	N	N	N	N	N	N	N	N	N	N
4XB7A93126	ThinkSystem 2.5" U.2 VA 30.72TB Read Intensive NVMe PCIe 5.0 x4 HS SSD	Y	Y	N	Y	Y	N	Y	N	N	N	N	N	N	Y	N	Y	Y	Y
2.5-inch hot-swap drives with PCIe 4.0 interface																			
4XB7A93892	ThinkSystem 2.5" U.2 VA 1.92TB Read Intensive NVMe PCIe 4.0 x4 HS SSD	Y	Y	N	N	N	Y	Y	N	N	N	N	N	N	N	N	Y	Y	Y
4XB7A93893	ThinkSystem 2.5" U.2 VA 3.84TB Read Intensive NVMe PCIe 4.0 x4 HS SSD	Y	Y	N	N	N	Y	Y	N	N	N	N	N	N	N	N	Y	Y	Y
4XB7A93894	ThinkSystem 2.5" U.2 VA 7.68TB Read Intensive NVMe PCIe 4.0 x4 HS SSD	Y	Y	N	N	N	Y	Y	N	N	N	N	N	N	N	N	N	Y	Y
4XB7A93895	ThinkSystem 2.5" U.2 VA 15.36TB Read Intensive NVMe PCIe 4.0 x4 HS SSD	Y	Y	N	N	N	Y	Y	N	N	N	N	N	N	N	N	N	Y	Y
3.5-inch hot-swap drives with PCIe 5.0 interface																			
4XB7B13984	ThinkSystem 3.5" U.2 VA 1.92TB Read Intensive NVMe PCIe 5.0 x4 HS SSD	N	N	N	N	N	N	N	N	N	N	N	N	N	N	N	N	N	N
4XB7B13985	ThinkSystem 3.5" U.2 VA 3.84TB Read Intensive NVMe PCIe 5.0 x4 HS SSD	N	N	N	N	N	N	N	N	N	N	N	N	N	N	N	N	N	N
4XB7B13986	ThinkSystem 3.5" U.2 VA 7.68TB Read Intensive NVMe PCIe 5.0 x4 HS SSD	N	N	N	N	N	N	N	N	N	N	N	N	N	N	N	N	N	N
4XB7B13987	ThinkSystem 3.5" U.2 VA 15.36TB Read Intensive NVMe PCIe 5.0 x4 HS SSD	N	N	N	N	N	N	N	N	N	N	N	N	N	N	N	N	N	N
E3.S 1T hot-swap drives with PCIe 5.0 interface																			
4XB7A93131	ThinkSystem E3.S 1T VA 1.92TB Read Intensive NVMe PCIe 5.0 x4 HS SSD v2	N	N	Y	Y	Y	N	Y	N	N	N	N	N	N	N	N	N	N	N
4XB7A93132	ThinkSystem E3.S 1T VA 3.84TB Read Intensive NVMe PCIe 5.0 x4 HS SSD v2	N	N	Y	Y	Y	N	Y	N	N	N	N	N	N	N	N	N	N	N
4XB7A93133	ThinkSystem E3.S 1T VA 7.68TB Read Intensive NVMe PCIe 5.0 x4 HS SSD v2	N	N	Y	Y	Y	N	Y	N	N	N	N	N	N	N	N	N	N	N
4XB7A93134	ThinkSystem E3.S 1T VA 15.36TB Read Intensive NVMe PCIe 5.0 x4 HS SSD v2	N	N	Y	Y	Y	N	Y	N	N	N	N	N	N	N	N	N	N	N
15mm trayless (non-hot-swap) drives with PCIe 4.0 interface																			
4XB7B09657	ThinkSystem 2.5" 15mm VA 1.92TB Read Intensive NVMe PCIe 4.0 x4 Trayless SSD	N	N	N	N	N	N	N	N	N	N	N	N	N	N	N	Y	N	N

Part Number	Description	4S 8S Intel V3/V4					GPU Rich					Edge							
		SR850 V3 (7D97 / 7D96)	SR860 V3 (7D94 / 7D93)	SR950 V3 (7DC5 / 7DC4)	SR850 V4 (7DJT / 7DJS)	SR860 V4 (7DJQ / 7DJN)	SR670 V2 (7Z22 / 7Z23)	SR675 V3 (7D9Q / 7D9R)	SR680a V3 (7DHE)	SR680a V3 B200 (7DM9)	SR685a V3 (7DHC)	SR780a V3 (7DJ5)	SR680a V4 (7DMK)	SE100 (7DGR)	SE350 (7Z46 / 7D1X)	SE350 V2 (7DA9)	SE360 V2 (7DAM)	SE450 (7D8T)	SE455 V3 (7DBY)
4XB7B09658	ThinkSystem 2.5" 15mm VA 3.84TB Read Intensive NVMe PCIe 4.0 x4 Trayless SSD	N	N	N	N	N	N	N	N	N	N	N	N	N	N	N	Y	N	
4XB7B09659	ThinkSystem 2.5" 15mm VA 7.68TB Read Intensive NVMe PCIe 4.0 x4 Trayless SSD	N	N	N	N	N	N	N	N	N	N	N	N	N	N	N	Y	N	
7mm trayless (non-hot-swap) drives with PCIe 4.0 interface																			
4XB7B09654	ThinkSystem 2.5" 7mm VA 960GB Read Intensive NVMe PCIe 4.0 x4 Trayless SSD	N	N	N	N	N	N	N	N	N	N	N	N	N	N	N	Y	N	
4XB7B09655	ThinkSystem 2.5" 7mm VA 1.92TB Read Intensive NVMe PCIe 4.0 x4 Trayless SSD	N	N	N	N	N	N	N	N	N	N	N	N	N	N	N	Y	N	
4XB7B09656	ThinkSystem 2.5" 7mm VA 3.84TB Read Intensive NVMe PCIe 4.0 x4 Trayless SSD	N	N	N	N	N	N	N	N	N	N	N	N	N	N	N	Y	N	
E3.S 1T trayless (non-hot-swap) drives with PCIe 5.0 interface																			
4XB7B12180	ThinkSystem E3.S 1T VA 1.92TB Read Intensive NVMe PCIe 5.0 x4 Trayless SSD	N	N	N	N	N	N	N	N	N	N	N	N	N	N	N	N	N	
4XB7B12181	ThinkSystem E3.S 1T VA 3.84TB Read Intensive NVMe PCIe 5.0 x4 Trayless SSD	N	N	N	N	N	N	N	N	N	N	N	N	N	N	N	N	N	
4XB7B12182	ThinkSystem E3.S 1T VA 7.68TB Read Intensive NVMe PCIe 5.0 x4 Trayless SSD	N	N	N	N	N	N	N	N	N	N	N	N	N	N	N	N	N	
4XB7B12183	ThinkSystem E3.S 1T VA 15.36TB Read Intensive NVMe PCIe 5.0 x4 Trayless SSD	N	N	N	N	N	N	N	N	N	N	N	N	N	N	N	N	N	
M.2 drives with PCIe 4.0 interface - not for B550 or B350 M.2 adapters																			
4XB7B09650	ThinkSystem M.2 VA 480GB Read Intensive NVMe PCIe 4.0 x4 NHS SSD	Y	Y	Y	N	N	N	Y	N	N	N	N	N	Y	N	N	N	Y	Y
4XB7B09651	ThinkSystem M.2 VA 960GB Read Intensive NVMe PCIe 4.0 x4 NHS SSD	N	N	N	N	N	N	Y	N	N	N	N	N	N	N	N	N	N	N
4XB7B09652	ThinkSystem M.2 VA 1.92TB Read Intensive NVMe PCIe 4.0 x4 NHS SSD	N	N	N	N	N	N	Y	N	N	N	N	N	Y	N	N	N	Y	Y
4XB7B09653	ThinkSystem M.2 VA 3.84TB Read Intensive NVMe PCIe 4.0 x4 NHS SSD	N	N	N	N	N	N	N	N	N	N	N	N	Y	N	N	N	Y	Y
M.2 drives with PCIe 4.0 interface - only for B550i or B350i internal M.2 adapters																			
4XB7A93140	ThinkSystem M.2 VA 480GB Read Intensive NVMe NHS SSD	N	N	N	Y	Y	N	N	N	N	N	N	N	N	N	N	N	N	N
4XB7A93141	ThinkSystem M.2 VA 960GB Read Intensive NVMe NHS SSD	N	N	N	Y	Y	N	N	N	N	N	N	Y	N	N	N	N	N	N
4XB7A93142	ThinkSystem M.2 VA 1.92TB Read Intensive NVMe NHS SSD	N	N	N	Y	Y	N	N	N	N	N	N	Y	N	N	N	N	N	N
M.2 drives with PCIe 4.0 interface - only for B550p or B550d hot-swap M.2 adapters																			

Part Number	Description	4S 8S Intel V3/V4					GPU Rich					Edge						
		SR850 V3 (7D97 / 7D96)	SR860 V3 (7D94 / 7D93)	SR950 V3 (7DC5 / 7DC4)	SR850 V4 (7DJT / 7DJS)	SR860 V4 (7DJQ / 7DJN)	SR670 V2 (7Z22 / 7Z23)	SR675 V3 (7D9Q / 7D9R)	SR680a V3 (7DHE)	SR680a V3 B200 (7DM9)	SR685a V3 (7DHC)	SR780a V3 (7DJ5)	SR680a V4 (7DMK)	SE100 (7DGR)	SE350 (7Z46 / 7D1X)	SE350 V2 (7DA9)	SE360 V2 (7DAM)	SE450 (7D8T)
4XB7B14665	ThinkSystem M.2 VA 480GB Read Intensive NVMe HS SSD	N	N	N	Y	Y	N	N	N	N	N	N	N	N	N	N	N	N
4XB7B14666	ThinkSystem M.2 VA 960GB Read Intensive NVMe HS SSD	N	N	N	Y	Y	N	N	N	N	N	Y	N	N	N	N	N	N
4XB7B14667	ThinkSystem M.2 VA 1.92TB Read Intensive NVMe HS SSD	N	N	N	Y	Y	N	N	N	N	N	Y	N	N	N	N	N	N

Table 6. Server support (Part 3 of 5)

Part Number	Description	Super Computing					1S Intel V2		2S Intel V2		AMD V1						
		SC750 V4 (7DDJ)	SC777 V4 (7DKA)	SD665 V3 (7D9P)	SD665-N V3 (7DAZ)	SD650 V3 (7D7M)	SD650-1 V3 (7D7L)	SD650-N V3 (7D7N)	ST50 V2 (7D8K / 7D8J)	ST250 V2 (7D8G / 7D8F)	SR250 V2 (7D7R / 7D7Q)	ST650 V2 (7Z75 / 7Z74)	SR630 V2 (7Z70 / 7Z71)	SR650 V2 (7Z72 / 7Z73)	SR635 (7Y98 / 7Y99)	SR655 (7Y00 / 7Z01)	SR645 (7D2Y / 7D2X)
2.5-inch hot-swap drives with PCIe 5.0 interface																	
4XB7B11683	ThinkSystem 2.5" U.2 VA 960GB Read Intensive NVMe PCIe 4.0 x4 HS SSD	N	N	N	N	N	N	N	N	N	N	N	N	N	N	Y	Y
4XB7A93122	ThinkSystem 2.5" U.2 VA 1.92TB Read Intensive NVMe PCIe 5.0 x4 HS SSD	N	N	N	N	N	N	N	N	N	N	N	N	N	N	N	N
4XB7A93123	ThinkSystem 2.5" U.2 VA 3.84TB Read Intensive NVMe PCIe 5.0 x4 HS SSD	N	N	N	N	N	N	N	N	N	N	N	N	N	N	N	N
4XB7A93124	ThinkSystem 2.5" U.2 VA 7.68TB Read Intensive NVMe PCIe 5.0 x4 HS SSD	N	N	N	N	N	N	N	N	N	N	N	N	N	N	N	N
4XB7A93125	ThinkSystem 2.5" U.2 VA 15.36TB Read Intensive NVMe PCIe 5.0 x4 HS SSD	N	N	N	N	N	N	N	N	N	N	N	N	N	N	N	N
4XB7A93126	ThinkSystem 2.5" U.2 VA 30.72TB Read Intensive NVMe PCIe 5.0 x4 HS SSD	N	N	N	N	N	N	N	N	N	N	N	N	N	N	N	N
2.5-inch hot-swap drives with PCIe 4.0 interface																	
4XB7A93892	ThinkSystem 2.5" U.2 VA 1.92TB Read Intensive NVMe PCIe 4.0 x4 HS SSD	N	N	N	N	N	N	N	N	N	Y	Y	Y	N	N	Y	Y
4XB7A93893	ThinkSystem 2.5" U.2 VA 3.84TB Read Intensive NVMe PCIe 4.0 x4 HS SSD	N	N	N	N	N	N	N	N	N	Y	Y	Y	N	N	Y	Y

Part Number	Description	Super Computing						1S Intel V2		2S Intel V2			AMD V1				
		SC750 V4 (7DDJ)	SC777 V4 (7DKA)	SD665 V3 (7D9P)	SD665-N V3 (7DAZ)	SD650 V3 (7D7M)	SD650-I V3 (7D7L)	SD650-N V3 (7D7N)	ST50 V2 (7D8K / 7D8J)	ST250 V2 (7D8G / 7D8F)	SR250 V2 (7D7R / 7D7Q)	ST650 V2 (7Z75 / 7Z74)	SR630 V2 (7Z70 / 7Z71)	SR650 V2 (7Z72 / 7Z73)	SR635 (7Y98 / 7Y99)	SR655 (7Y00 / 7Z01)	SR645 (7D2Y / 7D2X)
4XB7A93894	ThinkSystem 2.5" U.2 VA 7.68TB Read Intensive NVMe PCIe 4.0 x4 HS SSD	N	N	N	N	N	N	N	N	N	Y	Y	Y	N	N	Y	Y
4XB7A93895	ThinkSystem 2.5" U.2 VA 15.36TB Read Intensive NVMe PCIe 4.0 x4 HS SSD	N	N	N	N	N	N	N	N	N	Y	Y	Y	N	N	Y	Y
3.5-inch hot-swap drives with PCIe 5.0 interface																	
4XB7B13984	ThinkSystem 3.5" U.2 VA 1.92TB Read Intensive NVMe PCIe 5.0 x4 HS SSD	N	N	N	N	N	N	N	N	N	N	N	N	N	N	N	N
4XB7B13985	ThinkSystem 3.5" U.2 VA 3.84TB Read Intensive NVMe PCIe 5.0 x4 HS SSD	N	N	N	N	N	N	N	N	N	N	N	N	N	N	N	N
4XB7B13986	ThinkSystem 3.5" U.2 VA 7.68TB Read Intensive NVMe PCIe 5.0 x4 HS SSD	N	N	N	N	N	N	N	N	N	N	N	N	N	N	N	N
4XB7B13987	ThinkSystem 3.5" U.2 VA 15.36TB Read Intensive NVMe PCIe 5.0 x4 HS SSD	N	N	N	N	N	N	N	N	N	N	N	N	N	N	N	N
E3.S 1T hot-swap drives with PCIe 5.0 interface																	
4XB7A93131	ThinkSystem E3.S 1T VA 1.92TB Read Intensive NVMe PCIe 5.0 x4 HS SSD v2	N	N	N	N	N	N	N	N	N	N	N	N	N	N	N	N
4XB7A93132	ThinkSystem E3.S 1T VA 3.84TB Read Intensive NVMe PCIe 5.0 x4 HS SSD v2	N	N	N	N	N	N	N	N	N	N	N	N	N	N	N	N
4XB7A93133	ThinkSystem E3.S 1T VA 7.68TB Read Intensive NVMe PCIe 5.0 x4 HS SSD v2	N	N	N	N	N	N	N	N	N	N	N	N	N	N	N	N
4XB7A93134	ThinkSystem E3.S 1T VA 15.36TB Read Intensive NVMe PCIe 5.0 x4 HS SSD v2	N	N	N	N	N	N	N	N	N	N	N	N	N	N	N	N
15mm trayless (non-hot-swap) drives with PCIe 4.0 interface																	
4XB7B09657	ThinkSystem 2.5" 15mm VA 1.92TB Read Intensive NVMe PCIe 4.0 x4 Trayless SSD	N	N	Y	Y	Y	N	Y	N	N	N	N	N	N	N	N	N
4XB7B09658	ThinkSystem 2.5" 15mm VA 3.84TB Read Intensive NVMe PCIe 4.0 x4 Trayless SSD	N	N	Y	Y	Y	N	Y	N	N	N	N	N	N	N	N	N
4XB7B09659	ThinkSystem 2.5" 15mm VA 7.68TB Read Intensive NVMe PCIe 4.0 x4 Trayless SSD	N	N	Y	Y	Y	N	Y	N	N	N	N	N	N	N	N	N
7mm trayless (non-hot-swap) drives with PCIe 4.0 interface																	
4XB7B09654	ThinkSystem 2.5" 7mm VA 960GB Read Intensive NVMe PCIe 4.0 x4 Trayless SSD	N	N	Y	Y	Y	N	Y	N	N	N	N	N	N	N	N	N
4XB7B09655	ThinkSystem 2.5" 7mm VA 1.92TB Read Intensive NVMe PCIe 4.0 x4 Trayless SSD	N	N	Y	Y	Y	N	Y	N	N	N	N	N	N	N	N	N
4XB7B09656	ThinkSystem 2.5" 7mm VA 3.84TB Read Intensive NVMe PCIe 4.0 x4 Trayless SSD	N	N	Y	Y	Y	N	Y	N	N	N	N	N	N	N	N	N
E3.S 1T trayless (non-hot-swap) drives with PCIe 5.0 interface																	

Part Number	Description	Super Computing						1S Intel V2		2S Intel V2			AMD V1					
		SC750 V4 (7DDJ)	SC777 V4 (7DKA)	SD665 V3 (7D9P)	SD665-N V3 (7DAZ)	SD650 V3 (7D7M)	SD650-I V3 (7D7L)	SD650-N V3 (7D7N)	ST50 V2 (7D8K / 7D8J)	ST250 V2 (7D8G / 7D8F)	SR250 V2 (7D7R / 7D7Q)	ST650 V2 (7Z75 / 7Z74)	SR630 V2 (7Z70 / 7Z71)	SR650 V2 (7Z72 / 7Z73)	SR635 (7Y98 / 7Y99)	SR655 (7Y00 / 7Z01)	SR645 (7D2Y / 7D2X)	SR665 (7D2W / 7D2V)
4XB7B12180	ThinkSystem E3.S 1T VA 1.92TB Read Intensive NVMe PCIe 5.0 x4 Trayless SSD	Y	Y	Y	N	N	N	N	N	N	N	N	N	N	N	N	N	N
4XB7B12181	ThinkSystem E3.S 1T VA 3.84TB Read Intensive NVMe PCIe 5.0 x4 Trayless SSD	Y	Y	Y	N	N	N	N	N	N	N	N	N	N	N	N	N	N
4XB7B12182	ThinkSystem E3.S 1T VA 7.68TB Read Intensive NVMe PCIe 5.0 x4 Trayless SSD	Y	Y	Y	N	N	N	N	N	N	N	N	N	N	N	N	N	N
4XB7B12183	ThinkSystem E3.S 1T VA 15.36TB Read Intensive NVMe PCIe 5.0 x4 Trayless SSD	Y	Y	Y	N	N	N	N	N	N	N	N	N	N	N	N	N	N
M.2 drives with PCIe 4.0 interface - not for B550 or B350 M.2 adapters																		
4XB7B09650	ThinkSystem M.2 VA 480GB Read Intensive NVMe PCIe 4.0 x4 NHS SSD	N	N	N	N	N	N	N	N	N	N	N	N	N	N	N	Y	Y
4XB7B09651	ThinkSystem M.2 VA 960GB Read Intensive NVMe PCIe 4.0 x4 NHS SSD	N	N	N	Y	Y	N	Y	N	N	N	N	N	N	N	N	Y	Y
4XB7B09652	ThinkSystem M.2 VA 1.92TB Read Intensive NVMe PCIe 4.0 x4 NHS SSD	N	N	Y	Y	Y	N	Y	N	N	N	N	N	N	N	N	Y	Y
4XB7B09653	ThinkSystem M.2 VA 3.84TB Read Intensive NVMe PCIe 4.0 x4 NHS SSD	N	N	N	N	N	N	N	N	N	N	N	N	N	N	N	Y	Y
M.2 drives with PCIe 4.0 interface - only for B550i or B350i internal M.2 adapters																		
4XB7A93140	ThinkSystem M.2 VA 480GB Read Intensive NVMe NHS SSD	N	N	N	N	N	N	N	N	N	N	N	N	N	N	N	N	N
4XB7A93141	ThinkSystem M.2 VA 960GB Read Intensive NVMe NHS SSD	N	N	N	N	N	N	N	N	N	N	N	N	N	N	N	N	N
4XB7A93142	ThinkSystem M.2 VA 1.92TB Read Intensive NVMe NHS SSD	N	N	N	N	N	N	N	N	N	N	N	N	N	N	N	N	N
M.2 drives with PCIe 4.0 interface - only for B550p or B550d hot-swap M.2 adapters																		
4XB7B14665	ThinkSystem M.2 VA 480GB Read Intensive NVMe HS SSD	N	N	N	N	N	N	N	N	N	N	N	N	N	N	N	N	N
4XB7B14666	ThinkSystem M.2 VA 960GB Read Intensive NVMe HS SSD	N	N	N	N	N	N	N	N	N	N	N	N	N	N	N	N	N
4XB7B14667	ThinkSystem M.2 VA 1.92TB Read Intensive NVMe HS SSD	N	N	N	N	N	N	N	N	N	N	N	N	N	N	N	N	N

Table 7. Server support (Part 4 of 5)

Part Number	Description	Dense V2				4S V2		8S	4S V1		1S Intel V1				
		SD630 V2 (7D1K)	SD650 V2 (7D1M)	SD650-N V2 (7D1N)	SN650 V2 (7Z69)	SR850 V2 (7D31 / 7D32)	SR860 V2 (7Z59 / 7Z60)	SR950 (7X11 / 7X12)	SR850 (7X18 / 7X19)	SR850P (7D2F / 2D2G)	SR860 (7X69 / 7X70)	ST50 (7Y48 / 7Y50)	ST250 (7Y45 / 7Y46)	SR150 (7Y54)	SR250 (7Y52 / 7Y51)
2.5-inch hot-swap drives with PCIe 5.0 interface															
4XB7B11683	ThinkSystem 2.5" U.2 VA 960GB Read Intensive NVMe PCIe 4.0 x4 HS SSD	N	N	N	N	N	N	N	N	N	N	N	N	N	N
4XB7A93122	ThinkSystem 2.5" U.2 VA 1.92TB Read Intensive NVMe PCIe 5.0 x4 HS SSD	N	N	N	N	N	N	N	N	N	N	N	N	N	N
4XB7A93123	ThinkSystem 2.5" U.2 VA 3.84TB Read Intensive NVMe PCIe 5.0 x4 HS SSD	N	N	N	N	N	N	N	N	N	N	N	N	N	N
4XB7A93124	ThinkSystem 2.5" U.2 VA 7.68TB Read Intensive NVMe PCIe 5.0 x4 HS SSD	N	N	N	N	N	N	N	N	N	N	N	N	N	N
4XB7A93125	ThinkSystem 2.5" U.2 VA 15.36TB Read Intensive NVMe PCIe 5.0 x4 HS SSD	N	N	N	N	N	N	N	N	N	N	N	N	N	N
4XB7A93126	ThinkSystem 2.5" U.2 VA 30.72TB Read Intensive NVMe PCIe 5.0 x4 HS SSD	N	N	N	N	N	N	N	N	N	N	N	N	N	N
2.5-inch hot-swap drives with PCIe 4.0 interface															
4XB7A93892	ThinkSystem 2.5" U.2 VA 1.92TB Read Intensive NVMe PCIe 4.0 x4 HS SSD	N	N	N	N	Y	Y	N	N	N	N	N	N	N	N
4XB7A93893	ThinkSystem 2.5" U.2 VA 3.84TB Read Intensive NVMe PCIe 4.0 x4 HS SSD	N	N	N	N	Y	Y	N	N	N	N	N	N	N	N
4XB7A93894	ThinkSystem 2.5" U.2 VA 7.68TB Read Intensive NVMe PCIe 4.0 x4 HS SSD	N	N	N	N	Y	Y	N	N	N	N	N	N	N	N
4XB7A93895	ThinkSystem 2.5" U.2 VA 15.36TB Read Intensive NVMe PCIe 4.0 x4 HS SSD	N	N	N	N	Y	Y	N	N	N	N	N	N	N	N
3.5-inch hot-swap drives with PCIe 5.0 interface															
4XB7B13984	ThinkSystem 3.5" U.2 VA 1.92TB Read Intensive NVMe PCIe 5.0 x4 HS SSD	N	N	N	N	N	N	N	N	N	N	N	N	N	N
4XB7B13985	ThinkSystem 3.5" U.2 VA 3.84TB Read Intensive NVMe PCIe 5.0 x4 HS SSD	N	N	N	N	N	N	N	N	N	N	N	N	N	N
4XB7B13986	ThinkSystem 3.5" U.2 VA 7.68TB Read Intensive NVMe PCIe 5.0 x4 HS SSD	N	N	N	N	N	N	N	N	N	N	N	N	N	N
4XB7B13987	ThinkSystem 3.5" U.2 VA 15.36TB Read Intensive NVMe PCIe 5.0 x4 HS SSD	N	N	N	N	N	N	N	N	N	N	N	N	N	N
E3.S 1T hot-swap drives with PCIe 5.0 interface															
4XB7A93131	ThinkSystem E3.S 1T VA 1.92TB Read Intensive NVMe PCIe 5.0 x4 HS SSD v2	N	N	N	N	N	N	N	N	N	N	N	N	N	N
4XB7A93132	ThinkSystem E3.S 1T VA 3.84TB Read Intensive NVMe PCIe 5.0 x4 HS SSD v2	N	N	N	N	N	N	N	N	N	N	N	N	N	N

Part Number	Description	Dense V2				4S V2	8S	4S V1			1S Intel V1				
		SD630 V2 (7D1K)	SD650 V2 (7D1M)	SD650-N V2 (7D1N)	SN650 V2 (7Z69)	SR650 V2 (7D31 / 7D32)	SR660 V2 (7Z59 / 7Z60)	SR950 (7X11 / 7X12)	SR850 (7X18 / 7X19)	SR850P (7D2F / 2D2G)	SR860 (7X69 / 7X70)	ST50 (7Y48 / 7Y50)	ST250 (7Y45 / 7Y46)	SR150 (7Y54)	SR250 (7Y52 / 7Y51)
4XB7A93133	ThinkSystem E3.S 1T VA 7.68TB Read Intensive NVMe PCIe 5.0 x4 HS SSD v2	N	N	N	N	N	N	N	N	N	N	N	N	N	N
4XB7A93134	ThinkSystem E3.S 1T VA 15.36TB Read Intensive NVMe PCIe 5.0 x4 HS SSD v2	N	N	N	N	N	N	N	N	N	N	N	N	N	N
15mm trayless (non-hot-swap) drives with PCIe 4.0 interface															
4XB7B09657	ThinkSystem 2.5" 15mm VA 1.92TB Read Intensive NVMe PCIe 4.0 x4 Trayless SSD	N	N	N	N	N	N	N	N	N	N	N	N	N	N
4XB7B09658	ThinkSystem 2.5" 15mm VA 3.84TB Read Intensive NVMe PCIe 4.0 x4 Trayless SSD	N	N	N	N	N	N	N	N	N	N	N	N	N	N
4XB7B09659	ThinkSystem 2.5" 15mm VA 7.68TB Read Intensive NVMe PCIe 4.0 x4 Trayless SSD	N	N	N	N	N	N	N	N	N	N	N	N	N	N
7mm trayless (non-hot-swap) drives with PCIe 4.0 interface															
4XB7B09654	ThinkSystem 2.5" 7mm VA 960GB Read Intensive NVMe PCIe 4.0 x4 Trayless SSD	N	N	N	N	N	N	N	N	N	N	N	N	N	N
4XB7B09655	ThinkSystem 2.5" 7mm VA 1.92TB Read Intensive NVMe PCIe 4.0 x4 Trayless SSD	N	N	N	N	N	N	N	N	N	N	N	N	N	N
4XB7B09656	ThinkSystem 2.5" 7mm VA 3.84TB Read Intensive NVMe PCIe 4.0 x4 Trayless SSD	N	N	N	N	N	N	N	N	N	N	N	N	N	N
E3.S 1T trayless (non-hot-swap) drives with PCIe 5.0 interface															
4XB7B12180	ThinkSystem E3.S 1T VA 1.92TB Read Intensive NVMe PCIe 5.0 x4 Trayless SSD	N	N	N	N	N	N	N	N	N	N	N	N	N	N
4XB7B12181	ThinkSystem E3.S 1T VA 3.84TB Read Intensive NVMe PCIe 5.0 x4 Trayless SSD	N	N	N	N	N	N	N	N	N	N	N	N	N	N
4XB7B12182	ThinkSystem E3.S 1T VA 7.68TB Read Intensive NVMe PCIe 5.0 x4 Trayless SSD	N	N	N	N	N	N	N	N	N	N	N	N	N	N
4XB7B12183	ThinkSystem E3.S 1T VA 15.36TB Read Intensive NVMe PCIe 5.0 x4 Trayless SSD	N	N	N	N	N	N	N	N	N	N	N	N	N	N
M.2 drives with PCIe 4.0 interface - not for B550 or B350 M.2 adapters															
4XB7B09650	ThinkSystem M.2 VA 480GB Read Intensive NVMe PCIe 4.0 x4 NHS SSD	N	N	N	N	N	N	N	N	N	N	N	N	N	N
4XB7B09651	ThinkSystem M.2 VA 960GB Read Intensive NVMe PCIe 4.0 x4 NHS SSD	N	N	N	N	N	N	N	N	N	N	N	N	N	N
4XB7B09652	ThinkSystem M.2 VA 1.92TB Read Intensive NVMe PCIe 4.0 x4 NHS SSD	N	N	N	N	N	N	N	N	N	N	N	N	N	N
4XB7B09653	ThinkSystem M.2 VA 3.84TB Read Intensive NVMe PCIe 4.0 x4 NHS SSD	N	N	N	N	N	N	N	N	N	N	N	N	N	N
M.2 drives with PCIe 4.0 interface - only for B550i or B350i internal M.2 adapters															

Part Number	Description	Dense V2				4S V2	8S	4S V1			1S Intel V1			
		SD630 V2 (7D1K)	SD650 V2 (7D1M)	SD650-N V2 (7D1N)	SN650 V2 (7Z69)	SR650 V2 (7D31 / 7D32)	SR660 V2 (7Z59 / 7Z60)	SR950 (7X11 / 7X12)	SR850 (7X18 / 7X19)	SR850P (7D2F / 2D2G)	SR860 (7X69 / 7X70)	ST50 (7Y48 / 7Y50)	ST250 (7Y45 / 7Y46)	SR150 (7Y54)
4XB7A93140	ThinkSystem M.2 VA 480GB Read Intensive NVMe NHS SSD	N	N	N	N	N	N	N	N	N	N	N	N	N
4XB7A93141	ThinkSystem M.2 VA 960GB Read Intensive NVMe NHS SSD	N	N	N	N	N	N	N	N	N	N	N	N	N
4XB7A93142	ThinkSystem M.2 VA 1.92TB Read Intensive NVMe NHS SSD	N	N	N	N	N	N	N	N	N	N	N	N	N
M.2 drives with PCIe 4.0 interface - only for B550p or B550d hot-swap M.2 adapters														
4XB7B14665	ThinkSystem M.2 VA 480GB Read Intensive NVMe HS SSD	N	N	N	N	N	N	N	N	N	N	N	N	N
4XB7B14666	ThinkSystem M.2 VA 960GB Read Intensive NVMe HS SSD	N	N	N	N	N	N	N	N	N	N	N	N	N
4XB7B14667	ThinkSystem M.2 VA 1.92TB Read Intensive NVMe HS SSD	N	N	N	N	N	N	N	N	N	N	N	N	N

Table 8. Server support (Part 5 of 5)

Part Number	Description	2S Intel V1							Dense V1				
		ST550 (7X09 / 7X10)	SR530 (7X07 / 7X08)	SR550 (7X03 / 7X04)	SR570 (7Y02 / 7Y03)	SR590 (7X98 / 7X99)	SR630 (7X01 / 7X02)	SR650 (7X05 / 7X06)	SR670 (7Y36 / 7Y37)	SD530 (7X21)	SD650 (7X58)	SN550 (7X16)	SN850 (7X15)
2.5-inch hot-swap drives with PCIe 5.0 interface													
4XB7B11683	ThinkSystem 2.5" U.2 VA 960GB Read Intensive NVMe PCIe 4.0 x4 HS SSD	N	N	N	N	N	N	N	N	N	N	N	N
4XB7A93122	ThinkSystem 2.5" U.2 VA 1.92TB Read Intensive NVMe PCIe 5.0 x4 HS SSD	N	N	N	N	N	N	N	N	N	N	N	N
4XB7A93123	ThinkSystem 2.5" U.2 VA 3.84TB Read Intensive NVMe PCIe 5.0 x4 HS SSD	N	N	N	N	N	N	N	N	N	N	N	N
4XB7A93124	ThinkSystem 2.5" U.2 VA 7.68TB Read Intensive NVMe PCIe 5.0 x4 HS SSD	N	N	N	N	N	N	N	N	N	N	N	N
4XB7A93125	ThinkSystem 2.5" U.2 VA 15.36TB Read Intensive NVMe PCIe 5.0 x4 HS SSD	N	N	N	N	N	N	N	N	N	N	N	N
4XB7A93126	ThinkSystem 2.5" U.2 VA 30.72TB Read Intensive NVMe PCIe 5.0 x4 HS SSD	N	N	N	N	N	N	N	N	N	N	N	N
2.5-inch hot-swap drives with PCIe 4.0 interface													

Part Number	Description	2S Intel V1								Dense V1			
		ST550 (7X09 / 7X10)	SR530 (7X07 / 7X08)	SR550 (7X03 / 7X04)	SR570 (7Y02 / 7Y03)	SR590 (7X98 / 7X99)	SR630 (7X01 / 7X02)	SR650 (7X05 / 7X06)	SR670 (7Y36 / 7Y37)	SD530 (7X21)	SD650 (7X58)	SN550 (7X16)	SN850 (7X15)
4XB7A93892	ThinkSystem 2.5" U.2 VA 1.92TB Read Intensive NVMe PCIe 4.0 x4 HS SSD	N	N	N	N	N	N	N	N	N	N	N	N
4XB7A93893	ThinkSystem 2.5" U.2 VA 3.84TB Read Intensive NVMe PCIe 4.0 x4 HS SSD	N	N	N	N	N	N	N	N	N	N	N	N
4XB7A93894	ThinkSystem 2.5" U.2 VA 7.68TB Read Intensive NVMe PCIe 4.0 x4 HS SSD	N	N	N	N	N	N	N	N	N	N	N	N
4XB7A93895	ThinkSystem 2.5" U.2 VA 15.36TB Read Intensive NVMe PCIe 4.0 x4 HS SSD	N	N	N	N	N	N	N	N	N	N	N	N
3.5-inch hot-swap drives with PCIe 5.0 interface													
4XB7B13984	ThinkSystem 3.5" U.2 VA 1.92TB Read Intensive NVMe PCIe 5.0 x4 HS SSD	N	N	N	N	N	N	N	N	N	N	N	N
4XB7B13985	ThinkSystem 3.5" U.2 VA 3.84TB Read Intensive NVMe PCIe 5.0 x4 HS SSD	N	N	N	N	N	N	N	N	N	N	N	N
4XB7B13986	ThinkSystem 3.5" U.2 VA 7.68TB Read Intensive NVMe PCIe 5.0 x4 HS SSD	N	N	N	N	N	N	N	N	N	N	N	N
4XB7B13987	ThinkSystem 3.5" U.2 VA 15.36TB Read Intensive NVMe PCIe 5.0 x4 HS SSD	N	N	N	N	N	N	N	N	N	N	N	N
E3.S 1T hot-swap drives with PCIe 5.0 interface													
4XB7A93131	ThinkSystem E3.S 1T VA 1.92TB Read Intensive NVMe PCIe 5.0 x4 HS SSD v2	N	N	N	N	N	N	N	N	N	N	N	N
4XB7A93132	ThinkSystem E3.S 1T VA 3.84TB Read Intensive NVMe PCIe 5.0 x4 HS SSD v2	N	N	N	N	N	N	N	N	N	N	N	N
4XB7A93133	ThinkSystem E3.S 1T VA 7.68TB Read Intensive NVMe PCIe 5.0 x4 HS SSD v2	N	N	N	N	N	N	N	N	N	N	N	N
4XB7A93134	ThinkSystem E3.S 1T VA 15.36TB Read Intensive NVMe PCIe 5.0 x4 HS SSD v2	N	N	N	N	N	N	N	N	N	N	N	N
15mm trayless (non-hot-swap) drives with PCIe 4.0 interface													
4XB7B09657	ThinkSystem 2.5" 15mm VA 1.92TB Read Intensive NVMe PCIe 4.0 x4 Trayless SSD	N	N	N	N	N	N	N	N	N	N	N	N
4XB7B09658	ThinkSystem 2.5" 15mm VA 3.84TB Read Intensive NVMe PCIe 4.0 x4 Trayless SSD	N	N	N	N	N	N	N	N	N	N	N	N
4XB7B09659	ThinkSystem 2.5" 15mm VA 7.68TB Read Intensive NVMe PCIe 4.0 x4 Trayless SSD	N	N	N	N	N	N	N	N	N	N	N	N
7mm trayless (non-hot-swap) drives with PCIe 4.0 interface													
4XB7B09654	ThinkSystem 2.5" 7mm VA 960GB Read Intensive NVMe PCIe 4.0 x4 Trayless SSD	N	N	N	N	N	N	N	N	N	N	N	N
4XB7B09655	ThinkSystem 2.5" 7mm VA 1.92TB Read Intensive NVMe PCIe 4.0 x4 Trayless SSD	N	N	N	N	N	N	N	N	N	N	N	N
4XB7B09656	ThinkSystem 2.5" 7mm VA 3.84TB Read Intensive NVMe PCIe 4.0 x4 Trayless SSD	N	N	N	N	N	N	N	N	N	N	N	N

Part Number	Description	2S Intel V1								Dense V1			
		ST550 (7X09 / 7X10)	SR530 (7X07 / 7X08)	SR550 (7X03 / 7X04)	SR570 (7Y02 / 7Y03)	SR590 (7X98 / 7X99)	SR630 (7X01 / 7X02)	SR650 (7X05 / 7X06)	SR670 (7Y36 / 7Y37)	SD530 (7X21)	SD650 (7X58)	SN550 (7X16)	SN850 (7X15)
E3.S 1T trayless (non-hot-swap) drives with PCIe 5.0 interface													
4XB7B12180	ThinkSystem E3.S 1T VA 1.92TB Read Intensive NVMe PCIe 5.0 x4 Trayless SSD	N	N	N	N	N	N	N	N	N	N	N	N
4XB7B12181	ThinkSystem E3.S 1T VA 3.84TB Read Intensive NVMe PCIe 5.0 x4 Trayless SSD	N	N	N	N	N	N	N	N	N	N	N	N
4XB7B12182	ThinkSystem E3.S 1T VA 7.68TB Read Intensive NVMe PCIe 5.0 x4 Trayless SSD	N	N	N	N	N	N	N	N	N	N	N	N
4XB7B12183	ThinkSystem E3.S 1T VA 15.36TB Read Intensive NVMe PCIe 5.0 x4 Trayless SSD	N	N	N	N	N	N	N	N	N	N	N	N
M.2 drives with PCIe 4.0 interface - not for B550 or B350 M.2 adapters													
4XB7B09650	ThinkSystem M.2 VA 480GB Read Intensive NVMe PCIe 4.0 x4 NHS SSD	N	N	N	N	N	N	N	N	N	N	N	N
4XB7B09651	ThinkSystem M.2 VA 960GB Read Intensive NVMe PCIe 4.0 x4 NHS SSD	N	N	N	N	N	N	N	N	N	N	N	N
4XB7B09652	ThinkSystem M.2 VA 1.92TB Read Intensive NVMe PCIe 4.0 x4 NHS SSD	N	N	N	N	N	N	N	N	N	N	N	N
4XB7B09653	ThinkSystem M.2 VA 3.84TB Read Intensive NVMe PCIe 4.0 x4 NHS SSD	N	N	N	N	N	N	N	N	N	N	N	N
M.2 drives with PCIe 4.0 interface - only for B550i or B350i internal M.2 adapters													
4XB7A93140	ThinkSystem M.2 VA 480GB Read Intensive NVMe NHS SSD	N	N	N	N	N	N	N	N	N	N	N	N
4XB7A93141	ThinkSystem M.2 VA 960GB Read Intensive NVMe NHS SSD	N	N	N	N	N	N	N	N	N	N	N	N
4XB7A93142	ThinkSystem M.2 VA 1.92TB Read Intensive NVMe NHS SSD	N	N	N	N	N	N	N	N	N	N	N	N
M.2 drives with PCIe 4.0 interface - only for B550p or B550d hot-swap M.2 adapters													
4XB7B14665	ThinkSystem M.2 VA 480GB Read Intensive NVMe HS SSD	N	N	N	N	N	N	N	N	N	N	N	N
4XB7B14666	ThinkSystem M.2 VA 960GB Read Intensive NVMe HS SSD	N	N	N	N	N	N	N	N	N	N	N	N
4XB7B14667	ThinkSystem M.2 VA 1.92TB Read Intensive NVMe HS SSD	N	N	N	N	N	N	N	N	N	N	N	N

Operating system support

The Vendor Agnostic SSDs support the operating systems listed in the following tables:

- [2.5-inch hot-swap drives with PCIe 5.0 interface](#)
- [2.5-inch hot-swap drives with PCIe 4.0 interface](#)
- [E3.S 1T hot-swap drives](#)
- [Trayless drives](#)
- [M.2 drives](#)

Tip: These tables are automatically generated based on data from [Lenovo ServerProven](#).

2.5-inch hot-swap drives with PCIe 5.0 interface

The following table lists the OS support for the 2.5-inch hot-swap drives with PCIe 5.0 interface.

Table 9. Operating system support for ThinkSystem 2.5" U.2 VA 3.84TB Read Intensive NVMe PCIe 5.0 x4 HS SSD, 4XB7A93123

Operating systems	SR630 V3 (5th Gen Xeon)	SR860 V4	SR850 V4	SR650 V4/SR650a V4	SR630 V4	SD535 V3	SD550 V3	SR650 V3 (5th Gen Xeon)	SR630 V3 (4th Gen Xeon)	SR645 V3	SR675 V3	SR860 V3	SR850 V3	SR655 V3	SR650 V3 (4th Gen Xeon)	SR635 V3	SR665 V3
Microsoft Windows 10	Y	N	N	N	N	N	N	Y	N	Y	N	N	N	Y	Y	Y	Y
Microsoft Windows 11	Y	N	N	N	N	N	N	Y	Y	Y	N	N	N	Y	Y	Y	Y
Microsoft Windows Server 2019	Y	N	N	N	N	N	N	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y
Microsoft Windows Server 2022	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y
Microsoft Windows Server 2025	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y
Red Hat Enterprise Linux 8.6	N	N	N	N	N	N	N	N	Y	Y	Y	Y	Y	Y	Y	Y	Y
Red Hat Enterprise Linux 8.7	N	N	N	N	N	N	N	N	Y	Y	Y	Y	Y	Y	Y	Y	Y
Red Hat Enterprise Linux 8.8	Y	N	N	N	N	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y
Red Hat Enterprise Linux 8.9	N	N	N	N	N	Y	Y	N	N	N	Y	Y	Y	Y	N	N	N
Red Hat Enterprise Linux 8.10	Y	N	N	N	N	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y
Red Hat Enterprise Linux 9.0	N	N	N	N	N	N	N	N	Y	Y	Y	Y	Y	Y	Y	Y	Y
Red Hat Enterprise Linux 9.1	N	N	N	N	N	N	N	N	Y	Y	Y	Y	Y	Y	Y	Y	Y
Red Hat Enterprise Linux 9.2	Y	N	N	N	N	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y
Red Hat Enterprise Linux 9.3	N	N	N	N	N	Y	Y	N	N	N	Y	Y	Y	Y	N	N	N
Red Hat Enterprise Linux 9.4	Y	N	N	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y
Red Hat Enterprise Linux 9.5	Y	N	N	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y
Red Hat Enterprise Linux 9.6	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y
Red Hat Enterprise Linux 9.7	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y	N	Y	Y	Y	Y	Y	Y
Red Hat Enterprise Linux 9.8	Y	Y	Y	Y	N	Y	Y	Y	Y	Y	N	N	N	Y	Y	Y	Y
Red Hat Enterprise Linux 10.0	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y

	SR630 V3 (5th Gen Xeon)	SR860 V4	SR850 V4	SR650 V4/SR650a V4	SR630 V4	SD535 V3	SD550 V3	SR650 V3 (5th Gen Xeon)	SR630 V3 (4th Gen Xeon)	SR645 V3	SR675 V3	SR860 V3	SR850 V3	SR655 V3	SR650 V3 (4th Gen Xeon)	SR635 V3	SR665 V3
Operating systems																	
Red Hat Enterprise Linux 10.1	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y	N	Y	Y	Y	Y	Y	Y
Red Hat Enterprise Linux 10.2	Y	Y	Y	Y	N	Y	Y	Y	Y	Y	N	Y	Y	Y	Y	Y	Y
SUSE Linux Enterprise Server 15 SP4	N	N	N	N	N	N	N	N	Y	Y	Y	Y	Y	Y	Y	Y	Y
SUSE Linux Enterprise Server 15 SP5	Y	N	N	N	N	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y
SUSE Linux Enterprise Server 15 SP6	Y	N	N	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y
SUSE Linux Enterprise Server 15 SP7	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y
SUSE Linux Enterprise Server 16	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y	N	Y
Ubuntu 20.04.5 LTS or later with HWE kernel	N	N	N	N	N	Y	N	N	N	Y	Y	Y	Y	Y	N	Y	Y
Ubuntu 20.04 LTS or later with HWE kernel	Y	N	N	N	N	N	N	Y	Y	N	N	N	N	N	Y	N	N
Ubuntu 22.04.3 LTS or later with HWE kernel	Y	N	N	N	N	Y	Y	Y	N	N	N	N	N	N	N	N	N
Ubuntu 22.04.5 LTS or later with HWE kernel	N	Y	Y	Y	Y	Y	N	N	N	Y	Y	N	N	Y	N	N	Y
Ubuntu 22.04 LTS or later with HWE kernel	N	N	N	N	N	N	N	N	Y	Y	Y	Y	Y	Y	Y	Y	Y
Ubuntu 24.04 LTS or later with HWE kernel	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y
Ubuntu 26.04 LTS or later with HWE kernel	N	N	N	N	N	N	N	N	N	N	N	N	N	N	N	N	Y
VMware vSphere Hypervisor (ESXi) 7.0 U3	Y	N	N	N	N	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y
VMware vSphere Hypervisor (ESXi) 8.0	N	N	N	N	N	N	N	N	Y	Y	N	N	N	Y	Y	Y	Y
VMware vSphere Hypervisor (ESXi) 8.0 U1	N	N	N	N	N	N	N	N	Y	Y	Y	Y	Y	Y	Y	Y	Y
VMware vSphere Hypervisor (ESXi) 8.0 U2	Y	N	N	N	N	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y
VMware vSphere Hypervisor (ESXi) 8.0 U3	Y	N	N	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y
VMware vSphere Hypervisor (ESXi) 9.0	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y
VMware vSphere Hypervisor ESXi 9.1	Y	N	N	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y

2.5-inch hot-swap drives with PCIe 4.0 interface

The following table lists the OS support for the 2.5-inch hot-swap drives with PCIe 4.0 interface.

Table 10. Operating system support for ThinkSystem 2.5" U.2 VA 3.84TB Read Intensive NVMe PCIe 4.0 x4 HS SSD, 4XB7A93893 (Part 1 of 2)

	SR635 V3	SD535 V3	SD550 V3	SR650 V3 (5th Gen Xeon)	SR630 V3 (4th Gen Xeon)	SR630 V3 (5th Gen Xeon)	SE455 V3	SR675 V3	SR860 V3	SR850 V3	SR655 V3	SR650 V3 (4th Gen Xeon)	SR645	ST650 V2	ST650 V2	SR860 V2	SR850 V2	SR670 V2	SR650 V2	SR630 V2
Operating systems																				
Microsoft Windows Server 2016	N	N	N	N	N	N	N	N	N	N	N	N	Y	Y	Y	Y	Y	Y	Y	Y

	SR635 V3	SD535 V3	SD550 V3	SR650 V3 (5th Gen Xeon)	SR630 V3 (4th Gen Xeon)	SR630 V3 (5th Gen Xeon)	SE455 V3	SR675 V3	SR860 V3	SR850 V3	SR655 V3	SR650 V3 (4th Gen Xeon)	SR645	ST650 V2	ST650 V2	SR860 V2	SR850 V2	SR670 V2	SR650 V2	SR630 V2	
Operating systems																					
Microsoft Windows Server 2019	Y	N	N	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y
Microsoft Windows Server 2022	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y
Microsoft Windows Server 2025	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y
Red Hat Enterprise Linux 7.6	N	N	N	N	N	N	N	N	N	N	N	N	Y	N	N	N	N	N	N	N	N
Red Hat Enterprise Linux 7.7	N	N	N	N	N	N	N	N	N	N	N	N	Y	N	N	N	N	N	N	N	N
Red Hat Enterprise Linux 7.8	N	N	N	N	N	N	N	N	N	N	N	N	Y	N	N	N	N	N	N	N	N
Red Hat Enterprise Linux 7.9	N	N	N	N	N	N	N	N	N	N	N	N	Y	Y	Y	Y	Y	Y	Y	Y	Y
Red Hat Enterprise Linux 8.1	N	N	N	N	N	N	N	N	N	N	N	N	Y	N	N	N	N	N	N	N	N
Red Hat Enterprise Linux 8.2	N	N	N	N	N	N	N	N	N	N	N	N	Y	Y	Y	Y	Y	Y	Y	Y	Y
Red Hat Enterprise Linux 8.3	N	N	N	N	N	N	N	N	N	N	N	N	Y	Y	Y	Y	Y	Y	Y	Y	Y
Red Hat Enterprise Linux 8.4	N	N	N	N	N	N	N	N	N	N	N	N	Y	Y	Y	Y	Y	Y	Y	Y	Y
Red Hat Enterprise Linux 8.5	N	N	N	N	N	N	N	N	N	N	N	N	Y	Y	Y	Y	Y	Y	Y	Y	Y
Red Hat Enterprise Linux 8.6	Y	N	N	N	Y	N	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y
Red Hat Enterprise Linux 8.7	Y	N	N	N	Y	N	N	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y
Red Hat Enterprise Linux 8.8	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y
Red Hat Enterprise Linux 8.9	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y
Red Hat Enterprise Linux 8.10	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y
Red Hat Enterprise Linux 9.0	Y	N	N	N	Y	N	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y
Red Hat Enterprise Linux 9.1	Y	N	N	N	Y	N	N	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y
Red Hat Enterprise Linux 9.2	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y
Red Hat Enterprise Linux 9.3	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y
Red Hat Enterprise Linux 9.4	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y
Red Hat Enterprise Linux 9.5	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y
Red Hat Enterprise Linux 9.6	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y
Red Hat Enterprise Linux 9.7	Y	Y	Y	Y	Y	Y	Y	N	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y
Red Hat Enterprise Linux 9.8	Y	Y	Y	Y	Y	Y	N	N	N	N	Y	Y	N	N	N	N	N	N	N	N	N
Red Hat Enterprise Linux 10.0	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y	N	N	Y	Y	Y	Y
Red Hat Enterprise Linux 10.1	Y	Y	Y	Y	Y	Y	Y	N	Y	Y	Y	Y	Y	Y	Y	N	N	Y	Y	Y	Y
Red Hat Enterprise Linux 10.2	Y	Y	Y	Y	Y	Y	Y	N	Y	Y	Y	Y	N	Y	Y	N	N	Y	Y	Y	Y
SUSE Linux Enterprise Server 12 SP5	N	N	N	N	N	N	N	N	N	N	N	N	Y	Y	Y	Y	Y	Y	Y	Y	Y
SUSE Linux Enterprise Server 12 SP5 with Xen	N	N	N	N	N	N	N	N	N	N	N	N	Y	Y	Y	Y	Y	Y	Y	Y	Y
SUSE Linux Enterprise Server 15 SP1	N	N	N	N	N	N	N	N	N	N	N	N	Y	N	N	N	N	N	N	N	N
SUSE Linux Enterprise Server 15 SP1 with Xen	N	N	N	N	N	N	N	N	N	N	N	N	Y	N	N	N	N	N	N	N	N
SUSE Linux Enterprise Server 15 SP2	N	N	N	N	N	N	N	N	N	N	N	N	Y	Y	Y	Y	Y	Y	Y	Y	Y
SUSE Linux Enterprise Server 15 SP2 with Xen	N	N	N	N	N	N	N	N	N	N	N	N	Y	Y	Y	Y	Y	Y	Y	Y	Y

	SR635 V3	SD535 V3	SD550 V3	SR650 V3 (5th Gen Xeon)	SR630 V3 (4th Gen Xeon)	SR630 V3 (5th Gen Xeon)	SE455 V3	SR675 V3	SR860 V3	SR850 V3	SR655 V3	SR650 V3 (4th Gen Xeon)	SR645	ST650 V2	ST650 V2	SR860 V2	SR850 V2	SR670 V2	SR650 V2	SR630 V2	
Operating systems																					
SUSE Linux Enterprise Server 15 SP3	N	N	N	N	N	N	N	N	N	N	N	N	Y	Y	Y	Y	Y	Y	Y	Y	Y
SUSE Linux Enterprise Server 15 SP3 with Xen	N	N	N	N	N	N	N	N	N	N	N	N	Y	Y	Y	Y	Y	Y	Y	Y	Y
SUSE Linux Enterprise Server 15 SP4	Y	N	N	N	Y	N	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y
SUSE Linux Enterprise Server 15 SP4 with Xen	Y	N	N	N	Y	N	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y
SUSE Linux Enterprise Server 15 SP5	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y
SUSE Linux Enterprise Server 15 SP5 with Xen	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y
SUSE Linux Enterprise Server 15 SP6	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y
SUSE Linux Enterprise Server 15 SP7	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y
SUSE Linux Enterprise Server 16	N	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y	N	N	N	N	N	Y	Y	Y
VMware vSphere Hypervisor (ESXi) 6.7 U3	N	N	N	N	N	N	N	N	N	N	N	N	Y	Y	Y	N	N	Y	Y	Y	Y
VMware vSphere Hypervisor (ESXi) 7.0	N	N	N	N	N	N	N	N	N	N	N	N	Y	N	N	N	N	N	N	N	N
VMware vSphere Hypervisor (ESXi) 7.0 U1	N	N	N	N	N	N	N	N	N	N	N	N	Y	N	N	Y	Y	N	N	N	N
VMware vSphere Hypervisor (ESXi) 7.0 U2	N	N	N	N	N	N	N	N	N	N	N	N	Y	Y	Y	Y	Y	Y	Y	Y	Y
VMware vSphere Hypervisor (ESXi) 7.0 U3	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y
VMware vSphere Hypervisor (ESXi) 8.0	Y	N	N	N	Y	N	N	N	N	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y
VMware vSphere Hypervisor (ESXi) 8.0 U1	Y	N	N	N	Y	N	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y
VMware vSphere Hypervisor (ESXi) 8.0 U2	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y
VMware vSphere Hypervisor (ESXi) 8.0 U3	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y
VMware vSphere Hypervisor (ESXi) 9.0	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y	N	N	Y	Y	Y	Y
VMware vSphere Hypervisor ESXi 9.1	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y	N	N	Y	Y	Y	Y

Table 11. Operating system support for ThinkSystem 2.5" U.2 VA 3.84TB Read Intensive NVMe PCIe 4.0 x4 HS SSD, 4XB7A93893 (Part 2 of 2)

	SR665 V3	SR645 V3	SR665
Operating systems			
Microsoft Windows Server 2016	N	N	Y
Microsoft Windows Server 2019	Y	Y	Y
Microsoft Windows Server 2022	Y	Y	Y
Microsoft Windows Server 2025	Y	Y	Y
Red Hat Enterprise Linux 7.6	N	N	Y
Red Hat Enterprise Linux 7.7	N	N	Y
Red Hat Enterprise Linux 7.8	N	N	Y
Red Hat Enterprise Linux 7.9	N	N	Y
Red Hat Enterprise Linux 8.1	N	N	Y
Red Hat Enterprise Linux 8.2	N	N	Y

	SR665 V3	SR645 V3	SR665
Operating systems			
Red Hat Enterprise Linux 8.3	N	N	Y
Red Hat Enterprise Linux 8.4	N	N	Y
Red Hat Enterprise Linux 8.5	N	N	Y
Red Hat Enterprise Linux 8.6	Y	Y	Y
Red Hat Enterprise Linux 8.7	Y	Y	Y
Red Hat Enterprise Linux 8.8	Y	Y	Y
Red Hat Enterprise Linux 8.9	Y	Y	Y
Red Hat Enterprise Linux 8.10	Y	Y	Y
Red Hat Enterprise Linux 9.0	Y	Y	Y
Red Hat Enterprise Linux 9.1	Y	Y	Y
Red Hat Enterprise Linux 9.2	Y	Y	Y
Red Hat Enterprise Linux 9.3	Y	Y	Y
Red Hat Enterprise Linux 9.4	Y	Y	Y
Red Hat Enterprise Linux 9.5	Y	Y	Y
Red Hat Enterprise Linux 9.6	Y	Y	Y
Red Hat Enterprise Linux 9.7	Y	Y	Y
Red Hat Enterprise Linux 9.8	Y	Y	N
Red Hat Enterprise Linux 10.0	Y	Y	Y
Red Hat Enterprise Linux 10.1	Y	Y	Y
Red Hat Enterprise Linux 10.2	Y	Y	N
SUSE Linux Enterprise Server 12 SP5	N	N	Y
SUSE Linux Enterprise Server 12 SP5 with Xen	N	N	Y
SUSE Linux Enterprise Server 15 SP1	N	N	Y
SUSE Linux Enterprise Server 15 SP1 with Xen	N	N	Y
SUSE Linux Enterprise Server 15 SP2	N	N	Y
SUSE Linux Enterprise Server 15 SP2 with Xen	N	N	Y
SUSE Linux Enterprise Server 15 SP3	N	N	Y
SUSE Linux Enterprise Server 15 SP3 with Xen	N	N	Y
SUSE Linux Enterprise Server 15 SP4	Y	Y	Y
SUSE Linux Enterprise Server 15 SP4 with Xen	Y	Y	Y
SUSE Linux Enterprise Server 15 SP5	Y	Y	Y
SUSE Linux Enterprise Server 15 SP5 with Xen	Y	Y	Y
SUSE Linux Enterprise Server 15 SP6	Y	Y	Y
SUSE Linux Enterprise Server 15 SP7	Y	Y	Y
SUSE Linux Enterprise Server 16	Y	Y	Y
VMware vSphere Hypervisor (ESXi) 6.7 U3	N	N	Y
VMware vSphere Hypervisor (ESXi) 7.0	N	N	Y
VMware vSphere Hypervisor (ESXi) 7.0 U1	N	N	Y
VMware vSphere Hypervisor (ESXi) 7.0 U2	N	N	Y
VMware vSphere Hypervisor (ESXi) 7.0 U3	Y	Y	Y

	SR665 V3	SR645 V3	SR665
Operating systems			
VMware vSphere Hypervisor (ESXi) 8.0	Y	Y	Y
VMware vSphere Hypervisor (ESXi) 8.0 U1	Y	Y	Y
VMware vSphere Hypervisor (ESXi) 8.0 U2	Y	Y	Y
VMware vSphere Hypervisor (ESXi) 8.0 U3	Y	Y	Y
VMware vSphere Hypervisor (ESXi) 9.0	Y	Y	Y
VMware vSphere Hypervisor ESXi 9.1	Y	Y	Y

E3.S 1T hot-swap drives

The following table lists the OS support for the E3.S 1T hot-swap drives.

Table 12. Operating system support for ThinkSystem E3.S 1T VA 3.84TB Read Intensive NVMe PCIe 5.0 x4 HS SSD v2, 4XB7A93132

	SR675 V3	SR950 V3	SD530 V3	SR630 V4	SR650 V4/SR650a V4	SR850 V4	SR860 V4
Operating systems							
Microsoft Windows Server 2019	Y	N	N	N	N	N	N
Microsoft Windows Server 2022	Y	Y	Y	Y	Y	Y	Y
Microsoft Windows Server 2025	Y	Y	Y	Y	Y	Y	Y
Red Hat Enterprise Linux 8.6	Y	Y	N	N	N	N	N
Red Hat Enterprise Linux 8.7	Y	Y	N	N	N	N	N
Red Hat Enterprise Linux 8.8	Y	Y	Y	N	N	N	N
Red Hat Enterprise Linux 8.9	Y	Y	Y	N	N	N	N
Red Hat Enterprise Linux 8.10	Y	Y	Y	N	N	N	N
Red Hat Enterprise Linux 9.0	Y	Y	N	N	N	N	N
Red Hat Enterprise Linux 9.1	Y	Y	N	N	N	N	N
Red Hat Enterprise Linux 9.2	Y	Y	Y	N	N	N	N
Red Hat Enterprise Linux 9.3	Y	Y	Y	N	N	N	N
Red Hat Enterprise Linux 9.4	Y	Y	Y	Y	Y	N	N
Red Hat Enterprise Linux 9.5	Y	Y	Y	Y	Y	N	N
Red Hat Enterprise Linux 9.6	Y	Y	Y	Y	Y	Y	Y
Red Hat Enterprise Linux 9.7	N	Y	Y	Y	Y	Y	Y
Red Hat Enterprise Linux 9.8	N	N	Y	N	Y	Y	Y
Red Hat Enterprise Linux 10.0	Y	Y	Y	Y	Y	Y	Y
Red Hat Enterprise Linux 10.1	N	Y	Y	Y	Y	Y	Y
Red Hat Enterprise Linux 10.2	N	Y	Y	N	Y	Y	Y
SUSE Linux Enterprise Server 15 SP4	Y	Y	N	N	N	N	N

	SR675 V3	SR950 V3	SD530 V3	SR630 V4	SR650 V4/SR650a V4	SR850 V4	SR860 V4
Operating systems							
SUSE Linux Enterprise Server 15 SP4 with Xen	Y	Y	N	N	N	N	N
SUSE Linux Enterprise Server 15 SP5	Y	Y	Y	N	N	N	N
SUSE Linux Enterprise Server 15 SP5 with Xen	Y	Y	Y	N	N	N	N
SUSE Linux Enterprise Server 15 SP6	Y	Y	Y	Y	Y	N	N
SUSE Linux Enterprise Server 15 SP7	Y	Y	Y	Y	Y	Y	Y
SUSE Linux Enterprise Server 16	Y	Y	Y	Y	Y	Y	Y
Ubuntu 20.04.5 LTS or later with HWE kernel	Y	N	N	N	N	N	N
Ubuntu 22.04.3 LTS or later with HWE kernel	N	N	Y	N	N	N	N
Ubuntu 22.04.5 LTS or later with HWE kernel	Y	N	N	Y	Y	Y	Y
Ubuntu 22.04 LTS or later with HWE kernel	Y	N	N	N	N	N	N
Ubuntu 24.04 LTS or later with HWE kernel	Y	Y	Y	Y	Y	Y	Y
VMware vSphere Hypervisor (ESXi) 7.0 U3	Y	N	Y	N	N	N	N
VMware vSphere Hypervisor (ESXi) 8.0 U1	Y	N	N	N	N	N	N
VMware vSphere Hypervisor (ESXi) 8.0 U2	Y	Y	Y	N	N	N	N
VMware vSphere Hypervisor (ESXi) 8.0 U3	Y	Y	Y	Y	Y	N	N
VMware vSphere Hypervisor (ESXi) 9.0	Y	Y	Y	Y	Y	Y	Y
VMware vSphere Hypervisor ESXi 9.1	Y	N	Y	Y	Y	N	N

Trayless drives

The following table lists the OS support for the Trayless (non-hot-swap) drives.

Table 13. Operating system support for ThinkSystem 2.5" 15mm VA 3.84TB Read Intensive NVMe PCIe 4.0 x4 Trayless SSD, 4XB7B09658

	SD665-N V3	SD650 V3	SD665 V3	SD650 V3 (5th Gen Xeon)	SD650-N V3 (4th Gen Xeon)	SD650-N V3 (5th Gen Xeon)
Operating systems						
Red Hat Enterprise Linux 8.6	Y	Y	Y	N	N	N
Red Hat Enterprise Linux 8.10	Y	Y	Y	Y	N	N
Red Hat Enterprise Linux 9.0	Y	Y	Y	N	N	N
Red Hat Enterprise Linux 9.2	Y	Y	Y	Y	Y	Y
Red Hat Enterprise Linux 9.3	N	N	Y	N	N	N

	SR950 V3	SR860 V4	SR850 V4	SE100	SR650 V4/SR650a V4	SR630 V4	ST650 V3 (5th Gen Xeon)	SD535 V3	SD650-N V3 (5th Gen Xeon)	SD650-N V3 (4th Gen Xeon)	SD650 V3 (5th Gen Xeon)	SR650 V3 (5th Gen Xeon)	SR630 V3 (4th Gen Xeon)	SR630 V3 (5th Gen Xeon)	SD665 V3	SR645	SE455 V3	SD650 V3	SD665-N V3	SR675 V3	
Operating systems																					
Red Hat Enterprise Linux 7.8	N	N	N	N	N	N	N	N	N	N	N	N	N	N	N	Y	N	N	N	N	N
Red Hat Enterprise Linux 7.9	N	N	N	N	N	N	N	N	N	N	N	N	N	N	N	Y	N	N	N	N	N
Red Hat Enterprise Linux 8.1	N	N	N	N	N	N	N	N	N	N	N	N	N	N	N	Y	N	N	N	N	N
Red Hat Enterprise Linux 8.2	N	N	N	N	N	N	N	N	N	N	N	N	N	N	N	Y	N	N	N	N	N
Red Hat Enterprise Linux 8.3	N	N	N	N	N	N	N	N	N	N	N	N	N	N	N	Y	N	N	N	N	N
Red Hat Enterprise Linux 8.4	N	N	N	N	N	N	N	N	N	N	N	N	N	N	N	Y	N	N	N	N	N
Red Hat Enterprise Linux 8.5	N	N	N	N	N	N	N	N	N	N	N	N	N	N	N	Y	N	N	N	N	N
Red Hat Enterprise Linux 8.6	Y	N	N	N	N	N	N	N	N	N	N	N	Y	N	Y	Y	Y	Y	Y	Y	Y
Red Hat Enterprise Linux 8.7	Y	N	N	N	N	N	N	N	N	N	N	N	Y	N	N	Y	N	N	N	N	Y
Red Hat Enterprise Linux 8.8	Y	N	N	N	N	N	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y
Red Hat Enterprise Linux 8.9	Y	N	N	N	N	N	N	Y	N	N	N	Y	Y	Y	Y	Y	Y	N	N	Y	Y
Red Hat Enterprise Linux 8.10	Y	N	N	N	N	N	Y	Y	N	N	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y
Red Hat Enterprise Linux 9.0	N	N	N	N	N	N	N	N	N	N	N	N	Y	N	Y	Y	Y	Y	Y	Y	Y
Red Hat Enterprise Linux 9.1	N	N	N	N	N	N	N	N	N	N	N	N	Y	N	N	Y	N	N	N	N	Y
Red Hat Enterprise Linux 9.2	N	N	N	N	N	N	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y
Red Hat Enterprise Linux 9.3	N	N	N	N	N	N	N	Y	N	N	N	Y	Y	Y	Y	Y	Y	N	N	Y	Y
Red Hat Enterprise Linux 9.4	N	N	N	N	Y	Y	Y	Y	N	N	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y
Red Hat Enterprise Linux 9.5	N	N	N	N	Y	Y	Y	Y	N	N	N	Y	Y	Y	N	Y	Y	N	N	Y	Y
Red Hat Enterprise Linux 9.6	N	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y
Red Hat Enterprise Linux 9.7	Y	Y	Y	Y	Y	Y	Y	Y	N	N	N	Y	Y	Y	N	Y	Y	N	N	N	N
Red Hat Enterprise Linux 9.8	N	Y	Y	N	Y	N	Y	Y	N	N	N	Y	Y	Y	N	N	N	N	N	N	N
Red Hat Enterprise Linux 10.0	N	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y
Red Hat Enterprise Linux 10.1	Y	Y	Y	Y	Y	Y	Y	Y	N	N	N	Y	Y	Y	N	Y	Y	N	N	N	N
Red Hat Enterprise Linux 10.2	Y	Y	Y	N	Y	N	Y	Y	N	N	N	Y	Y	Y	N	N	Y	N	N	N	N
SUSE Linux Enterprise Server 12 SP5	N	N	N	N	N	N	N	N	N	N	N	N	N	N	N	Y	N	N	N	N	N
SUSE Linux Enterprise Server 12 SP5 with Xen	N	N	N	N	N	N	N	N	N	N	N	N	N	N	N	Y	N	N	N	N	N
SUSE Linux Enterprise Server 15 SP1	N	N	N	N	N	N	N	N	N	N	N	N	N	N	N	Y	N	N	N	N	N
SUSE Linux Enterprise Server 15 SP1 with Xen	N	N	N	N	N	N	N	N	N	N	N	N	N	N	N	Y	N	N	N	N	N
SUSE Linux Enterprise Server 15 SP2	N	N	N	N	N	N	N	N	N	N	N	N	N	N	N	Y	N	N	N	N	N
SUSE Linux Enterprise Server 15 SP2 with Xen	N	N	N	N	N	N	N	N	N	N	N	N	N	N	N	Y	N	N	N	N	N
SUSE Linux Enterprise Server 15 SP3	N	N	N	N	N	N	N	N	N	N	N	N	N	N	N	Y	N	N	N	N	N
SUSE Linux Enterprise Server 15 SP3 with Xen	N	N	N	N	N	N	N	N	N	N	N	N	N	N	N	Y	N	N	N	N	N
SUSE Linux Enterprise Server 15 SP4	Y	N	N	N	N	N	N	N	N	N	N	N	Y	N	Y	Y	Y	Y	Y	Y	Y
SUSE Linux Enterprise Server 15 SP4 with Xen	Y	N	N	N	N	N	N	N	N	N	N	N	Y	N	Y	Y	Y	Y	N	Y	Y
SUSE Linux Enterprise Server 15 SP5	Y	N	N	N	N	N	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y

Operating systems	SR950 V3	SR860 V4	SR850 V4	SE100	SR650 V4/SR650a V4	SR630 V4	ST650 V3 (5th Gen Xeon)	SD535 V3	SD650-N V3 (5th Gen Xeon)	SD650-N V3 (4th Gen Xeon)	SD650 V3 (5th Gen Xeon)	SR650 V3 (5th Gen Xeon)	SR630 V3 (4th Gen Xeon)	SR630 V3 (5th Gen Xeon)	SD665 V3	SR645	SE455 V3	SD650 V3	SD665-N V3	SR675 V3
SUSE Linux Enterprise Server 15 SP5 with Xen	Y	N	N	N	N	N	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y
SUSE Linux Enterprise Server 15 SP6	Y	N	N	N	Y	Y	Y	Y	N	N	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y
SUSE Linux Enterprise Server 15 SP7	Y	Y	Y	N	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y
SUSE Linux Enterprise Server 16	Y	Y	Y	N	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y
Ubuntu 18.04.6 LTS or later with HWE kernel	N	N	N	N	N	N	N	N	N	N	N	N	N	N	N	N	N	N	N	N
Ubuntu 20.04.5 LTS or later with HWE kernel	N	N	N	N	N	N	N	Y	N	N	N	N	N	N	Y	N	Y	N	Y	Y
Ubuntu 20.04 LTS or later with HWE kernel	N	N	N	N	N	N	N	N	N	N	N	Y	Y	Y	N	N	N	N	N	N
Ubuntu 22.04.2 LTS or later with HWE kernel	N	N	N	N	N	N	N	N	N	N	N	N	N	N	N	N	Y	N	N	N
Ubuntu 22.04.3 LTS or later with HWE kernel	N	N	N	N	N	N	Y	Y	Y	Y	Y	N	Y	N	Y	N	N	N	N	N
Ubuntu 22.04.5 LTS or later with HWE kernel	N	Y	Y	N	Y	Y	N	Y	N	N	N	N	N	N	Y	N	N	N	Y	Y
Ubuntu 22.04 LTS or later with HWE kernel	N	N	N	N	N	N	N	N	N	N	N	Y	Y	N	Y	Y	N	Y	Y	Y
Ubuntu 24.04.2 LTS or later with HWE kernel	N	N	N	Y	N	N	N	N	N	N	N	N	N	N	N	N	N	N	N	N
Ubuntu 24.04 LTS or later with HWE kernel	Y	Y	Y	N	Y	Y	Y	Y	N	N	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y
Ubuntu 26.04 LTS or later with HWE kernel	N	N	N	N	N	N	N	N	N	N	N	N	N	N	N	N	N	N	N	N
VMware vSphere Hypervisor (ESXi) 6.7 U3	N	N	N	N	N	N	N	N	N	N	N	N	N	N	N	Y	N	N	N	N
VMware vSphere Hypervisor (ESXi) 7.0	N	N	N	N	N	N	N	N	N	N	N	N	N	N	N	Y	N	N	N	N
VMware vSphere Hypervisor (ESXi) 7.0 U1	N	N	N	N	N	N	N	N	N	N	N	N	N	N	N	Y	N	N	N	N
VMware vSphere Hypervisor (ESXi) 7.0 U2	N	N	N	N	N	N	N	N	N	N	N	N	N	N	N	Y	N	N	N	N
VMware vSphere Hypervisor (ESXi) 7.0 U3	N	N	N	N	N	N	Y	Y	N	N	N	Y	Y	Y	N	Y	Y	N	N	Y
VMware vSphere Hypervisor (ESXi) 8.0	N	N	N	N	N	N	N	N	N	N	N	N	Y	N	N	Y	N	N	N	N
VMware vSphere Hypervisor (ESXi) 8.0 U1	N	N	N	N	N	N	N	N	N	N	N	N	Y	N	N	Y	Y	N	N	Y
VMware vSphere Hypervisor (ESXi) 8.0 U2	Y	N	N	N	N	N	Y	Y	N	N	N	Y	Y	Y	N	Y	Y	N	N	Y
VMware vSphere Hypervisor (ESXi) 8.0 U3	Y	N	N	N	Y	Y	Y	Y	N	N	N	Y	Y	Y	N	Y	Y	N	N	Y
VMware vSphere Hypervisor (ESXi) 9.0	Y	Y	Y	N	Y	Y	Y	Y	N	N	N	Y	Y	Y	N	Y	Y	N	N	Y
VMware vSphere Hypervisor ESXi 9.1	N	N	N	N	Y	Y	Y	Y	N	N	N	Y	Y	Y	N	Y	Y	N	N	Y

Table 15. Operating system support for ThinkSystem M.2 VA 960GB Read Intensive NVMe PCIe 4.0 x4

	ST650 V3 (4th Gen Xeon)	SR860 V3	SR850 V3	SR655 V3	SR650 V3 (4th Gen Xeon)	SR635 V3	SE450	SR665 V3	SR645 V3	SR665
Operating systems										
Microsoft Windows 10	N	N	N	Y	Y	Y	N	Y	Y	N
Microsoft Windows 11	N	N	N	Y	Y	Y	N	Y	Y	N
Microsoft Windows Server 2016	N	N	N	N	N	N	N	N	N	Y
Microsoft Windows Server 2019	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y
Microsoft Windows Server 2022	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y
Microsoft Windows Server 2025	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y
Red Hat Enterprise Linux 7.6	N	N	N	N	N	N	N	N	N	Y
Red Hat Enterprise Linux 7.7	N	N	N	N	N	N	N	N	N	Y
Red Hat Enterprise Linux 7.8	N	N	N	N	N	N	N	N	N	Y
Red Hat Enterprise Linux 7.9	N	N	N	N	N	N	Y	N	N	Y
Red Hat Enterprise Linux 8.1	N	N	N	N	N	N	N	N	N	Y
Red Hat Enterprise Linux 8.2	N	N	N	N	N	N	N	N	N	Y
Red Hat Enterprise Linux 8.3	N	N	N	N	N	N	N	N	N	Y
Red Hat Enterprise Linux 8.4	N	N	N	N	N	N	Y	N	N	Y
Red Hat Enterprise Linux 8.5	N	N	N	N	N	N	Y	N	N	Y
Red Hat Enterprise Linux 8.6	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y
Red Hat Enterprise Linux 8.7	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y
Red Hat Enterprise Linux 8.8	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y
Red Hat Enterprise Linux 8.9	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y
Red Hat Enterprise Linux 8.10	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y
Red Hat Enterprise Linux 9.0	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y
Red Hat Enterprise Linux 9.1	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y
Red Hat Enterprise Linux 9.2	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y
Red Hat Enterprise Linux 9.3	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y
Red Hat Enterprise Linux 9.4	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y
Red Hat Enterprise Linux 9.5	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y
Red Hat Enterprise Linux 9.6	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y
Red Hat Enterprise Linux 9.7	Y	Y	Y	Y	Y	Y	N	Y	Y	Y
Red Hat Enterprise Linux 9.8	Y	N	N	Y	Y	Y	N	Y	Y	N
Red Hat Enterprise Linux 10.0	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y
Red Hat Enterprise Linux 10.1	Y	Y	Y	Y	Y	Y	N	Y	Y	Y
Red Hat Enterprise Linux 10.2	Y	Y	Y	Y	Y	Y	N	Y	Y	N
SUSE Linux Enterprise Server 12 SP5	N	N	N	N	N	N	N	N	N	Y
SUSE Linux Enterprise Server 12 SP5 with Xen	N	N	N	N	N	N	N	N	N	Y

	ST650 V3 (4th Gen Xeon)	SR860 V3	SR850 V3	SR655 V3	SR650 V3 (4th Gen Xeon)	SR635 V3	SE450	SR665 V3	SR645 V3	SR665
Operating systems										
SUSE Linux Enterprise Server 15 SP1	N	N	N	N	N	N	N	N	N	Y
SUSE Linux Enterprise Server 15 SP1 with Xen	N	N	N	N	N	N	N	N	N	Y
SUSE Linux Enterprise Server 15 SP2	N	N	N	N	N	N	N	N	N	Y
SUSE Linux Enterprise Server 15 SP2 with Xen	N	N	N	N	N	N	N	N	N	Y
SUSE Linux Enterprise Server 15 SP3	N	N	N	N	N	N	N	N	N	Y
SUSE Linux Enterprise Server 15 SP3 with Xen	N	N	N	N	N	N	N	N	N	Y
SUSE Linux Enterprise Server 15 SP4	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y
SUSE Linux Enterprise Server 15 SP4 with Xen	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y
SUSE Linux Enterprise Server 15 SP5	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y
SUSE Linux Enterprise Server 15 SP5 with Xen	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y
SUSE Linux Enterprise Server 15 SP6	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y
SUSE Linux Enterprise Server 15 SP7	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y
SUSE Linux Enterprise Server 16	Y	Y	N	Y	Y	Y	N	Y	Y	Y
Ubuntu 18.04.6 LTS or later with HWE kernel	N	N	N	N	N	N	Y	N	N	N
Ubuntu 20.04.5 LTS or later with HWE kernel	N	Y	Y	Y	N	Y	Y	Y	Y	N
Ubuntu 20.04 LTS or later with HWE kernel	N	N	N	N	Y	N	N	N	N	N
Ubuntu 22.04.2 LTS or later with HWE kernel	N	N	N	N	N	N	N	N	N	N
Ubuntu 22.04.3 LTS or later with HWE kernel	N	N	N	N	N	N	N	N	N	N
Ubuntu 22.04.5 LTS or later with HWE kernel	N	N	N	Y	N	Y	N	Y	Y	N
Ubuntu 22.04 LTS or later with HWE kernel	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y
Ubuntu 24.04.2 LTS or later with HWE kernel	N	N	N	N	N	N	N	N	N	N
Ubuntu 24.04 LTS or later with HWE kernel	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y
Ubuntu 26.04 LTS or later with HWE kernel	N	N	N	N	N	N	N	Y	N	N
VMware vSphere Hypervisor (ESXi) 6.7 U3	N	N	N	N	N	N	N	N	N	Y
VMware vSphere Hypervisor (ESXi) 7.0	N	N	N	N	N	N	N	N	N	Y
VMware vSphere Hypervisor (ESXi) 7.0 U1	N	N	N	N	N	N	N	N	N	Y
VMware vSphere Hypervisor (ESXi) 7.0 U2	N	N	N	N	N	N	N	N	N	Y
VMware vSphere Hypervisor (ESXi) 7.0 U3	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y
VMware vSphere Hypervisor (ESXi) 8.0	N	N	N	Y	Y	Y	Y	Y	Y	Y
VMware vSphere Hypervisor (ESXi) 8.0 U1	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y
VMware vSphere Hypervisor (ESXi) 8.0 U2	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y
VMware vSphere Hypervisor (ESXi) 8.0 U3	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y
VMware vSphere Hypervisor (ESXi) 9.0	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y
VMware vSphere Hypervisor ESXi 9.1	Y	Y	Y	Y	Y	Y	N	Y	Y	Y

IBM SKLM Key Management support

To effectively manage a large deployment of SEDs in Lenovo servers, IBM Security Key Lifecycle Manager (SKLM) offers a centralized key management solution.

The IBM Security Key Lifecycle Manager software is available from Lenovo using the ordering information listed in the following table.

Table 17. IBM Security Key Lifecycle Manager licenses

Part number	Description
7S0A007FWW	IBM Security Key Lifecycle Manager Basic Edition Install License + SW Subscription & Support 12 Months
7S0A007HWW	IBM Security Key Lifecycle Manager For Raw Decimal Terabyte Storage Resource Value Unit License + SW Subscription & Support 12 Months
7S0A007KWW	IBM Security Key Lifecycle Manager For Raw Decimal Petabyte Storage Resource Value Unit License + SW Subscription & Support 12 Months
7S0A007MWW	IBM Security Key Lifecycle Manager For Usable Decimal Terabyte Storage Resource Value Unit License + SW Subscription & Support 12 Months
7S0A007PWW	IBM Security Key Lifecycle Manager For Usable Decimal Petabyte Storage Resource Value Unit License + SW Subscription & Support 12 Months

Warranty

The ThinkSystem Vendor Agnostic Read Intensive NVMe SSDs carry a one-year, customer-replaceable unit (CRU) limited warranty. When the SSDs are installed in a supported server, these drives assume the system's base warranty and any warranty upgrades.

Solid State Memory cells have an intrinsic, finite number of program/erase cycles that each cell can incur. As a result, each solid state device has a maximum amount of program/erase cycles to which it can be subjected. The warranty for Lenovo solid state drives (SSDs) is limited to drives that have not reached the maximum guaranteed number of program/erase cycles, as documented in the Official Published Specifications for the SSD product. A drive that reaches this limit may fail to operate according to its Specifications.

Physical specifications

The Vendor Agnostic SSDs have the following dimensions (without the hot-swap tray):

- Height: 7 mm (0.3 in.) or 15mm (0.59 in.)
- Width: 70 mm (2.8 in.)
- Depth: 100 mm (4.0 in.)

Operating environment

The Vendor Agnostic SSDs are supported in the following environment:

- Temperature:
 - Operating: 0 to 70 °C (32 to 158 °F)
 - Non-operating: -40 °C to 85 °C (-40 to 185 °F)
- Relative humidity: 5 to 95% (noncondensing)
- Maximum altitude: 3,050 m (10,000 ft)

Agency approvals

The Vendor Agnostic SSDs conform to the following regulations:

- UL
- TUV
- FCC
- CE Mark
- C-Tick Mark
- BSMI (Taiwan)
- KCC (Korea EMI)

Related publications and links

For more information, see the following documents:

- Lenovo ThinkSystem SSD Portfolio comparison:
<https://lenovopress.com/lp1261-lenovo-thinksystem-ssd-portfolio>

Related product families

Product families related to this document are the following:

- [Drives](#)

Notices

Lenovo may not offer the products, services, or features discussed in this document in all countries. Consult your local Lenovo representative for information on the products and services currently available in your area. Any reference to a Lenovo product, program, or service is not intended to state or imply that only that Lenovo product, program, or service may be used. Any functionally equivalent product, program, or service that does not infringe any Lenovo intellectual property right may be used instead. However, it is the user's responsibility to evaluate and verify the operation of any other product, program, or service. Lenovo may have patents or pending patent applications covering subject matter described in this document. The furnishing of this document does not give you any license to these patents. You can send license inquiries, in writing, to:

Lenovo (United States), Inc.
8001 Development Drive
Morrisville, NC 27560
U.S.A.
Attention: Lenovo Director of Licensing

LENOVO PROVIDES THIS PUBLICATION "AS IS" WITHOUT WARRANTY OF ANY KIND, EITHER EXPRESS OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF NON-INFRINGEMENT, MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE. Some jurisdictions do not allow disclaimer of express or implied warranties in certain transactions, therefore, this statement may not apply to you.

This information could include technical inaccuracies or typographical errors. Changes are periodically made to the information herein; these changes will be incorporated in new editions of the publication. Lenovo may make improvements and/or changes in the product(s) and/or the program(s) described in this publication at any time without notice.

The products described in this document are not intended for use in implantation or other life support applications where malfunction may result in injury or death to persons. The information contained in this document does not affect or change Lenovo product specifications or warranties. Nothing in this document shall operate as an express or implied license or indemnity under the intellectual property rights of Lenovo or third parties. All information contained in this document was obtained in specific environments and is presented as an illustration. The result obtained in other operating environments may vary. Lenovo may use or distribute any of the information you supply in any way it believes appropriate without incurring any obligation to you.

Any references in this publication to non-Lenovo Web sites are provided for convenience only and do not in any manner serve as an endorsement of those Web sites. The materials at those Web sites are not part of the materials for this Lenovo product, and use of those Web sites is at your own risk. Any performance data contained herein was determined in a controlled environment. Therefore, the result obtained in other operating environments may vary significantly. Some measurements may have been made on development-level systems and there is no guarantee that these measurements will be the same on generally available systems. Furthermore, some measurements may have been estimated through extrapolation. Actual results may vary. Users of this document should verify the applicable data for their specific environment.

© Copyright Lenovo 2026. All rights reserved.

This document, LP2256, was created or updated on March 17, 2026.

Send us your comments in one of the following ways:

- Use the online Contact us review form found at:
<https://lenovopress.lenovo.com/LP2256>
- Send your comments in an e-mail to:
comments@lenovopress.com

This document is available online at <https://lenovopress.lenovo.com/LP2256>.

Trademarks

Lenovo and the Lenovo logo are trademarks or registered trademarks of Lenovo in the United States, other countries, or both. A current list of Lenovo trademarks is available on the Web at <https://www.lenovo.com/us/en/legal/copytrade/>.

The following terms are trademarks of Lenovo in the United States, other countries, or both:

Lenovo®

ServerProven®

System x®

ThinkAgile®

ThinkSystem®

The following terms are trademarks of other companies:

AMD is a trademark of Advanced Micro Devices, Inc.

Intel®, the Intel logo and Xeon® are trademarks of Intel Corporation or its subsidiaries.

Linux® is the trademark of Linus Torvalds in the U.S. and other countries.

Microsoft®, Hyper-V®, Windows Server®, and Windows® are trademarks of Microsoft Corporation in the United States, other countries, or both.

IBM® and IBM Security® are trademarks of IBM in the United States, other countries, or both.

Other company, product, or service names may be trademarks or service marks of others.