

ThinkSystem NVIDIA RTX PRO 4500 Blackwell Server Edition PCIe Gen5 GPU

Product Guide

The ThinkSystem NVIDIA RTX PRO 4500 Blackwell Server Edition PCIe Gen5 GPU delivers a versatile platform to accelerate Deep Learning, Graphics and video processing applications in the Cloud and at the Edge. It is a full-height full-length, single-slot card that features 32 GB of GDDR7 memory, PCIe Gen5 x16 connectivity at a 165W power envelope. It is passively cooled card with a superior thermal design requiring system airflow to operate and handles challenging ambient environments with ease.



Figure 1. ThinkSystem NVIDIA RTX PRO 4500 Blackwell Server Edition PCIe Gen5 GPU (mockup)

Did you know?

As part of the NVIDIA OVX server platform, RTX PRO 4500 Blackwell GPU delivers the highest level of graphics, ray tracing, and simulation performance for NVIDIA Omniverse. With passive cooling, the GPU is designed to operate in servers such as the ThinkSystem SR665 V3.

Part number information

The following table shows the part numbers for the RTX PRO 4500 Blackwell GPU.

Table 1. Ordering information

Part number	Feature code	Description	NVIDIA part number	Controlled GPU status
4X67B12675	CG6A	ThinkSystem NVIDIA RTX PRO 4500 Blackwell Server Edition 32GB PCIe Gen5 Passive GPU	900-2G147-2700-030	Controlled

The RTX PRO 4500 Blackwell GPU is Controlled which means the GPU is not offered in certain markets, as determined by the US Government.

The PCIe option part numbers includes the following:

- One RTX PRO 4500 Blackwell GPU with full-height (3U) adapter bracket attached
- Documentation

Features

The ThinkSystem NVIDIA RTX PRO 4500 Blackwell Server Edition PCIe Gen5 GPU delivers a versatile platform to accelerate Deep Learning, Graphics and video processing applications in the Cloud and at the Edge. It is a full-height full-length, single-slot card that features 32 GB of GDDR7 memory, PCIe Gen5 x16 connectivity at a 165W power envelope. It is passively cooled card with a superior thermal design requiring system airflow to operate and handles challenging ambient environments with ease.

Powered by the NVIDIA Blackwell Architecture, RTX PRO 4500 Blackwell GPU provides revolutionary multi-precision performance to accelerate deep learning and machine learning training and inference, AI-audio and video effects, data analytics, cloud gaming, rendering, video transcoding, virtual workstations, virtual desktop, and many other workloads.

As part of NVIDIA AI, the RTX PRO 4500 Blackwell GPU supports all AI frameworks and neural network models, delivering dramatic performance and efficiency that maximizes the utility of at-scale deployments.

Key features:

- Fifth-gen Tensor Cores with support for FP4 precision
- Fourth-gen Ray Tracing Cores
- 32 GB of GDDR7 memory
- 800 GB/s of memory bandwidth
- Ninth-gen NVENC and sixth-gen NVDEC with 4:2:2 support
- PCIe Gen 5

Target workloads

- Data processing with NVIDIA CUDA-X Libraries
- Vision AI with NVIDIA Metropolis
- Small-model inference
- Graphics and visual computing
- Video processing and streaming

With the RTX PRO 4500 Blackwell Server Edition, massive, fragmented, multimodal enterprise data can be transformed into AI-ready data. Vector index builds and vector search applications are accelerated and optimized with cuVS for existing databases and vector search libraries, delivering up to 50x performance over CPU-only systems.

Technical specifications

The following table lists the specifications of the RTX PRO 4500 Blackwell GPU.

Table 2. RTX PRO 4500 Blackwell GPU specifications

Feature	Specification
GPU Architecture	NVIDIA Blackwell Architecture
NVIDIA CUDA Cores	10,496
NVIDIA Tensor Cores	5th Generation
NVIDIA RT Cores	82 (4th Generation)
GPU Memory	32 GB GDDR7
Memory Interface	256-bit
Memory Bandwidth	Up to 800 GB/s
ECC	Yes
FP4 Tensor Core	1.6 PFLOPS (peak)
FP8 Tensor Core	811 TFLOPS
FP16 Tensor Core	406 TFLOPS
BF16 Tensor Core	406 TFLOPS
TF32 Tensor Core	203 TFLOPS
FP32 Single-Precision Performance	51 TFLOPS (peak)
RT Core performance	154 TFLOPS (peak)
Host Interface	PCIe 5.0 x16
NVLink support	No
Power Consumption	165 W
Multi-Instance GPU (MIG)	Up to 2 MIGs @ 16GB*
Thermal Solution	Passive cooling
Form Factor	4.4" H x 10.5" L, Single Slot, Full Height, Full Length
Display Connectors	None
Encode / Decode Engines	3x NVENC encode, 3x NVDEC decode

Server support

The following tables list the ThinkSystem servers that are compatible.

Table 3. Server support (Part 1 of 5)

Part Number	Description	AMD V3				2S Intel V3/V4						Multi Node V3	1S V3				
		SR635 V3 (7D9H / 7D9G)	SR655 V3 (7D9F / 7D9E)	SR645 V3 (7D9D / 7D9C)	SR665 V3 (7D9B / 7D9A)	ST650 V3 (7D7B / 7D7A)	SR630 V3 (7D72 / 7D73)	SR650 V3 (7D75 / 7D76)	SR630 V4 (7DG8 / 7DG9)	SR650 V4 (7DGC / 7DGD)	SR650a V4 (7DGC / 7DGD)	SD535 V3 (7DD8 / 7DD1)	SD530 V3 (7DDA / 7DD3)	SD550 V3 (7DD9 / 7DD2)	ST45 V3 (7DH4 / 7DH5)	ST50 V3 (7DF4 / 7DF3)	ST250 V3 (7DCF / 7DCE)
4X67B12675	ThinkSystem NVIDIA RTX PRO 4500 Blackwell Server Edition 32GB PCIe Gen5 Passive GPU	N	N	N	4 ¹	N	N	N	N	N	N	N	N	N	N	N	N

1. Supported with 5th Gen AMD EPYC processors only

Table 4. Server support (Part 2 of 5)

Part Number	Description	4S 8S Intel V3/V4					GPU Rich					Edge						
		SR650 V3 (7D97 / 7D96)	SR860 V3 (7D94 / 7D93)	SR950 V3 (7DC5 / 7DC4)	SR850 V4 (7DJT / 7DJS)	SR860 V4 (7DJQ / 7DJN)	SR670 V2 (7Z22 / 7Z23)	SR675 V3 (7D9Q / 7D9R)	SR680a V3 (7DHE)	SR680a V3 B200 (7DM9)	SR685a V3 (7DHC)	SR780a V3 (7DJ5)	SR680a V4 (7DMK)	SE100 (7DGR)	SE350 (7Z46 / 7D1X)	SE350 V2 (7DA9)	SE360 V2 (7DAM)	SE450 (7D8T)
4X67B12675	ThinkSystem NVIDIA RTX PRO 4500 Blackwell Server Edition 32GB PCIe Gen5 Passive GPU	N	N	N	N	N	N	N	N	N	N	N	N	N	N	N	N	N

Table 5. Server support (Part 3 of 5)

Part Number	Description	Super Computing						1S Intel V2		2S Intel V2		AMD V1						
		SC750 V4 (7DDJ)	SC777 V4 (7DKA)	SD665 V3 (7D9P)	SD665-N V3 (7DAZ)	SD650 V3 (7D7M)	SD650-I V3 (7D7L)	SD650-N V3 (7D7N)	ST50 V2 (7D8K / 7D8J)	ST250 V2 (7D8G / 7D8F)	SR250 V2 (7D7R / 7D7Q)	ST650 V2 (7Z75 / 7Z74)	SR630 V2 (7Z70 / 7Z71)	SR650 V2 (7Z72 / 7Z73)	SR635 (7Y98 / 7Y99)	SR655 (7Y00 / 7Z01)	SR645 (7D2Y / 7D2X)	SR665 (7D2W / 7D2V)
4X67B12675	ThinkSystem NVIDIA RTX PRO 4500 Blackwell Server Edition 32GB PCIe Gen5 Passive GPU	N	N	N	N	N	N	N	N	N	N	N	N	N	N	N	N	N

Table 6. Server support (Part 4 of 5)

Part Number	Description	Dense V2				4S V2	8S	4S V1		1S Intel V1					
		SD630 V2 (7D1K)	SD650 V2 (7D1M)	SD650-N V2 (7D1N)	SN550 V2 (7Z69)	SR850 V2 (7D31 / 7D32)	SR860 V2 (7Z59 / 7Z60)	SR950 (7X11 / 7X12)	SR850 (7X18 / 7X19)	SR850P (7D2F / 2D2G)	SR860 (7X69 / 7X70)	ST50 (7Y48 / 7Y50)	ST250 (7Y45 / 7Y46)	SR150 (7Y54)	SR250 (7Y52 / 7Y51)
4X67B12675	ThinkSystem NVIDIA RTX PRO 4500 Blackwell Server Edition 32GB PCIe Gen5 Passive GPU	N	N	N	N	N	N	N	N	N	N	N	N	N	N



Table 7. Server support (Part 5 of 5)

Part Number	Description	2S Intel V1							Dense V1			
		ST550 (7X09 / 7X10)	SR530 (7X07 / 7X08)	SR550 (7X03 / 7X04)	SR570 (7Y02 / 7Y03)	SR590 (7X98 / 7X99)	SR630 (7X01 / 7X02)	SR650 (7X05 / 7X06)	SR670 (7Y36 / 7Y37)	SD530 (7X21)	SD650 (7X58)	SN550 (7X16)
4X67B12675	ThinkSystem NVIDIA RTX PRO 4500 Blackwell Server Edition 32GB PCIe Gen5 Passive GPU	N	N	N	N	N	N	N	N	N	N	N

Auxiliary power cables

The RTX PRO 4500 Blackwell GPU option part number does not ship with auxiliary power cables. Cables are server-specific due to length requirements. For CTO orders, auxiliary power cables are derived by the configurator. For field upgrades, cables will need to be ordered separately as listed in the table below.

Table 8. Auxiliary power cables for RTX PRO 4500 Blackwell GPU

Auxiliary power cable needed with the SR665 V3	
<p>400mm 16-pin (2x6+4) cable</p>  <p>Feature: BRWK SBB: SBB7A66338 Base: SC17B33047 FRU: 03KM846 Option: SR665 V3: 4X67A85856, ThinkSystem SR665 V3 GPU Full Length Thermal Option Kit*</p>	
<p>400mm Y-cable with 2x 16-pin (2x6+4) connectors (connects to two GPUs)</p>  <p>Feature: CG6L SBB: SBB7B10414 Base: SC17C34528 FRU: 03PU324 Option: None</p> <p>Cable usage in the SR665 V3:</p> <ul style="list-style-type: none"> • With 1, 2, or 3 GPUs, use 3x cable BRWK (GPUs in slots 1, 4, 7) • With 4 GPUs, use 2x cable BRWK (slots 1, 4) and 1x cable CG6L (slots 7 & 8) <p>* The option part numbers are for thermal kits and include other components needed to install the GPU. See the server product guide for details.</p>	

Regulatory approvals

The RTX PRO 4500 Blackwell GPU has the following regulatory approvals:

- RCM
- BSMI
- CE
- FCC
- ICES
- KCC
- cUL, UL
- VCCI

Operating environment

The RTX PRO 4500 Blackwell GPU has the following operating characteristics:

- Ambient temperature
 - Operational: 0°C to 50°C (-5°C to 55°C for short term*)
 - Storage: -40°C to 75°C
- Relative humidity:
 - Operational: 5-85% (5-93% short term*)
 - Storage: 5-95%

* A period not more than 96 hours consecutive, not to exceed 15 days per year.

Warranty

One year limited warranty. When installed in a Lenovo server, the GPU assumes the server's base warranty and any warranty upgrades.

Related publications

For more information, refer to these documents:

- ThinkSystem and ThinkAgile GPU Summary:
<https://lenovopress.lenovo.com/lp0768-thinksystem-thinkagile-gpu-summary>
- ServerProven compatibility:
<https://serverproven.lenovo.com/>
- RTX PRO 4500 Blackwell GPU product page:
<https://www.nvidia.com/en-us/data-center/rtx-pro-4500-blackwell-server-edition/>

Related product families

Product families related to this document are the following:

- [GPU adapters](#)

Notices

Lenovo may not offer the products, services, or features discussed in this document in all countries. Consult your local Lenovo representative for information on the products and services currently available in your area. Any reference to a Lenovo product, program, or service is not intended to state or imply that only that Lenovo product, program, or service may be used. Any functionally equivalent product, program, or service that does not infringe any Lenovo intellectual property right may be used instead. However, it is the user's responsibility to evaluate and verify the operation of any other product, program, or service. Lenovo may have patents or pending patent applications covering subject matter described in this document. The furnishing of this document does not give you any license to these patents. You can send license inquiries, in writing, to:

Lenovo (United States), Inc.
8001 Development Drive
Morrisville, NC 27560
U.S.A.
Attention: Lenovo Director of Licensing

LENOVO PROVIDES THIS PUBLICATION "AS IS" WITHOUT WARRANTY OF ANY KIND, EITHER EXPRESS OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF NON-INFRINGEMENT, MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE. Some jurisdictions do not allow disclaimer of express or implied warranties in certain transactions, therefore, this statement may not apply to you.

This information could include technical inaccuracies or typographical errors. Changes are periodically made to the information herein; these changes will be incorporated in new editions of the publication. Lenovo may make improvements and/or changes in the product(s) and/or the program(s) described in this publication at any time without notice.

The products described in this document are not intended for use in implantation or other life support applications where malfunction may result in injury or death to persons. The information contained in this document does not affect or change Lenovo product specifications or warranties. Nothing in this document shall operate as an express or implied license or indemnity under the intellectual property rights of Lenovo or third parties. All information contained in this document was obtained in specific environments and is presented as an illustration. The result obtained in other operating environments may vary. Lenovo may use or distribute any of the information you supply in any way it believes appropriate without incurring any obligation to you.

Any references in this publication to non-Lenovo Web sites are provided for convenience only and do not in any manner serve as an endorsement of those Web sites. The materials at those Web sites are not part of the materials for this Lenovo product, and use of those Web sites is at your own risk. Any performance data contained herein was determined in a controlled environment. Therefore, the result obtained in other operating environments may vary significantly. Some measurements may have been made on development-level systems and there is no guarantee that these measurements will be the same on generally available systems. Furthermore, some measurements may have been estimated through extrapolation. Actual results may vary. Users of this document should verify the applicable data for their specific environment.

© Copyright Lenovo 2026. All rights reserved.

This document, LP2391, was created or updated on March 17, 2026.

Send us your comments in one of the following ways:

- Use the online Contact us review form found at:
<https://lenovopress.lenovo.com/LP2391>
- Send your comments in an e-mail to:
comments@lenovopress.com

This document is available online at <https://lenovopress.lenovo.com/LP2391>.

Trademarks

Lenovo and the Lenovo logo are trademarks or registered trademarks of Lenovo in the United States, other countries, or both. A current list of Lenovo trademarks is available on the Web at <https://www.lenovo.com/us/en/legal/copytrade/>.

The following terms are trademarks of Lenovo in the United States, other countries, or both:

Lenovo®

ServerProven®

ThinkAgile®

ThinkSystem®

The following terms are trademarks of other companies:

AMD and AMD EPYC™ are trademarks of Advanced Micro Devices, Inc.

Intel®, the Intel logo is a trademark of Intel Corporation or its subsidiaries.

DirectX® is a trademark of Microsoft Corporation in the United States, other countries, or both.

Other company, product, or service names may be trademarks or service marks of others.