



# IBM High IOPS SSD PCIe Adapters (Withdrawn)

Product Guide (withdrawn product)

The IBM High IOPS SSD PCIe Adapters provide a new generation of ultra-high-performance storage based on solid state device technology for System x and BladeCenter. These adapters are alternatives to disk drives and are available in several sizes, from 160 GB to 1.2 TB. Designed for high-performance servers and computing appliances, these adapters deliver throughput of up to 300,000 I/O operations per second (IOPS), while providing the added benefits of lower power, cooling, and management overhead, and a smaller storage footprint.

The IBM 320GB High IOPS SSD PCIe Adapter is shown in Figure 1.





# Did you know?

These adapters use flash memory as the storage medium, contain no moving parts, and do not have the issues associated with vibration, noise, and mechanical failure. The adapters are built as block devices on a PCIe bus with advanced wear-leveling, advanced ECC, and N+1 chip-level redundancy, providing unparalleled reliability and efficiency.

## Part number information

Table 1 lists the ordering part numbers and feature codes.

Description	Part number	Feature code
IBM 160GB High IOPS SS Class SSD PCIe Adapter	46M0877	0096
IBM 320GB High IOPS MS Class SSD PCIe Adapter	46M0898	1649
IBM 320GB High IOPS SD Class SSD PCIe Adapter	46M0878	0097
320GB High IOPS SLC Adapter for IBM System x	81Y4535	A1NE
640GB High IOPS MLC Adapter for IBM System x	81Y4531	A1NC
640GB High IOPS MLC Duo Adapter for IBM System x	81Y4519	5985
640GB High IOPS SLC Duo Adapter for IBM System x	81Y4539	A1ND
1.28TB High IOPS MLC Duo Adapter for IBM System x	81Y4527	A1NB

The part numbers for the adapters include the following items:

- One PCIe adapter with 3U bracket
- 2U bracket (except for the Duo adapters, 81Y4519, 81Y4539, and 81Y4527)
- Quick install guide
- Documentation on a USB key
- Safety flyer

Figure 2 shows the 640GB High IOPS SLC Duo Adapter for IBM System x



Figure 2. 640GB High IOPS SLC Duo Adapter for IBM System x

### Features

Based on standard PCIe architecture coupled with silicon-based NAND clustering storage technology, the High IOPS Adapters are optimized for System x racks and can be deployed in blades via the PCIe expansion units. These scalable designs come with both Single Level Cell (SLC) and MultiLevel Cell (MLC) technologies in standard PCIe form factors. While MLC offers a cost-effective alternative, SLC provides over 12X more endurance and up to 30% better performance over MLC.

These adapters use NAND flash memory as the basic building block of solid-state storage and contain no moving parts, thus they are less sensitive to issues associated with vibration, noise, and mechanical failure. These adapters are built as block devices on a PCIe bus with advanced wear-leveling, ECC, and N+1 chip-level redundancy providing unparalleled reliability and efficiency.

Typical uses are applications with ultra-high performance I/O needs:

- Data-in-memory applications
- Medium to large databases
- Cache
- Video
- Data warehousing
- · Business intelligence and analytics
- Decision support

The IBM High IOPS SSD PCIe Adapters have the following features:

#### Performance features:

- High performance 230 times better IOPS. That means, for example, 97,014 IOPS at 4K block random reads versus 420 IOPS for a 15K RPM 146GB disk drive.
- Low latency of 50 ?s 1% of the latency of a 15K RPM 146GB disk drive.
- 600 MB/s random writes sustained.

#### **Reliability features:**

- Predictable lifetime.
- Up to 25 years of data retention.
- N+1 redundancy built-in to ensure data protection
- Available in SLC or MLC
- 11-bit ECC protection.
- Advance bad-block management algorithms enable taking blocks out of service when their failure rate becomes unacceptable.
- IBM High IOPS Launch Manager management suite.

#### **Energy efficiency features:**

- Low power consumption for performance: 9W delivering 100,000 IOPS versus 5.5W for 420 IOPS from a 15K RPM 146GB disk drive.
- Only 57 kWh/yr at 100,000 IOPS sustained.

# **Specifications**

The IBM High IOPS SSD PCIe Adapters have the following specifications:

- Storage capacity from 160 GB to 1.28 TB
- Functions as a PCIe storage and controller device -- operating system sees a block device
- PCI Express host interface as listed in Table 2

Note: These adapters cannot be used as bootable devices.

Table 2. PCI Express host interface specification

Description	Part number	PCIe interface
IBM 160GB High IOPS SS Class SSD PCIe Adapter	46M0877	PCle 1.0a (Gen1) x4
IBM 320GB High IOPS MS Class SSD PCIe Adapter	46M0898	PCle 1.0a (Gen1) x4
IBM 320GB High IOPS SD Class SSD PCle Adapter	46M0878	PCIe 2.0 (Gen2) x8
320GB High IOPS SLC Adapter for IBM System x	81Y4535	PCle 1.0a (Gen1) x4
640GB High IOPS MLC Adapter for IBM System x	81Y4531	PCle 1.1 (Gen1) x4
640GB High IOPS MLC Duo Adapter for IBM System x	81Y4519	PCIe 2.0 (Gen2) x8
640GB High IOPS SLC Duo Adapter for IBM System x	81Y4539	PCIe 2.0 (Gen2) x8
1.28TB High IOPS MLC Duo Adapter for IBM System x	81Y4527	PCIe 2.0 (Gen2) x8

# Comparison

Table 3 shows a comparison between the High IOPS SSD PCIe Adapters and solid-state drives.

			High	IOPS SSD	Cle Adapters Solid-state								
Model	160 SLC	320 MLC	320 SLC	320 SLC Duo	640 MLC	640 MLC Duo	640 SLC Duo	1.28 MLC	eXFlash 1.8" 50GB MLC (8 drives)	eXFlash 1.8" 200GB MLC (8 drives)			
Part number	46M0877	46M0898	81Y4535	46M0878	81Y4531	81Y4519	81Y4539	81Y4527	43W7726	43W7746			
Capacity	160 GB	320 GB	320 GB	320 GB	640 GB	640 GB	640 GB	1.28 TB	400 GB	1.6 TB			
Max IOPS 4KB Read	129K	128K	189K	301K	129K	301K	358K	316K	Non-RAID RAID 5: 12	: 203K; 21K			
Max IOPS 4KB Write	130K	108K	154K	110K	136K	109K	374K	277K	Non-RAID RAID 5: 22	: 140K; 2K			
Max transfer Read	754 MBps	735 MBps	787 MBps	1524 MBps	763 MBps	1703 MBps	1538 MBps	1511 MBps	Non-RAID MBps; RA MBps	: 2052 ID 5: 1668			
Max transfer Write	635 MBps	476 MBps	769 MBps	1129 MBps	543 MBps	961 MBps	1047 MBps	818 MBps	Non-RAID MBps; RA MBps	: 1864 ID 5: 1141			

Table 3. Comparison

# **Physical specifications**

Table 4 lists the dimensions and weight of each card.

#### Table 4. Physical specifications

Adapter	Dimensions
IBM 160GB High IOPS SS Class SSD PCIe Adapter	Height: 1.6 cm (0.625 in)
320GB High IOPS SLC Adapter for IBM System x	Depth: 16.8 cm (6.625 in)
640GB High IOPS MLC Adapter for IBM System x	Weight: 138 g (0.3 lb)
IBM 320GB High IOPS SD Class SSD PCIe Adapter	Height: 1.6 cm (0.625 in)
640GB High IOPS MLC Duo Adapter for IBM System x	Width: 11.0 cm (2.75 in)
640GB High IOPS SLC Duo Adapter for IBM System x	Depth: 17.0 cm (6.625 in)
1.28TB High IOPS MLC Duo Adapter for IBM System x	Weight: 279 g (0.61 lb)

## **Operating environment**

The adapters are supported in this environment:

- Temperature:
  - 10° to 35°C (50° to 95°F) at 0 to 914 m (0 to 3,000 ft)
  - 10° to 32°C (50° to 32°F) at 914 to 2,133 m (3,000 to 7,000 ft)
- Relative humidity:
  - 20% to 80% (non-condensing)

## Warranty

The IBM High IOPS SSD PCIe Adapters have a three-year limited warranty.

#### **Supported servers**

The IBM High IOPS SSD PCIe Adapters are supported in the IBM System x servers listed in Table 5.

Table 5. Subbulled System & Servers (Fail 1)	Table 5.	Supported	System x servers	(Part 1)
--	----------	-----------	------------------	----------

		00 M3	00 M2	00 M3	50 M2	50 M3	<b>30 M2</b>	00 M3	<b>30 M2</b>	00 M3	50	50 M2	50 M3	20 M3
		x31(	x32(	x32(	x32!	x32(	x34(	x34(	x35(	×35(	x35!	x35!	x35!	x362
IBM 160GB High IOPS SS Class SSD PCIe Adapter	46M0877	N	N	N	Ν	Ν	Ν	N	Ν	Ν	Ν	Ν	Y	N
IBM 320GB High IOPS MS Class SSD PCIe Adapter	46M0898	N	N	N	N	Ν	Ν	N	Ν	Ν	N	N	Y	N
IBM 320GB High IOPS SD Class SSD PCIe Adapter	46M0878	N	N	N	N	Ν	N	N	Ν	N	N	Ν	Y	N
320GB High IOPS SLC Adapter for IBM System x	81Y4535	N	N	N	Ν	Ν	Ν	N	Ν	Ν	Ν	Y	Y	Y
640GB High IOPS MLC Adapter for IBM System x	81Y4531	N	N	N	Ν	Ν	Ν	N	Ν	Ν	Ν	Y	Y	Y
640GB High IOPS MLC Duo Adapter for IBM System x	81Y4519	N	N	N	Ν	Ν	Ν	N	Ν	Ν	Ν	Y	Y	Y
640GB High IOPS SLC Duo Adapter for IBM System x	81Y4539	N	N	N	Ν	Ν	Ν	N	Ν	Ν	Ν	Y	Y	Y
1.28TB High IOPS MLC Duo Adapter for IBM System x	81Y4527	N	N	N	Ν	Ν	Ν	N	Ν	Ν	Ν	Y	Y	Y

Table 5. Supported System x servers (Part 2)

		3630 M3	3650 T	3650 M2	3650 M3	3655	3690 X5	3755	3755 M3	3850 M2	3950 M2	3850 X5	S22	X5
		×	X	X	×	X	×	X	X	X	X	×	Ξ	Ή
IBM 160GB High IOPS SS Class SSD PCle Adapter	46M0877	N	N	Y	Y	N	Y	N	N	Y	Y	Y	Y*	N
IBM 320GB High IOPS MS Class SSD PCle Adapter	46M0898	N	N	Y	Y	N	Y	N	N	Y	Y	Y	Y*	N
IBM 320GB High IOPS SD Class SSD PCle Adapter	46M0878	N	N	Y	Y	N	Y	N	N	Y	Y	Y	N	Y†
320GB High IOPS SLC Adapter for IBM System x	81Y4535	Y	N	Y	Y	N	Y	N	N	N	N	Y	N	N
640GB High IOPS MLC Adapter for IBM System x	81Y4531	Y	N	Y	Y	N	Y	N	N	N	N	Y	N	N
640GB High IOPS MLC Duo Adapter for IBM System x	81Y4519	Y	N	Y	Y	N	Y	N	N	Y	Y	Y	Y*	N
640GB High IOPS SLC Duo Adapter for IBM System x	81Y4539	Y	N	Y	Y	N	Y	N	N	N	N	Y	N	N
1.28TB High IOPS MLC Duo Adapter for IBM System x	81Y4527	Y	N	Y	Y	N	Y	N	N	N	N	Y	N	N

\* The HS22 supports these adapters with the addition of the IBM BladeCenter PCI Express I/O Expansion Unit (PEU3e), part number 43W4391

† The HX5 supports these adapters with the addition of the IBM BladeCenter PCI Express Gen 2 Expansion Blade (BPE4), part number 46M6730

See IBM ServerProven for the latest information on the adapters supported by each System x server type: http://ibm.com/servers/eserver/serverproven/compat/us/.

### Supported operating systems

The IBM High IOPS SSD PCIe Adapters support the following operating systems:

- Microsoft Windows Server 2003/2003 R2, Datacenter x64 Edition
- Microsoft Windows Server 2003/2003 R2, Enterprise x64 Edition
- Microsoft Windows Server 2003/2003 R2, Standard x64 Edition
- Microsoft Windows Server 2008 R2
- Microsoft Windows Server 2008, Datacenter x64 Edition
- Microsoft Windows Server 2008, Enterprise x64 Edition
- Microsoft Windows Server 2008, Standard x64 Edition
- Microsoft Windows Server 2008, Web x64 Edition
- Microsoft Windows Small Business Server 2008 Premium Edition
- Microsoft Windows Small Business Server 2008 Standard Edition
- Red Hat Enterprise Linux 5 Server with Xen x64 Edition
- Red Hat Enterprise Linux 5 Server x64 Edition
- Red Hat Enterprise Linux 6 Server x64 Edition
- SUSE LINUX Enterprise Server 10 for AMD64/EM64T
- SUSE LINUX Enterprise Server 10 with Xen for AMD64/EM64T
- SUSE LINUX Enterprise Server 11 for AMD64/EM64T
- SUSE LINUX Enterprise Server 11 with Xen for AMD64/EM64T

#### **Related publications**

For more information refer to these documents:

- IBM High IOPS SSD PCIe Adapters documentation
  - IBM High IOPS SSD Management Application
  - Release Notes
  - User Guide for Linux
  - User Guide for Windows

http://ibm.com/support/entry/portal/docdisplay?Indocid=MIGR-5083907

- IBM High IOPS SSD PCIe Adapters product page http://www.ibm.com/systems/storage/disk/ssd/ssd\_adapters.html
- IBM US Announcement Letters
   http://ibm.com/common/ssi/cgi-bin/ssialias?infotype=dd&subtype=ca&&htmlfid=897/ENUS109-396
   http://ibm.com/common/ssi/cgi-bin/ssialias?infotype=dd&subtype=ca&&htmlfid=897/ENUS111-051
- IBM System x Configuration and Options Guide http://www.ibm.com/support/docview.wss?uid=psg1SCOD-3ZVQ5W

#### **Related product families**

Product families related to this document are the following:

PCIe Flash Adapters

#### **Notices**

Lenovo may not offer the products, services, or features discussed in this document in all countries. Consult your local Lenovo representative for information on the products and services currently available in your area. Any reference to a Lenovo product, program, or service is not intended to state or imply that only that Lenovo product, program, or service may be used. Any functionally equivalent product, program, or service that does not infringe any Lenovo intellectual property right may be used instead. However, it is the user's responsibility to evaluate and verify the operation of any other product, program, or service. Lenovo may have patents or pending patent applications covering subject matter described in this document. The furnishing of this document does not give you any license to these patents. You can send license inquiries, in writing, to:

Lenovo (United States), Inc. 8001 Development Drive Morrisville, NC 27560 U.S.A. Attention: Lenovo Director of Licensing

LENOVO PROVIDES THIS PUBLICATION "AS IS" WITHOUT WARRANTY OF ANY KIND, EITHER EXPRESS OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF NON-INFRINGEMENT, MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE. Some jurisdictions do not allow disclaimer of express or implied warranties in certain transactions, therefore, this statement may not apply to you.

This information could include technical inaccuracies or typographical errors. Changes are periodically made to the information herein; these changes will be incorporated in new editions of the publication. Lenovo may make improvements and/or changes in the product(s) and/or the program(s) described in this publication at any time without notice.

The products described in this document are not intended for use in implantation or other life support applications where malfunction may result in injury or death to persons. The information contained in this document does not affect or change Lenovo product specifications or warranties. Nothing in this document shall operate as an express or implied license or indemnity under the intellectual property rights of Lenovo or third parties. All information contained in this document was obtained in specific environments and is presented as an illustration. The result obtained in other operating environments may vary. Lenovo may use or distribute any of the information you supply in any way it believes appropriate without incurring any obligation to you.

Any references in this publication to non-Lenovo Web sites are provided for convenience only and do not in any manner serve as an endorsement of those Web sites. The materials at those Web sites are not part of the materials for this Lenovo product, and use of those Web sites is at your own risk. Any performance data contained herein was determined in a controlled environment. Therefore, the result obtained in other operating environments may vary significantly. Some measurements may have been made on development-level systems and there is no guarantee that these measurements will be the same on generally available systems. Furthermore, some measurements may have been estimated through extrapolation. Actual results may vary. Users of this document should verify the applicable data for their specific environment.

#### © Copyright Lenovo 2024. All rights reserved.

This document, TIPS0729, was created or updated on January 4, 2012.

Send us your comments in one of the following ways:

- Use the online Contact us review form found at: https://lenovopress.lenovo.com/TIPS0729
- Send your comments in an e-mail to: comments@lenovopress.com

This document is available online at https://lenovopress.lenovo.com/TIPS0729.

### Trademarks

Lenovo and the Lenovo logo are trademarks or registered trademarks of Lenovo in the United States, other countries, or both. A current list of Lenovo trademarks is available on the Web at <a href="https://www.lenovo.com/us/en/legal/copytrade/">https://www.lenovo.com/us/en/legal/copytrade/</a>.

The following terms are trademarks of Lenovo in the United States, other countries, or both: Lenovo® BladeCenter® ServerProven® System x®

The following terms are trademarks of other companies:

Linux® is the trademark of Linus Torvalds in the U.S. and other countries.

Microsoft®, Windows Server®, and Windows® are trademarks of Microsoft Corporation in the United States, other countries, or both.

Other company, product, or service names may be trademarks or service marks of others.