

SATA 1.8-inch and 2.5-inch MLC Enterprise SSDs for System x

Product Guide (withdrawn product)

The SATA 1.8-inch and 2.5-inch MLC Enterprise solid-state drives (SSDs) for System x employ enterprise MLC NAND technology to bring an affordable, but performance-driven solution for applications requiring enterprise workloads with a mix of read-write operations. These industry standard 1.8-inch and 2.5-inch form factor SSD drives use a single-chip controller with a SATA interface on the system side and n-channels of NAND flash internally. They are targeted at databases and other enterprise workloads that require high I/O performance in random read and write operations including applications caching and tiering.

Figure 1 shows the SATA 1.8-inch MLC Enterprise SSD.



Figure 1. SATA 1.8-inch MLC Enterprise SSD

Did you know?

SATA MLC Enterprise solid-state drives for System x can be fully re-written up to eight times per day throughout their entire five-year life expectancy. These SSDs provide outstanding performance, endurance, reliability, and energy efficiency for both read- and write-intensive enterprise applications such as databases, data warehouses, corporate email and collaboration, actively connected users, medical imaging, and others.

Providing additional peace of mind, SATA 1.8-inch and 2.5-inch Enterprise MLC SSDs are covered under warranty. The drives carry a 1-year limited warranty, or when installed in an System x server, these drives assume your system's base warranty.

Part number information

Table 1 lists the information for ordering part numbers and feature codes.

Table 1. Ordering part numbers and feature codes

Description	Part number	Feature code
2.5-inch SSDs		
100GB SATA 2.5" MLC HS Enterprise SSD	00W1125	A3HR
100GB SATA 2.5" MLC SS Enterprise SSD	00W1130	A3HS
1.8-inch SSDs		
100GB SATA 1.8" MLC Enterprise SSD	00W1120	A3HQ
200GB SATA 1.8" MLC Enterprise SSD	49Y6119	A3AN
400GB SATA 1.8" MLC Enterprise SSD	49Y6124	A3AP

The part numbers include the following items:

- One SSD without a drive tray (1.8-inch SSDs) or one SSD with a hot-swap or simple-swap drive tray (2.5-inch SSDs)
- Technical Update Flyer
- Warranty Flyer
- *Important Notices* document

Figure 2 shows the SATA 2.5-inch MLC Enterprise SSD.



Figure 2. SATA 2.5-inch MLC Enterprise SSD

Features

- Industry standard 1.8-inch or 2.5-inch form factors
- Support for standard 2.5-inch drive bay (2.5-inch SSDs) or eXFlash drive bay (1.8-inch SSDs) or SSD drive bay (1.8-inch SSDs) on selected System x, iDataPlex®, BladeCenter® and Flex System™ servers
- Utilizes industry leading 24 nm MLC
- Cost-effective enterprise-grade MLC (eMLC) NAND technology
- MLC SATA drive with high read and write performance to fulfill client needs in the enterprise space
- High endurance, with up to six PB of total bytes written (TBW) to withstand applications with intensive read-write workloads
- Energy saving, with as little as 2.8 - 4.6 watt power consumption per drive
- Absence of moving parts to reduce potential failure points in the server
- Native command queuing (NCQ) with a queue depth of 32
- S.M.A.R.T. support
- Advanced Encrypting Standard (AES) 256-bit encryption
- Enterprise data path protection
- 55 bits per 512-byte sector ECC/EDC (BCH)
- Static wear leveling evenly distributes data across the drive
- Bad block management replaces failed blocks with new ones from the spare pool
- Performance throttling to ensure the lifetime expectation is met
- Power and thermal throttling to extend the life of the drive
- Data retention management to ensure availability and integrity of stored data
- Minimal write amplification for efficient flash utilization and extended life time

The key difference between Enterprise SSDs and Enterprise Value SSDs is their endurance (or life expectancy). SSDs have a huge but finite number of program/erase (P/E) cycles, which affects how long they can perform write operations and thus their life expectancy. Enterprise SSDs have significantly better endurance but higher cost/IOPS ratio compared to Enterprise Value SSDs. SSD write endurance is typically measured by the number of program/erase cycles that the drive can incur over its lifetime, listed as TBW in the device specification.

For example, with 400 GB SATA 1.8-inch MLC Enterprise SSD, the entire 400 GB can be fully re-written up to eight times per day (more than 3 TB writes per day) to meet the five-year lifetime expectation of the drive, while the Enterprise Value SSD can only sustain up to 40 GB writes per day (75 times less) to provide the same five-year lifetime.

Technical specifications

Table 2 presents technical specifications for the SATA MLC Enterprise solid-state drives.

Table 2. SATA MLC Enterprise SSD technical specifications

Specification	100 GB			200 GB	400 GB
Part number	00W1120	00W1125	00W1130	49Y6119	49Y6124
Interface	6 Gbps SATA	6 Gbps SATA	6 Gbps SATA	6 Gbps SATA	6 Gbps SATA
Hot-swap drive	Yes§	Yes	No	Yes§	Yes§
Form factor	1.8-inch	2.5-inch	2.5-inch	1.8-inch	1.8-inch
Capacity	100 GB	100 GB	100 GB	200 GB	400 GB
Endurance	5-year life time (1.5 PB TBW)	5-year life time (1.5 PB TBW)	5-year life time (1.5 PB TBW)	5-year life time (3 PB TBW)	5-year life time (6 PB TBW)
Data reliability	< 1 in 10 ¹⁸ bits read	< 1 in 10 ¹⁸ bits read	< 1 in 10 ¹⁸ bits read	< 1 in 10 ¹⁸ bits read	< 1 in 10 ¹⁸ bits read
MTBF	> 2,500,000 hours	> 2,500,000 hours	> 2,500,000 hours	> 2,500,000 hours	> 2,500,000 hours
IOPS read*	60,000	60,000	60,000	60,000	60,000
IOPS write*	40,000	40,000	40,000	40,000	40,000
Sequential read rate†	520 MBps	520 MBps	520 MBps	520 MBps	520 MBps
Sequential write rate†	500 MBps	500 MBps	500 MBps	500 MBps	500 MBps
Access time	< 0.1 ms	< 0.1 ms	< 0.1 ms	< 0.1 ms	< 0.1 ms
Shock	200 g, 10 ms 1500 g, 1 ms 1000 g, 0.5 ms	200 g, 10 ms 1500 g, 1 ms 1000 g, 0.5 ms	200 g, 10 ms 1500 g, 1 ms 1000 g, 0.5 ms	200 g, 10 ms 1500 g, 1 ms 1000 g, 0.5 ms	200 g, 10 ms 1500 g, 1 ms 1000 g, 0.5 ms
Vibration, operating	0.67 g rms 5-500 Hz	0.67 g rms 5-500 Hz	0.67 g rms 5-500 Hz	0.67 g rms 5-500 Hz	0.67 g rms 5-500 Hz
Vibration, non-operating	1.04 g rms 2-200 Hz	1.04 g rms 2-200 Hz	1.04 g rms 2-200 Hz	1.04 g rms 2-200 Hz	1.04 g rms 2-200 Hz
Typical power, reads	2.8 W	2.8 W	2.8 W	2.8 W	2.8 W
Typical power, writes	4.6 W	4.6 W	4.6 W	4.6 W	4.6 W

§ This SSD can be a hot-swap or non-hot-swap drive depending on the server in which it is installed.

* 4 KB block transfers

† 128 KB block transfers

The TBW value assigned to a solid-state device is the total bytes of written data (based on the number of P/E cycles) that a drive can be guaranteed to complete (% of remaining P/E cycles = % of remaining TBW). Reaching this limit does not cause the drive to immediately fail; the TBW simply denotes the maximum number of writes that can be guaranteed. A solid-state device will not fail upon reaching the specified TBW, but at some point after surpassing the TBW value (and based on manufacturing variance margins), the drive will reach the end-of-life point, at which time the drive will go into read-only mode. Because of such behavior by solid-state drives, careful planning must be done to use SSDs in the application environments to ensure that the TBW of the drive will not be exceeded prior to the required life expectancy.

Supported servers

The SATA MLC Enterprise SSDs and supported RAID controllers can be installed in the System x and iDataPlex servers identified in Table 3 and the BladeCenter and Flex System servers identified in Table 4.

Table 3. Supported System x and iDataPlex servers (Part 1)

Part number	Product description	x3200 M3 (7327, 7328)	x3250 M3 (4251, 4252)	x3400 M3 (7378, 7379)	x3500 M3 (7380)	x3550 M3 (7944)	x3620 M3 (7376)	x3630 M3 (7377)	x3650 M3 (7945)	x3755 M3 (7164)	dx360 M3 (6391)
00W1120	100GB SATA 1.8" MLC Enterprise SSD	N	N	N	N	N	N	N	N	N	N
00W1125	100GB SATA 2.5" MLC HS Enterprise SSD	Y	Y	Y	Y	Y	N	Y	Y	N	N
00W1130	100GB SATA 2.5" MLC SS Enterprise SSD	N	N	N	N	Y	N	N	N	N	Y
49Y6119	200GB SATA 1.8" MLC Enterprise SSD	N	N	N	N	N	N	N	N	N	N
49Y6124	400GB SATA 1.8" MLC Enterprise SSD	N	N	N	N	N	N	N	N	N	N

Table 3. Supported System x and iDataPlex servers (Part 2)

Part number	Product description	x3100 M4 (2582)	x3250 M4 (2583)	x3300 M4 (7382)	x3500 M4 (7383)	x3530 M4 (7160)	x3550 M4 (7914)	x3630 M4 (7158)	x3650 M4 (7915)	x3690 X5 (7147)	x3750 M4 (8722)	x3850 X5 (7143)	dx360 M4 (7912)
00W1120	100GB SATA 1.8" MLC Enterprise SSD	N	N	N	N	N	N	N	Y	Y	Y	Y	N
00W1125	100GB SATA 2.5" MLC HS Enterprise SSD	Y	Y	Y	Y	Y	Y	N	Y	Y	Y	Y	N
00W1130	100GB SATA 2.5" MLC SS Enterprise SSD	N	Y	N	N	Y	N	N	N	N	N	N	Y
49Y6119	200GB SATA 1.8" MLC Enterprise SSD	N	N	N	N	N	N	N	Y	Y	Y	Y	N
49Y6124	400GB SATA 1.8" MLC Enterprise SSD	N	N	N	N	N	N	N	Y	Y	Y	Y	N

Table 4. Supported BladeCenter and Flex System servers

Part number	Product description	HS12 (8028)	HS22 (7870)	HS22V (7871)	HS23 (7875)	HS23E (8038)	HX5 (7873)	x220 (7906)	x240 (8737)	x440 (7917)
00W1120	100GB SATA 1.8" MLC Enterprise SSD	N	N	Y	N	N	Y	N	N	N
00W1125	100GB SATA 2.5" MLC HS Enterprise SSD	N	Y	N	Y	Y	N	Y	Y	Y
00W1130	100GB SATA 2.5" MLC SS Enterprise SSD	N	N	N	N	N	N	N	N	N
49Y6119	200GB SATA 1.8" MLC Enterprise SSD	N	N	Y	N	N	Y	N	N	N
49Y6124	400GB SATA 1.8" MLC Enterprise SSD	N	N	Y	N	N	Y	N	N	N

See the ServerProven® website for the latest compatibility information for System x, BladeCenter, iDataPlex and Flex System servers: <http://www.lenovo.com/us/en/serverproven/>

Supported storage controllers

The SATA MLC Enterprise SSDs require a supported disk controller. Table 5 lists the System x controllers that support these solid-state drives installed in a supported server. Table 6 lists the BladeCenter and Flex System controllers that support these solid-state drives installed in a supported server.

Table 5. RAID controllers for System x and iDataPlex servers supported with internal SSDs (Part 1)

Part number	Product description	x3200 M3 (7327, 7328)	x3250 M3 (4251, 4252)	x3400 M3 (7378, 7379)	x3500 M3 (7380)	x3550 M3 (7944)	x3620 M3 (7376)	x3630 M3 (7377)	x3650 M3 (7945)	x3755 M3 (7164)	dx360 M3 (6391)
81Y4492	ServeRAID H1110 SAS/SATA Controller	Y	Y	Y	Y	Y	N	N	Y	N	N
90Y4304	ServeRAID M5016 SAS/SATA Controller	N	N	N	N	Y	N	N	Y	N	N
46M0829	ServeRAID M5015 SAS/SATA Controller	Y	Y	Y	Y	Y	N	Y	Y	N	Y
46M0916	ServeRAID M5014 SAS/SATA Controller	Y	Y	Y	Y	Y	N	Y	Y	N	Y
46M0831	ServeRAID M1015 SAS/SATA Controller	Y	Y	Y	Y	Y	N	Y	Y	N	Y
46M0969	ServeRAID B5015 SSD Controller	N	N	N	N	Y	N	N	Y	N	N
49Y4731	ServeRAID-BR10il SAS/SATA Controller v2	N	N	N	N	Y	N	N	Y	N	N
46M0912	6Gb Performance Optimized HBA	Y	Y	Y	Y	Y	N	Y	Y	N	Y

Table 5. RAID controllers for System x and iDataPlex servers supported with internal SSDs (Part 2)

Part number	Product description	x3100 M4 (2582)	x3250 M4 (2583)	x3300 M4 (7382)	x3500 M4 (7383)	x3530 M4 (7160)	x3550 M4 (7914)	x3630 M4 (7158)	x3650 M4 (7915)	x3690 X5 (7147)	x3750 M4 (8722)	x3850 X5 (7143)	dx360 M4 (7912)
Onboard	ServeRAID M5110e SAS/SATA Controller	N	N	N	N	N	N	N	Y	N	Y	N	N
81Y4481	ServeRAID M5110 SAS/SATA Controller	N	N	Y	Y	Y	Y	N	Y	N	Y	N	Y
81Y4448	ServeRAID M1115 SAS/SATA Controller	N	N	Y	Y	Y	Y	N	N	N	Y	N	Y
81Y4492	ServeRAID H1110 SAS/SATA Controller	Y	Y	Y	N	Y	Y	N	N	N	N	N	Y
90Y4304	ServeRAID M5016 SAS/SATA Controller	N	N	N	N	N	N	N	N	Y	N	Y	N
46M0829	ServeRAID M5015 SAS/SATA Controller	Y	Y	N	N	N	N	N	N	Y	N	Y	N
46M0916	ServeRAID M5014 SAS/SATA Controller	Y	Y	N	N	N	N	N	N	Y	N	Y	N
46M0831	ServeRAID M1015 SAS/SATA Controller	Y	Y	N	N	N	N	N	N	N	N	N	N
46M0969	ServeRAID B5015 SSD Controller	N	N	N	N	N	N	N	N	Y	N	Y	N
Onboard	ServeRAID C105	N	N	N	N	N	N	N	N	N	N	N	N
Onboard	ServeRAID C100	N	N	N	N	N	N	N	N	N	N	N	N
46M0912	6Gb Performance Optimized HBA	Y	Y	Y	Y	Y	Y	N	Y	Y	Y	Y	Y

Table 6. RAID controllers for BladeCenter and Flex System servers supported with internal SSDs

Part number	Product description	HS12 (8028)	HS22 (7870)	HS22V (7871)	HS23 (7875)	HS23E (8038)	HX5 (7873)	x220 (7906)	x240 (8737)	x440 (7917)
90Y4390	ServeRAID M5115 SAS/SATA Controller	N	N	N	N	N	N	Y	Y	Y
90Y4750	ServeRAID H1135 Controller	N	N	N	N	Y	N	Y	N	N
Onboard	ServeRAID C105	N	N	N	N	N	N	N	N	N
Onboard	Integrated LSI SAS2004	N	N	N	Y	N	N	N	Y	Y
46C7167	ServeRAID-MR10ie (CIOv) Controller	N	N	N	N	N	N	N	N	N
Onboard	Integrated LSI SAS1064e	N	Y	Y	N	N	N	N	N	N
46M6908	SSD Expansion Card for BladeCenter HX5	N	N	N	N	N	Y	N	N	N

See the ServerProven website for the latest information about the adapters supported by each System x server type: <http://www.lenovo.com/us/en/serverproven/>

Supported operating systems

Solid-state drives operate transparently to users, storage systems, applications, databases, and operating systems. The controllers that support SSDs are supported by the following operating systems:

- Microsoft Windows Server 2012
- Microsoft Windows Server 2008 R2
- Microsoft Windows Server 2008, Datacenter x64 Edition
- Microsoft Windows Server 2008, Datacenter x86 Edition
- Microsoft Windows Server 2008, Enterprise x64 Edition
- Microsoft Windows Server 2008, Enterprise x86 Edition
- Microsoft Windows Server 2008, Standard x64 Edition
- Microsoft Windows Server 2008, Standard x86 Edition
- Microsoft Windows Server 2008, Web x64 Edition
- Microsoft Windows Server 2008, Web x86 Edition
- Microsoft Windows Server 2008 Foundation
- Microsoft Windows Small Business Server 2008 Premium Edition
- Microsoft Windows Small Business Server 2008 Standard Edition
- Microsoft Windows Server 2003/2003 R2, Datacenter Edition
- Microsoft Windows Server 2003/2003 R2, Datacenter x64 Edition
- Microsoft Windows Server 2003/2003 R2, Enterprise Edition
- Microsoft Windows Server 2003/2003 R2, Enterprise x64 Edition
- Microsoft Windows Server 2003/2003 R2, Standard Edition
- Microsoft Windows Server 2003/2003 R2, Standard x64 Edition
- Microsoft Windows Server 2003, Web Edition
- Microsoft Windows Small Business Server 2003/2003 R2 Premium Edition

- Microsoft Windows Small Business Server 2003/2003 R2 Standard Edition
- Red Hat Enterprise Linux 6 Server Edition
- Red Hat Enterprise Linux 6 Server x64 Edition
- Red Hat Enterprise Linux 5 Server Edition
- Red Hat Enterprise Linux 5 Server Edition with Xen
- Red Hat Enterprise Linux 5 Server with Xen x64 Edition
- Red Hat Enterprise Linux 5 Server x64 Edition
- Red Hat Enterprise Linux 4 AS for AMD64/EM64T
- Red Hat Enterprise Linux 4 AS for x86
- SUSE LINUX Enterprise Server 11 for AMD64/EM64T
- SUSE LINUX Enterprise Server 11 for x86
- SUSE LINUX Enterprise Server 11 with Xen for AMD64/EM64T
- SUSE LINUX Enterprise Server 10 for AMD64/EM64T
- SUSE LINUX Enterprise Server 10 for x86
- SUSE LINUX Enterprise Server 10 with Xen for AMD64/EM64T
- VMware vSphere 5.1
- VMware vSphere 5
- VMware ESX 4.0
- VMware ESX 4.1
- VMware ESXi 4.0
- VMware ESXi 4.1

See ServerProven for the latest information about the specific versions and service packs supported: <http://www.lenovo.com/us/en/serverproven/>. Click **System x servers**, then **Disk controllers** to see the support matrix. Click the check mark that is associated with the System x server in question to see the details about operating system support.

Warranty

The SATA 1.8-inch and 2.5-inch MLC Enterprise SSDs carry a 1-year, customer-replaceable unit (CRU) limited warranty. When installed in a System x server, these drives assume your system's base warranty and any warranty upgrade.

Solid State Memory cells have an intrinsic, finite number of program/erase cycles that each cell can incur. As a result, each solid state device has a maximum amount of program/erase cycles to which it can be subjected. The warranty for Lenovo solid state drives (SSDs) is limited to drives that have not reached the maximum guaranteed number of program/erase cycles, as documented in the Official Published Specifications for the SSD product. A drive that reaches this limit may fail to operate according to its Specifications.

Physical specifications

The SATA 1.8-inch MLC Enterprise SSDs have the following physical specifications.

Dimensions and weight (approximate):

- Height: 5 mm (0.2 in.)
- Width: 54 mm (2.1 in.)
- Depth: 79 mm (3.1 in.)
- Weight: 39 g (0.1 lb)

Shipping dimensions and weight (approximate):

- Height: 32 mm (1.3 in.)
- Width: 226 mm (8.9 in.)
- Depth: 150 mm (5.9 in.)
- Weight: 400 g (0.9 lb)

The SATA 2.5-inch MLC Enterprise SSDs have the following physical specifications.

Dimensions and weight (approximate):

- Height: 9 mm (0.4 in.)
- Width: 70 mm (2.8 in.)
- Depth: 100 mm (4.0 in.)
- Weight: 99 g (0.2 lb)

Shipping dimensions and weight (approximate):

- Height: 63 mm (2.5 in.)
- Width: 174 mm (6.9 in.)
- Depth: 133 mm (5.2 in.)
- Weight: 448 g (1.0 lb)

Operating environment

The SATA 1.8-inch and 2.5-inch MLC Enterprise SSDs are supported in the following environment:

- Temperature: 0 - 70 °C (32 - 158°F)
- Relative humidity: 8 - 85% (noncondensing)
- Maximum altitude: 3,050 m (10,000 ft)

Agency approvals

The SATA 1.8-inch and 2.5-inch MLC Enterprise SSDs have the following agency approvals:

- UL
- CSA
- TUV
- FCC
- EMC
- CE Mark
- C-Tick Mark
- Taiwan (BSMI Certification)
- Korea EMI

Related publications

For more information see the following documents:

- US Announcement Letter for 200 GB and 400 GB 1.8-inch MLC Enterprise SSDs
<http://ibm.com/common/ssi/cgi-bin/ssialias?infotype=dd&subtype=ca&&htmlfid=897/ENUS112-150>
- US Announcement Letter for 100 GB 1.8-inch and 2.5-inch MLC Enterprise SSDs
<http://ibm.com/common/ssi/cgi-bin/ssialias?infotype=dd&subtype=ca&&htmlfid=897/ENUS112-178>
- ServeRAID Adapter Quick Reference
<http://lenovopress.com/tips0054>
- ServerProven
<http://www.lenovo.com/us/en/serverproven/>

Related product families

Product families related to this document are the following:

- [Drives](#)

Notices

Lenovo may not offer the products, services, or features discussed in this document in all countries. Consult your local Lenovo representative for information on the products and services currently available in your area. Any reference to a Lenovo product, program, or service is not intended to state or imply that only that Lenovo product, program, or service may be used. Any functionally equivalent product, program, or service that does not infringe any Lenovo intellectual property right may be used instead. However, it is the user's responsibility to evaluate and verify the operation of any other product, program, or service. Lenovo may have patents or pending patent applications covering subject matter described in this document. The furnishing of this document does not give you any license to these patents. You can send license inquiries, in writing, to:

Lenovo (United States), Inc.
8001 Development Drive
Morrisville, NC 27560
U.S.A.
Attention: Lenovo Director of Licensing

LENOVO PROVIDES THIS PUBLICATION "AS IS" WITHOUT WARRANTY OF ANY KIND, EITHER EXPRESS OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF NON-INFRINGEMENT, MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE. Some jurisdictions do not allow disclaimer of express or implied warranties in certain transactions, therefore, this statement may not apply to you.

This information could include technical inaccuracies or typographical errors. Changes are periodically made to the information herein; these changes will be incorporated in new editions of the publication. Lenovo may make improvements and/or changes in the product(s) and/or the program(s) described in this publication at any time without notice.

The products described in this document are not intended for use in implantation or other life support applications where malfunction may result in injury or death to persons. The information contained in this document does not affect or change Lenovo product specifications or warranties. Nothing in this document shall operate as an express or implied license or indemnity under the intellectual property rights of Lenovo or third parties. All information contained in this document was obtained in specific environments and is presented as an illustration. The result obtained in other operating environments may vary. Lenovo may use or distribute any of the information you supply in any way it believes appropriate without incurring any obligation to you.

Any references in this publication to non-Lenovo Web sites are provided for convenience only and do not in any manner serve as an endorsement of those Web sites. The materials at those Web sites are not part of the materials for this Lenovo product, and use of those Web sites is at your own risk. Any performance data contained herein was determined in a controlled environment. Therefore, the result obtained in other operating environments may vary significantly. Some measurements may have been made on development-level systems and there is no guarantee that these measurements will be the same on generally available systems. Furthermore, some measurements may have been estimated through extrapolation. Actual results may vary. Users of this document should verify the applicable data for their specific environment.

© Copyright Lenovo 2024. All rights reserved.

This document, TIPS0908, was created or updated on April 17, 2013.

Send us your comments in one of the following ways:

- Use the online Contact us review form found at:
<https://lenovopress.lenovo.com/TIPS0908>
- Send your comments in an e-mail to:
comments@lenovopress.com

This document is available online at <https://lenovopress.lenovo.com/TIPS0908>.

Trademarks

Lenovo and the Lenovo logo are trademarks or registered trademarks of Lenovo in the United States, other countries, or both. A current list of Lenovo trademarks is available on the Web at <https://www.lenovo.com/us/en/legal/copytrade/>.

The following terms are trademarks of Lenovo in the United States, other countries, or both:

Lenovo®
BladeCenter®
Flex System
ServeRAID
ServerProven®
System x®
eXFlash
iDataPlex®

The following terms are trademarks of other companies:

Linux® is the trademark of Linus Torvalds in the U.S. and other countries.

Microsoft®, Windows Server®, and Windows® are trademarks of Microsoft Corporation in the United States, other countries, or both.

Other company, product, or service names may be trademarks or service marks of others.